

```
1  #include "FullTime.h"
2
3
4
5  FullTime::FullTime(string first, string last, long id, double salary,      ↗
    double bonus):
6      EmployeeType(first,last, id)
7  {
8      emSalary = salary;
9      emBonus = bonus;
10
11  }
12  FullTime::~FullTime() {
13
14  }
15
16  void FullTime::set(string first, string last, long id, double salary,      ↗
    double bonus) {
17      setName(first, last);
18      setId(id);
19
20      emSalary = salary;
21      emBonus = bonus;
22
23  }
24
25  void FullTime::setSalary(double salary) {
26      emSalary = salary;
27
28
29  }
30
31
32  void FullTime::setBonus(double bonus) {
33      emBonus = bonus;
34  }
35
36
37
38  double FullTime::getSalary()const {
39      return emSalary;
40  }
41
42  double FullTime::getBonus()const {
43
44      return emBonus;
45  }
46
47
```

```
48 double FullTime::calcPay()const {
49     return emSalary + emBonus;
50 }
51
52
53 void FullTime::print()const {
54     cout << "ID: " << getId() << endl;
55
56     cout << "Name: ";
57     PersonType::print();
58
59     cout << fixed << setprecision(2);
60
61     cout << "Wages: $" << calcPay() << endl;
62
63
64 }
```