

```
1  // JASON JOHNSON , CADEN FISHER
2
3  #include "payRoll.h"
4
5  using namespace std;
6
7
8  Payroll::Payroll(int s)
9  {
10     size = s;
11     payRate = new double[size] {};
12     hours = new double[size] {};
13     finalPay = new double[size] {};
14
15 }
16
17
18
19 Payroll::~Payroll() {
20
21     delete payRate;
22     delete hours;
23     delete finalPay;
24
25     payRate = nullptr;
26     hours = nullptr;
27     finalPay = nullptr;
28 }
29
30
31 void Payroll::setPayrate(int i, double p) {
32
33     while (p <= 0) {
34         cout << "Error: pay rate must be greater than 0\n Enter new Payrate:";
35         cin >> p;
36     }
37
38     payRate[i] = p;
39
40 }
41
42
43
44 void Payroll::setHours(int i, double h) {
45
46     while (!(h > 0 && h <= 60)) {
47         cout << "Error: pay rate must be greater than 0\n Enter new Payrate:";
```

```
48     cin >> h;
49 }
50
51     hours[i] = h;
52
53
54
55 }
56
57 double Payroll::getPayrate(int i) const {
58     return payRate[i];
59 }
60
61 double Payroll::getHours(int i) const {
62     return hours[i];
63 }
64
65 double Payroll::getFinalPay(int i) const {
66     return finalPay[i];
67 }
68
69 void Payroll::findFinalPay(int i) {
70
71     finalPay[i] = hours[i] * payRate[i];
72
73 }
74
```