



```
1 import sqlite3
2
3 def main():
4     conn = sqlite3.connect('inventory.db')
5     cur = conn.cursor()
6
7     # Drop Table if exist
8     DropTable = '''DROP TABLE IF EXISTS Inventory'''
9     cur.execute(DropTable)
10
11     # Create Table
12     CreateTable = '''CREATE TABLE IF NOT EXISTS Inventory (ItemID INTEGER PRIMARY KEY NOT NULL, ItemName TEXT, Price REAL)'''
13
14     cur.execute(CreateTable)
15     conn.commit()
16
17     # Insert Data
18     InsertData = '''INSERT INTO Inventory (ItemName, Price) VALUES ("Screwdriver", 4.99), ("Hammer", 12.99), ("Vice Grips", 14.99)'''
19     cur.execute(InsertData)
20
21     # Select Data
22     NameAndPrice = '''SELECT ItemName, Price FROM Inventory'''
23     cur.execute(NameAndPrice)
24
25     #Fetch All - returns a list containing all the rows that result from a SELECT statement
26     results = cur.fetchall()
27
28     for row in results:
29         print(row)
30
31     for row in results:
32         # row[0] is the first value in the row (position 0)
33         # row[1] is the second value in the row (position 1).
34         print(f'{row[0]:30} {row[1]:5}')
35
36     #Fetch One - returns only one row each time it is called, as a tuple
37     row = cur.fetchone()
38
39     while (row != None):
40         print(f'{row[0]:30} {row[1]:5}')
41         row = cur.fetchone()
42
43     # Where Clause
44     RetailPrice1 = '''SELECT * FROM Inventory'''
45     RetailPrice2 = '''SELECT * FROM Inventory WHERE Price > 10.00'''
46     RetailPrice3 = '''SELECT * FROM Inventory WHERE Price > 10.00 ORDER BY Price'''
47
48     cur.execute(RetailPrice1)
49     resultsNew = cur.fetchall()
50
51     for row in resultsNew:
52         print(f'{row[0]:5} {row[1]:10} {row[2]:10}')
53
54     conn.close()
55
56 main()
```

---