

Introduction

About Verovio

Verovio is open-source music notation engraving software. It supports files encoded using the [Music Encoding Initiative](#), as well as MusicXML, Humdrum `**kern`, and Plaine and Easie. There are several versions of Verovio available: A command-line utility, a JavaScript library suitable for embedding notation on web-pages, and as a library for several other languages and platforms, including Python, iOS, Android, and Java. Verovio is cross-platform and can be used in digital environments of various kind. The output of Verovio is beautifully engraved music notation rendered using the Scalable Vector Graphics (SVG) format.

While Verovio can be used as a core component for building powerful music notation editors, it is not an editor itself. There are a number of engraving options available to help control and adjust, to a fine level of detail, the specifics of the engraving.

Verovio uses the Standard Music Font Layout (SMuFL) as the basis for its notation shapes. This means that any [SMuFL-compliant font](#) may be used to customize and personalize the look of the engraved output.

About this book

This book is intended to serve as a reference guide for how to work with Verovio, and is meant for users of all skill levels. The book is a collaborative work that brings together inputs from the many contributors to the Verovio projects under the editorial leadership of the RISM Digital Center team.

[How to cite it?]

The first three sections will provide a number of tutorials, starting at the very basic and ending at advanced topics in notation. By the end of these sections you should have a very good understanding of how to use Verovio in its different forms, and how you can start to integrate it into your own work.

The following sections will cover the specifics of Verovio, serving as a reference for the operations and options available. It will also cover how to build Verovio from the source code, and how to contribute to the active development of Verovio.

Getting help

As you work through this book, from the most basic to the most advanced topics, you may find that you are struggling to understand something. The quickest and easiest way to get help is to reach out on the `#verovio` channel in the [MEI Community's Slack chat](#). If you are not already a member, [you can join](#).

Licensing

Verovio is licensed under the OSI-approved [GNU Lesser General Public License \(LGPLv3\)](#). This means that Verovio can be used in any contexts that are compliant with the requirements of that license. In this section, we explain more concretely what you can do with it in your project, but also what is required or not allowed for you to do, and what we additionally recommend.

What is allowed

The LGPLv3 license allows you to use the Verovio library as-is in open-source projects that are compliant with this license. It can also be used in commercial products that are open-source or not. It can be a web application, a desktop application or a mobile one. The Verovio library can be embedded in the product and shipped with it without having your product itself to be open-source as long as the Verovio library is **not modified** and is dynamically linked to your product.

What is required

Whichever use you make of the library, you have to give **visible credit** to the Verovio library. For a web application, it has to be through a prominent notice on your web-site. For a mobile application, it has to be given in the metadata of the application (e.g., iOS App Store or the Google Play store).

Here are some minimal examples to follow:

- NomadPlay web application and in the App Store
- Trala in the App Store

Using Verovio in a product without giving credit is a clear **license violation**. However, it is also important to understand that, by giving the appropriate credits, you are not only fulfilling the very basic and free-of-charge requirements of the license but also supporting the community by recognizing its work. This will help us make Verovio better and more sustainable and will be beneficial to all users - including you - in the long-run.

What is not allowed

You are not allowed to make any modifications to the Verovio library without making all of your **changes publicly available** and under the original LGPLv3 license. For example, if you improve the layout algorithm, or add support for additional music notation elements, these improvements must be made open-source under LGPLv3. Not doing it is also a **license violation** and is un-supportive of the community.

What is recommended

Providing credit if you use Verovio, and making the source code of your modifications to the Verovio library available to the community, are the only minimal legal requirements. However, we strongly encourage you to go one step further and to ask for your changes to be integrated into the original code-base of Verovio with a **pull-request** to the [rism-digital/verovio](https://github.com/rism-digital/verovio) repository. Before your changes can be integrated into the repository, we will need you to accept the Verovio [Contributor License Agreement \(CLA\)](#). This is a standard procedure for open-source projects and will allow for the community to benefit directly from your work.

We would also be happy to hear about your use of Verovio in your applications. Please get in touch if you are using Verovio, and let us know where we can learn more about your project!

Overview

There?

Tutorial 1: Web-based notation

Layout options

Now that we have successfully rendered an MEI file to a web page, we can start to explore how to customize the SVG output. There are many possible options, most of which you will never need.

To start, we will first try and reduce the size of the image output, to demonstrate how we can scale the music notation to fit the screen.

Score navigation

Tutorial 2: Interactive notation

Introduction

Here is one example - we show measure 1 and 3 with a separator



XML

```
<measure n="1">
  <staff n="1">
    <layer n="1">
      <note dur="4" oct="5" pname="c" stem.dir="down">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="5" pname="d" stem.dir="down">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="5" pname="c" stem.dir="down">
        <accid accid="n" func="edit"/>
      </note>
      <note dur="4" oct="4" pname="b" stem.dir="down">
        <accid accid="f"/>
      </note>
    </layer>
  </staff>
</measure>
<!-- ... -->
<measure right="end" n="3">
  <staff n="1">
    <layer n="1">
      <note dur="4" oct="5" pname="c" stem.dir="down">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="4" pname="g" stem.dir="up">
        <accid accid="s" func="edit"/>
      </note>
      <note dur="4" oct="4" pname="e" stem.dir="up">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="4" pname="d" stem.dir="up">
        <accid accid.ges="n"/>
      </note>
    </layer>
  </staff>
</measure>
```

Here is another one - we show measure 1 and 2 without separator



XML

```
<measure n="1">
  <staff n="1">
    <layer n="1">
      <note dur="4" oct="4" pname="c" accid.ges="n"/>
      <note dur="4" oct="4" pname="d" accid.ges="n"/>
      <note dur="4" oct="4" pname="e" accid.ges="n"/>
      <note dur="4" oct="4" pname="f" accid.ges="n"/>
    </layer>
  </staff>
</measure>
<measure n="2">
  <staff n="1">
    <layer n="1">
      <beam>
        <note dur="8" oct="4" pname="g" accid.ges="n"/>
        <note dur="8" oct="4" pname="a" accid.ges="n"/>
      </beam>
      <beam>
        <note dur="8" oct="4" pname="b" accid.ges="n"/>
        <note dur="8" oct="5" pname="c" accid.ges="n"/>
      </beam>
      <beam>
        <note dur="8" oct="5" pname="d" accid.ges="n"/>
        <note dur="8" oct="5" pname="e" accid.ges="n"/>
      </beam>
      <beam>
        <note dur="8" oct="5" pname="f" accid.ges="n"/>
        <note dur="8" oct="5" pname="g" accid.ges="n"/>
      </beam>
    </layer>
  </staff>
</measure>
```

Inspecting the SVG

[Describe how to inspect the SVG output in the browser; useful to know for later chapters on how to style them!]

Working with CSS and SVG

Here is one example - show first note



XML

```

<measure n="1">
  <staff n="1">
    <layer n="1">
      <note dur="4" oct="5" pname="c" stem.dir="down">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="5" pname="d" stem.dir="down">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="5" pname="c" stem.dir="down">
        <accid accid="n" func="edit"/>
      </note>
      <note dur="4" oct="4" pname="b" stem.dir="down">
        <accid accid="f"/>
      </note>
    </layer>
  </staff>
</measure>
<!-- ... -->
<measure right="end" n="3">
  <staff n="1">
    <layer n="1">
      <note dur="4" oct="5" pname="c" stem.dir="down">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="4" pname="g" stem.dir="up">
        <accid accid="s" func="edit"/>
      </note>
      <note dur="4" oct="4" pname="e" stem.dir="up">
        <accid accid.ges="n"/>
      </note>
      <note dur="4" oct="4" pname="d" stem.dir="up">
        <accid accid.ges="n"/>
      </note>
    </layer>
  </staff>
</measure>

```

Here is another one - show first and last note

[SVG file is missing and need to be generated]

XML

[MEI file is missing and need to be generated]

XPath queries

Beyond tutorials: Advanced topics

Introduction

Transposition

SMuFL fonts

Embedded fonts

Selecting a font

Controlling the SVG output

HTML5

Towards SVG 2.0

Converting to PDF

Mensural notation

Duration alignment

Layout

Ligatures

Toolkit Reference

Input formats

MEI

humdrum

MusicXML

Plain and Easy

ABC

Output formats

SVG

MEI

MIDI

Timemap

Toolkit methods

Edit

Parse the editor actions passed as JSON string.

Only available for Emscripten-based compiles

Returns

bool

Parameters

Name	Type	Default	Description
json_editorAction	const std::string &	Ø	

Original header

C++

```
bool vrv::Toolkit::Edit(const std::string &json_editorAction)
```

Example call

PYTHON

```
result = toolkit.edit(json_editorAction)
```

EditInfo

Returns

std::string

Original header

C++

```
std::string vrv::Toolkit::EditInfo()
```

Example call

PYTHON

```
result = toolkit.editInfo()
```

GetAvailableOptions

Returns

std::string

Original header

C++

```
std::string vrv::Toolkit::GetAvailableOptions() const
```

Example call

PYTHON

```
result = toolkit.getAvailableOptions()
```

More info here

Example how to extended the documentation for a method

GetElementAttr

Return element attributes as a JSON string.

Returns

std::string

Parameters

Name	Type	Default	Description
xmlId	const std::string &	Ø	

Original header

C++

```
std::string vrv::Toolkit::GetElementAttr(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getElementAttr(xmlId)
```

GetElementsAtTime

Returns array of IDs of elements being currently played.

Returns

std::string

Parameters

Name	Type	Default	Description
millisec	int	Ø	

Original header

C++

```
std::string vrv::Toolkit::GetElementsAtTime(int millisec)
```

Example call

PYTHON

```
result = toolkit.getElementsAtTime(millisec)
```

GetExpansionIdsForElement

Returns a vector of ID strings of all elements (the notated and the expanded) for a given element.

Returns

std::string

Parameters

Name	Type	Default	Description
xmlId	const std::string &	Ø	

Original header

C++

```
std::string vrv::Toolkit::GetExpansionIdsForElement(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getExpansionIdsForElement(xmlId)
```

GetHumdrum

Returns

void

Parameters

Name	Type	Default	Description
output	std::ostream &	Ø	

Original header

C++

```
void vrv::Toolkit::GetHumdrum(std::ostream &output)
```

Example call

PYTHON

```
toolkit.getHumdrum(output)
```

GetHumdrum

Returns

std::string

Original header

C++

```
std::string vrv::Toolkit::GetHumdrum()
```

Example call

PYTHON

```
result = toolkit.getHumdrum()
```

GetHumdrumBuffer

Returns

const char *

Original header

C++

```
const char* vrv::Toolkit::GetHumdrumBuffer()
```

Example call

PYTHON

```
result = toolkit.getHumdrumBuffer()
```

GetHumdrumFile

Returns

bool

Parameters

Name	Type	Default	Description
filename	const std::string &	Ø	

Original header

C++

```
bool vrv::Toolkit::GetHumdrumFile(const std::string &filename)
```

Example call

PYTHON

```
result = toolkit.getHumdrumFile(filename)
```

GetInputFrom

Returns

int

Original header

C++

```
int vrv::Toolkit::GetInputFrom()
```

Example call

PYTHON

```
result = toolkit.getInputFrom()
```

GetLog

Concatenates the `vrv::logBuffer` into a string and returns it.

This is used only for Emscripten-based compilation. The `vrv::logBuffer` is filled by the `vrv::LogXXX` functions.

Returns

`std::string`

Original header

C++

```
std::string vrv::Toolkit::GetLog()
```

Example call

PYTHON

```
result = toolkit.getLog()
```

GetMEI

Get the MEI as a string.

Options (JSON) can be: `pageNo`: integer; (1-based), `scoreBased`: true, `noXmlIds`: false; true by default (noXmlIds: true), `@xml:id`: false; false by default - remove all `@xml:id` not used in the data - not implemented

Returns

`std::string`

Parameters

Name	Type	Default	Description
<code>jsonOptions</code>	<code>const std::string &</code>	<code>∅</code>	

Original header

C++

```
std::string vrv::Toolkit::GetMEI(const std::string &jsonOptions)
```

Example call

PYTHON

```
result = toolkit.getMEI(jsonOptions)
```

GetMIDIValuesForElement

Return MIDI values of the element with the ID (`xml:id`).

`RenderToMidi()` must be called prior to using this method.

Returns

`std::string`

Parameters

Name	Type	Default	Description
<code>xmlId</code>	<code>const std::string &</code>	<code>∅</code>	

Original header

C++

```
std::string vrv::Toolkit::GetMIDIValuesForElement(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getMIDIValuesForElement(xmlId)
```

GetNotatedIdForElement

Returns the ID string of the notated (the original) element.

Returns

std::string

Parameters

Name	Type	Default	Description
xmlId	const std::string &	Ø	

Original header

C++

```
std::string vrv::Toolkit::GetNotatedIdForElement(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getNotatedIdForElement(xmlId)
```

GetOption

Returns

std::string

Parameters

Name	Type	Default	Description
option	const std::string &	Ø	
defaultValue	bool	false	

Original header

C++

```
std::string vrv::Toolkit::GetOption(const std::string &option, bool defaultValue=false) const
```

Example call

PYTHON

```
result = toolkit.getOption(option, defaultValue)
```

GetOptions

Returns

std::string

Parameters

Name	Type	Default	Description
defaultValues	bool	Ø	

Original header

C++

```
std::string vrv::Toolkit::GetOptions(bool defaultValues) const
```

Example call

PYTHON

```
result = toolkit.getOptions(defaultValues)
```

GetOptions

Return the Options object of the Toolkit instance.

Original header

C++

```
Options* vrv::Toolkit::GetOptions()
```

Example call

PYTHON

```
result = toolkit.getOptions()
```

GetOutputTo

Returns

int

Original header

C++

```
int vrv::Toolkit::GetOutputTo()
```

Example call

PYTHON

```
result = toolkit.getOutputTo()
```

GetPageCount

Returns

int

Original header

C++

```
int vrv::Toolkit::GetPageCount()
```

Example call

PYTHON

```
result = toolkit.getPageCount()
```

GetPageWithElement

Return the page on which the element is the ID (xml:id) is rendered.

This takes into account the current layout options. Returns 0 if no element is found.

Returns

int

Parameters

Name	Type	Default	Description
xmlId	const std::string &	Ø	

Original header

C++

```
int vrv::Toolkit::GetPageWithElement(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getPageWithElement(xmlId)
```

GetScale

Returns

int

Original header

C++

```
int vrv::Toolkit::GetScale()
```

Example call

PYTHON

```
result = toolkit.getScale()
```

GetTimeForElement

Return the time at which the element is the ID (xml:id) is played.

RenderToMidi() must be called prior to using this method. Returns 0 if no element is found.

Returns

int

Parameters

Name	Type	Default	Description
xmlId	const std::string &	Ø	

Original header

C++

```
int vrv::Toolkit::GetTimeForElement(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getTimeForElement(xmlId)
```

GetTimesForElement

Return a JSON object string with the following key values for a given note: scoreTimeOnset, scoreTimeOffset, scoreTimeTiedDuration, realTimeOnsetMilliseconds, realTimeOffsetMilliseconds, realTimeTiedDurationMilliseconds.

Returns 0 if no element is found.

Returns

std::string

Parameters

Name	Type	Default	Description
xmlId	const std::string &	Ø	

Original header

C++

```
std::string vrv::Toolkit::GetTimesForElement(const std::string &xmlId)
```

Example call

PYTHON

```
result = toolkit.getTimeForElement(xmlId)
```

GetUuid

Return the ID of the Toolkit instance.

Returns

std::string

Original header

C++

```
std::string vrv::Toolkit::GetUuid()
```

Example call

PYTHON

```
result = toolkit.getUuid()
```

GetVersion

Returns the version number as a string.

This is used only for Emscripten-based compilation.

Returns

std::string

Original header

C++

```
std::string vrv::Toolkit::GetVersion()
```

Example call

PYTHON

```
result = toolkit.getVersion()
```

IdentifyInputFrom

Returns

FileFormat

Parameters

Name	Type	Default	Description
data	const std::string &	Ø	

Original header**C++**

```
FileFormat vrv::Toolkit::IdentifyInputFrom(const std::string &data)
```

Example call**PYTHON**

```
result = toolkit.identifyInputFrom(data)
```

LoadData

Load a string data with the type previously specified in the options.

By default, the methods try to auto-detect the type.

Returns

bool

Parameters

Name	Type	Default	Description
data	const std::string &	Ø	A string with the data (e.g., MEI data) to be loaded

Original header**C++**

```
bool vrv::Toolkit::LoadData(const std::string &data)
```

Example call**PYTHON**

```
result = toolkit.loadData(data)
```

LoadFile

Load a file from the file system.

Previously convert UTF16 files to UTF8 or extract files from MusicXML compressed files.

Returns

bool

Parameters

Name	Type	Default	Description
------	------	---------	-------------

filename	const std::string &	Ø	The filename to be loaded
----------	---------------------	---	---------------------------

Original header

C++

```
bool vrv::Toolkit::LoadFile(const std::string &filename)
```

Example call

PYTHON

```
result = toolkit.loadFile(filename)
```

LoadZipDataBase64

Load a MusicXML compressed file passed as base64 encoded string.

Returns

bool

Parameters

Name	Type	Default	Description
data	const std::string &	Ø	A ZIP file in base64 encoded string

Original header

C++

```
bool vrv::Toolkit::LoadZipDataBase64(const std::string &data)
```

Example call

PYTHON

```
result = toolkit.loadZipDataBase64(data)
```

LoadZipDataBuffer

Load a MusicXML compressed file passed as a buffer of bytes.

True if loading the buffer succeed, false otherwise

Returns

bool – True if loading the buffer succeed, false otherwise

Parameters

Name	Type	Default	Description
data	const unsigned char *	Ø	A ZIP file as a buffer of bytes
length	int	Ø	The size of the data buffer

Original header

C++

```
bool vrv::Toolkit::LoadZipDataBuffer(const unsigned char *data, int length)
```

Example call

PYTHON

```
result = toolkit.loadZipDataBuffer(data, length)
```

RedoLayout

Redo the layout of the loaded data.

This can be called once the rendering option were changed, For example with a new page (screen) height or a new zoom level.

Returns

void

Original header

C++

```
void vrv::Toolkit::RedoLayout()
```

Example call

PYTHON

```
toolkit.redoLayout()
```

RedoPagePitchPosLayout

Redo the layout of the pitch positions of the current drawing page.

Only the note vertical positions are recalculated with this method. RedoLayout() needs to be called for a full recalculation.

Returns

void

Original header

C++

```
void vrv::Toolkit::RedoPagePitchPosLayout()
```

Example call

PYTHON

```
toolkit.redoPagePitchPosLayout()
```

RenderToDeviceContext

Render the page to the deviceContext.

Page number is 1-based.

Returns

bool

Parameters

Name	Type	Default	Description
pageNo	int	Ø	
deviceContext	``	Ø	

Original header

C++

```
bool vrv::Toolkit::RenderToDeviceContext(int pageNo, DeviceContext *deviceContext)
```

Example call

PYTHON

```
result = toolkit.renderToDeviceContext(pageNo, deviceContext)
```

RenderToMIDI

Creates a midi file, opens it, and returns it (base64 encoded).

Returns

std::string

Original header**C++**

```
std::string vrv::Toolkit::RenderToMIDI()
```

Example call**PYTHON**

```
result = toolkit.renderToMIDI()
```

RenderToMIDIFile

Creates a midi file, opens it, and writes to it.

currently generates a dummy midi file.

Returns

bool

Parameters

Name	Type	Default	Description
filename	const std::string &	Ø	

Original header**C++**

```
bool vrv::Toolkit::RenderToMIDIFile(const std::string &filename)
```

Example call**PYTHON**

```
result = toolkit.renderToMIDIFile(filename)
```

RenderToPAE

Render the content to Plaine and Easie.

Only the top staff / layer is exported.

Returns

std::string

Original header**C++**

```
std::string vrv::Toolkit::RenderToPAE()
```

Example call**PYTHON**

```
result = toolkit.renderToPAE()
```

RenderToPAEFile

Export the content to a Plaine and Easie file.

Returns

bool

Parameters

Name	Type	Default	Description
filename	const std::string &	Ø	

Original header

C++

```
bool vrv::Toolkit::RenderToPAEFile(const std::string &filename)
```

Example call

PYTHON

```
result = toolkit.renderToPAEFile(filename)
```

RenderToSVG

Render the page in SVG and returns it as a string.

Page number is 1-based

Returns

std::string

Parameters

Name	Type	Default	Description
pageNo	int	1	
xml_declaration	bool	false	

Original header

C++

```
std::string vrv::Toolkit::RenderToSVG(int pageNo=1, bool xml_declaration=false)
```

Example call

PYTHON

```
result = toolkit.renderToSVG(pageNo, xml_declaration)
```

RenderToSVGFile

Render the page in SVG and save it to the file.

Page number is 1-based.

Returns

bool

Parameters

Name	Type	Default	Description
filename	const std::string &	Ø	
pageNo	int	1	

Original header

C++

```
bool vrv::Toolkit::RenderToSVGFile(const std::string &filename, int pageNo=1)
```

Example call

PYTHON

```
result = toolkit.renderToSVGFile(filename, pageNo)
```

RenderToTimemap

Creates a timemap file, and return it as a JSON string.

Returns

std::string

Original header

C++

```
std::string vrv::Toolkit::RenderToTimemap()
```

Example call

PYTHON

```
result = toolkit.renderToTimemap()
```

RenderToTimemapFile

Returns

bool

Parameters

Name	Type	Default	Description
filename	const std::string &	Ø	

Original header

C++

```
bool vrv::Toolkit::RenderToTimemapFile(const std::string &filename)
```

Example call

PYTHON

```
result = toolkit.renderToTimemapFile(filename)
```

SaveFile

Save an MEI file.

This is a lond description for Save.

Returns

bool

Parameters

Name	Type	Default	Description
filename	const std::string &	∅	This parameter is the filename
jsonOptions	const std::string &	∅	There are the options. It cannot be null

Original header

C++

```
bool vrv::Toolkit::SaveFile(const std::string &filename, const std::string &jsonOptions)
```

Example call

PYTHON

```
result = toolkit.saveFile(filename, jsonOptions)
```

SetHumdrumBuffer

Returns

void

Parameters

Name	Type	Default	Description
contents	const char *	∅	

Original header

C++

```
void vrv::Toolkit::SetHumdrumBuffer(const char *contents)
```

Example call

PYTHON

```
toolkit.setHumdrumBuffer(contents)
```

SetInputFrom

Returns

bool

Parameters

Name	Type	Default	Description
inputFrom	std::string const &	∅	

Original header

C++

```
bool vrv::Toolkit::SetInputFrom(std::string const &inputFrom)
```

Example call

PYTHON

```
result = toolkit.setInputFrom(inputFrom)
```

SetInputFrom

Returns

void

Parameters

Name	Type	Default	Description
format	FileFormat	Ø	

Original header

C++

```
void vrv::Toolkit::SetInputFrom(FileFormat format)
```

Example call

PYTHON

```
toolkit.setInputFrom(format)
```

SetOption

Returns

bool

Parameters

Name	Type	Default	Description
option	const std::string &	Ø	
value	const std::string &	Ø	

Original header

C++

```
bool vrv::Toolkit::SetOption(const std::string &option, const std::string &value)
```

Example call

PYTHON

```
result = toolkit.setOption(option, value)
```

SetOptions

Returns

bool

Parameters

Name	Type	Default	Description
jsonOptions	const std::string &	Ø	

Original header

C++

```
bool vrv::Toolkit::SetOptions(const std::string &jsonOptions)
```

Example call

PYTHON

```
result = toolkit.setOptions(jsonOptions)
```

SetOutputTo

Returns

bool

Parameters

Name	Type	Default	Description
outputTo	std::string const &	Ø	

Original header**C++**

```
bool vrv::Toolkit::SetOutputTo(std::string const &outputTo)
```

Example call**PYTHON**

```
result = toolkit.setOutputTo(outputTo)
```

SetResourcePath

Set the resource path for the Toolkit instance.

This method needs to be called if the constructor had initFont=false or if the resource path needs to be changed.

Returns

bool

Parameters

Name	Type	Default	Description
path	const std::string &	Ø	The path to the resource directory

Original header**C++**

```
bool vrv::Toolkit::SetResourcePath(const std::string &path)
```

Example call**PYTHON**

```
result = toolkit.setResourcePath(path)
```

SetScale

Returns

bool

Parameters

Name	Type	Default	Description
scale	int	Ø	

Original header

C++

```
bool vrv::Toolkit::SetScale(int scale)
```

Example call

PYTHON

```
result = toolkit.setScale(scale)
```

Toolkit

If `initFont` is set to `false`, `Resources::InitFonts` will have to be called explicitly.

Parameters

Name	Type	Default	Description
<code>initFont</code>	<code>bool</code>	<code>true</code>	

Original header

C++

```
vrv::Toolkit::Toolkit(bool initFont=true)
```

Example call

PYTHON

```
result = toolkit.toolkit(initFont)
```

Toolkit options

Base short options

All of the base options are short options in the command-line version of the toolkit. Most of them are command-line options that have no direct corresponding JSON key.

Name and parameter	Description	See also
<code>-a, --all-pages</code>	Output all pages	
<code>-h, --help</code>	Display this message	
<code>-f, --input-from <s></code>	Select input format from: “abc”, “darms”, “humdrum”, “mei”, “pae”, “xml” (musicxml) (default: “mei”)	Input formats
<code>-o, --outfile <s></code>	Output file name (use “-” as file name for standard output) (default: “svg”)	
<code>-t, --output-to <s></code>	Select output format to: “mei”, “pb-mei”, “svg”, or “midi” (default: “svg”)	Output formats
<code>-p, --page <i></code>	Select the page to engrave (default is 1)	
<code>-r, --resource-path <s></code>	Path to the directory with Verovio resources (default: “/usr/local/share/verovio”)	SetResourcePath Building the toolkit
<code>-s, --scale <i></code>	Scale of the output in percent (default: 100; min: 1; max: 1000)	
<code>- , --stdin</code>	Use “-” as input file or set the “--stdin” option for reading from the standard input	

Name and parameter	Description	See also
--v, --version	Display the version number	
-x, --xml-id-seed <i>	Seed the random number generator for XML IDs (default is random)	

Input and page layout options

Name and parameter	Description	See also
--adjust-page-height	Adjust the page height to the height of the content	
--adjust-page-width	Adjust the page width to the width of the content	
--breaks <s>	Define page and system breaks layout (default: "auto"; other values: ['none', 'auto', 'line', 'smart', 'encoded'])	
--breaks-smart-sb <f>	In smart breaks mode, the portion of system width usage at which an encoded sb will be used (default: 0.66; min: 0.0; max: 1.0)	
--clef-change-factor <f>	Set the ratio of normal clefs to changing clefs (default: 0.66; min: 0.25; max: 1.0)	
--condense <s>	Control condensed score layout (default: "auto"; other values: ['none', 'auto', 'encoded'])	
--condense-first-page	When condensing a score also condense the first page	
--condense-tempo-pages	When condensing a score also condense pages with a tempo change	
--even-note-spacing	Specify the linear spacing factor	
--expand <s>	Expand all referenced elements in the expansion (default: "")	
--footer <s>	Control footer layout (default: "auto"; other values: ['none', 'auto', 'encoded', 'always'])	
--header <s>	Control header layout (default: "auto"; other values: ['none', 'auto', 'encoded'])	
--hum-type	Include type attributes when importing from Humdrum	
--justify-vertically	Justify spacing vertically to fill the page	
--landscape	The landscape paper orientation flag	
--mensural-to-measure	Convert mensural sections to measure-based MEI	Ligatures Layout
--min-last-justification <f>	The last system is only justified if the unjustified width is greater than this percent (default: 0.8; min: 0.0; max: 1.0)	
--mm-output	Specify that the output in the SVG is given in mm (default is px)	
--no-justification	Do not justify the system	
--open-control-events	Render open control events	
--output-indent <i>	Output indentation value for MEI and SVG (default: 3; min: 1; max: 10)	
--output-indent-tab	Output indentation with tabulation for MEI and SVG	

Name and parameter	Description	See also
--output-smufl-xml-entities	Output SMuFL characters as XML entities instead of byte codes	
--page-height <i>	The page height (default: 2970; min: 100; max: 60000)	
--page-margin-bottom <i>	The page bottom margin (default: 50; min: 0; max: 500)	
--page-margin-left <i>	The page left margin (default: 50; min: 0; max: 500)	
--page-margin-right <i>	The page right margin (default: 50; min: 0; max: 500)	
--page-margin-top <i>	The page top margin (default: 50; min: 0; max: 500)	
--page-width <i>	The page width (default: 2100; min: 100; max: 60000)	
--remove-ids	Remove XML IDs in the MEI output that are not referenced	
--shrink-to-fit	Scale down page content to fit the page height if needed	
--svg-bounding-boxes	Include bounding boxes in SVG output	
--svg-format-raw	Writes SVG out with no line indenting or non-content newlines.	
--svg-html5	Write data-id and data-class attributes for JS usage and id clash avoidance.	
--svg-remove-xlink	Removes the xlink: prefix on href attributes for compatibility with some newer browsers.	
--svg-view-box	Use viewBox on svg root element for easy scaling of document	
--unit <i>	The MEI unit (1/2 of the distance between the staff lines) (default: 9; min: 6; max: 20)	
--use-brace-glyph	Use brace glyph from current font	
--use-facsimile	Use information in the element to control the layout	
--use-pg-footer-for-all	Use the pgFooter for all pages	
--use-pg-header-for-all	Use the pgHeader for all pages	

General layout options

Name and parameter	Description	See also
--bar-line-separation <f>	The default distance between multiple barlines when locked together (default: 0.8; min: 0.5; max: 2.0)	
--bar-line-width <f>	The barLine width (default: 0.3; min: 0.1; max: 0.8)	
--beam-max-slope <i>	The maximum beam slope (default: 10; min: 1; max: 20)	
--beam-min-slope <i>	The minimum beam slope	
--bracket-thickness <f>	The thickness of the system bracket (default: 1.0; min: 0.5; max: 2.0)	
--engraving-defaults <s>	Path to json file describing defaults for engraving SMuFL elements	

Name and parameter	Description	See also
--font <s>	Set the music font (default: "Leipzig")	
--grace-factor <f>	The grace size ratio numerator (default: 0.75; min: 0.5; max: 1.0)	
--grace-rhythm-align	Align grace notes rhythmically with all staves	
--grace-right-align	Align the right position of a grace group with all staves	
--hairpin-size <f>	The haripin size in MEI units (default: 3.0; min: 1.0; max: 8.0)	
--hairpin-thickness <f>	The thickness of the hairpin (default: 0.2; min: 0.1; max: 0.8)	
--justification-brace-group <f>	Space between staves inside a braced group ijustification (default: 1.0; min: 0.0; max: 10.0)	
--justification-bracket-group <f>	Space between staves inside a bracketed group justification (default: 1.0; min: 0.0; max: 10.0)	
--justification-staff <f>	The staff justification (default: 1.0; min: 0.0; max: 10.0)	
--justification-system <f>	The system spacing justification (default: 1.0; min: 0.0; max: 10.0)	
--ledger-line-extension <f>	The amount by which a ledger line should extend either side of a notehead (default: 0.54; min: 0.2; max: 1.0)	
--ledger-line-thickness <f>	The thickness of the ledger lines (default: 0.25; min: 0.1; max: 0.5)	
--lyric-hyphen-length <f>	The lyric hyphen and dash length (default: 1.2; min: 0.5; max: 3.0)	
--lyric-line-thickness <f>	The lyric extender line thickness (default: 0.25; min: 0.1; max: 0.5)	
--lyric-no-start-hyphen	Do not show hyphens at the beginning of a system	
--lyric-size <f>	The lyrics size in MEI units (default: 4.5; min: 2.0; max: 8.0)	
--lyric-top-min-margin <f>	The minmal margin above the lyrics in MEI units (default: 2.0; min: 0.0; max: 8.0)	
--lyric-word-space <f>	The lyric word space length (default: 1.2; min: 0.5; max: 3.0)	
--measure-number <s>	The measure numbering rule (unused) (default: "system"; other values: ['system', 'interval'])	
--midi-tempo-adjustment <f>	The MIDI tempo adjustment factor (default: 1.0; min: 0.2; max: 4.0)	
--min-measure-width <i>	The minimal measure width in MEI units (default: 15; min: 1; max: 30)	
--repeat-bar-line-dot-separation <f>	The default horizontal distance between the dots and the inner barline of a repeat barline (default: 0.3; min: 0.1; max: 1.0)	

Name and parameter	Description	See also
--repeat-ending-line-thickness <f>	Repeat and ending line thickness (default: 0.15; min: 0.1; max: 2.0)	
--slur-control-points <i>	Slur control points - higher value means more curved at the end (default: 5; min: 1; max: 10)	
--slur-curve-factor <i>	Slur curve factor - high value means rounder slurs (default: 10; min: 1; max: 100)	
--slur-endpoint-thickness <f>	The Endpoint slur thickness in MEI units (default: 0.1; min: 0.05; max: 0.25)	
--slur-height-factor <i>	Slur height factor - high value means flatter slurs (default: 5; min: 1; max: 100)	
--slur-max-height <f>	The maximum slur height in MEI units (default: 3.0; min: 2.0; max: 6.0)	
--slur-max-slope <i>	The maximum slur slope in degrees (default: 20; min: 0; max: 60)	
--slur-midpoint-thickness <f>	The midpoint slur thickness in MEI units (default: 0.6; min: 0.2; max: 1.2)	
--slur-min-height <f>	The minimum slur height in MEI units (default: 1.2; min: 0.3; max: 2.0)	
--spacing-brace-group <i>	Minimum space between staves inside a braced group in MEI units (default: 12; min: 0; max: 48)	
--spacing-bracket-group <i>	Minimum space between staves inside a bracketed group in MEI units (default: 12; min: 0; max: 48)	
--spacing-dur-detection	Detect long duration for adjusting spacing	
--spacing-linear <f>	Specify the linear spacing factor (default: 0.25; min: 0.0; max: 1.0)	
--spacing-non-linear <f>	Specify the non-linear spacing factor (default: 0.6; min: 0.0; max: 1.0)	
--spacing-staff <i>	The staff minimal spacing in MEI units (default: 12; min: 0; max: 48)	
--spacing-system <i>	The system minimal spacing in MEI units (default: 12; min: 0; max: 48)	
--staff-line-width <f>	The staff line width in unit (default: 0.15; min: 0.1; max: 0.3)	
--stem-width <f>	The stem width (default: 0.2; min: 0.1; max: 0.5)	
--sub-bracket-thickness <f>	The thickness of system sub-bracket (default: 0.2; min: 0.1; max: 2.0)	
--system-divider <s>	The display of system dividers (default: "auto"; other values: ['none', 'auto', 'left', 'left-right'])	
--system-max-per-page <i>	Maximun number of systems per page	
--text-enclosure-thickness <f>	The thickness of the line text enclosing box (default: 0.2; min: 0.1; max: 0.8)	
--thick-barline-thickness <f>	The thickness of the thick barline (default: 1.0; min: 0.5; max: 2.0)	

Name and parameter	Description	See also
--tie-endpoint-thickness <f>	The Endpoint tie thickness in MEI units (default: 0.1; min: 0.05; max: 0.25)	
--tie-midpoint-thickness <f>	The midpoint tie thickness in MEI units (default: 0.5; min: 0.2; max: 1.0)	
--tuplet-bracket-thickness <f>	The thickness of the tuplet bracket (default: 0.2; min: 0.1; max: 0.8)	
--tuplet-num-head	Placement of tuplet number on the side of the note head	

Element selectors and processing

Name and parameter	Description	See also
--app-x-path-query * <s>	Set the xPath query for selecting child elements, for example: <code>"/rdg[contains(@source, 'source-id')]"</code> ; by default the or the first is selected	
--choice-x-path-query * <s>	Set the xPath query for selecting child elements, for example: <code>"/orig"</code> ; by default the first child is selected	
--mdiv-x-path-query <s>	Set the xPath query for selecting the to be rendered; only one can be rendered (default: <code>""</code>)	
--subst-x-path-query * <s>	Set the xPath query for selecting child elements, for example: <code>"/del"</code> ; by default the first child is selected	
--transpose <s>	SUMMARY (default: <code>""</code>)	Transposition
--transpose-selected-only	Transpose only the selected content and ignore unselected editorial content	

Element margins

Name and parameter	Description	See also
--bottom-margin-artic <f>	The margin for artic in MEI units (default: 0.75; min: 0.0; max: 10.0)	
--bottom-margin-harm <f>	The margin for harm in MEI units (default: 1.0; min: 0.0; max: 10.0)	
--bottom-margin-header <f>	The margin for header in MEI units (default: 8.0; min: 0.0; max: 24.0)	
--default-bottom-margin <f>	The default bottom margin (default: 0.5; min: 0.0; max: 5.0)	
--default-left-margin <f>	The default left margin (default: 0.0; min: 0.0; max: 2.0)	
--default-right-margin <f>	The default right margin (default: 0.0; min: 0.0; max: 2.0)	
--default-top-margin <f>	The default top margin (default: 0.5; min: 0.0; max: 6.0)	
--left-margin-accid <f>	The margin for accid in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-bar-line <f>	The margin for barLine in MEI units (default: 0.0; min: 0.0; max: 2.0)	

Name and parameter	Description	See also
--left-margin-beat-rpt <f>	The margin for beatRpt in MEI units (default: 2.0; min: 0.0; max: 2.0)	
--left-margin-chord <f>	The margin for chord in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-clef <f>	The margin for clef in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-key-sig <f>	The margin for keySig in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-left-bar-line <f>	The margin for left barLine in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-m-rest <f>	The margin for mRest in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--left-margin-m-rpt2 <f>	The margin for mRpt2 in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--left-margin-mensur <f>	The margin for mensur in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-meter-sig <f>	The margin for meterSig in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-multi-rest <f>	The margin for multiRest in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--left-margin-multi-rpt <f>	The margin for multiRpt in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--left-margin-note <f>	The margin for note in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-rest <f>	The margin for rest in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--left-margin-right-bar-line <f>	The margin for right barLine in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--right-margin-accid <f>	The right margin for accid in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-bar-line <f>	The right margin for barLine in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-beat-rpt <f>	The right margin for beatRpt in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-chord <f>	The right margin for chord in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-clef <f>	The right margin for clef in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--right-margin-key-sig <f>	The right margin for keySig in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--right-margin-left-bar-line <f>	The right margin for left barLine in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--right-margin-m-rest <f>	The right margin for mRest in MEI units (default: 0.0; min: 0.0; max: 2.0)	

Name and parameter	Description	See also
--right-margin-m-rpt2 <f>	The right margin for mRpt2 in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-mensur <f>	The right margin for mensur in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--right-margin-meter-sig <f>	The right margin for meterSig in MEI units (default: 1.0; min: 0.0; max: 2.0)	
--right-margin-multi-rest <f>	The right margin for multiRest in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-multi-rpt <f>	The right margin for multiRpt in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-note <f>	The right margin for note in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-rest <f>	The right margin for rest in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--right-margin-right-bar-line <f>	The right margin for right barLine in MEI units (default: 0.0; min: 0.0; max: 2.0)	
--top-margin-artic <f>	The margin for artic in MEI units (default: 0.75; min: 0.0; max: 10.0)	
--top-margin-harm <f>	The margin for harm in MEI units (default: 1.0; min: 0.0; max: 10.0)	

Installing or building from sources

Secret page ;-) with tests for syntax highlighting...

Compile from sources is easy.

TERMINAL

```
ls -a
echo "Hello World!"
```

HTML / JAVASCRIPT

```
<html>
  <head>
    <script src="http://www.verovio.org/javascript/latest/verovio-toolkit-wasm.js" defer></script>
  </head>
  <body>
    <h1>Hello Verovio!</h1>
    <div id="notation"></div>
  </body>
</html>
```

JAVASCRIPT

```
int main() {
  var string;
  return 0;
}
```

JSON

```
{
  "adjustPageHeight":true,
  "breaks":"none",
  "pageHeight":2970,
  "pageWidth":2100,
  "header":"none",
  "footer":"none",
  "scale":50,
  "spacingStaff":4
}
```

C++

```
int main() {
  std::string string;
  return 0;
}
```

PYTHON

```
int main() {  
    std::string string;  
    return 0;  
}
```

XML

```
<?xml version="1.0" encoding="UTF-8"?>  
<?xml-model href="https://music-encoding.org/schema/4.0.0/mei-all.rng" type="application/xml" schematypens=  
"http://relaxng.org/ns/structure/1.0" ?>  
<?xml-model href="https://music-encoding.org/schema/4.0.0/mei-all.rng" type="application/xml" schematypens=  
"http://purl.oclc.org/dsdl/schematron" ?>  
<mei xmlns="http://www.music-encoding.org/ns/mei" meiversion="4.0.0">  
  <meiHead>  
    <fileDesc>  
      <titleStmt>  
        <title>Measure barline example</title>  
      </titleStmt>  
      <pubStmt>  
        <date>2017-05-04</date>  
      </pubStmt>  
      <seriesStmt>  
        <title>Verovio test suite</title>  
      </seriesStmt>  
      <notesStmt>  
        <annot>Verovio supports various types of barline for the "measure" elements. It also supports "scale" att  
ributes on "staffDef".</annot>  
      </notesStmt>  
    </fileDesc>  
  </meiHead>  
</mei>
```

Command-line version

Verovio codebase is C++17 compliant and is cross-platform. It has been tested on several operating systems and architectures. This section describes how to build the command-line version of the toolkit from the command-line or using some of the most popular IDEs. There are currently no pre-build binaries of the command-line toolkit available since building it is very straightforward.

MacOS or Linux

To build the command-line tool, you need [CMake](#) to be installed on your machine as well as a compiler supporting C++17. The commands to build are the following:

TERMINAL

```
cd tools  
cmake ../cmake  
make
```

This generates a verovio binary within ./tools. You can run Verovio from there or install it. Installing it means copying the executable and the resource files to directories whose paths are globally accessible. You simply need to run:

TERMINAL

```
sudo make install
```

If you do not install it and run it from `./tools` or from another directory, you need to use the `-r` option to set the appropriate resource directory. The parameter of the `-r` option has to be a path to the `./data` folder of the codebase.

Keep in mind that if you have installed, you should not run another version without re-installing it or using the `-r` options because otherwise the resources installed can be invalid. A typical problem is missing font glyphs that a newer version needs but that are not in the older version of the resources.

For seeing the command-line options, run:

TERMINAL

```
./verovio --help
```

(Until version 2.6.0, the `cmake` command was `cmake .` and not `cmake ../cmake .`)

Additional building options

By default the executable is not stripped. To strip it during the installation do

TERMINAL

```
sudo make install/strip
```

For building it without Plain and Easy support (without `regex.h`), run:

TERMINAL

```
cmake ../cmake -DNO_PAE_SUPPORT=ON
```

To allow PAE support again, you must run the command

TERMINAL

```
cmake ../cmake -DNO_PAE_SUPPORT=OFF
```

since running `cmake ../cmake` will not clear the state of the define variable.

The other building options are:

- `NO_ABC_SUPPORT` for the ABC importer to be turned on/off
- `NO_HUMDRUM_SUPPORT` for the Humdrum importer to be turned on/off
- `MUSICXML_DEFAULT_HUMDRUM` to use the MusicXML Humdrum importer by default instead of the direct MusicXML importer
- `BUILD_AS_LIBRARY` for Verovio to be built as dynamic shared library instead of a command-line executable

Uninstall a previous version

To uninstall a previously installed version of Verovio from the system, run:

TERMINAL

```
rm -f /usr/local/bin/verovio  
rm -rf /usr/local/share/verovio
```

Occasionally there are problems with updates necessary to the `Makefile` when compiling a new version of Verovio with `make`. It may be necessary to clear out the automatically generated `cmake` files and regenerate them. To do that, run:

TERMINAL

```
rm -rf CMakeFiles CMakeCache.txt Makefile cmake_install.cmake
```

Windows 10

To build Verovio on Windows 10 from the command-line, you will need to have [Microsoft C++ Build Tools](#) and [make](#) installed on your computer.

Run the following commands from the *x86 Native Tools Command Prompt for VS* (with administrator privileges):

TERMINAL

```
cd <sourceCode>/tools  
cmake ../cmake -G "NMake Makefiles"  
nmake  
nmake install
```

After the installation, add <sourceCode>/tools to the PATH of your system.

When running the commands, the resource path should be provided explicitly with the following option:

TERMINAL

```
-r "C:/Program Files (x86)/Verovio/share/verovio"
```

Xcode

For MacOS users, there is also an Xcode project in the Verovio root directory.

By default, humdrum support is turned off in Xcode. To turn it on, you need to use the `Verovio-Humdrum` building scheme.

Visual Studio

- Install CMake
- Go into the tools folder of Verovio
- Execute `cmake ../cmake -DNO_PAE_SUPPORT=ON` (add `-DCMAKE_GENERATOR_PLATFORM=x64` for a x64 solution)
- Open the resulting `Verovio.sln` with Visual Studio and build it from there

JavaScript and WebAssembly

Pre-build versions

The [verovio.org GitHub repository](https://github.com/verovio/verovio) provides compiled versions of the JavaScript toolkit. The toolkit is available in three options.

1. **verovio-toolkit.js** - in JavaScript (more precisely in asm.js)
2. **verovio-toolkit-wasm.js** – in WebAssembly
3. **verovio-toolkit-hum.js** – in JavaScript with the Humdrum support

A build of each of these is provided by CI for the development version as well as for each release.

The latest release is always available from:

```
https://www.verovio.org/javascript/latest/verovio-toolkit.js
```

The latest development version is available from:

```
https://www.verovio.org/javascript/develop/verovio-toolkit.js
```

Previous releases are available from their corresponding directory, e.g.:

```
https://www.verovio.org/javascript/2.7.1/verovio-toolkit.js
```

NPM

The latest stable version is available via NPM registry. The version distributed via NPM is the WebAssembly build. It can be installed with:

TERMINAL

```
npm install verovio
```

The homepage of the Verovio package includes documentation on how to use it.

Basic usage of the toolkit

For instructions on a basic usage of the JavaScript version of the toolkit, see the [Getting started](#) section of the [Tutorial 1: Web-based notation](#) chapter.

Building the toolkit

To build the JavaScript toolkit you need to have the [Emscripten](#) compiler installed on your machine. You also need [CMake](#). You need to run:

TERMINAL

```
cd emscripten
./buildToolkit -H
```

The toolkit will be written to:

```
./emscripten/build/verovio-toolkit.js
```

Building without `-H` will include the Humdrum support, which increases the size of the toolkit by about one third. In that case, the output will be written to `verovio-toolkit-hum.js`.

If you are building with another option set than previously, or if you want to regenerate the makefiles, add the option `-M`.

Python

Pre-build versions

Pre-build versions of the Python version of the toolkit are available through [PyPi](#) for every release since version 3.1.0.

The Python versions for which a pre-build is provided are 3.6, 3.7, 3.8 and 3.9. The platforms supported are MacOS 10.9, Linux with [manylinux](#) for x86-64, Win-32 and Win-amd64.

The latest release can be installed with:

TERMINAL

```
pip install verovio
```

A previous version can be installed with:

TERMINAL

```
pip install verovio==3.2.0
```

For all platforms or architectures for which a pre-build version is not available in the PyPi repository, a source distribution is available. It can be installed with the same command as above. This will automatically trigger the compilation of the package.

Basic usage of the toolkit

Once installed, the Verovio toolkit module can be imported with

PYTHON

```
import verovio
```

You can then create an instance of the toolkit and load data. For example:

PYTHON

```
tk = verovio.toolkit()
tk.loadFile("path-to-mei-file")
tk.getPageCount()
```

Once loaded, the data can be rendered to a string:

PYTHON

```
svg_string = tk.renderToSVG(1)
```

It can also be rendered to a file:

PYTHON

```
tk.renderToSVGFile( "page.svg", 1 )
```

Setting options

The options are set on the toolkit instance. For example, the following code will change the dimensions of the page and redo the layout for the previously loaded data:

PYTHON

```
tk.setOption( "pageHeight", "2100" )
tk.setOption( "pageWidth", "2900" )
tk.setScale(25)
tk.redoLayout()
tk.renderToSVGFile( "page-scaled.svg", 1 )
```

It is also possible to collect options in a Python Dictionary and pass them as Json dump to the toolkit:

PYTHON

```
import json
options = {
    'pageHeight': 1000,
    'pageWidth': 1000
}
tk.setOptions(json.dumps(options))
tk.redoLayout()
tk.renderToSVGFile( "page-square.svg", 1 )
```

Building the toolkit

To build the Python toolkit you need to have swig and swig-python installed on your machine (see [SWIG](#)) and the Python distutils package. Version 4.0 or newer of SWIG is recommended but older versions should work too. To install SWIG in MacOS using [Homebrew](#), type the command `brew install swig`.

The toolkit needs to be built from the root directory of the repository content. To build it in-place, run:

TERMINAL

```
python setup.py build_ext --inplace
```

If you want to install it, run:

TERMINAL

```
python setup.py build_ext
sudo python setup.py install
```

For building it with one or more specific options (e.g., without Plain and Easy support), run:

TERMINAL

```
python setup.py build_ext --inplace --define NO_PAE_SUPPORT
```

Building a Python wheel locally

You can build a Python wheel locally with:

TERMINAL

```
python setup.py bdist
```

For a source distribution, do:

TERMINAL

```
python setup.py sdist
```

In both cases, the wheel will be written to the `./dist` directory.

Building with CMake

The Python toolkit can be built with [CMake](#), which can be significantly faster because parallel processing can be used. This is also the approach to recommend when developing because it will not rebuild the entire codebase when a change it made to a file but only the files that actually need to rebuilt.

For this approach to work you need at least version 3.13 of CMake because it uses the option `-B` introduced in that version of CMake. The steps are:

TERMINAL

```
cd bindings
cmake ../cmake -B python -DBUILD_AS_PYTHON=ON
cd python
make -j8
```

If you want to enable or disable other specific options, you can do:

TERMINAL

```
cmake ../cmake -B python -DBUILD_AS_PYTHON=ON -DNO_PAE_SUPPORT=ON
```

Installation with CMake has not be tested yet

Resources for versions built locally

When using a version built locally, you usually have to specify the path to the Verovio resources. To do so, you can do

PYTHON

```
import verovio
tk = verovio.toolkit(False)
tk.setResourcePath("path-to-resource-dir")
```

Alternatively, you can set it before you create the instance of the toolkit

PYTHON

```
import verovio
verovio.setDefaultResourcePath("path-to-resource-dir")
tk = verovio.toolkit()
```

Other bindings

Java

To build the Java toolkit you need to have [swig](#) and [swig-java](#) installed on your machine (see [SWIG](#)) as well as [Maven](#). You need to run:

TERMINAL

```
cd bindings/java
mvn package
mvn package
```


Note the `mvn package` command needs to be run twice. You can test it with the MEI and PAE examples. For example – replace `X.X.X` with the appropriate version number:

TERMINAL

```
cd example-mei
javac -cp ../target/VerovioToolkit-X.X.X.jar main.java
java -cp ../target/VerovioToolkit-X.X.X.jar main
```

This should write an `output.svg` file in the current directory. The PAE example will write the SVG to the standard output.

See [this](#) issue for SVG output problems on non US Ubuntu installations.

CocoaPods

You can use [CocoaPods](#) to install Verovio by adding it to your Podfile :

```
platform :ios, '12.0'
use_frameworks!
target 'MyApp' do
  pod 'Verovio', :git => 'https://github.com/rism-ch/verovio.git', :branch => 'develop'
end
```

Then, run the following command:

TERMINAL

```
pod install
```

To use Verovio in your iOS project import

C++

```
#import <Verovio/Verovio-umbrella.h>
```

See <https://github.com/Noroxs/VerovioExample> for an example how to use it. To build and run the example, you need to:

- Navigate in the Terminal to the cloned directory
- Execute `pod update`
- Open the `VerovioExample.xcworkspace` and NOT the `VerovioExample.xcodeproj`
- Build and Run on any simulator or device

Contributing

Introduction

Coding guidelines

This document describes the coding style for the Verovio project for the C++ part of the codebase.

Formatting

Verovio uses a [Clang-Format \(5.0\)](#) coding style based on the [WebKit](#) style, with a few minor modifications. The modifications include:

```
AllowShortIfStatementsOnASingleLine: true
AllowShortLoopsOnASingleLine: true
ColumnLimit: 120
ConstructorInitializerAllOnOneLineOrOnePerLine: true
PointerAlignment: Right
```

The simplest way to fulfil the Verovio coding style is to use a clang-format tool and to apply the style defined in the [.clang-format](#) file available in the project root directory.

Downloading clang-format for OS X

An easy way to install clang-format on OS X computers is to use [Hombrew](#). Type this command in the terminal to install:

TERMINAL

```
brew install clang-format
```

Running clang-format

Please make sure you use version 5.0

To use clang-format to adjust a single file:

TERMINAL

```
clang-format -style=file -i some-directory/some-file.cpp
```

The `-style=file` option instructs clang-format to search for the `.clang-format` configuration file (recursively in some parent directory). The `-i` option is used to alter the file "in-place". If you don't give the `-i` option, a formatted copy of the file will be sent to standard output.

Includes and forward declarations

Includes in the header files must list first the system includes followed by the Verovio includes, if any, and then the includes for the libraries included in Verovio. All includes have to be ordered alphabetically:

C++

```

#include <string>
#include <utility>
#include <vector>

//-----

#include "attclasses.h"
#include "atttypes.h"

//-----

#include "pugixml.hpp"
#include "utf8.h"

```

In the header files, always use forward declarations (and not includes) whenever possible. Forward declaration have to be ordered alphabetically:

```

C++

class DeviceContext;
class Layer;
class StaffAlignment;
class Syl;
class TimeSpanningInterface;

```

In the implementation files, the first include in always the include of the corresponding header file, followed by the system includes and then the other Verovio includes with libraries at the end too, if any, also ordered alphabetically:

```

C++

#include "att.h"

//-----

#include <sstream>
#include <stdlib.h>

//-----

#include "object.h"
#include "vrv.h"

//-----

#include "pugixml.hpp"

```

Null and boolean

The null pointer value should be written as `NULL` . Boolean values should be written as `true` and `false` .

Class, method and member names

All class names must be in upper CamelCase. The internal capitalization follows the MEI one:

```

C++

class Measure;
class ScoreDef;
class StaffDef;

```

All method names must also be in upper CamelCase:

```
C++  
  
void Measure::AddStaff(Staff *staff) {}
```

All member names must be in lower camelCase. Instance members must be prefixed with `m_` and class (static) members with `s_`:

```
C++  
  
class Glyph {  
public:  
  
    /** An instance member */  
    int m_unitsPerEm;  
  
    /** A static member */  
    static std::string s_systemPath;  
};
```

In the class declaration, the methods are declared first, and then the member variables. For both, the declaration order is `public`, `protected`, and `private`.

Comments

Comments for describing methods can be grouped using `///@{` and `///@}` delimiters together with the `@name` indication:

```
C++  
  
/**  
 * @name Add children to an editorial element.  
 */  
///@{  
void AddFloatingElement(FloatingElement *child);  
void AddLayerElement(LayerElement *child);  
void AddTextElement(TextElement *child);  
///@}
```

LibMEI

The code for the attribute classes of Verovio are generated from the MEI schema using a modified version of LibMEI available [here](#). The code generated is included in the Verovio repository in `./libmei` and the LibMEI repository does not need to be cloned for building Verovio.

The attribute classes generated from the MEI schema provide all the members for the element classes of Verovio. They are implemented via multiple inheritance in element classes. The element classes corresponding to the MEI elements are not generated by LibMEI but are implemented explicitly in Verovio. They all inherit from the `Object` class (of the `vrv` namespace) or from a `Object` child class. They can inherit from various interfaces used for the rendering. All the MEI member are defined through the inheritance of generated attribute classes, either grouped as interfaces or individually.

For example, the MEI `<note>` is implemented as a `Note` class that inherit from `Object` through `LayerElement`. It also inherit from the `StemmedDrawingInterface` that holds data used for the rendering.

Its MEI members are defined through the `DurationInterface` and `PitchInterface` that regroup common fonctionnalities for durational and pitched MEI elements respectively plus some additional individual attribute classes.

The inheritance should always list `Object` (or the `Object` child class) first, followed by the rendering interfaces, followed by the attribute class interfaces, followed by the individual attribute classes, each of them ordered alphabetically:

C++

```
class Note : public LayerElement,
            public StemmedDrawingInterface,
            public DurationInterface,
            public PitchInterface,
            public AttColoration,
            public AttGraced,
            public AttStems,
            public AttTiepresent
```

In the implementation, the same order must be followed, for the constructor calls and for the registration of the interfaces and individual attribute classes:

C++

```
Note::Note()
: LayerElement("note-")
, StemmedDrawingInterface()
, DurationInterface()
, PitchInterface()
, AttColoration()
, AttGraced()
, AttStems()
, AttTiepresent()
{
    RegisterInterface(DurationInterface::GetAttClasses(), DurationInterface::IsInterface());
    RegisterInterface(PitchInterface::GetAttClasses(), PitchInterface::IsInterface());
    RegisterAttClass(ATT_COLORATION);
    RegisterAttClass(ATT_GRACED);
    RegisterAttClass(ATT_STEMS);
    RegisterAttClass(ATT_TIEPRESENT);

    Reset();
}
```

Resetting the attributes is required and follows the same order

C++

```
void Note::Reset()
{
    LayerElement::Reset();
    StemmedDrawingInterface::Reset();
    DurationInterface::Reset();
    PitchInterface::Reset();
    ResetColoration();
    ResetGraced();
    ResetStems();
    ResetTiepresent();

    // ...
}
```

Contributing workflow

Generate code with libMEI

Adding SMuFL glyphs

All SMuFL glyphs used by Verovio have to be available in the Leipzig font. For adding support for a new SMuFL glyph, the steps are:

1. Add the glyph to the Leipzig font file
2. Generate the Leipzig font as SVG font
3. Add the glyph to the list of supported glyph in the XSL list

Make sure you always add glyphs **only** in the develop-leipzig branch because conflict solving is problematic with the process of adding a glyph, in particular for the Leipzig font file. For this reason, make sure you always pull the latest version from the develop-leipzig branch before starting your work and do not wait too long before making a PR. If changes have been made in between, you will need to add your glyphs again.

When making a PR, always add an image (e.g., screenshot of FontForge) showing the glyphs.

Adding the glyph to the Leipzig font file

The file is `./fonts/Leipzig-5.2.sfd` and should be edited with FontForge. Very often it is possible to copy another existing glyph as basis for the new glyph. Leipzig is visually lighter and thinner than Bravura and new glyphs have to follow this design choice. Do not copy glyphs from Bravura. Make sure the font is valid by running "Element => "Find Problems...".

Once the new glyph(s) has/have been added, you also need to change the version number in the font info (menu "Element" => "Font Info" and then tab "PS Names" in fields "Version" and "Copyright" and tab "Comment" where you also need to add a comment together with the version number. The file can be saved.

Generate the Leipzig font as SVG font

From FontForge, export the with menu "File" => "Generate Fonts..." and select "SVG font" (option "validate before saving" can be turned off). The file needs to be written to `./fonts/Leipzig.svg`.

Add the glyph to the list of supported glyph in the XSL list

Open the file `./fonts/supported.xml` and uncomment the glyph(s) you added to Leipzig. The XSL file is then used to extract the glyphs supported by Verovio

Make a PR to the develop-leipzig branch

Once the PR will have been merged, the glyphs will be extracted from the SVG font by running the script `./fonts/generate_all.sh` (from `./fonts/`). This will extract all the glyphs from the SVG font file and calculate the their bounding boxes. When this is done you will see your glyphs in `./data/` and in `./include/vrv/smufl.h`

Table of Contents

Introduction	1
About Verovio	1
About this book	1
Getting help	1
Licensing	1
What is allowed	1
What is required	2
What is not allowed	2
What is recommended	2
Overview	2
There?	2
Tutorial 1: Web-based notation	3
Layout options	3
Score navigation	3
Tutorial 2: Interactive notation	4
Introduction	4
Inspecting the SVG	5
Working with CSS and SVG	5
XPath queries	6
Beyond tutorials: Advanced topics	7
Introduction	7
Transposition	7
SMuFL fonts	7
Embedded fonts	7
Selecting a font	7
Controlling the SVG output	7
HTML5	7
Towards SVG 2.0	7
Converting to PDF	7
Mensural notation	7
Duration alignment	7
Layout	7
Ligatures	7
Toolkit Reference	8
Input formats	8
MEI	8
humdrum	8
MusicXML	8
Plain and Easy	8
ABC	8
Output formats	8
SVG	8
MEI	8
MIDI	8
Timemap	8
Toolkit methods	8
Edit	8

EditInfo	8
GetAvailableOptions	9
More info here	9
GetElementAttr	9
GetElementsAtTime	9
GetExpansionIdsForElement	10
GetHumdrum	10
GetHumdrum	10
GetHumdrumBuffer	11
GetHumdrumFile	11
GetInputFrom	11
GetLog	12
GetMEI	12
GetMIDIValuesForElement	12
GetNotatedIdForElement	13
GetOption	13
GetOptions	13
GetOptions	14
GetOutputTo	14
GetPageCount	14
GetPageWithElement	15
GetScale	15
GetTimeForElement	15
GetTimesForElement	16
GetUuid	16
GetVersion	16
IdentifyInputFrom	17
LoadData	17
LoadFile	17
LoadZipDataBase64	18
LoadZipDataBuffer	18
RedoLayout	19
RedoPagePitchPosLayout	19
RenderToDeviceContext	19
RenderToMIDI	20
RenderToMIDIFile	20
RenderToPAE	20
RenderToPAEFile	21
RenderToSVG	21
RenderToSVGFile	21
RenderToTimemap	22
RenderToTimemapFile	22
SaveFile	22
SetHumdrumBuffer	23
SetInputFrom	23
SetInputFrom	24
SetOption	24
SetOptions	24
SetOutputTo	25
SetResourcePath	25

SetScale	25
Toolkit	26
Toolkit options	26
Base short options	26
Input and page layout options	27
General layout options	28
Element selectors and processing	31
Element margins	31
Installing or building from sources	34
Command-line version	35
MacOS or Linux	35
Additional building options	36
Uninstall a previous version	36
Windows 10	36
Xcode	37
Visual Studio	37
JavaScript and WebAssembly	37
Pre-build versions	37
NPM	37
Basic usage of the toolkit	38
Building the toolkit	38
Python	38
Pre-build versions	38
Basic usage of the toolkit	38
Setting options	39
Building the toolkit	39
Building a Python wheel locally	39
Building with CMake	40
Resources for versions built locally	40
Other bindings	40
Java	40
CocoaPods	41
Contributing	42
Introduction	42
Coding guidelines	42
Formatting	42
Downloading clang-format for OS X	42
Running clang-format	42
Includes and forward declarations	42
Null and boolean	43
Class, method and member names	43
Comments	44
LibMEI	44
Contributing workflow	45
Generate code with libMEI	45
Adding SMuFL glyphs	46
Adding the glyph to the Leipzig font file	46
Generate the Leipzig font as SVG font	46
Add the glyph to the list of supported glyph in the XSL list	46
Make a PR to the develop-leipzig branch	46

<hr/>	
-------	--