

Keybinds

Neovim Keybinds

Leader is `Space`.

Normal Mode

Keybind	What it does
<code><leader>pv</code>	Open netrw file explorer with <code>:Ex</code> .
<code><C-i></code>	Preserve default jump-forward behavior.
<code>J</code>	Join current line with next line and keep cursor position.
<code><C-d></code>	Move half-page down and center cursor.
<code><C-u></code>	Move half-page up and center cursor.
<code>n</code>	Next search result, centered and unfolded.
<code>N</code>	Previous search result, centered and unfolded.
<code>*</code>	Search word under cursor forward, centered and unfolded.
<code>#</code>	Search word under cursor backward, centered and unfolded.
<code>g*</code>	Search partial word under cursor forward, centered and unfolded.
<code>g#</code>	Search partial word under cursor backward, centered and unfolded.
<code><leader>y</code>	Yank to system clipboard.
<code><leader>Y</code>	Yank current line to system clipboard.
<code><leader>d</code>	Delete to black-hole register.
<code>Q</code>	Disabled.
<code><leader>f</code>	Format current buffer through LSP.
<code><C-k></code>	Jump to next quickfix item and center cursor.
<code><C-j></code>	Jump to previous quickfix item and center cursor.
<code><leader>k</code>	Jump to next location-list item and center cursor.
<code><leader>j</code>	Jump to previous location-list item and center cursor.
<code><leader>s</code>	Start project-wide substitute for word under cursor.
<code><leader>x</code>	Run <code>chmod +x</code> on the current file.
<code><leader>vpp</code>	Edit <code>~/ .config/nvim/lua/toofaeded/lazy.lua</code> .
<code><leader>mr</code>	Run <code>CellularAutomaton make_it_rain</code> .
<code><leader><leader></code>	Source the current file.
<code><C-a></code>	Select the entire buffer.
<code>gd</code>	Go to LSP definition.
<code>gD</code>	Go to LSP declaration.

Keybind	What it does
<code>gI</code>	Go to LSP implementation.
<code>gr</code>	Show LSP references.
<code>gl</code>	Open diagnostic float.
<code><leader>K</code>	Show LSP hover documentation.
<code><leader>vws</code>	Search LSP workspace symbols.
<code><leader>vd</code>	Open diagnostic float.
<code><leader>vca</code>	Run LSP code action.
<code><leader>vrn</code>	Rename symbol with LSP.

Command Mode

Keybind	What it does
<code><C-k></code>	Select previous completion item in command-line completion.
<code><C-j></code>	Select next completion item in command-line completion.
<code><Up></code>	Select previous completion item in command-line completion.
<code><Down></code>	Select next completion item in command-line completion.
<code><C-b></code>	Scroll completion documentation up.
<code><C-f></code>	Scroll completion documentation down.
<code><C-Space></code>	Trigger completion.
<code><C-e></code>	Close command-line completion.
<code><C-y></code>	Confirm selected completion item.

Insert Mode

Keybind	What it does
<code><C-c></code>	Leave insert mode like <code><Esc></code> .
<code><C-k></code>	Select previous completion item.
<code><C-j></code>	Select next completion item.
<code><Up></code>	Select previous completion item.
<code><Down></code>	Select next completion item.
<code><C-b></code>	Scroll completion documentation up.
<code><C-f></code>	Scroll completion documentation down.
<code><C-Space></code>	Trigger completion.

Keybind	What it does
<C-e>	Abort completion.
<C-y>	Confirm selected completion item.
<C-l>	Select next completion item, expand snippet, or jump forward in snippet.
<C-h>	Select previous completion item or jump backward in snippet when completion/snippets are active; otherwise falls back, so LSP signature help may run in LSP buffers.
<M-l>	Accept Copilot suggestion.
<M-j>	Next Copilot suggestion.
<M-k>	Previous Copilot suggestion.
<M-h>	Dismiss Copilot suggestion.
<c-\>	Toggle ToggleTerm terminal.

Splits and Buffers

Keybind	What it does
<M-h>	Move to left split.
<M-j>	Move to lower split.
<M-k>	Move to upper split.
<M-l>	Move to right split.
<M-Tab>	Disabled.
<Leader>pb	Pick open buffers with Telescope.
<C-e>	Toggle Harpoon quick menu.
<C-h>	Jump to Harpoon item 1.
<C-t>	Jump to Harpoon item 2.
<C-n>	Jump to Harpoon item 3.
<C-s>	Jump to Harpoon item 4.
<C-S-P>	Go to previous Harpoon item.
<C-S-N>	Go to next Harpoon item.
<c-g>	Toggle nvim-tree.
?	Show nvim-tree help when focused in nvim-tree.
<Leader>t	Toggle default terminal.
<Leader>th	Open horizontal terminal.
<Leader>tv	Open vertical terminal.
<Leader>tf	Open floating terminal.
<M-1>	Toggle horizontal terminal from normal or terminal mode.
<M-2>	Toggle vertical terminal from normal or terminal mode.

Keybind	What it does
<code><M-3></code>	Toggle floating terminal from normal or terminal mode.
Terminal <code><M-h></code>	Leave terminal mode and move to left split.
Terminal <code><M-j></code>	Leave terminal mode and move to lower split.
Terminal <code><M-k></code>	Leave terminal mode and move to upper split.
Terminal <code><M-l></code>	Leave terminal mode and move to right split.
Terminal <code><LeftRelease></code>	Re-enter insert mode after mouse release in terminal buffer.

Visual Mode

Keybind	What it does
<code>J</code>	Move selected lines down and reindent.
<code>K</code>	Move selected lines up and reindent.
<code><</code>	Indent left and keep selection.
<code>></code>	Indent right and keep selection.
<code><leader>p</code>	Paste over selection without replacing default register.
<code><leader>y</code>	Yank selection to system clipboard.
<code><leader>d</code>	Delete selection to black-hole register.
<code><leader>ri</code>	Refactoring.nvim inline variable.
<code><leader>hs</code>	Stage selected Git hunk range.
<code><leader>hr</code>	Reset selected Git hunk range.
<code>ih</code>	Select Git hunk text object in visual/operator-pending mode.
<code>s</code>	Leap forward target in visual/operator-pending mode.
<code>S</code>	Leap backward target in visual/operator-pending mode.
<code>gs</code>	Leap target across windows in visual/operator-pending mode.
<code><C-Space></code>	Start or expand Treesitter incremental selection.
<code><C-s></code>	Expand Treesitter selection by scope.
<code><M-Space></code>	Shrink Treesitter selection.
<code>aa</code>	Select Treesitter parameter outer.
<code>ia</code>	Select Treesitter parameter inner.
<code>af</code>	Select Treesitter function outer.
<code>if</code>	Select Treesitter function inner.
<code>ac</code>	Select Treesitter class outer.
<code>ic</code>	Select Treesitter class inner.

Plugin-Based

Keybind	What it does
<leader>a	Add current file to Harpoon list.
<leader>pf	Telescope find files.
<C-p>	Telescope Git files.
<leader>pws	Telescope grep word under cursor.
<leader>plws	Telescope grep WORD under cursor.
<leader>ps	Telescope grep prompted text.
<leader>vh	Telescope help tags.
<leader>pd	Telescope project discovery.
<leader>ph	Telescope project history.
<leader>n	Telescope notification history.
<leader>h	Open Alpha dashboard.
<leader>u	Toggle Undotree.
<leader>tt	Toggle Trouble.
<leader>tn	Jump to next Trouble item, skipping groups.
<leader>tp	Jump to previous Trouble item, skipping groups.
<leader>gd	Open Diffview.
<leader>gdc	Close Diffview.
<leader>gg	Open LazyGit.
<leader>gs	Open Fugitive Git status.
<leader>gp	Fugitive Git push from a Fugitive buffer.
<leader>ga	Fugitive Git add all from a Fugitive buffer.
<leader>gc	Fugitive Git commit with prompted message from a Fugitive buffer.
<leader>gP	Fugitive Git pull with rebase from a Fugitive buffer.
<leader>gt	Start Fugitive push with upstream target from a Fugitive buffer.
]c	Next Git hunk, or default diff next change in diff mode.
[c	Previous Git hunk, or default diff previous change in diff mode.
<leader>hs	Stage current Git hunk.
<leader>hr	Reset current Git hunk.
<leader>hS	Stage current buffer.
<leader>hR	Reset current buffer.
<leader>hp	Preview Git hunk.
<leader>hi	Preview Git hunk inline.
<leader>hb	Show full Git blame for current line.

Keybind	What it does
<code><leader>hd</code>	Diff current file against index.
<code><leader>hD</code>	Diff current file against previous revision.
<code><leader>hQ</code>	Send all Git hunks to quickfix.
<code><leader>hq</code>	Send current buffer Git hunks to quickfix.
<code><leader>tb</code>	Toggle current-line Git blame.
<code><leader>tw</code>	Toggle Git word diff.
<code>]]</code>	Go to next vim-illuminate reference.
<code>[[</code>	Go to previous vim-illuminate reference.
<code>gcc</code>	Toggle line comment with Comment.nvim.
<code>gbc</code>	Toggle block comment with Comment.nvim.
<code>gc</code>	Comment operator for line comments.
<code>gb</code>	Comment operator for block comments.
<code>gcO</code>	Add comment above current line.
<code>gco</code>	Add comment below current line.
<code>gcA</code>	Add comment at end of current line.
<code>]z</code>	Jump to next todo comment.
<code>[z</code>	Jump to previous todo comment.
<code><leader>z</code>	Open todo comments in Telescope.
<code>s</code>	Leap forward target.
<code>S</code>	Leap backward target.
<code>gs</code>	Leap target across windows.
<code>]m</code>	Treesitter next function start.
<code>]]</code>	Treesitter next class start; overridden by vim-illuminate after it loads.
<code>]M</code>	Treesitter next function end.
<code>]I</code>	Treesitter next class end.
<code>[m</code>	Treesitter previous function start.
<code>[[</code>	Treesitter previous class start; overridden by vim-illuminate after it loads.
<code>[M</code>	Treesitter previous function end.
<code>[I</code>	Treesitter previous class end.
<code><leader>s</code>	Treesitter swap next parameter; may conflict with normal-mode substitute mapping.
<code><leader>S</code>	Treesitter swap previous parameter.
<code><leader>un</code>	Dismiss all notifications.
<code><c-s></code>	Toggle Copilot auto-trigger.
Copilot panel <code><M-j></code>	Jump to next Copilot panel suggestion.
Copilot panel <code><M-k></code>	Jump to previous Copilot panel suggestion.
Copilot panel <code><M-l></code>	Accept Copilot panel suggestion.

Keybind	What it does
Copilot panel <code>r</code>	Refresh Copilot panel.
Copilot panel <code><M-CR></code>	Open Copilot panel item.
TeX <code><leader>lc</code>	Start VimTeX continuous compile.
TeX <code><leader>lb</code>	Run one-shot VimTeX build.
TeX <code><leader>ls</code>	Stop VimTeX compiler.
TeX <code><leader>lv</code>	View PDF with forward search.
TeX <code><leader>lq</code>	Open VimTeX errors in quickfix.
TeX <code><leader>la</code>	Deep clean LaTeX aux files.
TeX <code><leader>lr</code>	Reload VimTeX project.
TeX <code><leader>ll</code>	Run configured LaTeX lint.
TeX <code><leader>ld</code>	Open diagnostics float for current line.
TeX <code><leader>lm</code>	Open diagnostics location list.

Disabled Or Not Currently Spec'd

Keybind	Status
Zen Mode <code><leader>zz</code> , <code><leader>zZ</code>	Defined in <code>lua/extras/zenmode.lua</code> , but Zen Mode is commented out in <code>lua/toofaeded/init.lua</code> .
Flash keys	Defined in <code>lua/extras/flash.lua</code> , but Flash is commented out in <code>lua/toofaeded/init.lua</code> .
Tabby keys	Plugin spec is commented out in <code>lua/toofaeded/init.lua</code> .
Scrollbar keys	Plugin spec is commented out in <code>lua/toofaeded/init.lua</code> .