

Matrix Multiplication

Definition

Matrix Multiplication is used to multiply two matrices of the order $m \times n$ and $k \times l$ if the number of columns in the first matrix is the same as the number of rows in the second, i.e., if $n = k$, and results in a matrix of order $m \times l$. The product of matrices A and B is denoted as AB .

If the matrices A and B are as follows

$$A = \begin{bmatrix} a_{11} & a_{12} & \cdots & a_{1n} \\ a_{21} & a_{22} & \cdots & a_{2n} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1} & a_{m2} & \cdots & a_{mn} \end{bmatrix}, \quad B = \begin{bmatrix} b_{11} & b_{12} & \cdots & b_{1l} \\ b_{21} & b_{22} & \cdots & b_{2l} \\ \vdots & \vdots & \ddots & \vdots \\ b_{n1} & b_{n2} & \cdots & b_{nl} \end{bmatrix}$$

Then the product matrix AB is defined to be

$$AB = \begin{bmatrix} a_{11}b_{11} + \cdots + a_{1n}b_{n1} & a_{11}b_{12} + \cdots + a_{1n}b_{n2} & \cdots & a_{11}b_{1l} + \cdots + a_{1n}b_{nl} \\ a_{21}b_{11} + \cdots + a_{2n}b_{n1} & a_{21}b_{12} + \cdots + a_{2n}b_{n2} & \cdots & a_{21}b_{1l} + \cdots + a_{2n}b_{nl} \\ \vdots & \vdots & \ddots & \vdots \\ a_{m1}b_{11} + \cdots + a_{mn}b_{n1} & a_{m1}b_{12} + \cdots + a_{mn}b_{n2} & \cdots & a_{m1}b_{1l} + \cdots + a_{mn}b_{nl} \end{bmatrix}$$

Solution

A program to multiply two matrices of compatible sizes has been implemented in the following way:

```
def matmul(m1, m2):
    # Checking whether the matrices m1 and m2 are nested iterables
    for i in range(len(m1)):
        if (not hasattr(m1[i], '__iter__')):
            raise TypeError # If not raising a Type Error

    for i in range(len(m2)):
        if (not hasattr(m1[2], '__iter__')):
            raise TypeError # If not raising a Type Error

    # Checking for Axis Length Mismatch
    if(len(m1[0]) != len(m2)):
        raise ValueError # If so raising a Value Error

    # Creating an empty matrix(nested list with elements zero) with the number of rows of matrix m1 and columns of matrix m2
    productMatrix = [[0 for j in range(len(m2))] for i in range(len(m1))]

    # Iterating over every row in matrix m1
```

```

for row in range(len(m1)):
    # Iterating over every column in matrix m2
    for column in range(len(m2[0])):
        # Iterating over every element in each row of m1 and element of m2, which have the
        for current in range(len(m2)):
            # Multiplying each element in a given row of m1(row) with the corresponding ele
            # and incrementing the element in the given row and column (in the 'row'th row
            productMatrix[row][column] += m1[row][current] * m2[current][column]

# Returning the product matrix
return productMatrix

```

After testing for invalid inputs the program iterates over every row in the 1st matrix, every column in the 2nd matrix and every element in each of the rows of the 1st matrix and columns of the 2nd, multiplying and adding them to be stored as each element of the product matrix.

$$AB_{ij} = A_{i1}B_{1j} + A_{i2}B_{2j} + \cdots + A_{in}B_{nj} = \sum_{k=1}^n A_{ik}B_{kj},$$

Tested Cases

- If the input are not matrices (2D Nested iterable), lines 3 to 9 check for such inputs and raise a `TypeError`.
- If any element of the input is non-numeric, Python will automatically raise a `TypeError`.
- If the axis of the matrices do not match a `ValueError` is raised at line 14.
- If the lengths of all of the sub elements of either of the matrices do not match a `IndexError` will be raised by the interpreter when trying to perform multiplication at line 27.
- Testing every single possible extreme input case was not done.