X1 : PIN ASSIGNMENT
[ITH03FPA28-21PB0G1F6]



PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	38B93-3	COMM. JUNC TB	BA	16
B	38G93-3	COMM. JUNC TB	BA	16
C	84L30-1(MA), 84L31-1(MB)	COMM. JUNC TB	S1	16
D	84L32-1	COMM. JUNC TB	S1	16
E	–	–	–	–
F	–	–	–	–
G	–	–	–	–
H	–	–	–	–
J	–	–	–	–
K	–	–	–	–
L	8401-1/1	COMM. JUNC TB	S1	16, 4C
M	8401-1/2	COMM. JUNC TB	S1	16, 4C
N	8401-1/S	COMM. JUNC TB	S1	16, 4C
P	8401-1/3	COMM. JUNC TB	S1	16, 4C
R	8401-1/4	COMM. JUNC TB	S1	16, 4C
S	–	–	–	–
T	–	–	–	–
U	–	–	–	–
V	8404-1/1	COMM. JUNC TB	S1	16, 2C
W	8404-1/2	COMM. JUNC TB	S1	16, 2C
X	8404-1/S	COMM. JUNC TB	S1	16, 2C
Z	–	–	–	–
a	8410/1	COMM. RACK	S1	16, 4C
b	8410/2	COMM. RACK	S1	16, 4C
c	8410/S	COMM. RACK	S1	16, 4C
d	8410/3	COMM. RACK	S1	16, 4C
e	8410/4	COMM. RACK	S1	16, 4C
f	84L80	DESK CONSOLE	S1	16
g	84L20-1	COMM. JUNC TB	S1	16
h	84L21-1	COMM. JUNC TB	S1	16
j	84L81	DESK CONSOLE	S1	16
k	8480/1	DIMM. CONTROL	S1	16, 2C
m	8480/2	DIMM. CONTROL	S1	16, 2C
n	8480/S	DIMM. CONTROL	S1	16, 2C
p	–	–	–	–
r	84L26	DPH	S1	16
s	84L27	DPH	S1	16

X2 : PIN ASSIGNMENT
[ITH06F18-19SB0F6]



PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE	REMARK
A	8402-1/1	COMM. JUNC TB	S1	16, 2C	
B	8402-1/2	COMM. JUNC TB	S1	16, 2C	
C	8402-1/S	COMM. JUNC TB	S1	16, 2C	
D	–	–	–	–	
E	–	–	–	–	
F	–	–	–	–	
G	–	–	–	–	
H	–	LAPEL MIC1	–	–	MAKER SUPPLY
J	–	LAPEL MIC1	–	–	MAKER SUPPLY
K	–	LAPEL MIC1	–	–	MAKER SUPPLY

NOTE :

1. FABRICATEE HARNESS ASSEMBLY IN ACCORDANCE WITH REDE114797
   - SECTION. 16. MATERIAL AND WORKMANSHIP OF RTD CONCESSION AGREEMENT ATTACHMENT 7 . PART C
2. CONNECTION FOR EARTHING CABLE SHOULD BE FOLLOWED WITH REW000121CTO (CHASSY EARTHING DRAWING).
3. IF IT NEEDS A WIRING CONNECTION AT STUD TYPE TERMINAL SERIES, RING TERMINAL AND TERMINAL LUG SHOULD BE USED.
   RING TERMINAL AND TERMINAL LUG SHALL BE USED WITH BEING APPROVED (REFER TO DWG. REW000123CTO).
4. CP PART NUMBER IS INCORPORATED WITH Dwg No. CP710007
5. CRIMPING APPLICATION TOOL IS FOLLOWED WITH T&B VENDOR'S RECOMMENDATION.
6. DETAIL INFORMATION OF MAKER CABLES SUPPLIED BY EACH SUB-SYSTEM IS PROVIDED AT DWG NO.REW000122CTO
7. UNLESS OTHERWISE MENTIONED AT PIN ASSIGNMENT DWG, USING BUTT SPLICE IS NOT ALLOWED
8. IF IT NEEDS A WIRING CONNECTION AT WAGO SERIES CONNECTOR OR CAGE CLAMP TYPE TERMINAL BLOCK, FERRULES SHOULD BE USED.
9. DESIGNATION SLEEVE AT EACH END OF WIRE SHOULD BE SHRINKED
10. EMPTY HOLE OF CONNECTOR MUST BE PLUGGED WITH ACTUAL PIN FOR PRIMARY FUNCTION.
11. ALL OF THE CONNECTOR ACCESSORY MUST BE APPLIED WITH GROMMET, GASKET, BACKSHELL, CLAMP AND RUBBER TUBE.

기호 MARK	일자 DATE	변경내역 DETAIL OF REVISION(E.C ZONE)	설변번호 E.C NO.	설계 DGN	검도 CHK	승인 APP

품번 NO.	부품 번호 PART NO.	품명 DESCRIPTION	재질 MATERIAL	수량 Q'TY	중량 W.T	비고 REMARKS

승인 APP	D.I.KIM 2012.05.20	재질 MAT'L NA	명칭 TITLE: PIN ARRANGEMENT,DPO
검도 CHK	H.S.PARK 2012.05.20	총중량 G.W NA	
설계 DGN	J.H.KIM 2012.05.20	일반공차 MC WD CT	도면번호 DRG. NO: REW00076CT0 MS Ver. 00 Rev. ---
제도 DRG		SIZE C	SCALE: 매수 SHEET 1 of 1

참고번호 REF. NO.

HYUNDAI Rotem 현대로템주식회사

RNE1002

년--PRJT

정리번호

구분			
가공치수 GENERAL TOLERANCE	~ 40	2	4
	~ 30	2	3
	~ 10	1	1.5
	<3	0.5	1
주조 CASTING	~2050	–	7
	~1600	4	5
	~ 800	3	4
	~ 400	2	3
	~ 200	1.5	2
	~ 100	1	1.5
등급 GRADE		A	B
주조 주강품 CASTING (?)	~ 20M	8	16	0.6
	~ 15M	7	12	21
	~ 10M	6	10	18
	~ 8M	5	8	14
	~ 4M	4	6	11
	~ 2M	3	4	8
	~ 1M	2	3	6
	~ 315	1	2	4
	~ 100	1	2	3
	~ 30	1	1	1
등급 GRADE		A	B	C
주조 주강품 MELDING (?)	~ 20M	–	6.0	8.0
	~ 15M	–	5.0	7.0
	~ 10M	–	4.0	6.0
	~ 8M	–	3.0	5.0
	~ 4M	0.8	2.0	4.0
	~ 2M	0.5	1.2	3.0
	~ 1M	0.3	0.8	2.0
	~ 315	0.2	0.5	1.2
	~ 100	0.15	0.3	0.8
	~ 30	0.1	0.2	0.5
	3 ~ 6	0.05	0.1	0.2
등급 GRADE		A	B	C
기계 가공품 MACHINING (?)				
구분치않은 일반공차표 GENERAL TOLERANCE				

본 도면은 당사 재산으로서 허가없이 무단복사/배포 금지함. PROPERTY OF ISSUING ENTITY. CANNOT BE DISTRIBUTED OR REPRODUCED WITHOUT AUTHORIZATION.

AutoCAD