

X1: PIN ARRANGEMENT
PLUG : [FRITS4102R16S-1PB0G1F6]
RECEPTACLE : [FRITS4106F16S-1SB0F6]

* PID (R1)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	8206-6/1	COMM. JUNC. TB	S1	16, 2C
B	8206-6/2	COMM. JUNC. TB	S1	16, 2C
C	8206-6/S	COMM. JUNC. TB	S1	16, 2C
D	–	–	–	–
E	–	–	–	–
F	–	–	–	–
G	–	–	–	–

* PID (R2)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	8206-7/1	COMM. JUNC. TB	S1	16, 2C
B	8206-7/2	COMM. JUNC. TB	S1	16, 2C
C	8206-7/S	COMM. JUNC. TB	S1	16, 2C
D	–	–	–	–
E	–	–	–	–
F	–	–	–	–
G	–	–	–	–

* PID (L1)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	8206-10/1	COMM. JUNC. TB	S1	16, 2C
B	8206-10/2	COMM. JUNC. TB	S1	16, 2C
C	8206-10/S	COMM. JUNC. TB	S1	16, 2C
D	–	–	–	–
E	–	–	–	–
F	–	–	–	–
G	–	–	–	–

* PID (L2)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	8206-11/1	COMM. JUNC. TB	S1	16, 2C
B	8206-11/2	COMM. JUNC. TB	S1	16, 2C
C	8206-11/S	COMM. JUNC. TB	S1	16, 2C
D	–	–	–	–
E	–	–	–	–
F	–	–	–	–
G	–	–	–	–



X2: PIN ARRANGEMENT
PLUG : [UTG01412P]
RECEPTACLE : [UTG61412S]

* PID (R1)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	32U13-4	COMM. JUNC. TB	AC	16
B	32V13-3	COMM. JUNC. TB	AC	16
C	–	–	–	–
D	COM	–	–	16
E	–	–	–	–
F	–	–	–	–
G	–	–	–	–
H	–	–	–	–
J	–	–	–	–
K	–	–	–	–
L	COM	–	–	16
M	COM	–	–	16

ONLY MA
* NOTE 12
ONLY MB

* PID (R2)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	32U13-5	COMM. JUNC. TB	AC	16
B	32W13-2	COMM. JUNC. TB	AC	16
C	–	–	–	–
D	–	–	–	–
E	COM	–	–	16
F	–	–	–	–
G	–	–	–	–
H	–	–	–	–
J	–	–	–	–
K	COM	–	–	16
L	–	–	–	–
M	COM	–	–	16

ONLY MA
* NOTE 12
ONLY MB

* PID (L1)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	32U13-7	COMM. JUNC. TB	AC	16
B	32W13-4	COMM. JUNC. TB	AC	16
C	–	–	–	–
D	–	–	–	–
E	–	–	–	–
F	COM	–	–	16
G	–	–	–	–
H	–	–	–	–
J	COM	–	–	16
K	–	–	–	–
L	–	–	–	–
M	COM	–	–	16

ONLY MA
* NOTE 12
ONLY MB

* PID (L2)

PIN NO.	CBL NO.	TO (FROM)	CLASS	CBL SIZE
A	32U13-6	COMM. JUNC. TB	AC	16
B	32W13-5	COMM. JUNC. TB	AC	16
C	–	–	–	–
D	–	–	–	–
E	–	–	–	–
F	–	–	–	–
G	COM	–	–	16
H	COM	–	–	16
J	–	–	–	–
K	–	–	–	–
L	–	–	–	–
M	COM	–	–	16

ONLY MA
* NOTE 12
ONLY MB

X1 : PIN ASSIGNMENT
PLUG : [ITH03FPA22-14PB0G1F8]



* PID (F-END)

PIN NO.	PIN	CBL NO.	CBL SIZE
A	POWER VCC	32U13-2	16
B	SPARE	–	–
C	POWER GND	32V13-2	16
D	SPARE	–	–
E	TX1+	8206-4/1	16, 2C
F	TX1-	8206-4/2	16, 2C
G	TX1 SH	8206-4/S	16, 2C
H	SPARE	–	–
J	SPARE	–	–
K	SPARE	–	–
L	SPARE	–	–
M	SPARE	–	–
N	SPARE	–	–
P	SPARE	–	–
R	ADD1	COM	16
S	ADD10	COM	16
T	ADD GND	COM	16
U	SPARE	–	–
V	SPARE	–	–

* NOTE 12
ONLY MA
ONLY MB

X2/X3 : PIN ASSIGNMENT
[BNC CONNECTOR]

* PID (F-END)

PIN NO.	PIN	REMARK
CENTER	VIDEO OUT	MAKER SUPPLY
SHIELD	GND	

* PID (F-END)

PIN NO.	PIN	REMARK
CENTER	VIDEO IN	MAKER SUPPLY
SHIELD	GND	

X3: PIN ARRANGEMENT

* PID (R1,R2,L1,L2)

PIN NO.	PIN	REMARK
CENTER	VIDEO OUT	MAKER SUPPLY
SHIELD	GND	

X4: PIN ARRANGEMENT

* PID (R1,R2,L1,L2)

PIN NO.	PIN	REMARK
CENTER	VIDEO IN	MAKER SUPPLY
SHIELD	GND	

일반 공차 GENERAL TOLERANCE			
길이 LENGTH	~ 40	2	4
	~ 30	2	3
	~ 10	1	1.5
	<3	0.5	1
각도 ANGLE	~3150	–	7
	~1600	4	5
	~ 800	3	4
	~ 400	2	3
	~ 200	1.5	2
	~ 100	1	1.5
등급 GRADE		A	B
주조 주강품 CASTING (?)			
~ 20M	8	14	0.6
~ 16M	7	12	21
~ 12M	6	10	18
~ 8M	5	8	14
~ 4M	4	6	11
~ 2M	3	4	8
~ 1M	2	3	6
~ 315	1	2	4
~ 100	1	2	3
~ 30	1	1	1
등급 GRADE	A	B	C
주조 주강품 MELDING (?)			
~ 20M	–	6.0	8.0
~ 16M	–	5.0	7.0
~ 12M	–	4.0	6.0
~ 8M	–	3.0	5.0
~ 4M	0.8	2.0	4.0
~ 2M	0.5	1.2	3.0
~ 1M	0.3	0.8	2.0
~ 315	0.2	0.5	1.2
~ 100	0.15	0.3	0.8
~ 30	0.1	0.2	0.5
3 ~ 6	0.05	0.1	0.2
등급 GRADE	A	B	C
기계 가공품 MACHINING (?)			
구체적인값은 문의권장			
GENERAL TOLERANCE			

NOTE :

1. FABRICATEE HARNESS ASSEMBLY IN ACCORDANCE WITH REDE114797
   - SECTION. 16. MATERIAL AND WORKMANSHIP OF RTD CONCESSION AGREEMENT ATTACHMENT 7 . PART C
2. CONNECTION FOR EARTHING CABLE SHOULD BE FOLLOWED WITH REW000121CT0 (CHASSY EARTHING DRAWING).
3. IF IT NEEDS A WIRING CONNECTION AT STUD TYPE TERMINAL SERIES, RING TERMINAL AND TERMINAL LUG SHOULD BE USED.
   RING TERMINAL AND TERMINAL LUG SHALL BE USED WITH BEING APPROVED (REFER TO DWG. REW000123CT0).
4. CP PART NUMBER IS INCORPORATED WITH Dwg No. CP710007
5. CRIMPING APPLICATION TOOL IS FOLLOWED WITH T&B VENDOR'S RECOMMENDATION.
6. DETAIL INFORMATION OF MAKER CABLES SUPPLIED BY EACH SUB-SYSTEM IS PROVIDED AT DWG NO.REW000122CT0
7. UNLESS OTHERWISE MENTIONED AT PIN ASSIGNMENT DWG, USING BUTT SPLICE IS NOT ALLOWED
8. IF IT NEEDS A WIRING CONNECTION AT WAGO SERIES CONNECTOR OR CAGE CLAMP TYPE TERMINAL BLOCK, FERRULES SHOULD BE USED.
9. DESIGNATION SLEEVE AT EACH END OF WIRE SHOULD BE SHRINKED
10. EMPTY HOLE OF CONNECTOR MUST BE PLUGGED WITH ACTUAL PIN FOR PRIMARY FUNCTION.
11. ALL OF THE CONNECTOR ACCESSORY MUST BE APPLIED WITH GROMMET, GASKET, BACKSHELL, CLAMP AND RUBBER TUBE.
12. BOTH WIRE SHOULD BE COMMON WITH 16AWG WIRE FOR CODING ADDRESS

기호 MARK	일자 DATE	변경내역 DETAIL OF REVISION(E.C ZONE)	설변번호 E.C NO.	설계 DGN	검도 CHK	승인 APP

품번 NO.	부품번호 PART NO.	품명 DESCRIPTION	재질 MATERIAL	수량 QTY	중량 W.T	비고 REMARKS

승인 APP	D.I.KIM 2012.05.20	재질 MAT'L ASSY	명칭 TITLE: PIN ARRANGEMENT,PASSENGER INFORMATION DISPLAY
검도 CHK	H.S.PARK 2012.05.20	총중량 G.W	
설계 DGN	J.H.KIM 2012.05.20	일반공차 MC / WD / CT	도면번호 DRG. NO: MS REW00081CT0 Ver. 00 Rev. ---
제도 DRG		SIZE C	SCALE / 매수 SHEET 1 of 1
		참고번호 REF. NO.	HYUNDAI Rotem 현대로템주식회사

RNE1002
년-PRJT
정리번호

본 도면은 당사 재산으로서 허가없이 무단복사/배포 금지함. PROPERTY OF ISSUING ENTITY. CANNOT BE DISTRIBUTED OR REPRODUCED WITHOUT AUTHORIZATION.

AutoCAD