POWER INPUT



ETHERNET



ETHERNET



* CCTV OUTSIDE CAMERA (L)

PIN NO.	CBL NO.	TO(FROM)	CLASS	CBL SIZE
A	38B96-1	COMM. JUNC. TB	BA	16
B	38G96-2	COMM. JUNC. TB	BA	16

* CCTV OUTSIDE CAMERA (R)

PIN NO.	CBL NO.	TO(FROM)	CLASS	CBL SIZE
A	38B96-4	COMM. JUNC. TB	BA	16
B	38G96-5	COMM. JUNC. TB	BA	16

* CCTV SALOON CAMERA (CAM1)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8801/1	CCTV POE SW.	S1	MAKER
2	8801/2	CCTV POE SW.	S1	SUPPLY
3	8801/3	CCTV POE SW.	S1	(ETHERNET3)
4	8801/4	CCTV POE SW.	S1	

(8801/5,6,7,8 SHOULD BE TERMINATED)

* CCTV SALOON CAMERA (CAM2)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8802/1	CCTV POE SW.	S1	MAKER
2	8802/2	CCTV POE SW.	S1	SUPPLY
3	8802/3	CCTV POE SW.	S1	(ETHERNET4)
4	8802/4	CCTV POE SW.	S1	

(8802/5,6,7,8 SHOULD BE TERMINATED)

* CCTV SALOON CAMERA (CAM3)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8803/1	CCTV POE SW.	S1	MAKER
2	8803/2	CCTV POE SW.	S1	SUPPLY
3	8803/3	CCTV POE SW.	S1	(ETHERNET5)
4	8803/4	CCTV POE SW.	S1	

(8803/5,6,7,8 SHOULD BE TERMINATED)

* CCTV SALOON CAMERA (CAM4)

PIN NO.	CBL NO.	TO(FROM)	CLASS	BUNDLE NO.
1	8804/1	CCTV POE SW.	S1	MAKER
2	8804/2	CCTV POE SW.	S1	SUPPLY
3	8804/3	CCTV POE SW.	S1	(ETHERNET6)
4	8804/4	CCTV POE SW.	S1	

(8804/5,6,7,8 SHOULD BE TERMINATED)

* CCTV FRONT CAMERA (CAM1)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8806/1	CCTV POE SW.	S1	MAKER
2	8806/2	CCTV POE SW.	S1	SUPPLY
3	8806/3	CCTV POE SW.	S1	(ETHERNET9)
4	8806/4	CCTV POE SW.	S1	

(8806/5,6,7,8 SHOULD BE TERMINATED)

* CCTV CAB CAMERA (CAM1)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8807/1	CCTV POE SW.	S1	MAKER
2	8807/2	CCTV POE SW.	S1	SUPPLY
3	8807/3	CCTV POE SW.	S1	(ETHERNET10)
4	8807/4	CCTV POE SW.	S1	

(8807/5,6,7,8 SHOULD BE TERMINATED)

ETHERNET



* CCTV OUTSIDE CAMERA (L)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8808/1	CCTV POE SW.	S1	MAKER
2	8808/2	CCTV POE SW.	S1	SUPPLY
3	8808/3	CCTV POE SW.	S1	(ETHERNET12)
4	8808/4	CCTV POE SW.	S1	

(8808/5,6,7,8 SHOULD BE TERMINATED)

* CCTV OUTSIDE CAMERA (R)

PIN NO.	CBL NO.	TO(FROM)	CLASS	REMARK
1	8809/1	CCTV POE SW.	S1	MAKER
2	8809/2	CCTV POE SW.	S1	SUPPLY
3	8809/3	CCTV POE SW.	S1	(ETHERNET11)
4	8809/4	CCTV POE SW.	S1	

(8809/5,6,7,8 SHOULD BE TERMINATED)

NOTE :

1. FABRICATEE HARNESS ASSEMBLY IN ACCORDANCE WITH RE.DE114797
   - SECTION. 16. MATERIAL AND WORKMANSHIP OF RTD CONCESSION AGREEMENT ATTACHMENT 7 . PART C
2. CONNECTION FOR EARTHING CABLE SHOULD BE FOLLOWED WITH REW000121CT0 (CHASSY EARTHING DRAWING).
3. IF IT NEEDS A WIRING CONNECTION AT STUD TYPE TERMINAL SERIES, RING TERMINAL AND TERMINAL LUG SHOULD BE USED.
   RING TERMINAL AND TERMINAL LUG SHALL BE USED WITH BEING APPROVED (REFER TO DWG. REW000123CT0).
4. CP PART NUMBER IS INCORPORATED WITH Dwg No. CP710007
5. CRIMPING APPLICATION TOOL IS FOLLOWED WITH T&B VENDOR'S RECOMMENDATION.
6. DETAIL INFORMATION OF MAKER CABLES SUPPLIED BY EACH SUB-SYSTEM IS PROVIDED AT DWG NO.REW000122CT0
7. UNLESS OTHERWISE MENTIONED AT PIN ASSIGNMENT DWG, USING BUTT SPLICE IS NOT ALLOWED
8. IF IT NEEDS A WIRING CONNECTION AT WAGO SERIES CONNECTOR OR CAGE CLAMP TYPE TERMINAL BLOCK, FERRULES SHOULD BE USED.
9. DESIGNATION SLEEVE AT EACH END OF WIRE SHOULD BE SHRINKED
10. EMPTY HOLE OF CONNECTOR MUST BE PLUGGED WITH ACTUAL PIN FOR PRIMARY FUNCTION.
11. ALL OF THE CONNECTOR ACCESSORY MUST BE APPLIED WITH GROMMET, GASKET, BACKSHELL, CLAMP AND RUBBER TUBE.

기호 MARK	일자 DATE	변경내역 DETAIL OF REVISION(E.C ZONE)	설변번호 E.C NO.	설계 DGN	검도 CHK	승인 APP

품번 NO.	부품번호 PART NO.	품명 DESCRIPTION	재질 MATERIAL	수량 Q'TY	중량 W.T	비고 REMARKS

승인 APP	D.I.KIM 12.05.20	재질 MAT'L NA	명칭 TITLE: PIN ARRANGEMENT,CCTV CAMERA
검도 CHK	H.S.PARK 12.05.20	총중량 G. W NA	
설계 DGN	J.H.KIM 12.05.20	일반공차 MC WD CT	도면번호 DRG. NO: REW00083CT0 Ver. 00 Rev. --
제도 DRG		SIZE C	SCALE / 매수 SHEET 1 of 1

참고번호 REF. NO.

HYUNDAI Rotem 현대로템주식회사

RNE1002

주조 CASTING	~40	2	4
	~30	2	3
	~10	1	1.5
	< 3	0.5	1
드릴 DRILLING	~3150	–	7
	~1600	4	5
	~800	3	4
	~400	2	3
	~200	1.5	2
	~100	1	1.5
GRADE		A	B
주조 주물용 (? CASTING			
~2DM	B	14	24
~1SM	7	12	21
~1DM	6	10	18
~8M	5	8	14
~4M	4	6	11
~2M	3	4	8
~1M	2	3	6
~315	1	2	4
~120	1	2	3
~30	1	1	1
GRADE	A	B	C
용접 구조물 (? WELDING			
~2DM	–	6.0	8.0
~1SM	–	5.0	7.0
~1DM	–	4.0	6.0
~8M	–	3.0	5.0
~4M	0.8	2.0	4.0
~2M	0.5	1.2	3.0
~1M	0.3	0.8	2.0
~315	0.2	0.5	1.2
~120	0.15	0.3	0.8
~30	0.1	0.2	0.5
	0.05	0.1	0.2
GRADE	A	B	C
기계가공 (? MACHINING			

사용치않은 일반공차 GENERAL TOLERANCE

본 도면은 당사 재산으로서 허가없이 무단복사 / 배포 금지함.

CATIA