X1 : PIN ASSIGNMENT
[1TH03FPA28-21PB0G1F6]



PIN NO.	CBL NO.	CBL SIZE	REMARK	PIN NO.	CBL NO.	CBL SIZE	REMARK
A	84L26	16	POWER1-VCC	a	-	-	-
B	84L27	16	POWER1-GND	b	-	-	-
C	-	-	-	c	-	-	-
D	-	-	-	d	8404-6/1	16, 2C	DUAL TONE+(IN)
E	84L38-1(MA), 84L39-1(MB)	16	LIVE	e	8404-6/2	16, 2C	DUAL TONE-(IN)
F	84L40-1	16	LIVE-ADD(IN)	f	8404-6/S	16, 2C	DUAL TONE SH(IN)
G	-		LIVE-ADD(OUT)	g	-	-	-
H	-	-	-	h	-	-	-
J	-	-	-	j	-	-	-
K	8402-6/1	16, 2C	PA1+(IN)	k	-	-	-
L	8402-6/2	16, 2C	PA1-(IN)	l	-	-	-
M	8402-6/S	16, 2C	PA1 SH(IN)	m	-	-	-
N	-	-	-	n	-	-	-
P	-	-	-	p	-	-	-
R	-	-	-	r	-	-	-
S	84L20-2	16	MUTE+	s	-	-	-
T	84L21-2	16	MUTE-				
U	-	-	-				
V	-	-	-				
W	-	-	-				
X	-	-	-				
Z	-	-	-				

NOTE :

1. FABRICATEE HARNESS ASSEMBLY IN ACCORDANCE WITH REDE114797
   - SECTIION. 16. MATERIAL AND WORKMANSHIP OF RTD CONCESSION AGREEMENT ATTACHMENT 7 . PART C
2. CONNECTION FOR EARTHING CABLE SHOULD BE FOLLOWED WITH REW000121CTO (CHASSY EARTHING DRAWING).
3. IF IT NEEDS A WIRING CONNECTION AT STUD TYPE TERMINAL SERIES, RING TERMINAL AND TERMINAL LUG SHOULD BE USED.
   RING TERMINAL AND TERMINAL LUG SHALL BE USED WITH BEING APPROVED (REFER TO DWG. REW000123CTO).
4. CP PART NUMBER IS INCORPORATED WITH Dwg No. CP710007
5. CRIMPING APPLICATION TOOL IS FOLLOWED WITH T&B VENDOR'S RECOMMENDATION.
6. DETAIL INFORMATION OF MAKER CABLES SUPPLIED BY EACH SUB-SYSTEM IS PROVIDED AT DWG NO.REW000122CTO
7. UNLESS OTHERWISE MENTIONED AT PIN ASSIGNMENT DWG, USING BUTT SPLICE IS NOT ALLOWED
8. IF IT NEEDS A WIRING CONNECTION AT WAGO SERIES CONNECTOR OR CAGE CLAMP TYPE TERMINAL BLOCK, FERRULES SHOULD BE USED.
9. DESIGNATION SLEEVE AT EACH END OF WIRE SHOULD BE SHRINKED
10. EMPTY HOLE OF CONNECTOR MUST BE PLUGGED WITH ACTUAL PIN FOR PRIMARY FUNCTION.
11. ALL OF THE CONNECTOR ACCESSORY MUST BE APPLIED WITH GROMMET, GASKET, BACKSHELL, CLAMP AND RUBBER TUBE.

일반공차 GENERAL TOLERANCE			
길이 LENGTH	~ 40	2	4
	~ 30	2	3
	~ 10	1	1.5
	<3	0.5	1
각도 ANGLE	~2150	-	7
	~1600	4	5
	~ 800	3	4
	~ 400	2	3
	~ 200	1.5	2
	~ 100	1	1.5
등급 GRADE		A	B
압착 공차표 CRIMPING (?)			
~ 20M	8	14	0.6
~ 15M	7	12	21
~ 10M	6	10	18
~ 8M	5	8	14
~ 4M	4	6	11
~ 2M	3	4	8
~ 1M	2	3	6
~ 315	1	2	4
~ 100	1	2	3
~ 30	1	1	1
등급 GRADE	A	B	C
절삭 가공표 MACHINING (?)			
~ 20M	-	6.0	8.0
~ 10M	-	5.0	7.0
~ 10M	-	4.0	6.0
~ 6M	-	3.0	5.0
~ 4M	0.8	2.0	4.0
~ 2M	0.5	1.2	3.0
~ 1M	0.3	0.8	2.0
~ 315	0.2	0.5	1.2
~ 100	0.15	0.3	0.8
~ 30	0.1	0.2	0.5
3 ~ 6	0.05	0.1	0.2
등급 GRADE	A	B	C
가공 공차표 MACHINING (?)			
규격외일반 공차표 GENERAL TOLERANCE			

기호 MARK	일자 DATE	변경내역 DETAIL OF REVISION(E.C ZONE)	설변번호 E.C NO.	설계 DGN	검도 CHK	승인 APP

품번 NO.	부품 번호 PART NO.	품명 DESCRIPTION	재질 MATERIAL	수량 Q'TY	중량 W.T	비고 REMARKS
승인 APP	D.I.KIM 2012.05.20	재질 MAT'L NA	명칭 TITLE	PIN ARRANGEMENT,DRIVER PA HANDSET		
검도 CHK	H.S.PARK 2012.05.20	총중량 G.W NA				
설계 DGN	J.H.KIM 2012.05.20	일반공차 MC WD CT	도면번호 DRG. NO	REW00092CT0	Ver. 00 / Rev. ---	RNE1002
제도 DRG			SCALE	매수 SHEET 1 of 1		년--PRJT
		SIZE C				정리번호
		참고번호 REF. NO.	HYUNDAI Rotem 현대로템주식회사			

본 도면은 당사 재산으로서 허가없이 무단복사/배포 금지함. PROPERTY OF ISSUING ENTITY. CANNOT BE DISTRIBUTED OR REPRODUCED WITHOUT AUTHORIZATION.

AutoCAD