

Welcome to Managing Services.

## What you will learn

### At the core of the lesson

You will learn how to:

- Explain common commands that are used for managing services on Linux
- Explain common commands that are used for monitoring services on Linux



In this lesson, you will learn how to:

- Explain common commands that are used for managing services on Linux
- Explain common commands that are used for monitoring services on Linux

## Managing services on Linux

© 2021, Amazon Web Services, Inc. or its affiliates. All rights reserved.

This section covers common commands that you can use to manage services on Linux.

## Managing services with the `systemctl` command

- The following is the syntax of the `systemctl` command: `systemctl <subcommand> <service name>`
- The following are common troubleshooting tasks if services aren't working correctly:
  - Restart after any configuration change.
  - Restart when troubleshooting.
- The `systemctl` command has many subcommands, including status, start, stop, restart, enable, and disable.
- Services provide functionality such as networking, remote administration, and security.

You can also use the **service** command to manage services, but **systemctl** has more options and features.

## Managing services with the `systemctl` command

```
[ec2-user@myLinux ~]$ sudo systemctl status httpd
sudo systemctl status httpd
• httpd.service - The Apache HTTP Server
  Loaded: loaded (/usr/lib/systemd/system/httpd.service; disabled; vendor preset:
disabled)
  Active: inactive (dead)
  Docs: man:httpd.service(8)
[ec2-user@myLinux ~]$
```

```
[ec2-user@myLinux ~]$ sudo systemctl start httpd
[ec2-user@myLinux ~]$ sudo systemctl enable httpd
Created symlink from /etc/systemd/system/multi-user.target.wants/httpd.service to
/usr/lib/systemd/system/httpd.service.
[ec2-user@myLinux ~]$ sudo systemctl status httpd
• httpd.service - The Apache HTTP Server
  Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; vendor preset:
disabled)
  Active: active (running) since Thu 2021-06-10 14:03:04 UTC; 9s ago
```

After installing `httpd` (`yum install httpd`), the `sudo systemctl status httpd` command shows you that the service is not started or activated (to start the system at boot time).

The `sudo systemctl start httpd` command starts the service.

The `sudo systemctl enable httpd` command activates the service so that it is available after restarting the machine.

## Demonstration: Using systemctl to Manage Services



6

© 2021, Amazon Web Services, Inc. or its affiliates. All rights reserved.

Using the `systemctl` command, perform the following actions:

1. Show the running services.
2. List all services whether the service is active, exited, or failed.
3. List all active services.



Full commands for each item:

1. `systemctl`
2. `systemctl list-units --type=service`
3. `systemctl list-units --type=service --state=active`


## Monitoring on Linux

© 2021, Amazon Web Services, Inc. or its affiliates. All rights reserved.

This section covers common commands that you can use to monitor services on Linux.

## System performance information

Command	Description
<code>lscpu</code>	List CPU information
<code>lshw</code>	List hardware
<code>du</code>	Check file and directory sizes
<code>df</code>	Display disk size and free space
<code>fdisk</code>	List and modify partitions on the hard drive
<code>vmstat</code>	Indicate use of virtual memory
<code>free</code>	Indicate use of physical memory
<code>top</code>	Display system's processes and resource usage
<code>uptime</code>	Indicate the amount of time that the system has been up, number of users, and central processing unit (CPU) wait time



Familiarize yourself with these commands that you can use to monitor system performance.



## Examples

```
ec2-user@myLinux ~]$ dmesg
Architecture: x86_64
CPU op-mode(s): 32-bit, 64-bit
Byte Order: Little Endian
CPU(s): 1
On-line CPU(s) list: 0
Thread(s) per core: 1
Core(s) per socket: 1
Socket(s): 1
NUMA node(s): 1
Vendor ID: GenuineIntel
CPU family: 6
Model: 63
Model name: Intel(R) Xeon(R) CPU E5-2676 v3 @ 2.40GHz
Stepping: 2
```

```
ec2-user@myLinux ~]$ df
Filesystem      1K-blocks      Used Available Use% Mounted on
devtmpfs        492676      0    492676   0% /dev
tmpfs           503448      0    503448   0% /dev/shm
tmpfs           503448    548    502900   1% /run
tmpfs           503448      0    503448   0% /sys/fs/cgroup
/dev/xvda1      8376308 2614312  5761988  32% /
tmpfs          100692     12    100680   1% /run/user/1000
```


```
top - 07:24:45 up 19 min, 2 users, load average: 0.00, 0.00, 0.00
tasks: 123 total, 1 running, 85 sleeping, 0 stopped, 0 zombie
rCPU(s): 0.0 us, 0.0 sy, 0.0 ni, 100.0 id, 0.0 wa, 0.0 hi, 0.0 si, 0.0 st
KiB Mem : 1006896 total, 444876 free, 230900 used, 331920 buff/cache
KiB Swap: 0 total, 0 free, 0 used, 633072 avail Mem

  PID USER      PR  NI   VIRT   RES   SHR S %CPU  %MEM    TIME+  COMMAND
    1 root        20   0 125548   5412  3980 S  0.0   0.5   0:02.02 systemd
    2 root        20   0      0      0      0 S  0.0   0.0   0:00.00 kthreadd
    4 root        0 -20      0      0      0 I  0.0   0.0   0:00.00 kworker/0:0H
    6 root        0 -20      0      0      0 I  0.0   0.0   0:00.00 wa_percpu_v
    7 root        20   0      0      0      0 S  0.0   0.0   0:00.05 ksoftirqd/0
    8 root        20   0      0      0      0 I  0.0   0.0   0:00.15 rcu_sched
    9 root        20   0      0      0      0 I  0.0   0.0   0:00.00 rcu_bh
   10 root       rt   0      0      0      0 S  0.0   0.0   0:00.00 migration/0
   11 root       rt   0      0      0      0 S  0.0   0.0   0:00.00 watchdog/0
   12 root        20   0      0      0      0 S  0.0   0.0   0:00.00 cpuhp/0
```

These screen captures show examples of the commands in use.

## Amazon CloudWatch

- CloudWatch monitors the health and performance of your AWS resources and applications.
- It offers monitoring of Amazon Elastic Compute Cloud (Amazon EC2) instances, such as CPU usage, disk reads, and writes.
- You can create alarms. For example, when CPU usage exceeds a certain threshold, a notification is sent through Amazon Simple Notification Service (Amazon SNS).



10 © 2021, Amazon Web Services, Inc. or its affiliates. All rights reserved.

aws re/start

Amazon Elastic Compute Cloud (Amazon EC2) is an AWS compute service that you can use to create secure and scalable virtual computing resources.

Amazon Simple Notification (Amazon SNS) is a notification service that you can use to send messages to other AWS services or to individuals through email and SMS.

The screen capture demonstrates the monitoring on an EC2 instance, but Amazon CloudWatch can monitor many other AWS services.

Later lessons will cover CloudWatch and other AWS topics.

## Checkpoint questions



How might you use the **top** command when you are troubleshooting?



Why do you restart a service instead of restarting the entire computer?

### Answers:

1. If the CPU on the server is maximized, you can use the **top** command to determine what process might be responsible.
2. A server often hosts many services that users run. Restarting the entire server would mean that the reboot would also stop all the properly running services on the server. Restarting only the failing service means that the healthy services can continue to run.

## Key takeaways



- You use the `systemctl` command to manage services in Linux.
- The `top` command provides a real-time view of processes that are running on the system.
- `df` is the *disk free* command that you use to check the available space on a hard drive.
- You use the `du` command to display the amount of space that a file or directory uses.

12

© 2021, Amazon Web Services, Inc. or its affiliates. All rights reserved.

aws re/start

Key takeaways include:

- You use the `systemctl` command to manage services in Linux.
- The `top` command provides a real-time view of processes that are running on the system.
- `df` is the *disk free* command that you use to check the available space on a hard drive.
- You use the `du` command to display the amount of space that a file or directory uses.



Thank you

© 2021 Amazon Web Services, Inc. or its affiliates. All rights reserved. This work may not be reproduced or redistributed, in whole or in part, without prior written permission from Amazon Web Services, Inc. Commercial copying, lending, or selling is prohibited. Corrections, feedback, or other questions? Contact us at <https://support.aws.amazon.com/contact-us>. All trademarks are the property of their owners.



Thank you.