

Question 1

Which of the following statements about built-in database functions is correct? 0 / 1 point

Built-in database functions may increase network bandwidth consumed.

Built-in database functions reduce the amount of data that is retrieved.

Built-in database functions must be called from a programming language like Python.

Built-in database functions may increase processing time.

Incorrect

Incorrect. Built-in database functions can reduce processing time.

Question 2

Which of the following SQL queries would return the day of the week each dog was rescued? 1 / 1 point

SELECT DAY(RescueDate) From PetRescue WHERE Animal = 'Dog';

SELECT RescueDate From PetRescue WHERE Animal = 'Dog';

SELECT DAYOFWEEK(RescueDate) From PetRescue WHERE Animal = 'Dog';

SELECT DAYOFWEEK(RescueDate) From PetRescue;

Correct

Correct. The DAYOFWEEK() function returns the day of the week, and the WHERE clause correctly specifies the animal as a dog.

Question 3

What is the result of the following query: SELECT (Current_Date – RescueDate) FROM PetRescue 1 / 1 point

Returns how long it has been since each rescue.

Returns the rescue date for each rescue.

Returns today's date.

Returns the current date and rescue date columns.

Correct

Correct. This query returns how long it has been since the rescue.

Question 4

Which of the following queries will return the employees who earn less than the average salary? 1 / 1 point

SELECT * FROM Employees WHERE Salary < AVG(Salary)

SELECT * FROM Employees WHERE Salary < (SELECT AVG(Salary))

SELECT * FROM Employees WHERE Salary < (SELECT AVG(Salary) FROM Employees);

SELECT AVG(Salary) FROM Employees WHERE Salary < AVG(Salary)

Correct

Correct. The AVG(Salary) function must be included in a sub-query within the WHERE clause.

Question 5

What are the three ways to work with multiple tables in the same query? 1 / 1 point

Built-in functions, implicit joins, JOIN operators

Sub-queries, APPEND, JOIN operators

Sub-queries, Implicit joins, normalization.

Sub-queries, Implicit joins, JOIN operators

Correct

Correct: You can retrieve information from more than one table by using a sub-query, an implicit join, or a JOIN operator like INNER JOIN, LEFT OUTER JOIN, RIGHT OUTER JOIN, or FULL OUTER JOIN.