

REST DOCUMENTATION FOR STUDMISTO BACKEND

CONTENT

SLIDER.....	4
GET ALL SLIDER ITEMS.....	5
GET ONE SLIDER ITEM	6
ADD SLIDER ITEM	7
CHANGE SLIDER ITEM.....	8
DELETE SLIDER ITEM.....	9
ABOUT	10
GET ALL ABOUT ITEMS	11
GET ONE ABOUT ITEM.....	12
ADD ABOUT ITEM.....	13
CHANGE ABOUT ITEM	14
DELETE ABOUT ITEM	15
NEWS.....	16
GET ALL NEWS ITEMS	17
GET ONE NEWS ITEM	18
ADD NEWS ITEM.....	19
CHANGE NEWS ITEM.....	20
DELETE NEWS ITEM	21
QA	22
GET ALL QA ITEMS.....	23
GET ONE QA ITEM	24
ADD QA ITEM	25
CHANGE QA ITEM.....	26
DELETE QA ITEM.....	27
CONTACT.....	28
GET ALL CONTACT ITEMS	29
GET ONE CONTACT ITEM.....	30
ADD CONTACT ITEM	31
CHANGE CONTACT ITEM	33
DELETE CONTACT ITEM	35
LOGIN (JWT).....	36
LOGIN	37
LOGOUT.....	38
USER	39
GET PRINCIPAL USER	40
GET SOME USER	41

GET All USERS	42
ADD USER STAFF	43
ADD USER EXIST INMATE	44
UPDATE PRINCIPAL USER	46
UPDATE SOME USER	47
DELETE SOME USER.....	49
ROOM.....	50
GET SOME ROOM	51
GET All ROOMS.....	52
GET AVAILABLE ROOMS (for principal user)	53
ADD ROOM.....	54
UPDATE ROOM.....	55
DELETE ROOM	56

SLIDER

GET ALL SLIDER ITEMS

Link: <https://studmisto.herokuapp.com/slider>

Method: GET

Returns: All slider items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String

Example:

The screenshot shows a REST client interface with a GET request to `https://studmisto.herokuapp.com/slider`. The response is a JSON array of two slider items. The status is 200 OK, with a response time of 123 ms and a body size of 366 B.

KEY	VALUE	DESCRIPTION
Key	Value	Description

```
1 {
2   {
3     "photoLink": "First photoLink",
4     "title": "First title",
5     "description": "First description",
6     "id": 1
7   },
8   {
9     "photoLink": "Second photoLink",
10    "title": "Second title",
11    "description": "Second description",
12    "id": 2
13  }
14 }
```

Headers:

Headers		200 OK 123 ms 366 B Save Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

GET ONE SLIDER ITEM

Link: <https://studmisto.herokuapp.com/slider/{id}>

Method: GET

Returns: One slider item

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String

Example:

GET <https://studmisto.herokuapp.com/slider/1> Send Save

Params Auth Headers (6) Body Pre-req. Tests Settings ...

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK 495 ms 266 B Save Response

Pretty Raw Preview Visualize JSON

```
1 {
2   "photoLink": "First photoLink",
3   "title": "First title",
4   "description": "First description",
5   "id": 1
6 }
```

Headers:

Headers		200 OK 123 ms 366 B Save Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

ADD SLIDER ITEM

Link: <https://studmisto.herokuapp.com/slider>

Method: POST

Returns: All slider items

Request parameters:

KEY	TYPE	REQUIRED
title	String	true
description	String	true
photoLink	String	true

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String

Example:

POSThttps://studmisto.herokuapp.com/slider?title=New title&description=New description&photoLink=New photoLinkSendSave

ParamsAuthHeaders (7)BodyPre-reqTestsSettings

Query Params

KEY	VALUE	DESCRIPTION
<input checked="" type="checkbox"/> title	New title	
<input checked="" type="checkbox"/> description	New description ...	
<input checked="" type="checkbox"/> photoLink	New photoLink ...	
Key	Value	Description

Body200 OK122 ms455 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   {
3     "photoLink": "First photoLink",
4     "title": "First title",
5     "description": "First description",
6     "id": 1
7   },
8   {
9     "photoLink": "Second photoLink",
10    "title": "Second title",
11    "description": "Second description",
12    "id": 2
13  },
14  {
15    "photoLink": "New photoLink",
16    "title": "New title",
17    "description": "New description",
18    "id": 3
19  }
20 }
```

Headers:

Headers200 OK122 ms455 BSave Response	
KEY	VALUE
Server ⓘ	Cowboy
Connection ⓘ	keep-alive
Content-Type ⓘ	application/json
Transfer-Encoding ⓘ	chunked
Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
Via ⓘ	1.1 vegur

CHANGE SLIDER ITEM

Link: <https://studmisto.herokuapp.com/slider/{id}>

Method: PUT

Returns: All slider items

Request parameters:

KEY	TYPE	REQUIRED
title	String	true
description	String	true
photoLink	String	true

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String

Example:

PUThttps://studmisto.herokuapp.com/slider/1?title=New title for first item&description=New description for first item&photoLink=New photoLink fcSendSave

ParamsAuthHeaders (7)BodyPre-req. TestsSettings

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	title	New title for first item			
<input checked="" type="checkbox"/>	description	New description for first item ...			
<input checked="" type="checkbox"/>	photoLink	New photoLink for first item ...			
	Key	Value	Description		

Body

200 OK489 ms494 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 [{
2   {
3     "photoLink": "Second photoLink",
4     "title": "Second title",
5     "description": "Second description",
6     "id": 2
7   },
8   {
9     "photoLink": "New photolink",
10    "title": "New title",
11    "description": "New description",
12    "id": 3
13  },
14  {
15    "photoLink": "New photolink for first item",
16    "title": "New title for first item",
17    "description": "New description for first item",
18    "id": 1
19  }
20 ]
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

DELETE SLIDER ITEM

Link: <https://studmisto.herokuapp.com/slider/{id}>

Method: DELETE

Returns: All slider items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String

Example:

The screenshot shows a REST client interface. At the top, the method is set to 'DELETE' and the URL is 'https://studmisto.herokuapp.com/slider/1'. The 'Send' button is highlighted. Below the URL bar, the 'Params' tab is active, showing a table with columns 'KEY', 'VALUE', and 'DESCRIPTION'. The 'Body' tab is also visible, showing a JSON response in 'Pretty' format. The response is a JSON array with two objects, each containing 'photoLink', 'title', 'description', and 'id' fields. The status bar at the top right indicates a '200 OK' response with a time of '494 ms' and a body size of '360 B'.

KEY	VALUE	DESCRIPTION
Key	Value	Description

```
1 {
2   {
3     "photoLink": "Second photoLink",
4     "title": "Second title",
5     "description": "Second description",
6     "id": 2
7   },
8   {
9     "photoLink": "New photolink",
10    "title": "New title",
11    "description": "New description",
12    "id": 3
13  }
14 }
```

Headers:

Headers ▼		200 OK 122 ms 455 B Save Response ▼
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

ABOUT

GET ALL ABOUT ITEMS

Link: <https://studmisto.herokuapp.com/about>

Method: GET

Returns: All about items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
iconLink	String

Example:

GEThttps://studmisto.herokuapp.com/aboutSendSave

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK487 ms362 BSave Response

PrettyRawPreviewVisualizeJSON

```
1  {
2    {
3      "id": 4,
4      "title": "First title",
5      "description": "First description",
6      "iconLink": "First iconLink"
7    },
8    {
9      "id": 5,
10     "title": "Second title",
11     "description": "Second description",
12     "iconLink": "Second iconLink"
13   }
14 }
```

Headers:

Headers		200 OK123 ms366 BSave Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

GET ONE ABOUT ITEM

Link: <https://studmisto.herokuapp.com/about/{id}>

Method: GET

Returns: One about item

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
iconLink	String

Example:

GEThttps://studmisto.herokuapp.com/about/5SendSave

ParamsAuthHeaders (6)BodyPre-req. Tests Settings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK292 ms267 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "id": 5,
3   "title": "Second title",
4   "description": "Second description",
5   "iconLink": "Second iconLink"
6 }
```

Headers:

Headers		200 OK123 ms366 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT
	Via ⓘ	1.1 vegur

ADD ABOUT ITEM

Link: <https://studmisto.herokuapp.com/about>

Method: POST

Returns: All about items

Request parameters:

KEY	TYPE	REQUIRED
title	String	true
description	String	true
iconLink	String	true

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
iconLink	String

Example:

POST

https://studmisto.herokuapp.com/about?title=Second title&description=Second description&iconLink=Second iconLink

Send

Save

ParamsAuthHeaders (7)BodyPre-req. TestsSettings

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	title	Second title			
<input checked="" type="checkbox"/>	description	Second description			
<input checked="" type="checkbox"/>	iconLink	Second iconLink			
	Key	Value	Description		

Body

200 OK146 ms362 BSave Response

PrettyRawPreviewVisualizeJSON

```
1  [
2    {
3      "id": 4,
4      "title": "First title",
5      "description": "First description",
6      "iconLink": "First iconLink"
7    },
8    {
9      "id": 5,
10     "title": "Second title",
11     "description": "Second description",
12     "iconLink": "Second iconLink"
13   }
14 ]
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

CHANGE ABOUT ITEM

Link: <https://studmisto.herokuapp.com/about/{id}>

Method: PUT

Returns: All about items

Request parameters:

KEY	TYPE	REQUIRED
title	String	true
description	String	true
iconLink	String	true

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
iconLink	String

Example:

PUT

https://studmisto.herokuapp.com/about/5?title=New title for id 5&description=New description for id 5&iconLink=New iconLink for id 5

Send

Save

ParamsAuthHeaders (7)BodyPre-req. TestsSettings

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	title	New title for id 5			
<input checked="" type="checkbox"/>	description	New description for id 5			
<input checked="" type="checkbox"/>	iconLink	New iconLink for id 5			
	Key	Value	Description		

Body

200 OK431 ms380 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   {
3     "id": 4,
4     "title": "First title",
5     "description": "First description",
6     "iconLink": "First iconLink"
7   },
8   {
9     "id": 5,
10    "title": "New title for id 5",
11    "description": "New description for id 5",
12    "iconLink": "New iconLink for id 5"
13  }
14 }
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

DELETE ABOUT ITEM

Link: <https://studmisto.herokuapp.com/about/{id}>

Method: DELETE

Returns: All about items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
iconLink	String

Example:

DELETE

https://studmisto.herokuapp.com/about/4

Send

Save

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK452 ms287 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "id": 5,
3   "title": "New title for id 5",
4   "description": "New description for id 5",
5   "iconLink": "New iconLink for id 5"
6 }
7
8
```

Headers:

Headers			200 OK	122 ms	455 B	Save Response
	KEY	VALUE				
	Server	Cowboy				
	Connection	keep-alive				
	Content-Type	application/json				
	Transfer-Encoding	chunked				
	Date	Wed, 28 Oct 2020 10:52:21 GMT				
	Via	1.1 vegur				

NEWS

GET ALL NEWS ITEMS

Link: <https://studmisto.herokuapp.com/news>

Method: GET

Returns: All news items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String
date	Date

Example:

The screenshot shows a REST client interface. The top bar indicates a GET request to `https://studmisto.herokuapp.com/news` with a status of 200 OK, 110 ms, and 418 B. The response body is displayed in JSON format, showing an array of two news items. The first item has a title 'First title', description 'First description', photoLink 'First photolink', date '11:49 28.10.2020', and id 6. The second item has a title 'Second title', description 'Second description', photoLink 'Second photolink', date '11:50 28.10.2020', and id 7.

```
1 {
2   {
3     "title": "First title",
4     "description": "First description",
5     "photoLink": "First photolink",
6     "date": "11:49 28.10.2020",
7     "id": 6
8   },
9   {
10    "title": "Second title",
11    "description": "Second description",
12    "photoLink": "Second photolink",
13    "date": "11:50 28.10.2020",
14    "id": 7
15  }
16 }
```

Headers:

Headers ▼		200 OK 123 ms 366 B Save Response ▼
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

GET ONE NEWS ITEM

Link: <https://studmisto.herokuapp.com/news/{id}>

Method: GET

Returns: One news item

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String
date	Date

Example:

GET <https://studmisto.herokuapp.com/news/7> Send Save

Params Auth Headers (6) Body Pre-req. Tests Settings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK 130 ms 295 B Save Response

Pretty Raw Preview Visualize JSON

```
1 {  
2   "title": "Second title",  
3   "description": "Second description",  
4   "photoLink": "Second photoLink",  
5   "date": "11:50 28.10.2020",  
6   "id": 7  
7 }
```

Headers:

Headers		200 OK 123 ms 366 B Save Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

ADD NEWS ITEM

Link: <https://studmisto.herokuapp.com/news>

Method: POST

Returns: All news items

Request parameters:

NAME	TYPE	REQUIRED
title	String	true
description	String	true
photoLink	String	true

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String
date	Date

Example:

POST

https://studmisto.herokuapp.com/news?title=Second title&description=Second description&photoLink=Second photoLink

Send

Save

ParamsAuthHeaders (7)BodyPre-req. TestsSettings

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	title	Second title			
<input checked="" type="checkbox"/>	description	Second description			
<input checked="" type="checkbox"/>	photoLink	Second photoLink			
	Key	Value	Description		

Body

200 OK119 ms418 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   {
3     "title": "First title",
4     "description": "First description",
5     "photoLink": "First photoLink",
6     "date": "11:49 28.10.2020",
7     "id": 6
8   },
9   {
10    "title": "Second title",
11    "description": "Second description",
12    "photoLink": "Second photoLink",
13    "date": "11:50 28.10.2020",
14    "id": 7
15  }
16 }
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server	Cowboy
	Connection	keep-alive
	Content-Type	application/json
	Transfer-Encoding	chunked
	Date	Wed, 28 Oct 2020 10:52:21 GMT
	Via	1.1 vegur

CHANGE NEWS ITEM

Link: <https://studmisto.herokuapp.com/news/{id}>

Method: PUT

Returns: All news items

Request parameters:

NAME	TYPE	REQUIRED
title	String	true
description	String	true
photoLink	String	true

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String
date	Date

Example:

PUThttps://studmisto.herokuapp.com/news/7?title=New title for id 7&description=New description for id 7&photoLink=New photoLink for id 7SendSave

ParamsAuthHeaders (7)BodyPre-req. Tests Settings

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	title	New title for id 7			
<input checked="" type="checkbox"/>	description	New description for id 7			
<input checked="" type="checkbox"/>	photoLink	New photoLink for id 7			
	Key	Value	Description		

Body

200 OK531 ms436 BSave Response

PrettyRawPreviewVisualizeJSON

```
1  [
2    {
3      "title": "First title",
4      "description": "First description",
5      "photoLink": "First photoLink",
6      "date": "11:49 28.10.2020",
7      "id": 6
8    },
9    {
10     "title": "New title for id 7",
11     "description": "New description for id 7",
12     "photoLink": "New photoLink for id 7",
13     "date": "11:50 28.10.2020",
14     "id": 7
15   }
16 ]
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

DELETE NEWS ITEM

Link: <https://studmisto.herokuapp.com/news/{id}>

Method: DELETE

Returns: All news items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
title	String
description	String
photoLink	String
date	Date

Example:

DELETE

https://studmisto.herokuapp.com/news/7

Send

Save

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK112 ms294 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "title": "First title",
3   "description": "First description",
4   "photoLink": "First photoLink",
5   "date": "11:49 28.10.2020",
6   "id": 6
7 }
8
9
```

Headers:

Headers		200 OK122 ms455 BSave Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT	
Via ⓘ	1.1 vegur	

QA

GET ALL QA ITEMS

Link: <https://studmisto.herokuapp.com/qa>

Method: GET

Returns: All qa items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
question	String
answer	String

Example:

GEThttps://studmisto.herokuapp.com/qa

SendSave

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION	...	Bulk Edit
Key	Value	Description		

Body

200 OK110 ms309 BSave Response

PrettyRawPreviewVisualizeJSON

```
1  {
2    {
3      "question": "First question",
4      "answer": "First answer",
5      "id": 8
6    },
7    {
8      "question": "New question for id 9",
9      "answer": "New answer for id 9",
10     "id": 9
11   }
12 }
```

Headers:

Headers		200 OK123 ms366 BSave Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

GET ONE QA ITEM

Link: <https://studmisto.herokuapp.com/qa/{id}>

Method: GET

Returns: One qa item

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
question	String
answer	String

Example:

GEThttps://studmisto.herokuapp.com/qa/9

SendSave

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK117 ms246 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "question": "New question for id 9",
3   "answer": "New answer for id 9",
4   "id": 9
5 }
```

Headers:

Headers		200 OK123 ms366 BSave Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

ADD QA ITEM

Link: <https://studmisto.herokuapp.com/qa>

Method: POST

Returns: All qa items

Request parameters:

NAME	TYPE	REQUIRED
question	String	true
answer	String	true

Response parameters:

NAME	TYPE
id	Long
question	String
answer	String

Example:

POST <https://studmisto.herokuapp.com/qa/?question=Second question&answer=Second answer> Send Save

Params Auth Headers (7) Body Pre-req. Tests Settings

Query Params

KEY	VALUE	DESCRIPTION
<input checked="" type="checkbox"/> question	Second question	
<input checked="" type="checkbox"/> answer	Second answer	
Key	Value	Description

Body

200 OK 116 ms 297 B Save Response

Pretty Raw Preview Visualize JSON

```
1 [
2   {
3     "question": "First question",
4     "answer": "First answer",
5     "id": 8
6   },
7   {
8     "question": "Second question",
9     "answer": "Second answer",
10    "id": 9
11  }
12 ]
```

Headers:

Headers		200 OK 122 ms 455 B Save Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT	
Via ⓘ	1.1 vegur	

CHANGE QA ITEM

Link: <https://studmisto.herokuapp.com/qa/{id}>

Method: PUT

Returns: All qa items

Request parameters:

NAME	TYPE	REQUIRED
question	String	true
answer	String	true

Response parameters:

NAME	TYPE
id	Long
question	String
answer	String

Example:

PUT

https://studmisto.herokuapp.com/qa/9/?question=New question for id 9&answer=New answer for id 9

Send

Save

ParamsAuthHeaders (7)BodyPre-req. Tests Settings

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	question	New question for id 9			
<input checked="" type="checkbox"/>	answer	New answer for id 9			
	Key	Value	Description		

Body

200 OK468 ms309 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 [{
2   {
3     "question": "First question",
4     "answer": "First answer",
5     "id": 8
6   },
7   {
8     "question": "New question for id 9",
9     "answer": "New answer for id 9",
10    "id": 9
11   }
12 ]
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

DELETE QA ITEM

Link: <https://studmisto.herokuapp.com/qa/{id}>

Method: DELETE

Returns: All qa items

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
question	String
answer	String

Example:

DELETE

https://studmisto.herokuapp.com/qa/9

Send

Save

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION
Key	Value	Description

Body

200 OK192 ms234 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "question": "First question",
3   "answer": "First answer",
4   "id": 8
5 }
6
7
```

Headers:

Headers		200 OK122 ms455 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

CONTACT

GET ALL CONTACT ITEMS

Link: <https://studmisto.herokuapp.com/contacts>

Method: GET

Returns: All contact items

Request parameters: -

Response parameters:

NAME	TYPE
category	ContactCategory
name	String
position	String
address	String
email	String
phoneNumber1	String
phoneNumber2	String
id	Long

Example:

GEThttps://studmisto.herokuapp.com/contactsSendSave

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION	...	Bulk Edit
Key	Value	Description		

Body

200 OK272 ms408 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "category": "DORM_6",
3   "name": "Оксана Анатоліївна",
4   "position": "Завідуюча 6 гуртожитку",
5   "address": "Тичини 8а",
6   "email": "dorm6@gmail.com",
7   "phoneNumber1": "-",
8   "phoneNumber2": "380990990999",
9   "id": 10
10 }
11
12
```

Headers:

Headers		200 OK123 ms366 BSave Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT	
Via ⓘ	1.1 vegur	

GET ONE CONTACT ITEM

Link: <https://studmisto.herokuapp.com/contacts/{id}>

Method: GET

Returns: One contact item

Request parameters: -

Response parameters:

NAME	TYPE
category	ContactCategory
name	String
position	String
address	String
email	String
phoneNumber1	String
phoneNumber2	String
id	Long

Example:

GET

https://studmisto.herokuapp.com/contacts/10

Send

Save

ParamsAuthHeaders (6)BodyPre-req. TestsSettings

Query Params

KEY	VALUE	DESCRIPTION	...	Bulk Edit
Key	Value	Description		

Body

200 OK122 ms406 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   "category": "DORM_6",
3   "name": "Оксана Анатоліївна",
4   "position": "Завідуюча 6 гуртожитку",
5   "address": "Тичини 8а",
6   "email": "dorm6@gmail.com",
7   "phoneNumber1": "-",
8   "phoneNumber2": "380990990999",
9   "id": 10
10 }
```

Headers:

Headers		200 OK123 ms366 BSave Response
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:36:46 GMT
	Via ⓘ	1.1 vegur

ADD CONTACT ITEM

Link: <https://studmisto.herokuapp.com/contacts>

Method: POST

Returns: All contact items

Request parameters:

NAME	TYPE	REQUIRED
category	String	true
name	String	true
position	String	true
address	String	true
email	String	true
phoneNumber1	String	true
phoneNumber2	String	true

Available category values:

GENERAL

DORM_3

DORM_5

DORM_6

DORM_7

Response parameters:

NAME	TYPE
category	ContactCategory
name	String
position	String
address	String
email	String
phoneNumber1	String
phoneNumber2	String
id	Long

Example:

POSThttps://studmisto.herokuapp.com/contacts?category=DORM_6&name=Оксана Анатоліївна&position=Завідуюча 6 гуртожитку&address=Тичини 8а...SendSave

ParamsAuthHeaders (7)BodyPre-req. Tests Settings

Query Params


KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/> category	DORM_6			
<input checked="" type="checkbox"/> name ...	Оксана Анатоліївна ...			
<input checked="" type="checkbox"/> position ...	Завідуюча 6 гуртожитку			
<input checked="" type="checkbox"/> address	Тичини 8а ...			
<input checked="" type="checkbox"/> email ...	dorm6@gmail.com ...			
<input checked="" type="checkbox"/> phoneNumber1 ...	+380968552211 ...			
<input checked="" type="checkbox"/> phoneNumber2 ...	+380990990999			
Key	Value	Description		

Body

PrettyRawPreviewVisualizeJSON

```
1 {
2   {
3     "category": "DORM_6",
4     "name": "Оксана Анатоліївна",
5     "position": "Завідуюча 6 гуртожитку",
6     "address": "Тичини 8а",
7     "email": "dorm6@gmail.com",
8     "phoneNumber1": " 380968552211",
9     "phoneNumber2": " 380990990999",
10    "id": 10
11  }
12 }
```

Headers:

Headers ▼		 200 OK 122 ms 455 B Save Response ▼
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

CHANGE CONTACT ITEM

Link: <https://studmisto.herokuapp.com/contacts/{id}>

Method: PUT

Returns: All contacts items

Request parameters:

NAME	TYPE	REQUIRED
category	String	true
name	String	true
position	String	true
address	String	true
email	String	true
phoneNumber1	String	true
phoneNumber2	String	true

Available category values:

GENERAL

DORM_3

DORM_5

DORM_6

DORM_7

Response parameters:

NAME	TYPE
category	ContactCategory
name	String
position	String
address	String
email	String
phoneNumber1	String
phoneNumber2	String
id	Long

Example:

PUT

https://studmisto.herokuapp.com/contacts/10?category=DORM_6&name=Оксана Анатоліївна&position=Завідуюча 6 гуртожитку&address=Тичини ...

Send

Save

ParamsAuthHeaders (7)BodyPre-req. TestsSettings

Query Params

	KEY	VALUE	DESCRIPTION	***	Bulk Edit
<input checked="" type="checkbox"/>	category	DORM_6			
<input checked="" type="checkbox"/>	name ...	Оксана Анатоліївна ...			
<input checked="" type="checkbox"/>	position ...	Завідуюча 6 гуртожитку			
<input checked="" type="checkbox"/>	address	Тичини 8а ...			
<input checked="" type="checkbox"/>	email ...	dorm6@gmail.com ...			
<input checked="" type="checkbox"/>	phoneNumber1 ...	-			
<input checked="" type="checkbox"/>	phoneNumber2 ...	+380990990999			
	Key	Value	Description		


Body

200 OK156 ms408 BSave Response

PrettyRawPreviewVisualizeJSON

```
1 {
2   {
3     "category": "DORM_6",
4     "name": "Оксана Анатоліївна",
5     "position": "Завідуюча 6 гуртожитку",
6     "address": "Тичини 8а",
7     "email": "dorm6@gmail.com",
8     "phoneNumber1": "-",
9     "phoneNumber2": "380990990999",
10    "id": 10
11  }
12 }
```

Headers:

Headers ▼		 200 OK 122 ms 455 B Save Response ▼
	KEY	VALUE
	Server ⓘ	Cowboy
	Connection ⓘ	keep-alive
	Content-Type ⓘ	application/json
	Transfer-Encoding ⓘ	chunked
	Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT
	Via ⓘ	1.1 vegur

DELETE CONTACT ITEM

Link: <https://studmisto.herokuapp.com/contacts/{id}>

Method: DELETE

Returns: All contacts items

Request parameters: -

Response parameters:

NAME	TYPE
category	ContactCategory
name	String
position	String
address	String
email	String
phoneNumber1	String
phoneNumber2	String
id	Long

Example:

DELETE

https://studmisto.herokuapp.com/contacts/10

Send

Save

ParamsAuthHeaders (6)BodyPre-reqTestsSettings

Query Params

KEY	VALUE	DESCRIPTION	Bulk Edit
Key	Value	Description	

Body

200 OK128 ms174 BSave Response

PrettyRawPreviewVisualizeJSON

1

Headers:

Headers		200 OK122 ms455 BSave Response
KEY	VALUE	
Server ⓘ	Cowboy	
Connection ⓘ	keep-alive	
Content-Type ⓘ	application/json	
Transfer-Encoding ⓘ	chunked	
Date ⓘ	Wed, 28 Oct 2020 10:52:21 GMT	
Via ⓘ	1.1 vegur	

LOGIN (JWT)

LOGIN

Link: <https://studmisto.herokuapp.com/login>

Method: POST

Returns: email + jwt token

Request parameters:

NAME	TYPE	REQUIRED
email	String	true
password	String	true

Response parameters:

NAME	TYPE
email	String
token	String

Example:

POST

http://localhost:9000/login?email=123@gmail.com&password=123123123

Send

Save

Params

Query Params

	KEY	VALUE	DESCRIPTION	...	Bulk Edit
<input checked="" type="checkbox"/>	email	123@gmail.com			
<input checked="" type="checkbox"/>	password	123123123			
	Key	Value	Description		

Body

Pretty Raw Preview Visualize

JSON

200 OK 1424 ms 631 B Save Response

```
1 {
2   "email": "123@gmail.com",
3   "token": "eyJhbGciOiJIUzI1NiJ9.eyJzdWIiOiIxMjNAZ2Z1haWwY29tIiw1cm9sZSI6Ii1VTRVI1LCJpYXQ1OjE2MTE3MzYyMTUsImV4cCI6MTYxMjM0MTAxNX0.uoS3OjhQFaA8TY1ambShJTJEUEdQ0emcq1NKb7i130c"
4 }
```

Headers:

Body	Cookies	Headers (14)	Test Results	200 OK 1557 ms 631 B Save Response
KEY	VALUE			
Vary ⓘ	Origin			
Vary ⓘ	Access-Control-Request-Method			
Vary ⓘ	Access-Control-Request-Headers			
X-Content-Type-Options ⓘ	nosniff			
X-XSS-Protection ⓘ	1; mode=block			
Cache-Control ⓘ	no-cache, no-store, max-age=0, must-revalidate			
Pragma ⓘ	no-cache			
Expires ⓘ	0			
X-Frame-Options ⓘ	DENY			
Content-Type ⓘ	application/json			
Transfer-Encoding ⓘ	chunked			
Date ⓘ	Wed, 27 Jan 2021 07:55:21 GMT			
Keep-Alive ⓘ	timeout=60			
Connection ⓘ	keep-alive			

LOGOUT

Link: <https://studmisto.herokuapp.com/logout>

Method: POST

Returns: -

Request parameters: -

Response parameters: -

USER

GET PRINCIPAL USER

Link: <https://studmisto.herokuapp.com/user/principal>

Method: GET

Returns: basic information about principal user (example for personal room). In frontend don't show parameter's information if parameter is empty

Request parameters: -

Response parameters:

NAME	TYPE
name	String
email	String
gender	String
institute	String
groupName	String
status	String
position	String
dorm	String
roomNumber	Integer
balance	Integer
tariff	String
userpic	String

GET SOME USER

Link: <https://studmisto.herokuapp.com/user/{id}>

Method: GET

Returns: basic information about some user (by id) (example for admin`s monitoring). In frontend don't show parameter`s information if parameter is empty

Request parameters:

NAME	TYPE	REQUIRED
id	Long	true

Response parameters:

NAME	TYPE
name	String
email	String
gender	String
institute	String
groupName	String
status	String
position	String
dorm	String
roomNumber	Integer
balance	Integer
tariff	String
userpic	String

GET ALL USERS

Link: <https://studmisto.herokuapp.com/user/all>

Method: GET

Returns: basic information about all users (example for admin's monitoring). In frontend don't show parameter's information if parameter is empty

Request parameters: -

Response parameters:

NAME	TYPE
id	Long
name	String
email	String
gender	String
institute	String
groupName	String
status	String
position	String
dorm	String
roomNumber	Integer
balance	Integer
tariff	String
userpic	String

ADD USER STAFF

Link: <https://studmisto.herokuapp.com/user/addStaff>

Method: POST

Returns: "message" if success or "errorMessage" if not success

Request parameters:

NAME	TYPE	REQUIRED
firstName	String	true
secondName	String	true
email	String	true
gender	String	true
position	String	true
status	String	true

Available gender values:

Чоловік

Жінка

Available status values:

Адміністрація студмістечка

Адміністрація/Персонал гуртожитку №3

Адміністрація/Персонал гуртожитку №5

Адміністрація/Персонал гуртожитку №6

Адміністрація/Персонал гуртожитку №7

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success

ADD USER EXIST INMATE

Link: <https://studmisto.herokuapp.com/user/addExistInmate>

Method: POST

Returns: “message” if success or “errorMessage” if not success

Request parameters:

NAME	TYPE	REQUIRED
firstName	String	true
secondName	String	true
email	String	true
gender	String	true
groupName	String	true
institute	String	true
roomNumber	Integer	true
dorm	String	true
password	String	true
position	String	true
status	String	true
balance	Double	true
tariff	String	true

Available gender values:

Чоловік

Жінка

Available status values:

Мешканець

Очікування ордеру

Available institute values:

Інститут інформаційних технологій

Інститут нафтогазової інженерії

Інститут природничих наук і туризму

Інститут економіки і менеджменту

Інститут архітектури, будівництва та енергетики

Інститут гуманітарної підготовки та державного управління

Інститут інженерної механіки

Available dorm values:

Гуртожиток №3

Гуртожиток №5

Гуртожиток №6

Гуртожиток №7

Available tariff values:

Стандарт

Пільговий (півціни)

Нуль

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success

UPDATE PRINCIPAL USER

Link: <https://studmisto.herokuapp.com/user/principal>

Method: PUT

Returns: “message” if success or “errorMessage” if not success

Request parameters:

NAME	TYPE	REQUIRED
password1	String	false
password2	String	false
email	String	false
userpic	String	false

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success

UPDATE SOME USER

Link: <https://studmisto.herokuapp.com/user/{id}>

Method: PUT

Returns: “message” if success or “errorMessage” if not success

Request parameters:

NAME	TYPE	REQUIRED
id	Long	true
institute	String	false
groupName	String	false
tariff	String	false
dorm	String	false
roomNumber	Integer	false
status	String	false
position	String	false

Available status values (if user belongs to staff, the 2 last points is not access. And vice versa):

Адміністрація студмістечка

Адміністрація/Персонал гуртожитку №3

Адміністрація/Персонал гуртожитку №5

Адміністрація/Персонал гуртожитку №6

Адміністрація/Персонал гуртожитку №7

Мешканець

Очікування ордеру

Available institute values (if user belongs to inmates):

Інститут інформаційних технологій

Інститут нафтогазової інженерії

Інститут природничих наук і туризму

Інститут економіки і менеджменту

Інститут архітектури, будівництва та енергетики

Інститут гуманітарної підготовки та державного управління

Інститут інженерної механіки

Available dorm values (if user belongs to inmates):

Гуртожиток №3

Гуртожиток №5

Гуртожиток №6

Гуртожиток №7

Available tariff values (if user belongs to inmates):

Стандарт

Пільговий (півціни)

Нуль

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success

DELETE SOME USER

Link: <https://studmisto.herokuapp.com/user/{id}>

Method: DELETE

Returns: -

Request parameters:

NAME	TYPE	REQUIRED
id	Long	true

Response parameters: -

ROOM

GET SOME ROOM

Link: <https://studmisto.herokuapp.com/room/{id}>

Method: GET

Returns: information about room (by id)

Request parameters:

NAME	TYPE	REQUIRED
id	Long	true

Response parameters:

NAME	TYPE
id	String
roomNumber	String
stage	Integer
dorm	String
places	Integer
availablePlaces	Integer
gender	String

GET ALL ROOMS

Link: <https://studmisto.herokuapp.com/room/all>

Method: GET

Returns: information about all rooms. If parameter “dorm” doesn’t exist (null), will show rooms from all dorms.

Request parameters:

NAME	TYPE	REQUIRED
dorm	String	false

Available dorm values:

Гуртожиток №3

Гуртожиток №5

Гуртожиток №6

Гуртожиток №7

Response parameters:

NAME	TYPE
id	String
roomNumber	String
stage	Integer
dorm	String
places	Integer
availablePlaces	Integer
gender	String

GET AVAILABLE ROOMS (for principal user)

Link: <https://studmisto.herokuapp.com/room/all>

Method: GET

Returns: information about all rooms. If parameter “dorm” doesn’t exist (null), will show rooms from all dorms.

Request parameters:

NAME	TYPE	REQUIRED
dorm	String	false

Available dorm values (if user belongs to inmates):

Гуртожиток №3

Гуртожиток №5

Гуртожиток №6

Гуртожиток №7

Response parameters:

NAME	TYPE
id	String
roomNumber	String
stage	Integer
dorm	String
places	Integer
availablePlaces	Integer
gender	String

ADD ROOM

Link: <https://studmisto.herokuapp.com/room>

Method: POST

Returns: “message” if success or “errorMessage” if not success

Request parameters:

NAME	TYPE	REQUIRED
roomNumber	Integer	true
dorm	String	true
stage	Integer	true
places	Integer	true

Available dorm values:

Гуртожиток №3

Гуртожиток №5

Гуртожиток №6

Гуртожиток №7

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success

UPDATE ROOM

Link: <https://studmisto.herokuapp.com/room/{id}>

Method: PUT

Returns: “message” if success or “errorMessage” if not success

Request parameters:

NAME	TYPE	REQUIRED
id	Long	true
places	Integer	true

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success

DELETE ROOM

Link: <https://studmisto.herokuapp.com/room/{id}>

Method: DELETE

Returns: “message” if success or “errorMessage” if not success

Request parameters:

NAME	TYPE	REQUIRED
id	Long	true

Response parameters:

NAME	TYPE	DESCRIPTION
message	String	Exist if request is success
errorMessage	String	Exist if request is not success