

Git Hands-on - Exercise 2 (.gitignore)

Exercise: Implement .gitignore

Aim

To implement the .gitignore file to ignore unwanted files and folders from being tracked by Git.

Procedure

1. Navigate to project folder
`cd /e/DEEPSKILLING/"MODULE 11 GIT"/GitIgnoreDemo`
2. Initialize the repository
`git init`
3. Create a log file
`touch error.log`
4. Create a log directory
`mkdir log`
5. Create a sample file inside log
`touch log/sample.txt`
6. Create the .gitignore file
`touch .gitignore`
7. Open the file
`notepad .gitignore`
8. Add the following lines
`*.log`
`log/`
9. Check repository status
`git status`
10. Stage the .gitignore file
`git add .gitignore`
11. Commit changes
`git commit -m "Added .gitignore file"`
12. Push to GitHub
`git push -u origin main`

Expected Result

The .gitignore file ignores all .log files and the log folder. Only the required project files are committed and pushed to GitHub.

Screenshots

- .gitignore file contents
- git status

```
MINGW64:/e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo
vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ touch error.log

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ mkdir log

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ touch log/sample.txt

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ touch .gitignore

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ notepad .gitignore

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ git status
On branch master

No commits yet

Untracked files:
  (use "git add <file>..." to include in what will be committed)

        .gitignore

nothing added to commit but untracked files present (use "git add" to track)
```

- git commit output

```
vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ git add .gitignore

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ git commit -m "Added .gitignore file"
[master (root-commit) fa93ac5] Added .gitignore file
1 file changed, 2 insertions(+)
create mode 100644 .gitignore

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ git remote add origin https://github.com/madhulikaprograms/GitIgnoreDemo.git

vsubbb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (master)
$ git branch -M main
```

- git push output

```
vsubb@LAPTOP-5MP2SIQF MINGW64 /e/DEEPSKILLING/MODULE 11 GIT/GitIgnoreDemo (main)
$ git push -u origin main
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 240 bytes | 120.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0), pack-reused 0
To https://github.com/madhulikaprograms/GitIgnoreDemo.git
 * [new branch]      main -> main
branch 'main' set up to track 'origin/main'.
```

- GitHub repository after successful push

Conclusion

The .gitignore file was successfully implemented to ignore unwanted files and folders. The repository was committed and pushed to GitHub successfully.