Lecture 4: Instruction sets + RISC-V

Monday, January 14, 2019 9:03 AM

Outline

- What is an ISA?
- RISC-V
  - Features
  - Extensions
  - User-mode vs privileged
- Other ISAs
- HLL to machine code



ISAs

What is an ISA?

Instruction set architecture

Encodes operations (machine encoding)

Contract between hardware and the software

Parts of ISA?

registers (# of, size, behavior)

Hardware/software stack



memory interface
- addresses
- "word" size
- consistency
- virtual memory

Power modes / control

Input / output → interacting w/ other devices
- interrupts

What is part of an ISA?

x86 vs RISC

RISC-V

RISC?

[John Hennessy and David Patterson 2017 ACM A.M. Turing Award Lecture]



General machine encoding

31 27	26 25	24 20	19 15	14 12	11 7	6 0	
funct7		rs2	rs1	funct3	rd	opcode	R-type
imm[11:0]			rs1	funct3	rd	opcode	I-type
imm[11:5]		rs2	rs1	funct3	imm[4:0]	opcode	S-type
imm[12|10:5]		rs2	rs1	funct3	imm[4:1|11]	opcode	B-type
imm[31:12]					rd	opcode	U-type
imm[20|10:1|11|19:12]					rd	opcode	J-type

Instruction types

See page 16 Figure 2.3 in RISC-V reader or page 104 table 19.2 in RISC-V user-mode spec.

R-type

0000000	rs2	rs1	000	rd	0110011	ADD
0100000	rs2	rs1	000	rd	0110011	SUB
0000000	rs2	rs1	001	rd	0110011	SLL
0000000	rs2	rs1	010	rd	0110011	SLT
0000000	rs2	rs1	011	rd	0110011	SLTU
0000000	rs2	rs1	100	rd	0110011	XOR
0000000	rs2	rs1	101	rd	0110011	SRL
0100000	rs2	rs1	101	rd	0110011	SRA
0000000	rs2	rs1	110	rd	0110011	OR
0000000	rs2	rs1	111	rd	0110011	AND

Memory instructions

imm[11:0]		rs1	000	rd	0000011	LB
imm[11:0]		rs1	001	rd	0000011	LH
imm[11:0]		rs1	010	rd	0000011	LW
imm[11:0]		rs1	100	rd	0000011	LBU
imm[11:0]		rs1	101	rd	0000011	LHU
imm[11:5]	rs2	rs1	000	imm[4:0]	0100011	SB
imm[11:5]	rs2	rs1	001	imm[4:0]	0100011	SH
imm[11:5]	rs2	rs1	010	imm[4:0]	0100011	SW

Branch instructions

imm[12|10:5]	rs2	rs1	000	imm[4:1|11]	1100011	BEQ
imm[12|10:5]	rs2	rs1	001	imm[4:1|11]	1100011	BNE
imm[12|10:5]	rs2	rs1	100	imm[4:1|11]	1100011	BLT
imm[12|10:5]	rs2	rs1	101	imm[4:1|11]	1100011	BGE
imm[12|10:5]	rs2	rs1	110	imm[4:1|11]	1100011	BLTU
imm[12|10:5]	rs2	rs1	111	imm[4:1|11]	1100011	BGEU

Immediate instructions

imm[31:12]	rd	0110111	LUI
imm[31:12]	rd	0010111	AUIPC

imm[11:0]		rs1	000	rd	0010011	ADDI
imm[11:0]		rs1	010	rd	0010011	SLTI
imm[11:0]		rs1	011	rd	0010011	SLTIU
imm[11:0]		rs1	100	rd	0010011	XORI
imm[11:0]		rs1	110	rd	0010011	ORI
imm[11:0]		rs1	111	rd	0010011	ANDI
0000000	shamt	rs1	001	rd	0010011	SLLI
0000000	shamt	rs1	101	rd	0010011	SRLI
0100000	shamt	rs1	101	rd	0010011	SRAI

Jump and link

imm[20|10:1|11|19:12]			rd	1101111	JAL
imm[11:0]	rs1	000	rd	1100111	JALR

Extensions

Base	Version	Frozen?
RV32I	2.0	Y
RV32E	1.9	N
RV64I	2.0	Y
RV128I	1.7	N

Extension	Version	Frozen?
M	2.0	Y
A	2.0	Y
F	2.0	Y
D	2.0	Y
Q	2.0	Y
L	0.0	N
C	2.0	Y
B	0.0	N
J	0.0	N
T	0.0	N
P	0.1	N
V	0.2	N
N	1.1	N

mult
atomic
floatin

vector

DINO CPU → RV32I

Book RV64I

RV64IMAFD → RV64G

RV64GC

→ compressed insts.

↳ encodes insts in 16 bits instead of 32

+ Saves code space

- more complex to decode