12. Actividad 5 — Anonimización

Query | Query History

```sql
--12.1 Generalizar la edad
SELECT
    CASE
        WHEN edad BETWEEN 18 AND 30 THEN '18-30'
        WHEN edad BETWEEN 31 AND 45 THEN '31-45'
        ELSE '46+'
    END AS rango_edad,
    COUNT(*) AS total
FROM clientes
GROUP BY 1;
```

Data Output | Messages | Notifications

	rango_edad text	total bigint
1	31-45	4
2	46+	1

```sql
--12.2 Generalizar la región
SELECT
    LEFT(codigo_postal, 2) AS region,
    COUNT(*) AS total
FROM clientes
GROUP BY 1;
```

Data Output | Messages | Notifications

	region text	total bigint
1	82	1
2	80	3
3	81	1

```sql
--12.3 Combinar atributos
SELECT
    CASE
        WHEN edad BETWEEN 18 AND 30 THEN '18-30'
        WHEN edad BETWEEN 31 AND 45 THEN '31-45'
        ELSE '46+'
    END AS rango_edad,

    LEFT(codigo_postal, 2) AS region,

    COUNT(*) AS total

FROM clientes

GROUP BY 1, 2;
```

Data Output | Messages | Notifications

SQL

	rango_edad text	region text	total bigint
1	31-45	81	1
2	46+	82	1
3	31-45	80	3

```sql
--12.4 Suprimir grupos pequeños
--Como ejercicio didáctico se utilizará un umbral de cinco registros:

SELECT
    CASE
        WHEN edad BETWEEN 18 AND 30 THEN '18-30'
        WHEN edad BETWEEN 31 AND 45 THEN '31-45'
        ELSE '46+'
    END AS rango_edad,

    LEFT(codigo_postal, 2) AS region,

    COUNT(*) AS total

FROM clientes

GROUP BY 1, 2

HAVING COUNT(*) >= 5;
```

Data Output | Messages | Notifications

SQL

	rango_edad text	region text	total bigint