



Universidad Nacional Autónoma de México
Facultad de Ciencias



Licenciatura en Ciencias de la Computación

Seminario de Ciencias de la Computación B

Computación en la nube

Tarea 3

Programación de Eureka Server y Hystrix

Elizalde Maza Jesús Eduardo
321031686
Peredo López Citlalli Abigail
321161022

Profesor Gustavo Arturo Marquez Flores

10 de febrero del 2026

Objetivo

Entender la programación de microservicios usando las API's de Eureka Server y Hystrix.

Especificación

Continuación de la tarea 2. Programar en la tarea 2 las siguientes actividades:

- Agregar el servidor Eureka Server y agregar en él los microservicios de lista y modelos de autos.



The screenshot shows the Eureka Server web interface in a browser. The address bar shows 'localhost:8761'. The page title is 'Instances currently registered with Eureka'. Below this is a table with columns: Application, AMIs, Availability Zones, and Status. There are two rows: 'SERVICIO-ITEMS' and 'SERVICIO-PRODUCTOS'. Below the table is a section 'General Info' with a table of server metrics. The metrics include total-avail-memory (110mb), num-of-cpus (8), current-memory-usage (51mb (46%)), server-uptime (00:00), registered-replicas (http://localhost:8761/eureka/), unavailable-replicas (http://localhost:8761/eureka/), and available-replicas.

Application	AMIs	Availability Zones	Status
SERVICIO-ITEMS	n/a (1)	(1)	UP (1) - 192.168.0.2:8002
SERVICIO-PRODUCTOS	n/a (1)	(1)	UP (1) - 192.168.0.2:8001

Name	Value
total-avail-memory	110mb
num-of-cpus	8
current-memory-usage	51mb (46%)
server-uptime	00:00
registered-replicas	http://localhost:8761/eureka/
unavailable-replicas	http://localhost:8761/eureka/
available-replicas	

- Agregar un método alternativo en el microservicio de lista de autos, provocando un fallo en el microservicio de modelos de autos que este servicio de lista de autos llama, utilizando Hystrix.

Sin fallo



The screenshot shows a web browser with the address 'localhost:8002/ver/1/cantidad/2'. The page content is a JSON response from a microservice. The JSON object has a 'producto' field with an object containing 'id', 'marca', 'modelo', 'anio', 'precio', and 'createAt'. It also has 'cantidad', 'total', 'factura', and 'iva' fields.

```
{
  "producto": {
    "id": 1,
    "marca": "Ford",
    "modelo": "Focus",
    "anio": 2010,
    "precio": 250000,
    "createAt": "2026-04-10T00:00:00.000+00:00"
  },
  "cantidad": 2,
  "total": 500000,
  "factura": "Número de Factura 3444523",
  "iva": 75000
}
```

Con fallo



A screenshot of a web browser window. The address bar shows the URL `localhost:8002/ver/1/cantidad/2`. Below the address bar, there is a status bar that says "Impresión con formato estilístico" with a checked checkbox. The main content area of the browser displays a JSON object. The JSON object has a root key "producto" which is an object containing "id", "marca", "modelo", "anio", "precio", and "createAt". There is also a "cantidad" key, a "total" key, a "factura" key with a value "Número de Factura 3444523", and an "iva" key.

```
{
  "producto": {
    "id": 1,
    "marca": "Sin marca",
    "modelo": "Modelo no disponible",
    "anio": null,
    "precio": 0,
    "createAt": null
  },
  "cantidad": 2,
  "total": 0,
  "factura": "Número de Factura 3444523",
  "iva": 0
}
```