

# A Linear Algebraic Framework for Dynamic Scheduling Over Memory-Equipped Quantum Networks<sup>1</sup>

arXiv:2307.06009

Paolo Fittipaldi<sup>A</sup>   Anastasios Giovanidis<sup>A,B</sup>   Frédéric Grosshans<sup>A</sup>

<sup>A</sup>Sorbonne Université, CNRS, LIP6

<sup>B</sup>Ericsson AI Research & Systems

JFQI 2023



---

<sup>1</sup>P. F., Anastasios Giovanidis, and Frédéric Grosshans. "A Linear Algebraic Framework for Dynamic Scheduling Over Memory-Equipped Quantum Networks". In: *IEEE Transactions on Quantum Engineering [Accepted for Publication]* (2023).

# Outline

## Introduction

- The Problem of Scheduling
- Our Work

## The Framework


- Preliminary Information
- Ebit Queues
- Demand Queues

## Application of the Framework

- Scheduling Policies
- Results

# The Problem of Scheduling

## Classical Networks




- Regulation of packet traffic along the network routes
- Standard solutions are well-known in the classical domain<sup>2</sup>

---

<sup>2</sup>L. Tassiulas and A. Ephremides. "Stability properties of constrained queueing systems and scheduling policies for maximum throughput in multihop radio networks". In: *IEEE Transactions on Automatic Control* 37.12 (1992), pp. 1936–1948.

# The Problem of Scheduling

## Quantum Networks



- Regulating which swapping operations happen at a given time
- Max Weight policies have recently been proven useful in quantum networks as well<sup>34</sup>

---


Thirupathaiah Vasantam and Don Towsley. "A throughput optimal scheduling policy for a quantum switch". In: *Quantum Computing, Communication, and Simulation II*, ed. by Philip R. Hemmer and Alan L. Migdall. Vol. 12015. International Society for Optics and Photonics. SPIE, 2022, p. 1201505.

P. F., Anastasios Giovanidis, and Frédéric Grosshans. "A Linear Algebraic Framework for Quantum Internet Dynamic Scheduling". In: *IEEE International Conference on Quantum Computing and Engineering (QCE22)*. Broomfield, CO, United States, Sept. 2022.

## Contributions

- **Dynamically controlled scheduling framework for arbitrary topologies and multiple commodities;**
- Proposal of two classes of scheduling policies;
- Benchmarking of the proposed policies over nontrivial topologies;


## Notation



Arbitrary connected graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ :

- Switches located at  $\mathcal{V}$
- (Lossy) fiber links along  $\mathcal{E}$
- Additionally,  $\tilde{\mathcal{E}} = \mathcal{V} \times \mathcal{V}$  contains *all* possible edges


## Notation



Arbitrary connected graph  $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ :

- Switches located at  $\mathcal{V}$
- (Lossy) fiber links along  $\mathcal{E}$
- Additionally,  $\tilde{\mathcal{E}} = \mathcal{V} \times \mathcal{V}$  contains *all* possible edges

## A Bird's-Eye View



$\forall i, j \in \tilde{\mathcal{E}} :$


- An *Ebit Queue*  $q_{ij}(t)$  keeps track of the stored entangled pairs
- A *Demand Queue*  $d_{ij}(t)$  stores user demand (if any).

### Objective

Linear equations that describe their intertwined evolution.



## A Bird's-Eye View




$\forall i, j \in \tilde{\mathcal{E}} :$

- An *Ebit Queue*  $q_{ij}(t)$  keeps track of the stored entangled pairs
- A *Demand Queue*  $d_{ij}(t)$  stores user demand (if any).

### Objective

Linear equations that describe their intertwined evolution.

## A Bird's-Eye View




$\forall i, j \in \tilde{\mathcal{E}} :$

- An *Ebit Queue*  $q_{ij}(t)$  keeps track of the stored entangled pairs
- A *Demand Queue*  $d_{ij}(t)$  stores user demand (if any).

### Objective

Linear equations that describe their intertwined evolution.

## A Bird's-Eye View



$\forall i, j \in \tilde{\mathcal{E}} :$

- An *Ebit Queue*  $q_{ij}(t)$  keeps track of the stored entangled pairs
- A *Demand Queue*  $d_{ij}(t)$  stores user demand (if any).

## Objective

Linear equations that describe their intertwined evolution.

## Ebit Queues

$\forall i, j \in \tilde{\mathcal{E}} :$

$$\begin{bmatrix} q_{AB}(t+1) \\ q_{BC}(t+1) \\ q_{AC}(t+1) \\ \dots \end{bmatrix} = \begin{bmatrix} q_{AB}(t) \\ q_{BC}(t) \\ q_{AC}(t) \\ \dots \end{bmatrix} + \begin{bmatrix} a_{AB}(t) \\ a_{BC}(t) \\ a_{AC}(t) \\ \dots \end{bmatrix} - \begin{bmatrix} \ell_{AB}(t) \\ \ell_{BC}(t) \\ \ell_{AC}(t) \\ \dots \end{bmatrix} \pm \text{scheduling}$$

## Ebit Queues

$\forall i, j \in \tilde{\mathcal{E}} :$

$$\begin{bmatrix} q_{AB}(t+1) \\ q_{BC}(t+1) \\ q_{AC}(t+1) \\ \dots \end{bmatrix} = \begin{bmatrix} q_{AB}(t) \\ q_{BC}(t) \\ q_{AC}(t) \\ \dots \end{bmatrix} + \begin{bmatrix} a_{AB}(t) \\ a_{BC}(t) \\ a_{AC}(t) \\ \dots \end{bmatrix} - \begin{bmatrix} \ell_{AB}(t) \\ \ell_{BC}(t) \\ \ell_{AC}(t) \\ \dots \end{bmatrix} \pm \text{scheduling}$$

# Ebit Queues

## Notation for Swapping

$$r_{i[j]k}(t) = n \in \mathbb{N}$$

### Example

$r_{A[B]C}(2) = 3 \rightarrow$  Three swapping operations at node  $B$  from queues  $AB$ ,  $BC$  to  $AC$  are scheduled to happen at time step 2.

# Ebit Queues

## Notation for Swapping


$$r_{i[j]k}(t) = n \in \mathbb{N}$$

### Example

$r_{A[B]C}(2) = 3 \rightarrow$  Three swapping operations at node  $B$  from queues  $AB$ ,  $BC$  to  $AC$  are scheduled to happen at time step 2.

$$\mathbf{r}(t) = [r_{A[B]C}(t) \quad r_{B[C]D}(t) \quad \dots]$$

## Ebit Queues

The *M* Matrix

	$A[B]C$	$B[C]D$	$A[B]D$	$A[C]D$
$AB$	-1	0	-1	0
$BC$	-1	-1	0	0
$CD$	0	-1	0	-1
$AC$	+1	0	0	-1
$BD$	0	+1	-1	0
$AD$	0	0	+1	+1

$$\mathbf{q}(t+1) = \mathbf{q}(t) - \boldsymbol{\ell}(t) + \mathbf{a}(t) + \mathbf{M}\mathbf{r}(t)$$



## Consuming Pairs to Serve Demands

$$\tilde{M} = \left[ M \quad | \quad -\mathbb{I}_{N_{\text{queues}}} \right]$$

	$A[B]C$	$B[C]D$	$A[B]D$	$A[C]D$	$AB$	$BC$	$CD$	$AC$	$BD$	$AD$
$AB$	-1	0	-1	0	-1	0	0	0	0	0
$BC$	-1	-1	0	0	0	-1	0	0	0	0
$CD$	0	-1	0	-1	0	0	-1	0	0	0
$AC$	+1	0	0	-1	0	0	0	-1	0	0
$BD$	0	+1	-1	0	0	0	0	0	-1	0
$AD$	0	0	+1	+1	0	0	0	0	0	-1

$$\mathbf{r}(t) = \left[ r_{A[B]C}(t) \quad r_{B[C]D}(t) \quad \dots \quad | \quad r_{AB}(t) \quad r_{BC}(t) \quad \dots \right]$$

## Demand Queues

$$\mathbf{q}(t+1) = \mathbf{q}(t) + \mathbf{a}(t) - \boldsymbol{\ell}(t) + \tilde{\mathbf{M}}\mathbf{r}(t)$$

$$\blacktriangleright \mathbf{d}(t+1) = \mathbf{d}(t) + \mathbf{b}(t) + \tilde{\mathbf{N}}\mathbf{r}(t)$$

$$\blacktriangleright \tilde{\mathbf{N}} = \left[ \mathbb{0}_{N_{\text{queues}} \times N_{\text{transitions}}} \mid -\mathbb{I}_{N_{\text{queues}}} \right]$$

## Recap

- $\forall (i, j) \in \tilde{\mathcal{E}}$  there is an ebit queue and a demand queue.
- Scheduling  $\rightarrow$  Deciding  $\mathbf{r}(t)$  given some information about  $\mathbf{q}$  and  $\mathbf{d}$
- Information about routing and topology is encoded in the  $\mathbf{M}$  matrix.

# Deriving a Scheduling Policy

## The Lyapunov Function

$$V(t) = \frac{1}{2} \mathbf{d}^T(t) \mathbf{d}(t) = d_{AB}^2 + d_{BC}^2 + d_{CD}^2 \dots$$

- Scalar measure of the overall system stability;
- Standard tool in classical Network Science;
- Akin to a potential in physics;

# Deriving a Scheduling Policy

## Lyapunov Drift

$$V(t) = \frac{1}{2} \mathbf{d}^T(t) \mathbf{d}(t)$$

$$\Delta V = \frac{1}{2} \mathbb{E}[\mathbf{d}^T(t+1) \mathbf{d}(t+1) - \mathbf{d}^T(t) \mathbf{d}(t) | \mathcal{I}(t)]$$

Expanding the mathematics, we obtain a **controllable expression** that gauges the effects of a given scheduling decision on the system.

# Deriving a Scheduling Policy

## The Full Information Quadratic Scheduler

$$\Delta V = \frac{1}{2} \mathbb{E}[\mathbf{d}^T(t+1)\mathbf{d}(t+1) - \mathbf{d}^T(t)\mathbf{d}(t) | \mathcal{I}(t)] \rightarrow \begin{cases} \mathbf{r}(t) = \arg \min \left( \mathbf{w}^T(t) \cdot \mathbf{r}(t) + \right. \\ \left. + \frac{1}{2} \mathbf{r}(t)^T \tilde{\mathbf{N}}^T \tilde{\mathbf{N}} \mathbf{r}(t) \right) \\ \text{s.t. } \mathbf{r}(t) \in \mathcal{R}(t) \\ \mathbf{w}(t) = (\mathbf{d}(t) + \mathbf{b}(t))^T \tilde{\mathbf{N}} \end{cases}$$

$$\mathcal{R}(t) = \left\{ \mathbf{r}(t) \in \mathbb{N}^d \mid \begin{array}{l} -\tilde{\mathbf{M}}\mathbf{r}(t) \leq \mathbf{q}(t) - \boldsymbol{\ell}(t) + \mathbf{a}(t) \\ -\tilde{\mathbf{N}}\mathbf{r}(t) \leq \mathbf{d}(t) + \mathbf{b}(t) \end{array} \right\}$$

- At every time step, solve the optimization problem
- + High performance
- Large communication requirements
- High computational cost

# Deriving a Scheduling Policy

## The Full Information Quadratic Scheduler

$$\Delta V = \frac{1}{2} \mathbb{E}[\mathbf{d}^T(t+1)\mathbf{d}(t+1) - \mathbf{d}^T(t)\mathbf{d}(t) | \mathcal{I}(t)] \rightarrow \begin{cases} \mathbf{r}(t) = \arg \min \left( \mathbf{w}^T(t) \cdot \mathbf{r}(t) + \right. \\ \left. + \frac{1}{2} \mathbf{r}(t)^T \tilde{\mathbf{N}}^T \tilde{\mathbf{N}} \mathbf{r}(t) \right) \\ \text{s.t. } \mathbf{r}(t) \in \mathcal{R}(t) \\ \mathbf{w}(t) = (\mathbf{d}(t) + \mathbf{b}(t))^T \tilde{\mathbf{N}} \end{cases}$$

$$\mathcal{R}(t) = \left\{ \mathbf{r}(t) \in \mathbb{N}^d \mid \begin{array}{l} -\tilde{\mathbf{M}}\mathbf{r}(t) \leq \mathbf{q}(t) - \ell(t) + \mathbf{a}(t) \\ -\tilde{\mathbf{N}}\mathbf{r}(t) \leq \mathbf{d}(t) + \mathbf{b}(t) \end{array} \right\}$$

- At every time step, solve the optimization problem
- + High performance
- Large communication requirements
- High computational cost

# Deriving a Scheduling Policy

## The Full Information Quadratic Scheduler

$$\Delta V = \frac{1}{2} \mathbb{E}[\mathbf{d}^T(t+1)\mathbf{d}(t+1) - \mathbf{d}^T(t)\mathbf{d}(t) | \mathcal{I}(t)] \rightarrow \begin{cases} \mathbf{r}(t) = \arg \min \left( \mathbf{w}^T(t) \cdot \mathbf{r}(t) + \right. \\ \left. + \frac{1}{2} \mathbf{r}(t)^T \tilde{\mathbf{N}}^T \tilde{\mathbf{N}} \mathbf{r}(t) \right) \\ \text{s.t. } \mathbf{r}(t) \in \mathcal{R}(t) \\ \mathbf{w}(t) = (\mathbf{d}(t) + \mathbf{b}(t))^T \tilde{\mathbf{N}} \end{cases}$$

$$\mathcal{R}(t) = \left\{ \mathbf{r}(t) \in \mathbb{N}^d \quad \left| \quad \begin{array}{l} -\tilde{\mathbf{M}}\mathbf{r}(t) \leq \mathbf{q}(t) - \boldsymbol{\ell}(t) + \mathbf{a}(t) \\ -\tilde{\mathbf{N}}\mathbf{r}(t) \leq \mathbf{d}(t) + \mathbf{b}(t) \end{array} \right. \right\}$$

- At every time step, solve the optimization problem
- + High performance
- Large communication requirements
- High computational cost



# Deriving a Scheduling Policy

## The Full Information Quadratic Scheduler

$$\Delta V = \frac{1}{2} \mathbb{E}[\mathbf{d}^T(t+1)\mathbf{d}(t+1) - \mathbf{d}^T(t)\mathbf{d}(t) | \mathcal{I}(t)] \rightarrow \begin{cases} \mathbf{r}(t) = \arg \min \left( \mathbf{w}^T(t) \cdot \mathbf{r}(t) + \right. \\ \left. + \frac{1}{2} \mathbf{r}(t)^T \tilde{\mathbf{N}}^T \tilde{\mathbf{N}} \mathbf{r}(t) \right) \\ \text{s.t. } \mathbf{r}(t) \in \mathcal{R}(t) \\ \mathbf{w}(t) = (\mathbf{d}(t) + \mathbf{b}(t))^T \tilde{\mathbf{N}} \end{cases}$$

$$\mathcal{R}(t) = \left\{ \mathbf{r}(t) \in \mathbb{N}^d \quad \left| \quad \begin{array}{l} -\tilde{\mathbf{M}}\mathbf{r}(t) \leq \mathbf{q}(t) - \ell(t) + \mathbf{a}(t) \\ -\tilde{\mathbf{N}}\mathbf{r}(t) \leq \mathbf{d}(t) + \mathbf{b}(t) \end{array} \right. \right\}$$

- At every time step, solve the optimization problem
- + High performance
- Large communication requirements
- High computational cost

# Alternative Scheduling Policies

## PROBLEMS

- Quadratic integer optimization is computationally expensive;
- Full-Information scheduling has impossible communication constraints;

## SOLUTIONS

- Suppress the quadratic term in the optimization problem → **MAX-WEIGHT SCHEDULING**;
- Replace all the information we don't have with educated guesses → **LOCAL INFORMATION SCHEDULING**

## Alternative Scheduling Policies

### PROBLEMS

- Quadratic integer optimization is computationally expensive;
- Full-Information scheduling has impossible communication constraints;

### SOLUTIONS

- Suppress the quadratic term in the optimization problem → **MAX-WEIGHT SCHEDULING**;
- Replace all the information we don't have with educated guesses → **LOCAL INFORMATION SCHEDULING**

## Alternative Scheduling Policies

### PROBLEMS

- Quadratic integer optimization is computationally expensive;
- Full-Information scheduling has impossible communication constraints;

### SOLUTIONS

- Suppress the quadratic term in the optimization problem → **MAX-WEIGHT SCHEDULING**;
- Replace all the information we don't have with educated guesses → **LOCAL INFORMATION SCHEDULING**

## Alternative Scheduling Policies

### PROBLEMS

- Quadratic integer optimization is computationally expensive;
- Full-Information scheduling has impossible communication constraints;

### SOLUTIONS

- Suppress the quadratic term in the optimization problem → **MAX-WEIGHT SCHEDULING**;
- Replace all the information we don't have with educated guesses → **LOCAL INFORMATION SCHEDULING**

## Alternative Scheduling Policies

### PROBLEMS




- Quadratic integer optimization is computationally expensive;
- Full-Information scheduling has impossible communication constraints;

### SOLUTIONS

- Suppress the quadratic term in the optimization problem → **MAX-WEIGHT SCHEDULING**;
- Replace all the information we don't have with educated guesses → **LOCAL INFORMATION SCHEDULING**



# Result Example

## FIMW Scheduler, Simple Topology



## Results



## Grid with Holes





## Results

## Watts-Strogatz Graph



## Summary

- We introduced a multicommodity dynamically controlled framework for scheduling on general topologies;
- We derived a class of scheduling policies for quantum networks that minimizes the square norm of the demand backlog;
- Our framework was demonstrated to be useful as a benchmarking tool for arbitrary policies over non-trivial topologies.
- Outlook
  - Introducing quantum noise in the framework;
  - Provide analytical demonstration of stability and optimality of policies.

## References



**F., P., Anastasios Giovanidis, and Frédéric Grosshans.** “A Linear Algebraic Framework for Dynamic Scheduling Over Memory-Equipped Quantum Networks”. In: *IEEE Transactions on Quantum Engineering [Accepted for Publication]* (2023).



**F., P., Anastasios Giovanidis, and Frédéric Grosshans.** “A Linear Algebraic Framework for Quantum Internet Dynamic Scheduling”. In: *IEEE International Conference on Quantum Computing and Engineering (QCE22)*. Broomfield, CO, United States, Sept. 2022.



**Tassiulas, L. and A. Ephremides.** “Stability properties of constrained queueing systems and scheduling policies for maximum throughput in multihop radio networks”. In: *IEEE Transactions on Automatic Control* 37.12 (1992), pp. 1936–1948.



**Vasantam, Thirupathaiah and Don Towsley.** “A throughput optimal scheduling policy for a quantum switch”. In: *Quantum Computing, Communication, and Simulation II*. Ed. by Philip R. Hemmer and Alan L. Migdall. Vol. 12015. International Society for Optics and Photonics. SPIE, 2022, p. 1201505.