

LINEAR OPTICAL LOGICAL BELL MEASUREMENTS

CONSTRUCTIONS & OPTIMALITY

arXiv:2101.11082 & arXiv:2302.07908


Frédéric Grosshans

with Paul Hilaire, Yaron Castor, Edwin Barnes, Sophia E. Economou

December 14, 2023, Tokyo, JFQI



OUR GOAL: TELEPORT QUBITS FAR AWAY



Linear Optical Bell Measurement

A family of photonic tree codes


Optimal loss-tolerant LO-BSMs

What's next?

LINEAR OPTICAL BELL MEASUREMENT

PHYSICAL BELL STATE MEASUREMENT

[Weinfurter '94] „Innsbruck scheme”




- $\Pr(\text{success}) = \frac{1}{2}$
- known to be optimal

[Calsamiglia&Lütkenhaus '99]

PHYSICAL BELL STATE MEASUREMENT

[Weinfurter '94] „Innsbruck scheme”




- $\Pr(\text{success}) = \frac{1}{2}$
- known to be optimal

[Calsamiglia&Lütkenhaus '99]

PHYSICAL BELL STATE MEASUREMENT

[Weinfurter '94] „Innsbruck scheme”




- $\Pr(\text{success}) = \frac{1}{2}$
- known to be optimal

[Calsamiglia&Lütkenhaus '99]

$$\begin{array}{lll} X_a X_b = & +1 & -1 \\ Z_a Z_b = +1 & \Phi^+ & \Phi^- \\ Z_a Z_b = -1 & \Psi^+ & \Psi^- \end{array}$$

PHYSICAL BELL STATE MEASUREMENT

[Weinfurter '94] „Innsbruck scheme”



- $\Pr(\text{success}) = \frac{1}{2}$
- known to be optimal

[Calsamiglia&Lütkenhaus '99]

$X_a X_b =$	$+1$	-1
$Z_a Z_b = +1$	Φ^+	Φ^-
$Z_a Z_b = -1$	Ψ^+	Ψ^-


Actually equivalent to
Measure $Z_a Z_b$. If

$Z_a Z_b \stackrel{?}{=} +1$: Measure $X_a X_b$

$Z_a Z_b \stackrel{?}{=} -1$: Measure Z_a

PHYSICAL BELL STATE MEASUREMENT

[Weinfurter '94] „Innsbruck scheme”



- $\Pr(\text{success}) = \frac{1}{2}$
- known to be optimal

[Calsamiglia&Lütkenhaus '99]

$X_a X_b =$	$+1$	-1
$Z_a Z_b = +1$	Φ^+	Φ^-
$Z_a Z_b = -1$	Ψ^+	Ψ^-


Actually equivalent to
Measure $Z_a Z_b$. If

$Z_a Z_b \stackrel{?}{=} -1$: Measure $X_a X_b$


$Z_a Z_b \stackrel{?}{=} +1$: Measure Z_a

A FAMILY OF PHOTONIC TREE CODES

THE TREE CODE AND ITS DECODING




GOOD PERFORMANCES



- (a-b) for 15-15-2 tree (691 qubits)

GOOD PERFORMANCES




- (a-b) for 15-15-2 tree (691 qubits)

- For $n \rightarrow \infty$, numerics show $P_{\text{BSM}} \rightarrow \begin{matrix} 1 \\ \swarrow \searrow \\ 0 \end{matrix}$ around

- $\eta_{\text{stat}}^{\min} \rightarrow .81640568 \dots \approx \sqrt{\frac{2}{3}}$

- $\eta_{\text{dyn}}^{\min} \rightarrow .50000000 \dots \approx \frac{1}{2}$

TOO GOOD PERFORMANCES TO BE TRUE ?



- (a-b) for 15-15-2 tree (691 qubits)

- For $n \rightarrow \infty$, numerics show $P_{BSM} \rightarrow \begin{matrix} 1 \\ \swarrow \searrow \\ 0 \end{matrix}$ around


- $\eta_{\text{stat}}^{\min} \rightarrow .81640568 \dots \approx \sqrt{\frac{2}{3}}$

- $\eta_{\text{dyn}}^{\min} \rightarrow .50000000 \dots \approx \frac{1}{2}$

- but [Lee, Ralph, Jeong '19] showed

- $\eta_{LO}^{\min} > \frac{1}{\sqrt{2}} \approx .70710681 \dots$

GOOD PERFORMANCES



- (a-b) for 15-15-2 tree (691 qubits)

- For $n \rightarrow \infty$, numerics show $P_{\text{BSM}} \rightarrow \begin{matrix} 1 \\ \swarrow \searrow \\ 0 \end{matrix}$ around

- $\eta_{\text{stat}}^{\min} \rightarrow .81640568 \dots \approx \sqrt{\frac{2}{3}}$


- $\eta_{\text{dyn}}^{\min} \rightarrow .50000000 \dots \approx \frac{1}{2}$

- but [Lee, Ralph, Jeong '19] showed

- $\eta_{\text{LO}}^{\min} > \frac{1}{\sqrt{2}} \approx .70710681 \dots$

- [Lee, Ralph, Jeong '19]'s proof assumed BSMs measurement but single-photon measurements are useful!

CAN WE DO BETTER WITH SURFACE CODES?



- Surface codes are more efficient than tree codes
- ...and we can use the same tricks

CAN WE DO BETTER WITH SURFACE CODES?

- Surface code are more efficient than tree codes
- ...and we can use the same tricks
- Paul & I had a lot of ideas about beating the static $\sqrt{\frac{2}{3}}$ -bound

CAN WE DO BETTER WITH SURFACE CODES?


- Surface code are more efficient than tree codes
- ...and we can use the same tricks
- Paul & I had a lot of ideas about beating the static $\sqrt{\frac{2}{3}}$ -bound
Yaron proved us wrong

CAN WE DO BETTER WITH SURFACE CODES?

- Surface code are more efficient than tree codes
- ...and we can use the same tricks
- Paul & I had a lot of ideas about beating the static $\sqrt{\frac{2}{3}}$ -bound
Yaron proved us wrong
- Easier to find analytical bounds

OPTIMAL LOSS-TOLERANT LO-BSMs

NO CLONING BOUND AND LOGICAL BSM




Data only depends on the product $\eta_a \eta_b$ so
no cloning condition has to be ensured by $\eta_a \eta_b$


$$\begin{aligned} \forall \eta_a, \eta_b : \eta_a \eta_b > \frac{1}{2} &\Rightarrow \begin{cases} \frac{1}{2} < \eta_a < 1 & \nexists \text{ copy of } a \\ \frac{1}{2} < \eta_b < 1 & \nexists \text{ copy of } b \end{cases} \\ \exists \eta_a, \eta_b : \eta_a \eta_b \leq \frac{1}{2} &\Leftarrow \begin{cases} \eta_a \leq \frac{1}{2} & \exists \text{ copy of } a \\ \eta_b = 1 \end{cases} \end{aligned}$$

This is the $\frac{1}{\sqrt{2}}$ bound of [Lee, Ralph, Jeong '14] and they provide an explicit code achieving it

LOCAL OBSERVABLE DECODING




LOCAL OBSERVABLE DECODING




$$\text{If } [\hat{O}_C, \hat{O}'_C] \neq 0, \eta_{O_C}^{\min} + \eta_{O'_C}^{\min} > 1$$

USING STATIC BSMS TO MEASURE X AND Z




USING STATIC BSMS TO MEASURE X AND Z


(a)



(b)



USING STATIC BSMS TO MEASURE X AND Z



Success if $\eta_a \Pr(XX) > \eta_X^{\min}$ & $\eta_a \Pr(ZZ) > \eta_Z^{\min}$

$\Rightarrow \eta_a \eta_b > \max \left(\frac{\eta_X^{\min}}{\Pr(XX)}, \frac{\eta_Z^{\min}}{\Pr(ZZ)} \right) \geq \frac{2}{3}$ since $\Pr(XX) + \Pr(ZZ) = \frac{2}{3}$ and $\eta_X^{\min} + \eta_Z^{\min} > 1$

USING STATIC BSMS TO MEASURE X AND Z

Success if $\eta_a \Pr(XX) > \eta_X^{\min}$ & $\eta_a \Pr(ZZ) > \eta_Z^{\min}$

$\Rightarrow \eta_a \eta_b > \max\left(\frac{\eta_X^{\min}}{\Pr(XX)}, \frac{\eta_Z^{\min}}{\Pr(ZZ)}\right) \geq \frac{2}{3}$ since $\Pr(XX) + \Pr(ZZ) = \frac{2}{3}$ and $\eta_X^{\min} + \eta_Z^{\min} > 1$

USING STATIC BSMS TO MEASURE X AND Z

Success if $\eta_a \Pr(XX) > \eta_X^{\min}$ & $\eta_a \Pr(ZZ) > \eta_Z^{\min}$

$\Rightarrow \eta_a \eta_b > \max\left(\frac{\eta_X^{\min}}{\Pr(XX)}, \frac{\eta_Z^{\min}}{\Pr(ZZ)}\right) \geq \frac{2}{3}$ since $\Pr(XX) + \Pr(ZZ) = \frac{2}{3}$ and $\eta_X^{\min} + \eta_Z^{\min} > 1$

Limit achieved with random BSMS ($\Pr\{XX\} = \Pr\{ZZ\} = \frac{3}{4}$)


and surface codes with $\frac{1}{2}$ threshold¹

¹or our trees if $.5000000 \dots = \frac{1}{2}$



ADAPTIVE LO SPMs + BSMs ENOUGH FOR THE NO-CLONING THRESHOLD

There is a concatenated $(2, n)$ -Shor code allowing to make BSMs when

$$\min(\eta_b, \eta_a) > \frac{1}{2}$$



PERFORMANCES



WHAT'S NEXT?

WHAT'S NEXT?

- Look at actual good QECC (finite number of qubits, finite efficiency)
- Take into account the preparation cost of the codes
- Static LOBSM setting if we allow more general linear-optical information processing ?
- Find (and implement) a realistic one !