CASE #1

Author: José Gabriel Marín Aguilar c.2022119819

Problem Overview

The Documento Único Aduanero (DUA) is the official customs declaration document required for import and export operations in Costa Rica, regulated by the Ministerio de Hacienda.

Preparing a DUA requires interpreting heterogeneous documents such as invoices, packing lists, certificates of origin, transport documents, and permits. These files vary in format (Excel, Word, PDF, scanned images), structure, terminology, and quality. Manual preparation is:

- Repetitive
- Error-prone
- Highly dependent on expert knowledge
- Time-consuming

Proposed Solution

DUA Streamliner is an AI-powered system that ingests a folder containing heterogeneous trade documents, extracts relevant customs data using semantic models, maps the information into the official DUA template, and generates a pre-filled Word document with confidence indicators.

The system does not replace the customs expert; it reduces operational workload and shifts the expert's role toward validation and decision-making.

Pros	Cons
Reduces manual workload	OCR accuracy depends on document quality
Minimizes data entry errors	AI extraction requires continuous validation
Standardizes DUA preparation	Legal responsibility remains with the declarant
Improves processing time	

1. Frontend Design

1.1 Technology Stack

- **Application type:** Web application fully responsive for tablet and mobile access.
- **Web Framework:** React 19.2
- **Runtime:** Node.js 21.x
- **Coding Language:** TypeScript 5.9.3
- **Bundler:** Vite 6.x
- **UI Framework:** MUI 6.x
- **Routing:** React Router DOM 6.25.x

- **Authentication approach:** Custom JWT-based authentication with email OTP verification
- **Unit Testing:** Jest 30.2.0
- **Data Validation:** Zod 3.x
- **Code prettier framework:** Prettier 3.x
- **Code style framework:** ESLint 9.x with @typescript-eslint 7.x
- **Integration testing tools:** Playwright 1.58.2
- **Cloud service:** Amazon Web Services (AWS)
- **Hosted services within the cloud service:**
  - AWS ECS Fargate
  - AWS Elastic Container Registry (ECR)
  - AWS Application Load Balancer (ALB)
  - AWS CloudFront
  - AWS CloudWatch
  - AWS Certificate Manager (ACM)
- **Code repositories service:** GitHub
- **Code automation task tool:** npm scripts (Node.js 21.x runtime)
- **CI CD pipelines technology:** GitHub Actions
- **Environments:**
  - Development
  - Quality Assurance
  - Stage
  - Production
- **Environment deployment tools:**
  - Docker 25.x
  - Terraform 1.8.x
  - AWS CLI 2.x
- **Observability framework:**
  - AWS CloudWatch
  - OpenTelemetry JS 1.x
  - Sentry

1.2 UX/UI Analysis

Core Business Process

The application allows customs operators to automatically generate a Documento Único Aduanero (DUA) from multiple source documents.

Users authenticate using their credentials and a one-time token sent to their email. Once logged in, they can either review previously generated DUAs or initiate the creation of a new one.

When generating a new DUA, the user configures the generation parameters such as accepted document formats and the template version to be used. The system then processes the uploaded documents, extracts the relevant customs information using AI models, and maps the data into the official DUA structure.

During processing, the user can monitor the progress of the extraction and generation process. Once completed, the system displays the generated DUA in a PDF viewer where the user can review and download

the final document.

Usability Attributes

- Learnability
- Consistency
- Accessibility
- Error prevention
- Clear system feedback
- Efficiency
- Confidence transparency
- Responsive behavior

Wireframes

User Login

The user logs into the system using their username, password, and a one-time authentication token received via email. 



Select Option

After authentication, the user can choose between generating a new DUA or reviewing previously generated declarations.



DUA History

The system displays a list of previously generated DUAs associated with the user account. Each record can later be expanded or downloaded.



Generator Configuration

The user configures the generation process before uploading documents.

Configuration options include:

- Accepted document formats (PDF, Image, Word, Excel)
- DUA template version (latest from the Ministry of Finance or custom uploaded template)
- AI extraction mode (fast scan / detailed extraction)



Upload Files

The user uploads the commercial documents required to generate the DUA. Files can be uploaded using drag-and-drop or manual selection. Supported formats include:

- PDF
- DOCX
- XLSX
- Images







Processing Progress

During the document processing stage, the user can monitor the progress of the generation pipeline. The interface displays a progress bar and indicates the current step of the process.



DUA Result

Once the process is completed, the generated DUA is displayed in a PDF preview interface. The user can review the document and download it as a PDF file.

Alternative view

Another version of the wireframes can be found here: Coderick AI generated wireframes

---

1.3 Component Design Strategy

DUA Streamliner uses **Atomic Design** over a **component-based React architecture**. The interface is built from small reusable UI elements that are progressively composed into larger components and full pages. This approach improves consistency, maintainability, and scalability, while keeping presentation concerns separate from business logic.

Reusability is achieved by implementing shared UI elements only once and reusing them across screens. Common controls such as buttons, text fields, dialogs, upload areas, progress bars, tables, alerts, and PDF preview containers are placed in a shared component layer. Feature-specific components are then composed from those base elements. This reduces duplication and ensures that the same interaction patterns are preserved across the full application.

Styling is centralized through a single theme layer built on top of MUI. Colors, typography, spacing, border radius, shadows, and component variants are defined in in `src/theme/theme.ts` and propagated through the full application. This allows visual updates to be applied globally without modifying business components. Branding is handled in the same layer by defining the project color palette, logo usage, icon rules, and UI tokens as part of the shared theme configuration.

Internationalization is implemented through a centralized i18n configuration, where all user-facing labels, messages, button texts, and validation messages are externalized into locale files such as `src/i18n/en.json` and `src/i18n/es.json` of being hardcoded inside components. This makes the UI language-independent and simplifies future support for multiple languages, currencies, and regional formats.

Responsiveness is addressed at the component level using responsive layouts, breakpoints, and adaptive sizing rules. Components are designed to work consistently across desktop, tablet, and mobile browser widths, while preserving readability and workflow clarity. Since responsiveness is solved in the shared component system, the behavior propagates to the rest of the screens without redefining each page independently.

Accessibility is also enforced at the component level. Shared components follow consistent semantic structure, keyboard navigation rules, visible focus states, sufficient contrast, and reusable feedback patterns. This makes accessibility improvements scalable, because once a shared component is improved, the change benefits all screens that reuse it.

Strategy Summary

Strategy Summary

- **Name of the strategy:** Atomic Design with component-based React architecture
- **Reutilization by:** shared components in `src/components/atoms/`, `src/components/molecules/`, `src/components/organisms/`, `src/components/templates/`, and page composition in `src/components/pages/`
- **Internationalization by:** centralized locale resources in `src/i18n/`
- **Responsiveness by:** responsive MUI layouts, theme breakpoints in `src/theme/theme.ts`, and adaptive page composition in `src/components/templates/`

Suggested Component Structure

```
src/
  components/
    atoms/
    molecules/
    organisms/
    templates/
    pages/
```

```
    hooks/
    theme/
    i18n/
```

1.4 Security

Security in DUA Streamliner follows modern web application security principles, focusing on authentication, authorization, session handling, and safe management of sensitive information. The frontend uses custom JWT-based authentication, secure route protection, and centralized session-aware services, while sensitive values remain outside the source code.

Authentication is implemented with email or username, password, and a one-time token sent by email as a lightweight multi-factor mechanism. The frontend consumes the authentication flow through `src/auth/authProvider.tsx`, `src/services/authService.ts`, and `src/api/authApiClient.ts`. After successful login, the backend issues a JWT token used to protect subsequent requests.

The project uses **independent authentication** instead of external Single Sign-On. This keeps the architecture simpler and gives the platform full control over users, claims, and roles. Authorization is implemented using **Role-Based Access Control (RBAC)**. Authenticated users are assigned roles and claims, and route-level protection is enforced through `src/auth/authGuard.tsx` and `src/auth/permissionGuard.tsx`.

The frontend session is managed through JWT tokens, protected navigation, and centralized auth state. Sensitive configuration values such as API endpoints, client configuration, and runtime environment variables are kept in `src/settings/env.ts` and deployment-level secret storage.

Security-Related Classes and Location

```
src/
  auth/
    authProvider.tsx
    authGuard.tsx
    permissionGuard.tsx

  services/
    authService.ts

  api/
    authApiClient.ts

  settings/
    env.ts
```

Roles

Typical roles within the system include:

- Importer / Exporter – Users who generate and manage DUA declarations.

- Customs Officer – Users who review submitted declarations.
- Administrator – Users who manage system configurations and permissions.

RBAC simplifies permission management while maintaining clear separation of responsibilities between different user groups. The authorization rules are enforced in the backend through middleware or guards that validate the user's role and permissions before executing protected operations.

Permissions and Claims

Permissions within the system are defined using structured claims, which represent the actions a user can perform. These claims can be embedded inside the authentication token or validated on the server side.

Code	Description
CREATE-DUA	Allows the user to generate a new DUA declaration.
UPLOAD-DOCUMENT	Allows the user to upload supporting documents for a declaration.
VIEW-DUA	Allows the user to view previously generated declarations.
EDIT-DUA	Allows the user to modify declaration data before submission.
REVIEW-DUA	Allows customs officers to review submitted declarations.
ADMIN-MANAGE-USERS	Allows administrators to manage user accounts and roles.

These claims are evaluated by the backend authorization layer to ensure that users only perform actions allowed by their role.

1.5 Layered Design

The DUA Streamliner frontend is organized as a layered architecture by responsibility. Each layer isolates a specific concern of the web application, allowing the UI, workflow orchestration, security, validation, external communication, and system configuration to evolve independently. This improves maintainability, testability, and consistency across the main flows of the platform.

The execution starts in the **Authentication Layer** and **Authorization Layer**, which control secure access, session awareness, and role-based route protection. The **Routing Layer**, implemented in `src/router/appRouter.tsx` and `src/router/protectedRoute.tsx`, connects the main screens and defines protected navigation between login, history, generator configuration, upload, processing, and result pages.

The **Component Layer** is the visual layer of the application and follows the Atomic Design strategy selected for the project. It is composed of atoms, molecules, organisms, templates, and pages inside `src/components/`. React hooks in `src/hooks/` are placed close to this layer because they are triggered from components and coordinate user interactions such as login submission, document upload, DUA generation, and history loading.

Below the UI, the **DUA Workflow Services** layer orchestrates the main frontend use cases. It coordinates authentication flow, file upload, generation requests, progress tracking, history retrieval, and result delivery

through services in `src/services/`. This layer consumes API clients in `src/api/`, applies schemas from `src/validation/` before and after external calls, and reads configuration from `src/settings/`.

Supporting layers complete the architecture. The **Models Layer** in `src/models/` defines frontend domain objects such as `User`, `DUA`, `Document`, `Goods`, and `GenerationJob`. The **State Management Layer** in `src/state/` stores global application state such as session status, current workflow step, generated declarations, and upload progress. The **Utilities Layer** in `src/utils/` contains reusable helpers and formatters. The **Observability / Notifications Layer** in `src/observability/` captures frontend errors, telemetry events, process logs, and user-facing notifications.

Typical Responsibility Layers

- Authentication Layer
- Authorization Layer
- Routing Layer
- Component Layer
- Hooks Layer
- DUA Workflow Services
- Validation Layer
- API Clients Layer
- Settings Layer
- Models Layer
- State Management
- Utilities Layer
- Observability / Notifications

Suggested Folder Architecture

```
src/
  auth/
    authProvider.tsx
    authGuard.tsx
    permissionGuard.tsx

  router/
    appRouter.tsx
    protectedRoute.tsx

  components/
    atoms/
    molecules/
    organisms/
    templates/
    pages/

  hooks/
    useAuth.ts
    useDuaGeneration.ts
    useUploadDocuments.ts
    useDuaHistory.ts
```

```
services/
  authService.ts
  duaGenerationService.ts
  fileUploadService.ts
  duaHistoryService.ts
  notificationService.ts

api/
  httpClient.ts
  authApiClient.ts
  duaApiClient.ts
  uploadApiClient.ts

validation/
  authSchemas.ts
  uploadSchemas.ts
  duaSchemas.ts
  responseSchemas.ts

state/
  store.ts
  slices/

models/
  User.ts
  DUA.ts
  Document.ts
  Goods.ts
  GenerationJob.ts
  factories/
    duaFactory.ts

utils/
  formatters.ts
  fileHelpers.ts
  dateUtils.ts

settings/
  env.ts
  routes.ts
  constants.ts

observability/
  logger.ts
  telemetry.ts
  errorTracking.ts
```

Execution Flow

- The user enters the application through the authentication flow.
- Authorization and routing validate access to protected screens.

- Pages are built from atoms, molecules, organisms, templates, and hooks.
- Hooks trigger DUA workflow services.
- Services validate input and delegate backend communication to API clients.
- API clients use centralized settings and endpoints.
- Responses are validated and mapped into frontend models.
- State management stores the updated session, workflow, and result data.
- Components re-render the UI.
- Observability captures logs, errors, progress events, and notifications.

Layered Design Diagram



Mermaid Diagram

```
flowchart TD
    A[Authentication Layer] --> B[Authorization Layer]
    B --> C[Routing Layer]
    C --> D[Component Layer]

    subgraph UI[Component Layer]
        D1[Atoms]
        D2[Molecules]
        D3[Organisms]
        D4[Templates]
        D5[Pages]
        D6[Hooks]
    end

    D --> E[DUA Workflow Services]
```

```
    E --> F[Validation Layer]
    E --> G[API Clients]
    G --> H[Settings]
    E --> I[Observability / Notifications]

    J[Models Layer] -. supports .-> D
    K[State Management] -. supports .-> D
    L[Utilities Layer] -. supports .-> D
```

1.6 Design Patterns

The frontend applies object-oriented and architectural patterns only where they add clarity to the workflow.

- The **Provider pattern** is used for authentication context and shared application state. It centralizes session awareness in `src/auth/authProvider.tsx` and avoids passing auth state through multiple component levels.
- The **Guard pattern** is used for route protection and permission validation. `src/auth/authGuard.tsx` protects authenticated routes and `src/auth/permissionGuard.tsx` protects role- or claim-based actions.
- The **Singleton pattern** is used for the shared HTTP client in `src/api/httpClient.ts` so that API configuration, interceptors, and authentication headers are defined once.
- The **Factory pattern** is used to build frontend domain objects such as `DUA`, `Document`, or `GenerationJob` from API responses before they reach the UI through `src/models/factories/duaFactory.ts`.
- The **Observer pattern** is applied through state subscriptions and reactive UI updates. Components refresh automatically when the global store in `src/state/store.ts` changes or when workflow hooks in `src/hooks/useDuaGeneration.ts` receive new progress state.
- The **Strategy pattern** is used where behavior may vary by configuration, such as document upload handling, template selection, or confidence rendering, mainly inside `src/services/duaGenerationService.ts`, `src/services/fileUploadService.ts`, and reusable UI components in `src/components/`.
- The **Facade pattern** is used in the workflow services layer. Services such as `src/services/duaGenerationService.ts` expose simple methods to the UI while internally coordinating validation, API calls, settings, and notifications.
- The **Interceptor pattern** is applied in `src/api/httpClient.ts` to inject tokens, handle authorization failures, and support session invalidation.
- The **Pub/Sub pattern** is used for notifications and progress events. `src/services/notificationService.ts` and the observability modules in `src/observability/` allow upload and generation status to update the UI without tight coupling.

Pattern Usage and Location

Pattern	Purpose	Main Location
Provider	Authentication and shared app context	`src/auth/authProvider.tsx`

Pattern	Purpose	Main Location
Guard	Route and permission protection	`src/auth/authGuard.tsx`, `src/auth/permissionGuard.tsx`
Singleton	Shared HTTP client	`src/api/httpClient.ts`
Factory	Build domain models from API data	`src/models/factories/duaFactory.ts`
Observer	UI refresh from state changes	`src/state/`, `src/hooks/`
Strategy	Variable workflow behavior	`src/services/duaGenerationService.ts`, `src/services/fileUploadService.ts`
Facade	Simplified orchestration for UI calls	`src/services/duaGenerationService.ts`
Interceptor	Token injection and session invalidation	`src/api/httpClient.ts`
Pub/Sub	Notifications and progress events	`src/services/notificationService.ts`, `src/observability/`

1.7 `/src` Scaffold

```
src/
  auth/
    authProvider.tsx
    authGuard.tsx
    permissionGuard.tsx

  router/
    appRouter.tsx
    protectedRoute.tsx

  components/
    atoms/
      Button.tsx
      InputField.tsx
      ProgressBar.tsx
    molecules/
      LoginForm.tsx
      FileUploadBox.tsx
      ConfidenceBadge.tsx
    organisms/
      HistoryTable.tsx
      GeneratorConfigForm.tsx
      PdfViewerPanel.tsx
    templates/
      AuthTemplate.tsx
```

```
        DashboardTemplate.tsx
        WorkflowTemplate.tsx
      pages/
        LoginPage.tsx
        SelectOptionPage.tsx
        DuaHistoryPage.tsx
        GeneratorConfigurationPage.tsx
        UploadDocumentsPage.tsx
        ProcessingProgressPage.tsx
        DuaResultPage.tsx

    hooks/
      useAuth.ts
      useDuaGeneration.ts
      useUploadDocuments.ts
      useDuaHistory.ts

    services/
      authService.ts
      duaGenerationService.ts
      fileUploadService.ts
      duaHistoryService.ts
      notificationService.ts

    api/
      httpClient.ts
      authApiClient.ts
      duaApiClient.ts
      uploadApiClient.ts

    validation/
      authSchemas.ts
      uploadSchemas.ts
      duaSchemas.ts
      responseSchemas.ts

    state/
      store.ts
      slices/
        authSlice.ts
        duaSlice.ts
        uploadSlice.ts

    models/
      User.ts
      DUA.ts
      Document.ts
      Goods.ts
      GenerationJob.ts
      factories/
        duaFactory.ts

    utils/
      formatters.ts
```

```
      fileHelpers.ts
      dateUtils.ts

    settings/
      env.ts
      routes.ts
      constants.ts

    observability/
      logger.ts
      telemetry.ts
      errorTracking.ts

    i18n/
      en.json
      es.json

    theme/
      theme.ts
```