

# Package ‘srn’

November 14, 2018

**Title** Sub-Regional Nexus Modeling Tool

**Version** 0.0.1

**Description** Package to process water-energy-land nexus data to different sub-regional levels.

**Depends**

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** true

**Suggests** testthat, knitr, rmarkdown

**RoxygenNote** 6.1.0

**Imports**

RColorBrewer, rgcam, tibble, dplyr, tmap, ggplot2, scales, utils,tidyr, rlang, grDevices, processx

**Remotes** github::JGCRI/rgcam

**VignetteBuilder** knitr

## R topics documented:

srn . . . . .	1
srn.assumptions . . . . .	2
srn.chart . . . . .	2
srn.chartsProcess . . . . .	4
srn.colors . . . . .	6
srn.readgcam . . . . .	7
srn.templates . . . . .	8

<b>Index</b>	<b>10</b>
--------------	-----------

---

srn	<i>srn: Sub-Regional nexus Package</i>
-----	--

---

## Description

The SRN package provides

## SRN functions

The SRN functions ...

---

srn.assumptions	<i>srn.assumptions</i>
-----------------	------------------------

---

### Description

This function loads holds the different assumptions used throughout the srn package.

### Usage

```
srn.assumptions()
```

### Details

List of Assumptions

- convEJ2TWh
- convEJ2GW
- conv1975USDperGJ22017USDperMWh
- conv1975USDperGJ22017USDperMBTU
- convertGgTgMTC
- GWPTYPE

### Value

A list of assumptions

### Examples

```
library(srn)
a<-srn.assumptions()
a # will give full list of assumptions
```

---

srn.chart	<i>srn.chart</i>
-----------	------------------

---

### Description

This function produce different kinds of charts for the srn package. It requires a table in the SRN format. Each figure is accompanied with a csv table.

### Usage

```
srn.chart(data, chartType = "bar", position = "stack", xData = "x",
  yData = "value", class = "class1", group = "scenario",
  classPalette = "classPalette1", classLabel = "classLabel1",
  xLabel = "xLabel", yLabel = "yLabel", facet_rows = "region",
  facet_columns = "scenario", ncolrow = 4, scales = "fixed",
  useNewLabels = 1, units = "units", xBreaksMaj = 10,
  xBreaksMin = 5, yBreaksMaj = 5, yBreaksMin = 10,
  sizeBarLines = 0.5, sizeLines = 1.5)
```

**Arguments**

data	data table for charting
chartType	Type of chart: "bar" or "line"
position	Position in bar charts. "identity", "stack" or "dodge"
xData	Default "x"
yData	Default "value"
class	Default "class1"
group	Default "scenario"
classPalette	Default "classPalette1"
classLabel	Default "classLabel1"
xLabel	Default "xLabel"
yLabel	Default "units"
facet_rows	Default "region"
facet_columns	Default "scenario"
ncolrow	Number of columns or Rows for Faceted plots
scales	Default "fixed"
useNewLabels	Default 1
units	Default "units"
xBreaksMaj	Default 10
xBreaksMin	Default 5
yBreaksMaj	Default 5
yBreaksMinn	Default 10
sizeBarLines	Default 0.5
sizeLines	Default 1.5

**Value**

Returns the formatted data used to produce chart

**Examples**

```
# Examples below show the default chart with minimum information
# and then adding progressively more details.
```

```
library(tibble)
tbl <- tribble (
  ~x,    ~value,
  2010,   15,
  2020,   20,
  2030,   30
)
srn.chart(data=tbl,xData="x",yData="value",chartType = "line")
srn.chart(data=tbl,xData="x",yData="value",chartType = "bar")
```

---

srn.chartsProcess	<i>srn.chartsProcess</i>
-------------------	--------------------------

---

## Description

This function produces charts given any number of tables in the srn format. The `srn.chart()` function produces charts for each region and scenario. If there are more than one scenario then the function also produces a folder for diffplots. The input tables should be .csv files with the following columns: scenario, region, sources, param, x, xLabel, vintage, class1, class2, units, value, aggregate, classLabel1, classPalette1, classLabel2, classPalette2. Running the `srn.readgcam` automatically produces an empty template with these columns for the relevant parameters. Each column is defined below:

## Usage

```
srn.chartsProcess(dataTables = NULL, rTable = NULL, scenRef = NULL,
  dirOutputs = paste(getwd(), "/outputs", sep = ""), pdfpng = "png",
  xCompare = c("2015", "2030", "2050", "2100"), paramsSelect = "All",
  regionsSelect = "All", xData = "x", yData = "value",
  xLabel = "xLabel", yLabel = "units", aggregate = "sum",
  class = "class", classPalette = "pal_Basic", regionCompareOnly = 0)
```

## Arguments

dataTables	Vector of strings with full path to datatables to be read in. Example <code>c("D:/srn/outputs/Colombia/region", "D:/srn/outputs/Colombia/regional/dataTableLocal_Colombia_1975to2100.csv")</code> . Where "dataTableLocal_Colombia_1975to2100.csv" is the new datafile created based on "dataTableTemplate_Colombia_1975to2100.csv" and contains new local data.
rTable	If a table is created directly in R as a data.frame or tibble it can be entered here.
scenRef	The reference scenario to compare against. Default will pick first scenario from list of all scenarios
dirOutputs	Full path to directory for outputs
pdfpng	Choose the format for outputs. Either "pdf", "png" or "both". Default is "png"
xCompare	Choose the years to compare scenarios for xScenSelectYears plot. Default is <code>c("2015", "2030", "2050", "2100")</code>
paramsSelect	Default = "All". Select the parameters to analyze from the tables provided. The parameters corresponding to the different gcam query files are as follows: <ul style="list-style-type: none"> <li>"Query" : "Param"</li> <li>"Total final energy by aggregate end-use sector" : "finalNrgbySec"</li> <li>"GDP per capita MER by region" : "gdp"</li> <li>"GDP MER by region" : "gdp"</li> <li>"GDP Growth Rate (Percent)" : Calculated based on the GDP MER by region.</li> <li>"Population by region"</li> <li>"ag production by tech" : Where technologies signify irrigated or rainfed</li> </ul>
regionsSelect	Default = "All". Select regions to create charts for.
xData	Default "x"

yData	Default "value"
xLabel	Default "xLabel"
yLabel	Default "units"
aggregate	Default "sum"
class	Default "class"
classPalette	Default "pal_Basic" from srn.colors()\$pal_Basic
regionCompareOnly	Default 0. If set to 1, will only run comparison plots and not individual regions

## Details

### List of Assumptions

- scenario: The name of the new data scenario
- region: The region for the data
- sources: Sources for the data
- param: Name of the parameter
- x: The x axis variable values
- xLabel: X axis Label
- vintage: Vintages if any. If not relevant then just enter "Vintage"
- class1: Classes or types (eg. if param is water\_demands then the classes may be Industry, Agriculture etc.)
- class2: A second category of classes if exists.
- units: Units for the parameter. These are used as the y axis label.
- value: The parameter value.
- aggregate: Either "sum" or "mean". This parameter is used to determine how to aggregate across regions or scenarios.
- classLabel1: If class1 exists then this will be legend Label. If it doesn't exist enter "classLabel1"
- classPalette1: An R or srn.colors() palette. Can leave the default as "pal\_16".
- classLabel2: If class2 exists then this will be legend Label. If it doesn't exist enter "classLabel2"
- classPalette2: An R or srn.colors() palette. Can leave the default as "pal\_16".

## Value

Produces charts in output folder and also returns combined table in srn format.

---

`srn.colors`*srn.colors*

---

## Description

This function loads various color palettes used previously in GCAM as well as new palettes for SRN modeling to the global environment

## Usage

```
srn.colors()
```

## Details

List of Color Palettes

- `pal_HDDCDD`
- `pal_16`
- `elec_tech_colors`
- `elec_renew_colors`
- `building_colors`
- `trn_fuel_colors`
- `enduse_fuel_numbered`
- `enduse_colors`
- `pal_pri_ene`
- `pal_pri_fuelcost`
- `pal_emiss_sector`
- `pal_landuse`
- `pal_hydrogen`
- `pal_refliq`
- `emiss_by_enduse_colors`
- `biouse_colors`
- `pal_Basic`
- `pal_Gas`
- `pal_Diff`
- `pal_Diff5`
- `pal_Absolute`
- `pal_Absolute5`
- `pal_Unassigned`
- `pal_elec_subsec`
- `pal_elec_finalNrgFuel`
- `pal_elec_techs`
- `pal_elec_sec`
- `pal_finalNrg_sec`
- `pal_pri_ene`
- `pal_elec_tech_colors`

**Value**

A list of color palettes.

**Examples**

```
library(srn)
a<-srn.colors()
pie(rep(1,length(a$pal_Basic)),label=names(a$pal_Basic),col=a$pal_Basic)
```

---

srn.readgcam	<i>srn.readgcam</i>
--------------	---------------------

---

**Description**

This function connects to a gcamdatabase and uses a query file to out results into a table ready for plotting.

**Usage**

```
srn.readgcam(gcamdatabasePath, gcamdatabaseName,
  queryxml = "srnQueries.xml", scenOrigNames, scenNewNames = NULL,
  reReadData = T, dataProj = "dataProj.proj",
  dirOutputs = paste(getwd(), "/outputs", sep = ""),
  regionsSelect = NULL, queriesSelect = "All")
```

**Arguments**

gcamdatabasePath	Path to gcam database folder
gcamdatabaseName	Name of gcam database
queryxml	Full path to query.xml file
scenOrigNames	Original Scenarios names in GCAM database in a string vector. For example c('scenario1','scenario2').
scenNewNames	New Names which may be shorter and more useful for figures etc. Default will use Original Names. For example c('scenario1','scenario2')
reReadData	If TRUE will read the GCAM data base and create a queryData.proj file in the same folder as the GCAM database. If FALSE will load a '.proj' file if a file with full path is provided otherwise it will search for a dataProj.proj file in the existing folder which may have been created from an old run.
dataProj	Optional. A default 'dataProj.proj' is produced if no .Proj file is specified.
dirOutputs	Full path to directory for outputs
regionsSelect	The regions to analyze in a vector. Example c('Colombia','Argentina')
queriesSelect	Default = "All". Vector of queries to read from the queryxml for example c("Total final energy by aggregate end-use sector", "Population by region"). The queries must be available in the queryxml file. Current list of available parameters are: <ul style="list-style-type: none"> <li>"Total final energy by aggregate end-use sector"</li> </ul>

- "GDP per capita MER by region" : Where MER is "Market Exchange Rate"
- "GDP MER by region" : Where MER is "Market Exchange Rate"
- "GDP Growth Rate (Percent)" : Calculated based on the GDP MER by region.
- "Population by region"
- "ag production by tech" : Where technologies signify irrigated or rainfed

## Value

A list with the scenarios in the gcam database, queries in the queryxml file and a tibble with gcam data formatted for srn charts.

---

srn.templates	<i>srn.templates</i>
---------------	----------------------

---

## Description

This script holds various templates used for different scripts.

## Usage

```
srn.printPdfPng(figure, dir, filename, figWidth = 13, figHeight = 9,
  pdfpng = "png")

srn.chartsThemeLight()

srn.tmapAnimate(map, filename = "animation.gif", width, height,
  delay = 60)

srn.tmapLayout()
```

## Arguments

figure	Figure to be printed in function srn.printPdfPng
dir	Directory to print figure to in function srn.printPdfPng
filename	Filename for figure printed in function srn.printPdfPng
figWidth	Figure Width in inches for figures to be printed in function srn.printPdfPng
figHeight	Figure height in inches for figures to be printed in function srn.printPdfPng
pdfpng	Either "pdf", "png" or "both" to define the format of output
map	A tmap object with facets which will be converted to animations
width	Width of map in inches.
height	Hieght of map
delay	Delay. Time between animations = delay/100. Default is 60 or 0.6 seconds.



**Details**

List of Templates in this script:

- `srn.printPdfPng`: Function used to print charts to a pdf or png or both.
- `srn.chartsThemeLight`: A light ggplot theme for charts
- `srn.tmapAnimate`: A function to animate tmaps across a variable.
- `srn.tmapLayout`: A fuction to define tmap layouts

**Value**

A list of different templates

# Index

- \*Topic **assumptions**
  - srn.assumptions, 2
- \*Topic **charts**,
  - srn.chart, 2
  - srn.chartsProcess, 4
  - srn.templates, 8
- \*Topic **colors**,
  - srn.colors, 6
- \*Topic **database**,
  - srn.readgcam, 7
- \*Topic **diffplots**
  - srn.chart, 2
  - srn.chartsProcess, 4
- \*Topic **gcam**,
  - srn.readgcam, 7
- \*Topic **gcam**
  - srn.readgcam, 7
- \*Topic **maps**,
  - srn.templates, 8
- \*Topic **palette**
  - srn.colors, 6
- \*Topic **print**
  - srn.templates, 8
- \*Topic **query**
  - srn.readgcam, 7
- \*Topic **templates**,
  - srn.templates, 8

  

- srn, 1
- srn-package (srn), 1
- srn.assumptions, 2
- srn.chart, 2
- srn.chartsProcess, 4
- srn.chartsThemeLight (srn.templates), 8
- srn.colors, 6
- srn.printPdfPng (srn.templates), 8
- srn.readgcam, 7
- srn.templates, 8
- srn.tmapAnimate (srn.templates), 8
- srn.tmapLayout (srn.templates), 8