

Package ‘metis’

July 9, 2019

Title Sub-Regional Nexus Modeling Tool

Version 0.0.1

Description Package to process water-energy-land nexus data to different sub-regional levels.

Depends

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 6.1.1

Imports raster (>= 2.7.15),
RColorBrewer (>= 1.1.2),
rgcam (>= 0.5.0),
tibble (>= 1.4.2),
ggalluvial (>= 0.9.1),
dplyr (>= 0.7.7),
tmap (>= 2.1.1),
ggplot2 (>= 3.1.0),
scales (>= 0.5.0),
utils (>= 3.5.0),
tidyr (>= 0.8.1),
rlang (>= 0.3.0),
grDevices (>= 3.5.0),
processx (>= 3.2.0),
rgdal (>= 1.2.20),
magrittr (>= 1.5),
sp (>= 1.2.7),
methods (>= 3.5.0),
tidyselect (>= 0.2.5),
rgeos (>= 0.3.26),
zoo (>= 1.8.4),
stats (>= 3.5.0),
dbplyr (>= 1.3.0),
RSQLite (>= 2.1.1),
ggrepel (>= 0.8.1),
data.table,
stringr (>= 1.3.1),
DBI

Suggests testthat (>= 2.0.1),
knitr (>= 1.20),
rmarkdown (>= 1.10)
Remotes github::JGCRI/rgcam
VignetteBuilder knitr

R topics documented:

metis	2
metis.assumptions	2
metis.bia	3
metis.boundaries	4
metis.chart	6
metis.chartsProcess	9
metis.colors	12
metis.grid2poly	13
metis.gridByPoly	14
metis.io	15
metis.map	15
metis.mapProcess	18
metis.prepGrid	21
metis.printPdfPng	22
metis.readgcam	23
Index	25

metis	<i>metis: Sub-Regional nexus Package</i>
-------	--

Description

The Metis package provides

Metis functions

The Metis functions ...

metis.assumptions	<i>metis.assumptions</i>
-------------------	--------------------------

Description

This function loads holds the different assumptions used throughout the metis package.

Usage

metis.assumptions()

Details

List of Assumptions

- convEJ2TWh
- convEJ2GW
- conv1975USDperGJ22017USDperMWh
- conv1975USDperGJ22017USDperMBTU
- convertGgTgMTC
- GWPType

Value

A list of assumptions

Examples

```
library(metis)
a<-metis.assumptions()
a # will give full list of assumptions
```

metis.bia	<i>metis.bia</i>
-----------	------------------

Description

This function downscales GCAM electricity generation and installed capacity onto a grid, based on WRI PowerWatch dataset of present capacity

Usage

```
metis.bia(biaInputsFolder = "NA", biaInputsFiles = "NA",
  reReadData = 1, regionsSelect = NULL, dataProj = "dataProj.proj",
  dataProjPath = gcamdatabasePath, scenOrigNames = NULL,
  scenNewNames = NULL, gcamdatabasePath = "NA",
  gcamdatabaseName = "NA", queryxml = "metisQueries.xml",
  queryPath = paste(getwd(), "/dataFiles/gcam", sep = ""),
  queriesSelect = "All", paramsSelect = c("elecByTech",
    "elecCapBySubsector"), gridChoice = "grid_050", diagnosticsON = T,
  subsectorNA_distribute = "even", nameAppend = "")
```

Arguments

biaInputsFolder	Bia Inputs Folder Path
biaInputsFiles	Bia Inputs Folder Path
reReadData	Default = 1. will read the GCAM data base and create a queryData.proj file in the same folder as the GCAM database. If FALSE will load a '.proj' file if a file with full path is provided otherwise it will search for a dataProj.proj file in the existing folder which may have been created from an old run.

regionsSelect	The regions to analyze in a vector. Example c('Colombia','Argentina')
dataProj	Optional. A default 'dataProj.proj' is produced if no .Proj file is specified.
dataProjPath	Folder that contains the dataProj or where it will be produced.
scenOrigNames	Original Scenarios names in GCAM database in a string vector. For example c('scenario1','scenario2').
scenNewNames	New Names which may be shorter and more useful for figures etc. Default will use Original Names. For example c('scenario1','scenario2')
gcamdatabasePath	Path to gcam database folder
gcamdatabaseName	Name of gcam database
queryxml	Full path to query.xml file
queryPath	Folder that contains the query.xml file. By default it is the same folder as specified by gcamdatabasePath
queriesSelect	Default = "All". Vector of queries to read from the queryxml for example
paramsSelect	Default = c("elecByTech", "elecCapBySubsector") . Vector of parameters to be read from the GCAM database
gridChoice	Default = "grid_050" . Choice of whether to use 50 km x 50 km grid cells ("grid_050") or 25 km x 25 km ("grid_025").
diagnosticsON	Default = T.
subsectorNA distribute	Default = "even". Choose "even" for even distribution or "totalOther" to distribute based on sum of all other subsectors..
nameAppend	Default=""

Value

A tibble with GCAM electricity generation distributed on a grid for selected regions

metis.boundaries	<i>metis.boundaries</i>
------------------	-------------------------

Description

This function takes a .csv file with gridded lat, long data and aggregates the data by spatial boundaries given different shapefiles.

Usage

```
metis.boundaries(boundaryRegShape = NULL, boundaryRegShpFolder = NULL,
  boundaryRegShpFile = NULL, boundaryRegCol = NULL,
  boundaryRegionsSelect = NULL, subRegShape = NULL,
  subRegShpFolder = NULL, subRegShpFile = NULL, subRegCol = NULL,
  subRegionsSelect = NULL, subRegType = "subRegType",
  dirOutputs = paste(getwd(), "/outputs", sep = ""), nameAppend = "",
  expandPercent = 2, overlapShape = NULL, overlapShpFolder = NULL,
  overlapShpFile = NULL, labelsSize = 1.2, fillcolorNA = NULL,
```

```
projX = "+proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0",
extendedFillColor = "grey75", extendedBGColor = "lightblue1",
extendedHighLightColor = "cornsilk1", extendedLabelsColor = "grey30",
extendedLabelSize = 0.7, extension = T, fillPalette = "Spectral",
cropSubShape2Bound = T, grids = NULL, innerMargins = c(0.1, 0.2,
0.1, 0.2), outerMargins = c(0.01, 0.01, 0.01, 0.01))
```

Arguments

boundaryRegShape

Default=NULL. Boundary region shape if already read into R.

boundaryRegShpFolder

Default= NULL. Folder containing boundary region shapefile. Suggested: paste(getwd(),"/dataFiles/gis/boundaryRegShpFolder", sep=""),

boundaryRegShpFile

Default=NULL. Name of shapefile. Suggested: paste("ne_10m_admin_0_countries",sep=""),

boundaryRegCol Default=NULL. Column name with region names. Suggested "NAME_0",

boundaryRegionsSelect

Default=NULL. The region to choose from the given shapefile.

subRegShape Default=NULL. Sub-region shape if already read into R.

subRegShpFolder

Default=NULL. Folder containing boundary region shapefile. Suggested paste(getwd(),"/dataFiles/gis/subRegShpFolder", sep=""),

subRegShpFile

Default=NULL. Name of sub-region shapefile. Suggested paste("ne_10m_admin_1_states_provinces",sep=""),

subRegCol Default= NULL. Suggested for states "name",

subRegionsSelect

Default=NULL. The region to choose from the given sub-region shapefile.

subRegType Default="subRegType". Type of subregion. Eg. "states", "basins" etc.

dirOutputs Default=paste(getwd(),"/outputs",sep Default=""). Location for outputs.

nameAppend Default="". Name to append to saved files.

expandPercent Default=2. Percentage to expand boundary region beyond chosen region.

overlapShape Default = NULL. If boundary lines of another shapefile are desired specify the shape here.

overlapShpFolder

Default = NULL. For GCAM basins use paste(getwd(),"/dataFiles/gis/basin_gcam",sep="").

overlapShpFile Default = NULL. For GCAM basins use ="Global235_CLM_final_5arcmin_multipart"

labelsSize Default =1.2.

fillcolorNA Default =NULL. Fill color for NA values.

projX Default =" +proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0".

extendedFillColor

Default = "grey75". Color used to fill extended land areas.

extendedBGColor

Default = "lightblue1". Color used to fill background/water bodies.

extendedHighLightColor

Default = "cornsilk1". Color used to highlight region of analysis.

extendedLabelsColor	Default = "grey30". Color for extended country name labels.
extdendedLabelSize	Default = 0.7. Size of extended country name labels.
extension	Default = T. Should the map be extended beyond chosen shapefile boudnaries.
fillPalette	Default = "Spectral". Palette to use to fill subregions.
cropSubShape2Bound	Default = T. If subregion shape file is larger than boundary file.
grids	Default = NULL. Metis comes with 0.5 and 0.25 grids in c(paste(getwd(), "/dataFiles/grids/emptyGrid/
innerMargins	Default = c(0,0.1,0,0.1), # bottom, left, top, right
outerMargins	Default = c(0.01,0.01,0.01,0.01) # bottom, left, top, right paste(getwd(), "/dataFiles/grids/emptyGrids/
	This may happen in the case of disputed boundaries.

Value

A table with data by polygon ID for each shapefile provided

metis.chart	<i>metis.chart</i>
-------------	--------------------

Description

This function produce different kinds of charts for the metis package. It requires a table in the Metis format. Each figure is accompanied with a csv table.

Usage

```
metis.chart(data, dataNorm = NULL, chartType = "bar",
  position = "stack", xData = "x", yData = "value",
  class = "class1", group = "scenario",
  classPalette = "classPalette1", classLabel = "classLabel1",
  color = NULL, xLabel = "xLabel", yLabel = "yLabel",
  facet_rows = NULL, facet_columns = NULL, ncolrow = 4,
  facetBGColor = "grey30", facetLabelColor = "white",
  facetLabelSize = 1.5, scales = "fixed", useNewLabels = 0,
  units = "units", xBreaksMaj = 10, xBreaksMin = 5,
  yBreaksMaj = 5, yBreaksMin = 10, sizeBarLines = 0.5,
  sizeLines = 1.5, sectorToOrder = NULL, sectorFromOrder = NULL,
  removeCols = NULL, bubbleSize = 10, sankeyAxis1 = NULL,
  sankeyAxis2 = NULL, sankeyAxis1Label = "axis1Label",
  sankeyAxis2Label = "axis2Label", sankeyGroupColor = NULL,
  printFig = T, fileName = "chart", title = NULL,
  dirOutputs = paste(getwd(), "/outputs", sep = ""), figWidth = 13,
  figHeight = 9, pdfpng = "png", sankeyLabelsOn = 1,
  colOrder1 = NULL, colOrderName1 = NULL, colOrder2 = NULL,
  colOrderName2 = NULL, pointsOn = 1, pointsSize = 4)
```

Arguments

data	Data table for charting
dataNorm	Normalized data to plot under actual data in bubble plots. Default = NULL,
chartType	Type of chart: "bar", "line", "bubble", "sankey"
position	Position in bar charts. "identity", "stack" or "dodge"
xData	X axis data variable (dataframe or table column name). Default "x".
yData	Y axis data variable (dataframe or table column name).Default "value"
class	Class data variable (dataframe or table column name).Default "class1"
group	Group (dataframe or table column name).Default "scenario"
classPalette	Color palette to use for multiple classes. Must be a color palette eg. c("red","blue","green") or a metis.colors() palette eg. metis.colors()\$pal_Basic. Default "classPalette1"
classLabel	Label to be used for legend title. Default "classLabel1"
color	A single color name for single class charts. Default NULL
xLabel	X axis title. Default "xLabel"
yLabel	Y axis title. Default "units"
facet_rows	Data variable to be used for facet rows (dataframe or table column name).Default "region"
facet_columns	Data variable to be used for facet columns (dataframe or table column name).Default "scenario"
ncolrow	Number of columns or Rows for Faceted plots.
facetBGColor	Facet background color. Default ="grey30",
facetLabelColor	Facet title text color. Default= "white",
facetLabelSize	Facet title text size. Default =1.5,
scales	Fixed or free scales for multiple sankey plots. Default "fixed"
useNewLabels	"1" or "0". Converts labels to title-case.Default 0
units	Data units. Default "units"
xBreaksMaj	X axis major breaks. Default 10
xBreaksMin	X axis minor breaks. Default 5
yBreaksMajn	Y axis major breaks. Default 5
yBreaksMinn	Y axis minor breaks. Default 10
sizeBarLines	Bar plot line size. Default 0.5
sizeLines	Line plot line size. Default 1.5
sectorToOrder	Order of "to" column variables in bubble plots. Default = NULL,
sectorFromOrder	Order of "from" column variables in bubble plots. Default = NULL,
removeCols	Option to remove certain columns from bubble plots. Default = NULL,
bubbleSize	Bubble plot bubble size. Default = 10,
sankeyAxis1	Sankey axis 1 data variable (dataframe or table column name). Default = NULL,
sankeyAxis2	Sankey axis 2 data variable (dataframe or table column name).Default = NULL,

```

sankeyAxis1Label      Sankey axis 1 title data variable (dataframe or table column name).Default =
                      "axis1Label",
sankeyAxis2Label      Sankey axis 2 title variable (dataframe or table column name).Default = "axis2Label",
sankeyGroupColor      Which axis variables will be used to color flow paths (One of the sankey axis).
                      Default = NULL,
printFig              Whether plot should be printed or not. Default = T,
fileName              File name for plot to be saved. Default = "chart",
title                 Figure title. Default = NULL
dirOutputs            Output directory to save figure. Default = paste(getwd(),"/outputs",sep Default
                      = "")
figWidth              Figure width. Default = 9,
figHeight             Figure height. Default = 7,
pdfpng                Whether to save plot as pdf or png. Choice between "pdf" or "png". Default =
                      "png",
sankeyLabelsOn        Turn on labels for sankey stratum categories. "1" or "0". Default =1
colOrder1             Order for sankey column 1. Default = NULL,
colOrderName1         Column name with sankey variables for column order 1. Default = NULL,
colOrder2             Order for sankey column 1. Default = NULL,
colOrderName2         Column name with sankey variables for column order 1. Default = NULL,
pointsOn              Include points on lines. Default = 1
pointsSize            ISize of points on line. Default = 4

```

Value

Returns the formatted data used to produce chart

Examples

```

library(tibble)

# Simple example with progressively more features
tbl <- tibble::tribble (
  ~x,    ~value,
  2010,   15,
  2020,   20,
  2030,   30)

metis.chart(data = tbl, xData = "x", yData = "value", chartType = "line")
metis.chart(data = tbl, xData = "x", yData = "value", chartType = "bar")
metis.chart(data = tbl, xData = "x", yData = "value", chartType = "bar", color = "blue",
            yLabel = "New y Label", xLabel = "New X label", printFig = TRUE,
            fileName = "newFileName", title = "Title")

# More detailed data with facets
tbl_multi <- tibble::tribble (
  ~x,    ~value, ~region,    ~scen,    ~fuel,
  2010,   25,    "region1",  "scenA",  "Oil",
  2020,   30,    "region1",  "scenA",  "Oil",

```



```

2030, 40, "region1", "scenA", "Oil",
2010, 25, "region2", "scenA", "Oil",
2020, 10, "region2", "scenA", "Oil",
2030, 60, "region2", "scenA", "Oil",
2010, 75, "region1", "scenB", "Oil",
2020, 30, "region1", "scenB", "Oil",
2030, 20, "region1", "scenB", "Oil",
2010, 25, "region2", "scenB", "Oil",
2020, 10, "region2", "scenB", "Oil",
2030, 90, "region2", "scenB", "Oil",
2010, 55, "region1", "scenA", "Gas",
2020, 40, "region1", "scenA", "Gas",
2030, 30, "region1", "scenA", "Gas",
2010, 35, "region2", "scenA", "Gas",
2020, 30, "region2", "scenA", "Gas",
2030, 32, "region2", "scenA", "Gas",
2010, 16, "region1", "scenB", "Gas",
2020, 28, "region1", "scenB", "Gas",
2030, 39, "region1", "scenB", "Gas",
2010, 12, "region2", "scenB", "Gas",
2020, 26, "region2", "scenB", "Gas",
2030, 37, "region2", "scenB", "Gas")

```

```
my_pal <- RColorBrewer::brewer.pal(9, "Set1")
```

```
metis.chart(data = tbl_multi, xData = "x", yData = "value", class="fuel",
            chartType = "line", classPalette=my_pal,
            facet_rows="region", facet_columns="scen")
```

```
my_pal <- metis.colors()$pal_Basic
```

```
metis.chart(data = tbl_multi, xData = "x", yData = "value", class="fuel", position="stack",
            group="fuel", chartType = "bar", classPalette=my_pal,
            facet_rows="region", facet_columns="scen")
```

```
metis.chart(data = tbl_multi, xData = "x", yData = "value", class="fuel", position="dodge",
            group="fuel", chartType = "bar", classPalette=my_pal,
            facet_rows="region", facet_columns="scen")
```

```
metis.chartsProcess      metis.chartsProcess
```

Description

This function produces charts given any number of tables in the metis format. The `metis.chart()` function produces charts for each region and scenario. If there are more than one scenario then the function also produces a folder for diffplots. The input tables should be .csv files with the following columns: scenario, region, sources, param, x, xLabel, vintage, class1, class2, units, value, aggregate, classLabel1, classPalette1, classLabel2, classPalette2. Running the `metis.readgcam` automatically produces an empty template with these columns for the relevant parameters. Each column is defined below:

Usage

```
metis.chartsProcess(dataTables = NULL, rTable = NULL, scenRef = NULL,
  dirOutputs = paste(getwd(), "/outputs", sep = ""), pdfpng = "png",
  xRange = "All", xCompare = c("2015", "2030", "2050", "2100"),
  paramsSelect = "All", regionsSelect = "All", xData = "x",
  yData = "value", xLabel = "xLabel", yLabel = "units",
  aggregate = "sum", class = "class", classPalette = "pal_Basic",
  regionCompareOnly = 0, scenarioCompareOnly = 0, useNewLabels = 0,
  sizeBarLines = 0, sizeLines = 1.5, folderName = "analysis",
  nameAppend = "", scensSelect = "All", colOrder1 = NULL,
  colOrderName1 = NULL, colOrder2 = NULL, colOrderName2 = NULL)
```

Arguments

dataTables	Vector of strings with full path to datatables to be read in. Example <code>c("D:/metis/outputs/Colombia/dataTableLocal_Colombia_1975to2100.csv")</code> . Where "dataTableLocal_Colombia_1975to2100.csv" is the new datafile created based on "dataTableTemplate_Colombia_1975to2100.csv" and contains new local data.
rTable	If a table is created directly in R as a data.frame or tibble it can entered here.
scenRef	The reference scenario to compare against. Default will pick first scenario from list of all scenarios
dirOutputs	Full path to directory for outputs. Default is <code>paste(getwd(), "/outputs", sep = "")</code>
pdfpng	Choose the format for outputs. Either "pdf", "png" or "both". Default is "png"
xRange	Default "All". Range of x values eg. <code>c(2001:2005)</code>
xCompare	Choose the years to compare scenarios for xScenSelectYears plot. Default is <code>c("2015", "2030", "2050", "2100")</code>
paramsSelect	Default = "All". Select the parameters to analyze from the the tables provided. Full list of parameters: <code>c("finalNrgbySec", "primNrgConsumByFuel", "elecByTech", "watConsumBySec", "watWithdrawBySec", "watWithdrawBy-Crop", "watBioPhysCons", "irrWatWithBasin", "irrWatConsBasin", "gdpPerCapita", "gdp", "gdpGrowthRate", "pop", "agProdbyIrrRfd", "agProdBiomass", "agProd-Forest", "agProdByCrop", "landIrrRfd", "aggLandAlloc", "LUCemiss", "co2emission", "co2emissionByEndUse", "ghgEmissionByGHG", "ghgEmissByGHGGROUPS")</code>
regionsSelect	Default = "All". Select regions to create charts for.
xData	Default "x"
yData	Default "value"
xLabel	Default "xLabel"
yLabel	Default "units"
aggregate	Default "sum"
class	Default "class"
classPalette	Default "pal_Basic" from <code>metis.colors()\$pal_Basic</code>
regionCompareOnly	Default 0. If set to 1, will only run comparison plots and not individual
scenarioCompareOnly	Default 0. If set to 1, will only run comparison plots and not individual
useNewLabels	Default 0
sizeBarLines	Default 0.5

sizeLines	Default 1.5
folderName	Default ="analysis"
nameAppend	Default =""
scensSelect	Default = "All". Select regions to create charts for.
colOrder1	Default = NULL,
colOrderName1	Default = NULL,
colOrder2	Default = NULL,
colOrderName2	Default = NULL,

Details

List of Assumptions

- scenario: The name of the new data scenario
- region: The region for the data
- sources: Sources for the data
- param: Name of the parameter
- x: The x axis variable values
- xLabel: X axis Label
- vintage: Vintages if any. If not relevant then just enter "Vintage"
- class1: Classes or types (eg. if param is water_demands then the classes may be Industry, Agriculture etc.)
- class2: A second category of classes if exists.
- units: Units for the parameter. These are used as the y axis label.
- value: The parameter value.
- aggregate: Either "sum" or "mean". This parameter is used to determine how to aggregate across regions or scenarios.
- classLabel1: If class1 exists then this will be legend Label. If it doesnt exist enter "classLabel1"
- classPalette1: An R or metis.colors() palette. Can leave the default as "pal_16".
- classLabel2: If class2 exists then this will be legend Label. If it doesnt exist enter "classLabel2"
- classPalette2: An R or metis.colors() palette. Can leave the default as "pal_16".

Value

Produces charts in output folder and also returns combined table in metis format.

`metis.colors`*metis.colors*

Description

This function loads various color palettes used previously in GCAM as well as new palettes for Metis modeling to the global environment

Usage

```
metis.colors(palx = NULL)
```

Arguments

`palx` Palette name to view the palette colors. Eg. `metis.colors("pal_Basic")`

Details

List of Color Palettes

- `pal_HDDCDD`
- `pal_16`
- `elec_tech_colors`
- `elec_renew_colors`
- `building_colors`
- `trn_fuel_colors`
- `enduse_fuel_numbered`
- `enduse_colors`
- `pal_pri_ene`
- `pal_pri_fuelcost`
- `pal_emiss_sector`
- `pal_landuse`
- `pal_hydrogen`
- `pal_reflq`
- `emiss_by_enduse_colors`
- `biouse_colors`
- `pal_Basic`
- `pal_Gas`
- `pal_Diff`
- `pal_Diff5`
- `pal_Absolute`
- `pal_Absolute5`
- `pal_Unassigned`
- `pal_pri_ene`

- pal_nrg
- pal_hot
- pal_wet
- pal_div_wet
- pal_div_RdBl
- pal_green
- pal_div_BrGn
- pal_div_BIRd
- pal_sankey
- pal_spectral
- pal_ScarcityCat

Value

A list of color palettes.

Examples

```
library(metis)
a<-metis.colors()
pie(rep(1,length(a$pal_Basic)),label=names(a$pal_Basic),col=a$pal_Basic)
```

metis.grid2poly

metis.grid2poly

Description

This function takes a .csv file with gridded lat, long data and aggregates the data by spatial boundaries given different shapefiles.

Usage

```
metis.grid2poly(grid = NULL, subRegShape = NULL,
  subRegShpFolder = NULL, subRegShpFile = NULL, subRegCol = NULL,
  subRegType = "subRegType", aggType = NULL,
  dirOutputs = paste(getwd(), "/outputs", sep = ""), nameAppend = "",
  labelsSize = 1.2, paramsSelect = "All", sqliteUSE = F,
  sqliteDBNamePath = paste(getwd(), "/outputs/Grids/gridMetis.sqlite",
  sep = ""))
```

Arguments

grid Default=NULL. Grid file in .csv format or a R table, data frame or tibble with as a minimum columns with "lat", "lon" and "value",

subRegShape Default=NULL. shapefile over which grid data is to be aggregated.

subRegShpFolder

Default=NULL. Folder containing boundary region shapefile. Suggested paste(getwd(), "/dataFiles/gridMetis.sqlite", sep = ""),

subRegShpFile	Default=NULL. Name of sub-region shapefile. Suggested paste("ne_10m_admin_1_states_provinces", Default=""),
subRegCol	Default= NULL. Suggested for states "name",
subRegType	Default="subRegType". Eg. "states", "basins" etc.
aggType	Default=NULL. Aggregation method to be used. Either "vol" or "depth" depending on the type of data provided.
dirOutputs	Default=paste(getwd(), "/outputs", sep Default=""),
nameAppend	Default="",
labelsSize	Default =1.2. Label size for the region names for the gridoverlay plot.
paramsSelect	Default = "All"
sqliteUSE	Default = T,
sqliteDBNamePath	Default = paste(getwd(), "/outputs/Grids/gridMetis.sqlite", sep = "")

Value

A table with data by polygon ID for each shapefile provided

metis.gridByPoly	<i>metis.gridByPoly</i>
------------------	-------------------------

Description

This function finds the grids located within a given shapefiles regions

Usage

```
metis.gridByPoly(grid = NULL, boundaryRegShpFolder = NULL,
  boundaryRegShpFile = NULL, colName = NULL,
  outputDir = paste(getwd(), "/outputs", sep = ""),
  fname = "gridByPoly", saveFile = F)
```

Arguments

grid	Default = NULL. Full path to grid file.
boundaryRegShpFolder	Default = NULL,
boundaryRegShpFile	Default = NULL,
colName	Default = NULL,
outputDir	Default = paste(getwd(), "/outputs", sep=""),
fname	Default = "gridByPoly"
saveFile	Default = F. If want csv output then change to T

Value

Prints out graphic

metis.io

*metis.io***Description**

This function prepares gridded data for use with domestic metis modules.

Usage

```
metis.io(ioTable0 = NULL, useIntensity = 0, A0 = NULL,
  dirOutputs = paste(getwd(), "/outputs", sep = ""), nameAppend = "",
  figWidth = 9, figHeight = 7, sankeyLabelAbsPlots = 1,
  combSubRegionPlots = 1)
```

Arguments

<code>ioTable0</code>	Initial ioTable. Must have columns: supplySubSector,total,export and cap. Each supply sector should also have imports. Default = NULL,
<code>useIntensity</code>	Boolean to use given intensity or not. Default is set to 0.
<code>A0</code>	Intensity matrix. Default Null.
<code>dirOutputs</code>	Default =paste(getwd(),"/outputs",sep=""),
<code>nameAppend</code>	Modified intensity matrix. Default =NULL,
<code>figWidth</code>	Default = 9,
<code>figHeight</code>	Default = 7,
<code>sankeyLabelAbsPlots</code>	Default = 1
<code>combSubRegionPlots</code>	Default = 1

Value

A table with data by polygon ID for each shapefile provided

metis.map

*metis.map***Description**

This function produce different kinds of maps for the metis package. Each figure is accompanied with a csv table.

Usage

```
metis.map(dataPolygon = NULL, dataGrid = NULL, dataRaster = NULL,
  shpFolder = NULL, shpFile = NULL, fillPalette = "Spectral",
  borderColor = "gray20", lwd = 1, lty = 1, bgColor = "white",
  frameShow = F, fillColumn = NULL, labels = F, labelsSize = 1.2,
  labelsColor = "black", labelsAutoPlace = T, figWidth = 9,
  figHeight = 7, legendWidth = -1, legendShow = F,
  legendOutside = F, legendTextSize = 1, legendTitleSize = 2,
  legendOutsidePosition = NULL, legendPosition = NULL,
  legendDigits = NULL, legendTitle = "Legend",
  legendStyle = "pretty", legendFixedBreaks = 5, legendBreaks = NULL,
  pdfpng = "png", underLayer = NULL, overLayer = NULL,
  printFig = T, fileName = "map", dirOutputs = paste(getwd(),
  "/outputs", sep = ""), facetFreeScale = F, facetRows = NA,
  facetCols = 3, facetBGColor = "grey30", facetLabelColor = "white",
  facetLabelSize = 1.5, alpha = 1, fillcolorNA = "gray",
  fillshowNA = NA, fillcolorNULL = "gray", facetsON = T,
  panellabel = NULL, multiFacetRows = NULL, multiFacetCols = NULL,
  mapTitle = NULL, mapTitleSize = 1, numeric2Cat_list = NULL,
  catParam = NULL, innerMargins = c(0.01, 0.01, 0.01, 0.01),
  outerMargins = c(0.01, 0.01, 0.01, 0.01))
```

Arguments

dataPolygon	Default = NULL,
dataGrid	Default = NULL,
dataRaster	Default = NULL,
shpFolder	Default = paste(getwd(), "/dataFiles/gis/admin_gadm36_1", sep Default = ""),
shpFile	Default = paste("gadm36_1", sep Default = ""),
fillPalette	Default = "Spectral",
borderColor	Default = "gray20",
lwd	Default = 1,
lty	Default = 1,
bgColor	Default = "white",
frameShow	Default = F,
fillColumn	Default = NULL, # Or give column data with
labels	Default = F,
labelsSize	Default = 1.2,
labelsColor	Default = "black",
labelsAutoPlace	Default = F,
figWidth	Default = 9,
figHeight	Default = 7,
legendWidth	Default = -1,
legendShow	Default = F,
legendOutside	Default = T,


```

legendTextSize Default = 0.8,
legendTitleSize
    Default = 1,
legendOutsidePosition
    Default = NULL, # "right","left","top","bottom", "center"
legendPosition Default = NULL, # c("RIGHT","top") - RIGHT LEFT TOP BOTTOM
legendDigits Default = NULL,
legendTitle Default = "Legend",
legendStyle Default = "pretty",
legendFixedBreaks
    Default = "5",
legendBreaks Default = NULL,
pdfpng Default = "png",
underLayer Default = NULL,
overLayer Default = NULL,
printFig Default = T,
fileName Default = "map",
dirOutputs Default = paste(getwd(),"/outputs",sep Default = ""),
facetFreeScale Default = F,
facetRows Default = NA,
facetCols Default = 3,
facetBGColor Default = "grey75",
facetLabelColor
    Default = "black",
facetLabelSize Default = 1.5,
alpha Default = 1
fillcolorNA Default = NULL
fillshowNA Default = NA
fillcolorNULL Default = NULL
facetsON Default = F,
panelLabel Default = NULL,
multiFacetRows Default = NULL,
multiFacetCols Default = NULL,
mapTitle Default = NULL
mapTitleSize Default = 1
numeric2Cat_list
    Default = NULL,
catParam Default = NULL
innerMargins Default = c(0,0,0,0), # bottom, left, top, right
outerMargins Default = c(0.01,0.01,0.01,0.01) # bottom, left, top, right

```

Value

Returns the formatted data used to produce chart

metis.mapProcess	<i>metis.mapProcess</i>
------------------	-------------------------

Description

This function produce different kinds of maps for the metis package. Each figure is accompanied with a csv table.

Usage

```
metis.mapProcess(polygonDataTables = NULL, gridDataTables = NULL,
  dirOutputs = paste(getwd(), "/outputs", sep = ""),
  mapsOutFolderName = "mapOutputs", frameShow = T, xRange = "All",
  labels = F, labelsSize = 1.2, subRegShape = NULL,
  subRegShpFolder = NULL, subRegShpFile = NULL, subRegCol = NULL,
  dirNameAppend = "", nameAppend = "", legendOutsideSingle = T,
  legendOutsidePosition = NULL, legendPosition = NULL,
  legendFixedBreaks = 5, legendTitleSize0 = 2, legendTextSize0 = 1,
  legendTitleSizeI = 1.5, legendTextSizeI = 1, animateOn = T,
  delay = 100, scenRef = NULL, extension = F,
  boundaryRegShape = NULL, boundaryRegShpFolder = NULL,
  boundaryRegShpFile = NULL, boundaryRegCol = NULL,
  boundaryRegionsSelect = NULL, fillColorNA = NULL,
  extendedLabels = T, extendedFillColor = "grey75",
  extendedBGColor = "lightblue1", extendedHighLightColor = "cornsilk1",
  extendedLabelsColor = "grey30", extdendedLabelSize = 0.7,
  extendedShape = NULL, extendedShapeCol = NULL, expandPercent = 3,
  projX = "+proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0",
  figWidth = 6, figHeight = 7, scaleRange = NULL,
  paramsSelect = "All", indvScenarios = "All", GCMRCPSSPPol = F,
  multiFacetCols = "scenarioRCP", multiFacetRows = "scenarioGCM",
  legendOutsideMulti = T, legendPositionMulti = NULL,
  legendTitleSizeMulti = NULL, legendTextSizeAnim = NULL,
  legendTextSizeMulti = NULL, refGCM = NULL, refRCP = NULL,
  chosenRefMeanYears = NULL, mapTitleSize = 0.5,
  facetLabelSizeMulti = 3, numeric2Cat_list = NULL, diffOn = F)
```

Arguments

polygonDataTables	Default = NULL,
gridDataTables	Default = NULL,
dirOutputs	Default = paste(getwd(), "/outputs", sep = ""),
mapsOutFolderName	Default = "mapOutputs",
frameShow	Default = T. Whether to plot frame around maps and facets.
xRange	Default = "All",
labels	Default = F,
labelsSize	Default = 1.2,

```

subRegShape      Default = NULL,
subRegShpFolder      Default = paste(getwd(), "/dataFiles/gis/admin_gadm36", sep=""),
subRegShpFile      Default = paste("gadm36_1", sep=""),
subRegCol      Default = "NAME_1",
dirNameAppend      Default = ""
nameAppend      Default = ""
legendOutsideSingle      Default = F, Single plots by default have legends inside. This can be moved out
                        if wanted.
legendOutsidePosition      Default = NULL, # "right", "left", "top", "bottom", "center"
legendPosition      Default = NULL, # c("RIGHT", "top") - RIGHT LEFT TOP BOTTOM
legendFixedBreaks      Default = "5",
legendTitleSizeO      Default = 2,
legendTextSizeO      Default = 1,
legendTitleSizeI      Default = 1,
legendTextSizeI      Default = 0.5,
animateOn      Default = T,
delay      Default = 100,
scenRef      Default = NULL
extension      Default = F,
boundaryRegShape      Default = NULL,
boundaryRegShpFolder      Default= NULL . Suggested paste(getwd(), "/dataFiles/gis/naturalEarth", sep De-
                        fault="")
boundaryRegShpFile      Default=NULL . Suggested paste("ne_10m_admin_0_countries", sep Default=""),
boundaryRegCol      Default=NULL. Suggested "NAME_0",
boundaryRegionsSelect      Default = NULL,
fillcolorNA      Default = NULL
extendedLabels      Default = T
extendedFillColor      Default = "grey75",
extendedBGColor      Default = "lightblue1",
extendedHighLightColor      Default = "cornsilk1",
extendedLabelsColor      Default = "grey30",

```

```

extdendedLabelSize      Default =0.7,
extendedShape           Default =NULL,
extendedShapeCol        Default =NULL,
expandPercent           Default =2
projX                   Default = projX="+proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0"
figWidth                Default =9
figHeight               Default =7
scaleRange              Default NULL. Dataframe with columns param, maxScale, minScale to indicate
                        maximum and minumum values for a parameter scale.
paramsSelect            Default ="All"
indvScenarios           Default ="All",
GCMRCPSSPPo1           Default = F,
multiFacetCols          Default ="scenarioRCP",
multiFacetRows          Default ="scenarioGCM",
legendOutsideMulti      Default = NULL,
legendPositionMulti     Default = NULL,
legendTitleSizeMulti    Default = NULL,
legendTextSizeAnim      Default = NULL,
legendTextSizeMulti     Default = NULL,
refGCM                  Default = NULL , eg. "gfdl-esm2m"
refRCP                  Default = NULL , eg. "rcp2p6"
chosenRefMeanYears      Default=NULL
mapTitleSize            Default=0.5
facetLabelSizeMulti     Default =3
numeric2Cat_list        Default=NULL,
diffOn                  Default = F. Whether to calculate diff values between scenarios.

```

Value

Returns the formatted data used to produce chart

metis.prepGrid	<i>metis.prepGrid</i>
----------------	-----------------------

Description

This function prepares gridded data for use with other metis modules.

Usage

```
metis.prepGrid(demeterFolder = "NA", demeterScenario = "NA",
  demeterTimesteps = seq(from = 2005, to = 2100, by = 5),
  demeterUnits = "NA", tethysFolder = "NA", tethysScenario = "NA",
  tethysUnits = "NA", tethysFiles = c("wddom", "wdelec", "wdirr",
    "wdliv", "wdmfg", "wdmin", "wdnonag", "wdtotal"),
  copySingleTethysScenbyXanthos = NULL, xanthosFolder = "NA",
  xanthosFiles = "NA", xanthosScenarioAssign = "NA",
  xanthosCoordinatesPath = "NA", xanthosGridAreaHeCsPath = "NA",
  scarcityXanthosRollMeanWindow = 10, spanLowess = 0.25,
  popFolder = "NA", popFiles = "NA", biaFolder = "NA",
  biaFiles = "NA", popUnits = "NA", dirOutputs = paste(getwd(),
    "/outputs", sep = ""), reReadData = 1, gridMetisData = paste(getwd(),
    "/outputs/Grids/gridMetis.RData", sep = ""), sqliteUSE = F,
  sqliteDBNamePath = paste(getwd(), "/outputs/Grids/gridMetis.sqlite",
    sep = ""))
```

Arguments

demeterFolder	Full path to demeter outputs
demeterScenario	Name of demeter scenario
demeterTimesteps	Default is seq(from=2005,to=2100,by=5)
demeterUnits	No Default
tethysFolder	Folder for tethys results
tethysScenario	Scenario name for tethys run
tethysUnits	No Default
tethysFiles	Default=c("wddom","wdelec","wdirr","wdliv","wdmfg","wdmin","wdnonag","wdtotal"),
copySingleTethysScenbyXanthos	Default=NULL,
xanthosFolder	Xanthos Folder Path
xanthosFiles	Xanthos Files to Read
xanthosScenarioAssign	Default "NA". Scenario name if testing single scenario.
xanthosCoordinatesPath	paste(getwd(),"/dataFiles/grids/xanthosCoords/coordinates.csv",sep="")
xanthosGridAreaHeCsPath	=paste(getwd(),"/dataFiles/grids/xanthosRunsChris/reference/Grid_Areas_ID.csv",sep=""),

```
scarcityXanthosRollMeanWindow
    Default = 10,
spanLowess      Default = 0.25
popFolder       Default = <-paste(getwd(),"/dataFiles/grids/griddedIDsPop/",sep="")
popFiles        Default = <-"grid_pop_map"
biaFolder       Default = <-paste(getwd(),"/dataFiles/grids/griddedIDsbia/",sep="")
biaFiles        Default = <-"grid_bia_map"
popUnits        Default = <-"person"
dirOutputs      Default = paste(getwd(),"/outputs",sep=""),
reReadData      Default = 1,
gridMetisData   Default = paste(dirOutputs, "/Grids/gridMetis.RData", sep = "")
sqliteUSE       Default = T,
sqliteDBNamePath
    Default = paste(getwd(),"/outputs/Grids/gridMetis.sqlite", sep = "")
```

Value

A table with data by polygon ID for each shapefile provided

metis.printPdfPng	<i>metis.printPdfPng</i>
-------------------	--------------------------

Description

This function prints figure to pdf or png.

Usage

```
metis.printPdfPng(figure = NULL, dir = getwd(), filename = "plot",
  figWidth = 13, figHeight = 9, pdfpng = "png")
```

Arguments

figure	Default=NULL. Figure to be printed
dir	Default = getwd(). Directory to print figure
filename	Default = "plot". File name
figWidth	Default=13.
figHeight	Default=9.
pdfpng	Default="png". Either "pdf" or "png"

Value

Prints out graphic

metis.readgcam	<i>metis.readgcam</i>
----------------	-----------------------

Description

This function connects to a gcamdatabase and uses a query file to out results into a table ready for plotting.

Usage

```
metis.readgcam(gcamdatabasePath = NULL, gcamdatabaseName = NULL,
  queryxml = "metisQueries.xml", queryPath = paste(getwd(),
    "/dataFiles/gcam", sep = ""), scenOrigNames = NULL,
  scenNewNames = NULL, reReadData = T, dataProj = "dataProj.proj",
  dataProjPath = paste(getwd(), "/outputs", sep = ""),
  dirOutputs = paste(getwd(), "/outputs", sep = ""),
  regionsSelect = NULL, queriesSelect = "All", paramsSelect = "All")
```

Arguments

gcamdatabasePath	Path to gcam database folder
gcamdatabaseName	Name of gcam database
queryxml	Name of the query.xml file. By default it is "metisQueries.xml"
queryPath	Folder that contains the query.xml file. By default it is the same folder as specified by gcamdatabasePath
scenOrigNames	Original Scenarios names in GCAM database in a string vector. For example c('scenario1','scenario2').
scenNewNames	New Names which may be shorter and more useful for figures etc. Default will use Original Names. For example c('scenario1','scenario2')
reReadData	If TRUE will read the GCAM data base and create a queryData.proj file in the same folder as the GCAM database. If FALSE will load a '.proj' file if a file with full path is provided otherwise it will search for a dataProj.proj file in the existing folder which may have been created from an old run.
dataProj	Optional. A default 'dataProj.proj' is produced if no .Proj file is specified.
dataProjPath	Folder that contains the dataProj or where it will be produced. By default it is the same folder as specified by gcamdatabasePath
dirOutputs	Full path to directory for outputs
regionsSelect	The regions to analyze in a vector. Example c('Colombia','Argentina'). Full list: c(USA, Africa_Eastern, Africa_Northern, Africa_Southern, Africa_Western, Australia_NZ, Brazil, Canada Central America and Caribbean, Central Asia, China, EU-12, EU-15, Europe_Eastern, Europe_Non_EU, European Free Trade Association, India, Indonesia, Japan, Mexico, Middle East, Pakistan, Russia, South Africa, South America_Northern, South America_Southern, South Asia, South Korea, Southeast Asia,

queriesSelect	<p>Default = "All". Vector of queries to read from the queryxml for example c("Total final energy by aggregate end-use sector", "Population by region"). The queries must be available in the queryxml file. Current list of queries and generated paramaters are:</p> <ul style="list-style-type: none"> • "Total final energy by aggregate end-use sector". Parameters generated: finalNrgbySec. • "primary energy consumption by region (direct equivalent)". Parameters generated: primNrgConsumByFuel • "Electricity generation by aggregate technology". Parameters generated: elecByTech • "water withdrawals by sector". Parameters generated: watWithdrawBySec • "water consumption by sector". Parameters generated: watConsumBySec • "water withdrawals by crop". Parameters generated: watWithdrawByCrop • "biophysical water demand by crop type and land region". Parameters generated: watBioPhysCons • "water withdrawals by water mapping source". Parameters generated: irrWatWithBasin • "water consumption by water mapping source". Parameters generated: irrWatConsBasin • "GDP per capita MER by region". Where MER is "Market Exchange Rate". Parameters generated: gdpPerCapita. • "GDP MER by region". Where MER is "Market Exchange Rate". Parameters generated: gdp, gdpGrowthRate • "Population by region". Parameters generated: pop. • "ag production by tech". Where technologies signify irrigated or rainfed. Parameters generated: agProdbyIrrRfd • "Ag Production by Crop Type". Parameters generated: agProdBiomass, agProdForest, agProdByCrop • "land allocation by crop and water source". Parameters generated: landIrrRfd • "aggregated land allocation". Parameters generated: aggLandAlloc • "Land Use Change Emission". Parameters generated: LUCemissFut • "GHG emissions by subsector". Parameters generated: ghgEmissByGHG-GROUPS, ghgEmissionByGHG • "CO2 emissions by sector". Parameters generated: co2emissionBySector • "nonCO2 emissions by sector". Parameters generated: nonco2emissionBySectorGWP5, nonco2emissionBySectorGTP5, nonco2emissionBySectorOrigUnits
paramsSelect	<p>Default = "All". If desired select a subset of paramaters to analyze from the full list of parameters: c("finalNrgbySec", "primNrgConsumByFuel", "elecByTech", "watConsumBySec", "watWithdrawBySec", "watWithdrawByCrop", "watBioPhysCons", "irrWatWithBasin", "irrWatConsBasin", "gdpPerCapita", "gdp", "gdpGrowthRate", "pop", "agProdbyIrrRfd", "agProdBiomass", "agProdForest", "agProdByCrop", "landIrrRfd", "aggLandAlloc", "LUCemiss", "co2emissionBySector", "nonco2emissionBySector")</p>

Value

A list with the scenarios in the gcam database, queries in the queryxml file and a tibble with gcam data formatted for metis charts.

Index

- *Topic **assumptions**
 - metis.assumptions, 2
- *Topic **bubble**,
 - metis.chart, 6
- *Topic **charts**,
 - metis.chart, 6
 - metis.chartsProcess, 9
 - metis.map, 15
 - metis.mapProcess, 18
 - metis.printPdfPng, 22
- *Topic **colors**,
 - metis.colors, 12
- *Topic **database**,
 - metis.boundaries, 4
 - metis.grid2poly, 13
 - metis.io, 15
 - metis.prepGrid, 21
 - metis.readgcam, 23
- *Topic **diffplots**,
 - metis.chart, 6
- *Topic **diffplots**
 - metis.chartsProcess, 9
 - metis.map, 15
 - metis.mapProcess, 18
 - metis.printPdfPng, 22
- *Topic **downscale**,
 - metis.bia, 3
- *Topic **downscaled**
 - metis.bia, 3
- *Topic **downscaling**,
 - metis.bia, 3
- *Topic **electricity**,
 - metis.bia, 3
- *Topic **gcam**,
 - metis.bia, 3
 - metis.boundaries, 4
 - metis.grid2poly, 13
 - metis.io, 15
 - metis.prepGrid, 21
 - metis.readgcam, 23
- *Topic **gcam**
 - metis.boundaries, 4
 - metis.grid2poly, 13
- metis.io, 15
- metis.prepGrid, 21
- metis.readgcam, 23
- *Topic **generation**,
 - metis.bia, 3
- *Topic **grid**,
 - metis.gridByPoly, 14
- *Topic **gridded**,
 - metis.bia, 3
- *Topic **palette**
 - metis.colors, 12
- *Topic **polygon**
 - metis.gridByPoly, 14
- *Topic **query**
 - metis.boundaries, 4
 - metis.grid2poly, 13
 - metis.io, 15
 - metis.prepGrid, 21
 - metis.readgcam, 23
- *Topic **sankey**.
 - metis.chart, 6
- *Topic **shape**,
 - metis.gridByPoly, 14
- metis, 2
- metis-package (metis), 2
- metis.assumptions, 2
- metis.bia, 3
- metis.boundaries, 4
- metis.chart, 6
- metis.chartsProcess, 9
- metis.colors, 12
- metis.grid2poly, 13
- metis.gridByPoly, 14
- metis.io, 15
- metis.map, 15
- metis.mapProcess, 18
- metis.prepGrid, 21
- metis.printPdfPng, 22
- metis.readgcam, 23