Team 9 Class Access Guide

Excel Accessibility Hub | Phase 4 | Updated November 1, 2026

These application credentials are intentionally shared for class demonstrations and testing.

Team 9 deployed URLs

Service	URL
Website	https://3.139.178.70.sslip.io/system/
System base URL	https://3.139.178.70.sslip.io/system
System API documentation	https://3.139.178.70.sslip.io/system/docs
Tester base URL	https://3.139.178.70.sslip.io/tester
Tester API documentation	https://3.139.178.70.sslip.io/tester/docs

Shared application tokens

Identity	Token	Purpose
userA	`QMxgTEcsbuHJaVRV7M1h4NwEaPqeYMEEJHtV9o6OMPA`	Owner uploads, corrections and downloads; first test user
userB	`hRawDUIYyjy_glcn_NLxc6-QZPeWIdpy_-lLW6lSwIg`	Second test user for ownership isolation
reviewer	`P7jbZevd0ZZ7KzAoPICUG9E-DHz9MoATPgw4H0EtC_M`	Read-only access to userA's granted workbooks
test-admin	`7f5pJMFZF1vy5x_UU_SeXmG6UhdAFM3J1uZKw90PCb8`	System /test/setup and /test/report only; no workbook access
operator	`nrTr9hMvQ472w9OfyfLLYxF7sjaN5_-WDfKXmjtVsBk`	Tester /test/setup, /test/run and /test/report endpoints

Use the website

1. Open https://3.139.178.70.sslip.io/system/. Paste the **userA** token into **User access token** (no Bearer prefix), then choose **Connect**.

2. Select an **.xlsx** workbook and choose **Upload and check**. Wait for the audit, then read its findings and limitations.

3. For each finding, select **APPLY** only for a supported correction and supply the requested values. Use **DECLINE** or **MARK REVIEWED** as appropriate. Unselected findings stay unresolved.

4. Choose **Submit selected decisions** and wait. Use **Download remediated workbook** to save the separate output; the original stays unchanged. Review output findings and download its **audit report (JSON)**.

5. Save the workbook ID and use **Open history** to select a version/audit. For another upload to it, choose **New version of workbook in history**. Use **Re-audit selected version** to check the existing file again.

People using the same token share one identity. Reviewers connect with the **reviewer** token and open a granted workbook ID. Keep this tab open during recovery; use **Resume pending operation** after uncertain remediation acceptance. Reloading loses recovery state.

Run the Hosted Tester

Specification 2.1.0 | Ruleset 2.0.0 | Suite 2.1.1 (253 cases)

1. Open https://3.139.178.70.sslip.io/tester/docs.
2. Choose **Authorize**, enter the **operator** token without a Bearer prefix, and authorize.
3. Execute **POST /test/setup**. To test Team 12's system, use:

```
{"target_url":"https://13.184.14.226.sslip.io"}
```

To self-test, set **target_url** to https://3.139.178.70.sslip.io/system. Target credentials are configured on the server; continue using **Team 9's operator token** in this tester.

4. Require setup status **201**, copy its **session_id**, then execute **POST /test/run** once:

```
{"session_id":"PASTE_RETURNED_SESSION_ID"}
```

5. Retrieve the stored report with **GET /test/report**, using the same **session_id** query parameter.

Each prepared session runs once. A run can take 30 minutes. After a lost response, retrieve the report instead of repeating the run POST; a **409** report response means it is not ready. Poll within the original run deadline. Do not automatically repeat an uncertain setup POST.

Authentication and timing

Other HTTP clients use `Authorization: Bearer TOKEN`. Use **operator** for tester endpoints, **test-admin** for direct system testing endpoints, and **user or reviewer** tokens for authorized project operations. Local installations use their own credentials.

Tester setup timeout	Suite run timeout	Client read timeout
45 seconds	1,800 seconds (30 minutes)	At least 1,830 seconds

Approved target systems

Team 9: https://3.139.178.70.sslip.io/system
Team 12: https://13.184.14.226.sslip.io

Select the exact URL in `target_url`; no token fields are needed in the setup body. Other targets require server configuration. For reverse testing, use **Team 12's tester and its own operator token**, selecting Team 9's system as the target.

Understanding Phase 4 results

The six checks cover alternative text, worksheet names, table headers, merged cells, hyperlink text and color/contrast. Merged-cell and color/contrast findings require manual review; other findings may also need manual work when a safe correction is unavailable.

`REMEDIATION_AVAILABLE`: supported corrections await your decisions.
`REVIEW_REQUIRED`: the findings require manual review.
`REMEDIATED`: a separate output was generated; unresolved findings may remain.
DECLINE and **MARK REVIEWED** record decisions; they do not change workbook content.

Results support human review and are not a compliance determination. Earlier audits/reports keep their original versions and results. Corrections need the latest successful Phase 4 audit; re-audit older versions first. HTTP coverage excludes the UI; code coverage measures workbook and audit code.

After an uncertain upload or re-audit, check history before retrying.

Before a Phase 4 run, check target health (Team 9 or Team 12): `rulesetVersion` must be **2.0.0**.