Team 9 Class Access Guide

Excel Accessibility Hub | Phase 3 | Updated October 18, 2026

These application credentials are intentionally shared for class demonstrations and testing.

Team 9 deployed URLs

Service	URL
Website	https://3.139.178.70.sslip.io/system/
System base URL	https://3.139.178.70.sslip.io/system
System API documentation	https://3.139.178.70.sslip.io/system/docs
Tester base URL	https://3.139.178.70.sslip.io/tester
Tester API documentation	https://3.139.178.70.sslip.io/tester/docs

Shared application tokens

Identity	Token	Purpose
userA	`QMxgTEcsbuHJaVRV7M1h4NwEaPqeYMEEJHtV9o6OMPA`	Website uploads and owner access; first test user
userB	`hRawDUIYyjy_glcn_NLxc6-QZPeWIdpy_-lLW6lSwIg`	Second test user for ownership isolation
reviewer	`P7jbZevd0ZZ7KzAoPICUG9E-DHz9MoATPgw4H0EtC_M`	Reviewer with an explicit grant to userA's resources
test-admin	`7f5pJMFZF1vy5x_UU_SeXmG6UhdAFM3J1uZKw90PCb8`	System /test/setup and /test/report endpoints
operator	`nrTr9hMvQ472w9OfyfLLYxF7sjaN5_-WDfKXmjtVsBk`	Tester /test/setup, /test/run and /test/report endpoints

Use the website

1. Open https://3.139.178.70.sslip.io/system/.
2. Paste the **userA** token into **User access token**. Enter only the token; the website adds the Bearer prefix.
3. Select an **.xlsx** workbook and choose **Upload and check**.

People using the same token share that application identity. The system checks alternative text and generic worksheet names; results support human review.

These tokens belong to this deployed AWS instance. Local installations use their own generated credentials.

Run the Hosted Tester

Choose the target system, prepare a session, then run it once.

1. Open https://3.139.178.70.sslip.io/tester/docs.
2. Choose **Authorize**, enter the **operator** token without a Bearer prefix, and authorize.
3. Execute **POST /test/setup**. To run Team 9's tester against Team 12's system, use:

```
{"target_url":"https://13.184.14.226.sslip.io"}
```

To run a self-test instead, set **target_url** to https://3.139.178.70.sslip.io/system. Team 12's target credentials are configured on the server; continue using **Team 9's operator token** in this tester.

4. Copy the returned **session_id**. Execute **POST /test/run** with that value:

```
{"session_id":"PASTE_RETURNED_SESSION_ID"}
```

5. Retrieve the stored report with **GET /test/report**, supplying the same session ID as its query parameter.

Each prepared session runs once. Create a new session for a new run. After a lost run response, retrieve the report instead of repeating the run POST.

Authentication and timing

Other HTTP clients use `Authorization: Bearer TOKEN`. Use **operator** for tester endpoints, **test-admin** for direct system testing endpoints, and the appropriate **user or reviewer** token for project operations.

Tester setup timeout	Suite run timeout	Client read timeout
45 seconds	600 seconds	At least 630 seconds

Approved target systems

Team 9: https://3.139.178.70.sslip.io/system
Team 12: https://13.184.14.226.sslip.io
Both targets are configured for Team 9's tester. Select the exact URL in `target_url`; no token fields are needed in the setup body. Other targets require server configuration.

For the reverse direction, use **Team 12's tester and its own operator token**, selecting Team 9's system as the target.