

3_4 25 e, 16 bs, 256 ml, 0.1 wd, 1e-5 lr

April 13, 2025

0.1 Packages, Library Imports, File Mounts, & Data Imports ** Run All **

```
[1]: !pip install -q transformers  
!pip install -q torchinfo  
!pip install -q datasets  
!pip install -q evaluate  
!pip install -q nltk  
!pip install -q contractions  
!pip install -q hf_xet  
!pip install -q sentencepiece
```

491.2/491.2 kB

9.8 MB/s eta 0:00:00

116.3/116.3 kB

12.0 MB/s eta 0:00:00

183.9/183.9 kB

18.9 MB/s eta 0:00:00

143.5/143.5 kB

15.2 MB/s eta 0:00:00

194.8/194.8 kB

20.3 MB/s eta 0:00:00

ERROR: pip's dependency resolver does not currently take into account all the packages that are installed. This behaviour is the source of the following dependency conflicts.

torch 2.6.0+cu124 requires nvidia-cublas-cu12==12.4.5.8; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cublas-cu12 12.5.3.2 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cuda-cupti-cu12==12.4.127; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cuda-cupti-cu12 12.5.82 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cuda-nvrtc-cu12==12.4.127; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cuda-nvrtc-cu12 12.5.82 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cuda-runtime-cu12==12.4.127; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cuda-runtime-cu12 12.5.82 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cudnn-cu12==9.1.0.70; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cudnn-cu12 9.3.0.75 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cufft-cu12==11.2.1.3; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cufft-cu12 11.2.3.61 which is incompatible.

torch 2.6.0+cu124 requires nvidia-curand-cu12==10.3.5.147; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-curand-cu12 10.3.6.82 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cusolver-cu12==11.6.1.9; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cusolver-cu12 11.6.3.83 which is incompatible.

torch 2.6.0+cu124 requires nvidia-cuspars-cu12==12.3.1.170; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-cuspars-cu12 12.5.1.3 which is incompatible.

torch 2.6.0+cu124 requires nvidia-nvjitlink-cu12==12.4.127; platform_system == "Linux" and platform_machine == "x86_64", but you have nvidia-nvjitlink-cu12 12.5.82 which is incompatible.

gcsfs 2025.3.2 requires fsspec==2025.3.2,² but you have fsspec 2024.12.0 which is incompatible.

2.4 MB/s eta 0:00:00
289.9/289.9 kB
7.1 MB/s eta 0:00:00
118.3/118.3 kB
11.6 MB/s eta 0:00:00
53.8/53.8 MB
40.1 MB/s eta 0:00:00

```
[2]: !sudo apt-get update
      !sudo apt-get install tree
```

```
Hit:1 http://archive.ubuntu.com/ubuntu jammy InRelease
Get:2 http://archive.ubuntu.com/ubuntu jammy-updates InRelease [128 kB]
Get:3 https://cloud.r-project.org/bin/linux/ubuntu jammy-cran40/ InRelease
[3,632 B]
Get:4 https://developer.download.nvidia.com/compute/cuda/repos/ubuntu2204/x86_64
InRelease [1,581 B]
Get:5 https://r2u.stat.illinois.edu/ubuntu jammy InRelease [6,555 B]
Get:6 http://security.ubuntu.com/ubuntu jammy-security InRelease [129 kB]
Get:7 http://archive.ubuntu.com/ubuntu jammy-backports InRelease [127 kB]
Get:8 https://developer.download.nvidia.com/compute/cuda/repos/ubuntu2204/x86_64
Packages [1,383 kB]
Get:9 https://r2u.stat.illinois.edu/ubuntu jammy/main amd64 Packages [2,688 kB]
Get:10 https://ppa.launchpadcontent.net/deadsnakes/ppa/ubuntu jammy InRelease
[18.1 kB]
Get:11 http://archive.ubuntu.com/ubuntu jammy-updates/universe amd64 Packages
[1,542 kB]
Hit:12 https://ppa.launchpadcontent.net/graphics-drivers/ppa/ubuntu jammy
InRelease
Get:13 https://r2u.stat.illinois.edu/ubuntu jammy/main all Packages [8,824 kB]
Get:14 http://archive.ubuntu.com/ubuntu jammy-updates/main amd64 Packages [3,099
kB]
Hit:15 https://ppa.launchpadcontent.net/ubuntugis/ppa/ubuntu jammy InRelease
Get:16 http://security.ubuntu.com/ubuntu jammy-security/universe amd64 Packages
[1,243 kB]
Get:17 https://ppa.launchpadcontent.net/deadsnakes/ppa/ubuntu jammy/main amd64
Packages [34.3 kB]
Get:18 http://security.ubuntu.com/ubuntu jammy-security/restricted amd64
Packages [4,000 kB]
Get:19 http://security.ubuntu.com/ubuntu jammy-security/main amd64 Packages
[2,788 kB]
Fetched 26.0 MB in 2s (12.3 MB/s)
Reading package lists... Done
W: Skipping acquire of configured file 'main/source/Sources' as repository
'https://r2u.stat.illinois.edu/ubuntu jammy InRelease' does not seem to provide
it (sources.list entry misspelt?)
Reading package lists... Done
```

```

Building dependency tree... Done
Reading state information... Done
The following NEW packages will be installed:
  tree
0 upgraded, 1 newly installed, 0 to remove and 47 not upgraded.
Need to get 47.9 kB of archives.
After this operation, 116 kB of additional disk space will be used.
Get:1 http://archive.ubuntu.com/ubuntu jammy/universe amd64 tree amd64 2.0.2-1
[47.9 kB]
Fetched 47.9 kB in 0s (360 kB/s)
debconf: unable to initialize frontend: Dialog
debconf: (No usable dialog-like program is installed, so the dialog based
frontend cannot be used. at /usr/share/perl5/Debconf/FrontEnd/Dialog.pm line 78,
<> line 1.)
debconf: falling back to frontend: Readline
debconf: unable to initialize frontend: Readline
debconf: (This frontend requires a controlling tty.)
debconf: falling back to frontend: Teletype
dpkg-preconfigure: unable to re-open stdin:
Selecting previously unselected package tree.
(Reading database ... 126213 files and directories currently installed.)
Preparing to unpack .../tree_2.0.2-1_amd64.deb ...
Unpacking tree (2.0.2-1) ...
Setting up tree (2.0.2-1) ...
Processing triggers for man-db (2.10.2-1) ...

```

```

[3]: #@title Imports
import nltk
from nltk.tokenize import RegexpTokenizer
import sentencepiece
import contractions
import spacy

import evaluate
from datasets import load_dataset, Dataset, DatasetDict

import torch
import torch.nn as nn
from torchinfo import summary

import transformers
from transformers import AutoTokenizer, AutoModel,
    ↳AutoModelForSequenceClassification, TrainingArguments, Trainer, BertConfig,
    ↳BertForSequenceClassification

import os

```

```

import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

import sklearn
from sklearn.feature_extraction.text import TfidfVectorizer
from sklearn.naive_bayes import MultinomialNB
from sklearn.metrics import classification_report, \
    precision_recall_fscore_support, accuracy_score

import json
import datetime
import zoneinfo
from datetime import datetime

```

```
[4]: # @title Mount Google Drive
```

```
[5]: from google.colab import drive
drive.mount('/content/drive')
```

Mounted at /content/drive

```
[6]: dir_root = '/content/drive/MyDrive/266-final/'
# dir_data = '/content/drive/MyDrive/266-final/data/'
# dir_data = '/content/drive/MyDrive/266-final/data/se21-t1-comp-lex-master/'
dir_data = '/content/drive/MyDrive/266-final/data/266-comp-lex-master'
dir_models = '/content/drive/MyDrive/266-final/models/'
dir_results = '/content/drive/MyDrive/266-final/results/'
log_filename = "experiment_runs.txt"
log_filepath = os.path.join(dir_results, log_filename)
```

```
[7]: wandbai_api_key = ""
```

```
[8]: !tree /content/drive/MyDrive/266-final/data/266-comp-lex-master/
```

```

/content/drive/MyDrive/266-final/data/266-comp-lex-master/
  fe-test-labels
    test_multi_df.csv
    test_single_df.csv
  fe-train
    train_multi_df.csv
    train_single_df.csv
  fe-trial-val
    trial_val_multi_df.csv
    trial_val_single_df.csv
  test-labels
    lcp_multi_test.tsv

```

```

    lcp_single_test.tsv
train
    lcp_multi_train.tsv
    lcp_single_train.tsv
trial
    lcp_multi_trial.tsv
    lcp_single_trial.tsv

```

6 directories, 12 files

```
[9]: !ls -R /content/drive/MyDrive/266-final/data/266-comp-lex-master/
```

```

/content/drive/MyDrive/266-final/data/266-comp-lex-master/:
fe-test-labels  fe-train  fe-trial-val  test-labels  train  trial

/content/drive/MyDrive/266-final/data/266-comp-lex-master/fe-test-labels:
test_multi_df.csv  test_single_df.csv

/content/drive/MyDrive/266-final/data/266-comp-lex-master/fe-train:
train_multi_df.csv  train_single_df.csv

/content/drive/MyDrive/266-final/data/266-comp-lex-master/fe-trial-val:
trial_val_multi_df.csv  trial_val_single_df.csv

/content/drive/MyDrive/266-final/data/266-comp-lex-master/test-labels:
lcp_multi_test.tsv  lcp_single_test.tsv

/content/drive/MyDrive/266-final/data/266-comp-lex-master/train:
lcp_multi_train.tsv  lcp_single_train.tsv

/content/drive/MyDrive/266-final/data/266-comp-lex-master/trial:
lcp_multi_trial.tsv  lcp_single_trial.tsv

```

```
[10]: !tree /content/drive/MyDrive/266-final/data/266-comp-lex-master/
```

```

/content/drive/MyDrive/266-final/data/266-comp-lex-master/
fe-test-labels
    test_multi_df.csv
    test_single_df.csv
fe-train
    train_multi_df.csv
    train_single_df.csv
fe-trial-val
    trial_val_multi_df.csv
    trial_val_single_df.csv
test-labels
    lcp_multi_test.tsv
    lcp_single_test.tsv
train

```

```

    lcp_multi_train.tsv
    lcp_single_train.tsv
trial
    lcp_multi_trial.tsv
    lcp_single_trial.tsv

```

6 directories, 12 files

```
[11]: #@title Import Data
```

```
[12]: df_names = [
    "train_single_df",
    "train_multi_df",
    "trial_val_single_df",
    "trial_val_multi_df",
    "test_single_df",
    "test_multi_df"
]

loaded_dataframes = {}

for df_name in df_names:
    if "train" in df_name:
        subdir = "fe-train"
    elif "trial_val" in df_name:
        subdir = "fe-trial-val"
    elif "test" in df_name:
        subdir = "fe-test-labels"
    else:
        subdir = None

    if subdir:
        read_path = os.path.join(dir_data, subdir, f"{df_name}.csv")
        loaded_df = pd.read_csv(read_path)
        loaded_dataframes[df_name] = loaded_df
        print(f"Loaded {df_name} from {read_path}")

# for df_name, df in loaded_dataframes.items():
#     print(f"\n>>> {df_name} shape: {df.shape}")
#     if 'binary_complexity' in df.columns:
#         print(df['binary_complexity'].value_counts())
#         print(df.info())
#         print(df.head())

for df_name, df in loaded_dataframes.items():
    globals()[df_name] = df
    print(f"{df_name} loaded into global namespace.")
```

```

Loaded train_single_df from /content/drive/MyDrive/266-final/data/266-comp-lex-
master/fe-train/train_single_df.csv
Loaded train_multi_df from /content/drive/MyDrive/266-final/data/266-comp-lex-
master/fe-train/train_multi_df.csv
Loaded trial_val_single_df from /content/drive/MyDrive/266-final/data/266-comp-
lex-master/fe-trial-val/trial_val_single_df.csv
Loaded trial_val_multi_df from /content/drive/MyDrive/266-final/data/266-comp-
lex-master/fe-trial-val/trial_val_multi_df.csv
Loaded test_single_df from /content/drive/MyDrive/266-final/data/266-comp-lex-
master/fe-test-labels/test_single_df.csv
Loaded test_multi_df from /content/drive/MyDrive/266-final/data/266-comp-lex-
master/fe-test-labels/test_multi_df.csv
train_single_df loaded into global namespace.
train_multi_df loaded into global namespace.
trial_val_single_df loaded into global namespace.
trial_val_multi_df loaded into global namespace.
test_single_df loaded into global namespace.
test_multi_df loaded into global namespace.

```

- Functional tests pass, we can proceed with Baseline Modeling

0.2 Experiments

0.2.1 Helper Functions **** Run ****

```

[13]: MODEL_LINEAGE = {}

def get_model_and_tokenizer(
    remote_model_name: str = None,
    local_model_path: str = None,
    config=None
):
    """
    Loads the model & tokenizer for classification.
    If 'local_model_path' is specified, load from that path.
    Otherwise, fall back to 'remote_model_name'.

    Optional: 'config' can be a custom BertConfig/AutoConfig object
    to override certain configuration parameters.

    Records complete traceable lineage in the global MODEL_LINEAGE.
    """
    global MODEL_LINEAGE

    if local_model_path:
        print(f"Loading from local path: {local_model_path}")
        tokenizer = AutoTokenizer.from_pretrained(local_model_path)

```



```

# If a config object is provided, we pass it to from_pretrained.
# Otherwise, it just uses the config that is part of local_model_path.
if config is not None:
    model = AutoModelForSequenceClassification.from_pretrained(
        local_model_path,
        config=config
    )
else:
    model = AutoModelForSequenceClassification.
↳from_pretrained(local_model_path)

MODEL_LINEAGE = {
    "type": "offline_checkpoint",
    "path": local_model_path,
    "timestamp": datetime.now().strftime("%Y-%m-%d %H:%M:%S")
}
elif remote_model_name:
    print(f>Loading from Hugging Face model: {remote_model_name}")
    tokenizer = AutoTokenizer.from_pretrained(remote_model_name)

    if config is not None:
        model = AutoModelForSequenceClassification.from_pretrained(
            remote_model_name,
            config=config
        )
    else:
        model = AutoModelForSequenceClassification.
↳from_pretrained(remote_model_name)

    MODEL_LINEAGE = {
        "type": "huggingface_hub",
        "path": remote_model_name,
        "timestamp": datetime.now().strftime("%Y-%m-%d %H:%M:%S")
    }
else:
    raise ValueError("You must provide either a remote_model_name or a
↳local_model_path!")

return model, tokenizer

```

```

[14]: def freeze_unfreeze_layers(model, layers_to_unfreeze=None):
    """
    Toggles requires_grad = False for all parameters
    except for those whose names contain any string in layers_to_unfreeze.
    By default, always unfreeze classifier/heads.
    """
    if layers_to_unfreeze is None:

```

```

layers_to_unfreeze = ["classifier.", "pooler."]

for name, param in model.named_parameters():
    if any(substring in name for substring in layers_to_unfreeze):
        param.requires_grad = True
    else:
        param.requires_grad = False

```

```

[15]: def encode_examples(examples, tokenizer, text_col, max_length=256):
    """
    Tokenizes a batch of texts from 'examples[text_col]' using the given
    ↪ tokenizer.
    Returns a dict with 'input_ids', 'attention_mask', etc.
    """
    texts = examples[text_col]
    encoded = tokenizer(
        texts,
        truncation=True,
        padding='max_length',
        max_length=max_length
    )
    return encoded

```

```

[16]: def prepare_dataset(df, tokenizer, text_col, label_col, max_length=256):
    """
    Converts a Pandas DataFrame to a Hugging Face Dataset,
    then applies 'encode_examples' to tokenize.
    """
    dataset = Dataset.from_pandas(df)

    dataset = dataset.map(
        lambda batch: encode_examples(batch, tokenizer, text_col, max_length),
        batched=True
    )

    dataset = dataset.rename_column(label_col, "labels")
    dataset.set_format(type='torch',
                       columns=['input_ids', 'attention_mask', 'labels'])
    return dataset

```

```

[17]: def compute_metrics(eval_pred):
    """
    Computes classification metrics, including accuracy, precision, recall, and
    ↪ F1.
    """
    logits, labels = eval_pred
    preds = np.argmax(logits, axis=1)

```

```

metric_accuracy = evaluate.load("accuracy")
metric_precision = evaluate.load("precision")
metric_recall = evaluate.load("recall")
metric_f1 = evaluate.load("f1")

accuracy_result = metric_accuracy.compute(predictions=preds,
↪references=labels)
precision_result = metric_precision.compute(predictions=preds,
↪references=labels, average="binary")
recall_result = metric_recall.compute(predictions=preds,
↪references=labels, average="binary")
f1_result = metric_f1.compute(predictions=preds, references=labels,
↪average="binary")

return {
    "accuracy" : accuracy_result["accuracy"],
    "precision": precision_result["precision"],
    "recall" : recall_result["recall"],
    "f1" : f1_result["f1"]
}

```

```

[18]: def gather_config_details(model):
    """
    Enumerates every attribute in model.config
    """
    config_items = {}
    for attr_name, attr_value in vars(model.config).items():
        config_items[attr_name] = attr_value
    return config_items

def gather_model_details(model):
    """
    Extracts total layers, total params, trainable params, and activation
    ↪function
    from a Transformers model. Adjust logic as needed for different
    ↪architectures.
    """
    details = {}

    try:
        total_params = model.num_parameters()
        trainable_params = model.num_parameters(only_trainable=True)
    except AttributeError:
        all_params = list(model.parameters())
        total_params = sum(p.numel() for p in all_params)
        trainable_params = sum(p.numel() for p in all_params if p.requires_grad)

```

```

details["model_total_params"] = total_params
details["model_trainable_params"] = trainable_params

if hasattr(model, "bert") and hasattr(model.bert, "pooler"):
    act_obj = getattr(model.bert.pooler, "activation", None)
    details["pooler_activation_function"] = act_obj.__class__.__name__ if
↪act_obj else "N/A"
else:
    details["pooler_activation_function"] = "N/A"

details["config_attributes"] = gather_config_details(model)
return details

def gather_all_run_metrics(trainer, train_dataset=None, val_dataset=None,
↪test_dataset=None):
    """
    Gathers final training metrics, final validation metrics, final test
↪metrics.

    Instead of only parsing the final train_loss from the log, we also do a full
    trainer.evaluate(train_dataset) to get the same set of metrics that val/
↪test have.
    """
    results = {}

    if train_dataset is not None:
        train_metrics = trainer.evaluate(train_dataset)
        for k, v in train_metrics.items():
            results[f"train_{k}"] = v
    else:
        results["train_metrics"] = "No train dataset provided"

    if val_dataset is not None:
        val_metrics = trainer.evaluate(val_dataset)
        for k, v in val_metrics.items():
            results[f"val_{k}"] = v
    else:
        results["val_metrics"] = "No val dataset provided"

    if test_dataset is not None:
        test_metrics = trainer.evaluate(test_dataset)
        for k, v in test_metrics.items():
            results[f"test_{k}"] = v
    else:
        results["test_metrics"] = "No test dataset provided"

    return results

```

```

# def log_experiment_results_json(experiment_meta, model_details, run_metrics,
    ↪ log_file):
#     """
#     Logs experiment metadata, model details, and metrics to a JSON lines file.
#     Automatically concatenates the 'checkpoint_path' to the 'model_lineage'.
#     """
#     checkpoint_path = model_details.get("checkpoint_path")
#     if checkpoint_path:
#         if "model_lineage" not in model_details:
#             model_details["model_lineage"] = ""
#         if model_details["model_lineage"]:
#             model_details["model_lineage"] += " -> "
#         model_details["model_lineage"] += checkpoint_path
#
#     record = {
#         "timestamp": str(datetime.datetime.now()),
#         "experiment_meta": experiment_meta,
#         "model_details": model_details,
#         "run_metrics": run_metrics
#     }
#
#     with open(log_file, "a", encoding="utf-8") as f:
#         json.dump(record, f)
#         f.write("\n")

def log_experiment_results_json(experiment_meta, model_details, run_metrics,
    ↪ log_file):
    """
    Logs experiment metadata, model details, and metrics to a JSON lines file.
    Automatically concatenates the 'checkpoint_path' to the 'model_lineage'
    and uses Pacific time for the timestamp.
    """
    checkpoint_path = model_details.get("checkpoint_path")
    if checkpoint_path:
        if "model_lineage" not in model_details:
            model_details["model_lineage"] = ""
        if model_details["model_lineage"]:
            model_details["model_lineage"] += " -> "
        model_details["model_lineage"] += checkpoint_path

    pacific_time = datetime.now(zoneinfo.ZoneInfo("America/Los_Angeles")) # ↪
    ↪ update to support pacific time
    timestamp_str = pacific_time.isoformat()

    record = {
        "timestamp": timestamp_str,

```

```

        "experiment_meta": experiment_meta,
        "model_details": model_details,
        "run_metrics": run_metrics
    }

    with open(log_file, "a", encoding="utf-8") as f:
        json.dump(record, f)
        f.write("\n")

```

0.2.2 Experiment Cohort Design

```

[19]: # Define Experiment Parameters

named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert

# learning_rate = 1e-3
# learning_rate = 1e-4
learning_rate = 1e-5
# learning_rate = 5e-6
# learning_rate = 5e-7
# learning_rate = 5e-8

# num_epochs = 1
# num_epochs = 3
# num_epochs = 5
num_epochs = 25
# num_epochs = 15
# num_epochs = 20

# length_max = 128
length_max = 256
# length_max = 348
# length_max = 512

# size_batch = 1
# size_batch = 4
# size_batch = 8
size_batch = 16
# size_batch = 24
# size_batch = 32
# size_batch = 64
# size_batch = 128

```

```

# regularization_weight_decay = 0
regularization_weight_decay = 0.1
# regularization_weight_decay = 0.5

y_col = "binary_complexity"
# y_col = "complexity"

x_task = "single"
# x_task = "multi"

# x_col = "sentence"
x_col = "sentence_no_contractions"
# x_col = "pos_sequence"
# x_col = "dep_sequence"
# x_col = "morph_sequence"

if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df

custom_config = BertConfig.from_pretrained("bert-base-cased")

custom_config.hidden_dropout_prob = 0.1
# custom_config.intermediate_size = 3072
# custom_config.intermediate_size = 6144
# custom_config.num_attention_heads = 12
# custom_config.num_hidden_layers = 12
custom_config.gradient_checkpointing = False
custom_config.attention_probs_dropout_prob = 0.1
# custom_config.max_position_embeddings = 512
# custom_config.type_vocab_size = 2
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
# custom_config.vocab_size = 28996 # must match

# model.bert.pooler.activation = nn.ReLU() # Tanh() replaced as the pooler
# layer activation function in side-by-side with 1.1

```

/usr/local/lib/python3.11/dist-packages/huggingface_hub/utils/_auth.py:104:

UserWarning:

Error while fetching `HF_TOKEN` secret value from your vault: 'Requesting secret HF_TOKEN timed out. Secrets can only be fetched when running from the Colab UI.'

You are not authenticated with the Hugging Face Hub in this notebook.

If the error persists, please let us know by opening an issue on GitHub (https://github.com/huggingface/huggingface_hub/issues/new).

```
warnings.warn(
```

```
config.json: 0%|          | 0.00/570 [00:00<?, ?B/s]
```

```
[20]: def train_transformer_model(
    model,
    tokenizer,
    train_dataset,
    val_dataset,
    output_dir=dir_results,
    num_epochs=num_epochs,
    batch_size=size_batch,
    lr=learning_rate,
    weight_decay=regularization_weight_decay
):
    """
    Sets up a Trainer and trains the model for 'num_epochs' using the given
    ↪dataset.
    Returns the trained model and the Trainer object for possible re-use or
    ↪analysis.
    """

    training_args = TrainingArguments(
        output_dir=output_dir,
        num_train_epochs=num_epochs,
        per_device_train_batch_size=batch_size,
        per_device_eval_batch_size=batch_size,
        evaluation_strategy="epoch",
        save_strategy="no",
        logging_strategy="epoch",
        learning_rate=lr,
        weight_decay=weight_decay,
        report_to=["none"], # or "wandb"
        warmup_steps=100
    )

    trainer = Trainer(
        model=model,
        args=training_args,
        train_dataset=train_dataset,
        eval_dataset=val_dataset,
        tokenizer=tokenizer, # optional
        compute_metrics=compute_metrics
    )

    trainer.train()
```



```
return model, trainer
```

Model Inspection ** Run **

```
[21]: print("model checkpoints:", dir_models)
      !ls /content/drive/MyDrive/266-final/models/
```

```
model checkpoints: /content/drive/MyDrive/266-final/models/
multi_bert-base-cased_binary_complexity_20250408_143322
multi_bert-base-cased_binary_complexity_20250409_175804
multi_bert-base-cased_binary_complexity_20250409_175954
multi_bert-base-cased_binary_complexity_20250409_180139
multi_bert-base-cased_binary_complexity_20250409_185057
multi_bert-base-cased_binary_complexity_20250409_185213
multi_bert-base-cased_binary_complexity_20250409_185333
multi_bert-base-cased_binary_complexity_20250409_234934
multi_bert-base-cased_binary_complexity_20250410_001637
multi_bert-base-cased_binary_complexity_20250410_003117
multi_bert-base-cased_binary_complexity_20250410_004527
single_bert-base-cased_binary_complexity_20250408_043117
single_bert-base-cased_binary_complexity_20250408_043334
single_bert-base-cased_binary_complexity_20250408_043750
single_bert-base-cased_binary_complexity_20250409_175702
single_bert-base-cased_binary_complexity_20250409_175900
single_bert-base-cased_binary_complexity_20250409_180045
single_bert-base-cased_binary_complexity_20250409_185027
single_bert-base-cased_binary_complexity_20250409_185141
single_bert-base-cased_binary_complexity_20250409_185303
single_bert-base-cased_binary_complexity_20250409_234236
single_bert-base-cased_binary_complexity_20250410_000508
single_bert-base-cased_binary_complexity_20250410_002813
single_bert-base-cased_binary_complexity_20250410_004230
```

```
[22]: # Load Model & Tokenizer
      # model, tokenizer = get_model_and_tokenizer(named_model) # deprecated argument
      ↪structure
      # model, tokenizer = get_model_and_tokenizer("/content/drive/MyDrive/266-final/
      ↪models/....") # proposed argument usage for checkpointed models

      # for name, param in model.named_parameters():
      #     print(name)

      model, tokenizer = get_model_and_tokenizer(
          remote_model_name="bert-base-cased",
          local_model_path=None,
```

```

        config=custom_config
    )

    # model, tokenizer = get_model_and_tokenizer(
    #     local_model_path="my_local_bert_path",
    #     config=custom_config
    # )

    print("=====")
    print(named_model, ":")
    print("=====")
    # print(model)
    print("=====")
    print(model.config)
    print("=====")
    print("num_parameters:", model.num_parameters())
    print("=====")
    print("num_trainable_parameters:", model.num_parameters(only_trainable=True))

```

Loading from Hugging Face model: bert-base-cased

tokenizer_config.json: 0%| | 0.00/49.0 [00:00<?, ?B/s]

vocab.txt: 0%| | 0.00/213k [00:00<?, ?B/s]

tokenizer.json: 0%| | 0.00/436k [00:00<?, ?B/s]

model.safetensors: 0%| | 0.00/436M [00:00<?, ?B/s]

Some weights of BertForSequenceClassification were not initialized from the model checkpoint at bert-base-cased and are newly initialized:

['classifier.bias', 'classifier.weight']

You should probably TRAIN this model on a down-stream task to be able to use it for predictions and inference.

=====

bert-base-cased :

=====

=====

```

BertConfig {
  "_attn_implementation_autoset": true,
  "architectures": [
    "BertForMaskedLM"
  ],
  "attention_probs_dropout_prob": 0.1,
  "classifier_dropout": null,
  "gradient_checkpointing": false,
  "hidden_act": "gelu",
  "hidden_dropout_prob": 0.1,
  "hidden_size": 768,
  "initializer_range": 0.02,

```

```

    "intermediate_size": 3072,
    "layer_norm_eps": 1e-12,
    "max_position_embeddings": 512,
    "model_type": "bert",
    "num_attention_heads": 12,
    "num_hidden_layers": 12,
    "pad_token_id": 0,
    "position_embedding_type": "absolute",
    "torch_dtype": "float32",
    "transformers_version": "4.50.3",
    "type_vocab_size": 2,
    "use_cache": true,
    "vocab_size": 28996
}

```

```

=====
num_parameters: 108311810
=====
num_trainable_parameters: 108311810

```

Layer Configuration ** Run **

[23]: *# Freeze/Unfreeze Layers & Additional Activation Function Configuration*

```

layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier.",
]

freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)

for name, param in model.named_parameters():
    print(name, "requires_grad=", param.requires_grad)

print("\nLayers that are 'True' are trainable. 'False' are frozen.")

print("=====")
print(named_model, ":")
print("=====")
# print(model)
print("=====")

```

```

print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("=====")
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))

```

```

bert.embeddings.word_embeddings.weight requires_grad= True
bert.embeddings.position_embeddings.weight requires_grad= True
bert.embeddings.token_type_embeddings.weight requires_grad= True
bert.embeddings.LayerNorm.weight requires_grad= True
bert.embeddings.LayerNorm.bias requires_grad= True
bert.encoder.layer.0.attention.self.query.weight requires_grad= True
bert.encoder.layer.0.attention.self.query.bias requires_grad= True
bert.encoder.layer.0.attention.self.key.weight requires_grad= True
bert.encoder.layer.0.attention.self.key.bias requires_grad= True
bert.encoder.layer.0.attention.self.value.weight requires_grad= True
bert.encoder.layer.0.attention.self.value.bias requires_grad= True
bert.encoder.layer.0.attention.output.dense.weight requires_grad= True
bert.encoder.layer.0.attention.output.dense.bias requires_grad= True
bert.encoder.layer.0.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.0.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.0.intermediate.dense.weight requires_grad= True
bert.encoder.layer.0.intermediate.dense.bias requires_grad= True
bert.encoder.layer.0.output.dense.weight requires_grad= True
bert.encoder.layer.0.output.dense.bias requires_grad= True
bert.encoder.layer.0.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.0.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.1.attention.self.query.weight requires_grad= False
bert.encoder.layer.1.attention.self.query.bias requires_grad= False
bert.encoder.layer.1.attention.self.key.weight requires_grad= False
bert.encoder.layer.1.attention.self.key.bias requires_grad= False
bert.encoder.layer.1.attention.self.value.weight requires_grad= False
bert.encoder.layer.1.attention.self.value.bias requires_grad= False
bert.encoder.layer.1.attention.output.dense.weight requires_grad= False
bert.encoder.layer.1.attention.output.dense.bias requires_grad= False
bert.encoder.layer.1.attention.output.LayerNorm.weight requires_grad= False
bert.encoder.layer.1.attention.output.LayerNorm.bias requires_grad= False
bert.encoder.layer.1.intermediate.dense.weight requires_grad= False
bert.encoder.layer.1.intermediate.dense.bias requires_grad= False
bert.encoder.layer.1.output.dense.weight requires_grad= False
bert.encoder.layer.1.output.dense.bias requires_grad= False
bert.encoder.layer.1.output.LayerNorm.weight requires_grad= False
bert.encoder.layer.1.output.LayerNorm.bias requires_grad= False
bert.encoder.layer.2.attention.self.query.weight requires_grad= False
bert.encoder.layer.2.attention.self.query.bias requires_grad= False
bert.encoder.layer.2.attention.self.key.weight requires_grad= False
bert.encoder.layer.2.attention.self.key.bias requires_grad= False
bert.encoder.layer.2.attention.self.value.weight requires_grad= False

```


bert.encoder.layer.8.attention.self.value.bias requires_grad= True
bert.encoder.layer.8.attention.output.dense.weight requires_grad= True
bert.encoder.layer.8.attention.output.dense.bias requires_grad= True
bert.encoder.layer.8.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.8.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.8.intermediate.dense.weight requires_grad= True
bert.encoder.layer.8.intermediate.dense.bias requires_grad= True
bert.encoder.layer.8.output.dense.weight requires_grad= True
bert.encoder.layer.8.output.dense.bias requires_grad= True
bert.encoder.layer.8.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.8.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.9.attention.self.query.weight requires_grad= True
bert.encoder.layer.9.attention.self.query.bias requires_grad= True
bert.encoder.layer.9.attention.self.key.weight requires_grad= True
bert.encoder.layer.9.attention.self.key.bias requires_grad= True
bert.encoder.layer.9.attention.self.value.weight requires_grad= True
bert.encoder.layer.9.attention.self.value.bias requires_grad= True
bert.encoder.layer.9.attention.output.dense.weight requires_grad= True
bert.encoder.layer.9.attention.output.dense.bias requires_grad= True
bert.encoder.layer.9.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.9.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.9.intermediate.dense.weight requires_grad= True
bert.encoder.layer.9.intermediate.dense.bias requires_grad= True
bert.encoder.layer.9.output.dense.weight requires_grad= True
bert.encoder.layer.9.output.dense.bias requires_grad= True
bert.encoder.layer.9.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.9.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.10.attention.self.query.weight requires_grad= True
bert.encoder.layer.10.attention.self.query.bias requires_grad= True
bert.encoder.layer.10.attention.self.key.weight requires_grad= True
bert.encoder.layer.10.attention.self.key.bias requires_grad= True
bert.encoder.layer.10.attention.self.value.weight requires_grad= True
bert.encoder.layer.10.attention.self.value.bias requires_grad= True
bert.encoder.layer.10.attention.output.dense.weight requires_grad= True
bert.encoder.layer.10.attention.output.dense.bias requires_grad= True
bert.encoder.layer.10.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.10.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.10.intermediate.dense.weight requires_grad= True
bert.encoder.layer.10.intermediate.dense.bias requires_grad= True
bert.encoder.layer.10.output.dense.weight requires_grad= True
bert.encoder.layer.10.output.dense.bias requires_grad= True
bert.encoder.layer.10.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.10.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.11.attention.self.query.weight requires_grad= True
bert.encoder.layer.11.attention.self.query.bias requires_grad= True
bert.encoder.layer.11.attention.self.key.weight requires_grad= True
bert.encoder.layer.11.attention.self.key.bias requires_grad= True
bert.encoder.layer.11.attention.self.value.weight requires_grad= True

```

bert.encoder.layer.11.attention.self.value.bias requires_grad= True
bert.encoder.layer.11.attention.output.dense.weight requires_grad= True
bert.encoder.layer.11.attention.output.dense.bias requires_grad= True
bert.encoder.layer.11.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.11.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.11.intermediate.dense.weight requires_grad= True
bert.encoder.layer.11.intermediate.dense.bias requires_grad= True
bert.encoder.layer.11.output.dense.weight requires_grad= True
bert.encoder.layer.11.output.dense.bias requires_grad= True
bert.encoder.layer.11.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.11.output.LayerNorm.bias requires_grad= True
bert.pooler.dense.weight requires_grad= True
bert.pooler.dense.bias requires_grad= True
classifier.weight requires_grad= True
classifier.bias requires_grad= True

```

Layers that are 'True' are trainable. 'False' are frozen.

```

=====
bert-base-cased :
=====

```

```

BertConfig {
  "_attn_implementation_autoset": true,
  "architectures": [
    "BertForMaskedLM"
  ],
  "attention_probs_dropout_prob": 0.1,
  "classifier_dropout": null,
  "gradient_checkpointing": false,
  "hidden_act": "gelu",
  "hidden_dropout_prob": 0.1,
  "hidden_size": 768,
  "initializer_range": 0.02,
  "intermediate_size": 3072,
  "layer_norm_eps": 1e-12,
  "max_position_embeddings": 512,
  "model_type": "bert",
  "num_attention_heads": 12,
  "num_hidden_layers": 12,
  "pad_token_id": 0,
  "position_embedding_type": "absolute",
  "torch_dtype": "float32",
  "transformers_version": "4.50.3",
  "type_vocab_size": 2,
  "use_cache": true,
  "vocab_size": 28996
}

```



```

=====
num_parameters: 108311810
=====
num_trainable_parameters: 58696706

```

Dataset Preparation ** Run **

```

[24]: # Tokenize & Prepare Datasets

train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max
)

val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max
)

test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max
)

print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])

```

```
Map: 0%|          | 0/7662 [00:00<?, ? examples/s]
```

```
Map: 0%|          | 0/421 [00:00<?, ? examples/s]
```

```
Map: 0%|          | 0/917 [00:00<?, ? examples/s]
```

Datasets prepared. Sample from train_data_hf:

```

{'labels': tensor(0), 'input_ids': tensor([ 101, 1252, 1106, 1103, 3824,
1104, 19892, 11220, 1324, 1119,
1522, 3839, 117, 1272, 1103, 1555, 1104, 1103, 11563, 5609,
1106, 1172, 132, 1152, 2446, 1122, 1113, 1147, 3221, 119,
102, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0])

```


Experiment configuration used with this experiment:

model used: bert-base-cased
learning rate used: 1e-05
number of epochs: 25
maximum sequence length: 256
batch size used: 16
regularization value: 0.1
outcome variable: binary_complexity
task: single
input column: sentence_no_contractions

[26]: *# Train & Evaluate*

```
trained_model, trainer_obj = train_transformer_model(  
    model=model,  
    tokenizer=tokenizer,  
    train_dataset=train_data_hf,  
    val_dataset=val_data_hf,  
    output_dir=dir_results,  
    num_epochs=num_epochs,  
    batch_size=size_batch,  
    lr=learning_rate,  
    weight_decay=regularization_weight_decay  
)  
  
metrics = trainer_obj.evaluate()  
print("Validation metrics:", metrics)  
  
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None  
print("Test metrics:", test_metrics)
```

/usr/local/lib/python3.11/dist-packages/transformers/training_args.py:1611:

FutureWarning: `evaluation_strategy` is deprecated and will be removed in
version 4.46 of Transformers. Use `eval_strategy` instead

warnings.warn(

<ipython-input-20-c2ee9f934517>:31: FutureWarning: `tokenizer` is deprecated and
will be removed in version 5.0.0 for `Trainer.__init__`. Use `processing_class`
instead.

trainer = Trainer(

<IPython.core.display.HTML object>

Downloading builder script: 0%| | 0.00/4.20k [00:00<?, ?B/s]

Downloading builder script: 0%| | 0.00/7.56k [00:00<?, ?B/s]

Downloading builder script: 0%| | 0.00/7.38k [00:00<?, ?B/s]

Downloading builder script: 0%| | 0.00/6.79k [00:00<?, ?B/s]

<IPython.core.display.HTML object>

```

Validation metrics: {'eval_loss': 1.8727476596832275, 'eval_accuracy':
0.6080760095011877, 'eval_precision': 0.5780346820809249, 'eval_recall':
0.5208333333333334, 'eval_f1': 0.547945205479452, 'eval_runtime': 2.6804,
'eval_samples_per_second': 157.064, 'eval_steps_per_second': 10.073, 'epoch':
25.0}
Test metrics: {'eval_loss': 1.9690210819244385, 'eval_accuracy':
0.5561613958560524, 'eval_precision': 0.5435897435897435, 'eval_recall':
0.48072562358276644, 'eval_f1': 0.5102286401925391, 'eval_runtime': 4.0332,
'eval_samples_per_second': 227.36, 'eval_steps_per_second': 14.38, 'epoch':
25.0}

```

[27]: *# save model checkpoint*

```

timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    f"{x_task}_{named_model}_{y_col}_{timestamp}")

trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")

```

Model checkpoint saved to: /content/drive/MyDrive/266-final/models/single_bert-base-cased_binary_complexity_20250410_031404

[28]:

```

experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze
}

model_info = gather_model_details(trained_model)

all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf
)

log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,

```

```

    log_file=log_filepath
)

print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

<IPython.core.display.HTML object>

EXPERIMENT LOGGED TO:
/content/drive/MyDrive/266-final/results/experiment_runs.txt

0.2.4 3.1.2: from pretrained bert-base-cased Y: multi task 2 & X: sentence_no_contractions — Y

```

[29]: # Define Experiment Parameters

named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert

# learning_rate = 1e-3
# learning_rate = 1e-4
learning_rate = 1e-5
# learning_rate = 5e-6
# learning_rate = 5e-7
# learning_rate = 5e-8

# num_epochs = 1
# num_epochs = 3
# num_epochs = 5
num_epochs = 25
# num_epochs = 15
# num_epochs = 20

# length_max = 128
length_max = 256
# length_max = 348
# length_max = 512

# size_batch = 1
# size_batch = 4
# size_batch = 8
size_batch = 16
# size_batch = 24
# size_batch = 32
# size_batch = 64
# size_batch = 128

```

```

# regularization_weight_decay = 0
regularization_weight_decay = 0.1
# regularization_weight_decay = 0.5

y_col = "binary_complexity"
# y_col = "complexity"

# x_task = "single"
x_task = "multi"

# x_col = "sentence"
x_col = "sentence_no_contractions"
# x_col = "pos_sequence"
# x_col = "dep_sequence"
# x_col = "morph_sequence"

if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df

custom_config = BertConfig.from_pretrained("bert-base-cased")

custom_config.hidden_dropout_prob = 0.1
# custom_config.intermediate_size = 3072
# custom_config.intermediate_size = 6144
# custom_config.num_attention_heads = 12
# custom_config.num_hidden_layers = 12
custom_config.gradient_checkpointing = False
custom_config.attention_probs_dropout_prob = 0.1
# custom_config.max_position_embeddings = 512
# custom_config.type_vocab_size = 2
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
# custom_config.vocab_size = 28996 # must match

# model.bert.pooler.activation = nn.ReLU() # Tanh() replaced as the pooler_
↳ layer activation function in side-by-side with 1.1

```

```

[30]: print("model checkpoints:", dir_models)
      !ls /content/drive/MyDrive/266-final/models/

```

```

model checkpoints: /content/drive/MyDrive/266-final/models/
multi_bert-base-cased_binary_complexity_20250408_143322

```

```

multi_bert-base-cased_binary_complexity_20250409_175804
multi_bert-base-cased_binary_complexity_20250409_175954
multi_bert-base-cased_binary_complexity_20250409_180139
multi_bert-base-cased_binary_complexity_20250409_185057
multi_bert-base-cased_binary_complexity_20250409_185213
multi_bert-base-cased_binary_complexity_20250409_185333
multi_bert-base-cased_binary_complexity_20250409_234934
multi_bert-base-cased_binary_complexity_20250410_001637
multi_bert-base-cased_binary_complexity_20250410_003117
multi_bert-base-cased_binary_complexity_20250410_004527
single_bert-base-cased_binary_complexity_20250408_043117
single_bert-base-cased_binary_complexity_20250408_043334
single_bert-base-cased_binary_complexity_20250408_043750
single_bert-base-cased_binary_complexity_20250409_175702
single_bert-base-cased_binary_complexity_20250409_175900
single_bert-base-cased_binary_complexity_20250409_180045
single_bert-base-cased_binary_complexity_20250409_185027
single_bert-base-cased_binary_complexity_20250409_185141
single_bert-base-cased_binary_complexity_20250409_185303
single_bert-base-cased_binary_complexity_20250409_234236
single_bert-base-cased_binary_complexity_20250410_000508
single_bert-base-cased_binary_complexity_20250410_002813
single_bert-base-cased_binary_complexity_20250410_004230
single_bert-base-cased_binary_complexity_20250410_031404

```

```

[31]: # Load Model & Tokenizer
# model, tokenizer = get_model_and_tokenizer(named_model) # deprecated argument
↳ structure
# model, tokenizer = get_model_and_tokenizer("/content/drive/MyDrive/266-final/
↳ models/....") # proposed argument usage for checkpointed models

# for name, param in model.named_parameters():
#     print(name)

model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config
)

# model, tokenizer = get_model_and_tokenizer(
#     local_model_path="my_local_bert_path",
#     config=custom_config
# )

print("=====")
print(named_model, ":")

```

```

print("=====")
# print(model)
print("=====")
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("=====")
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))

```

Loading from Hugging Face model: bert-base-cased

Some weights of BertForSequenceClassification were not initialized from the model checkpoint at bert-base-cased and are newly initialized:

['classifier.bias', 'classifier.weight']

You should probably TRAIN this model on a down-stream task to be able to use it for predictions and inference.

=====

bert-base-cased :

=====

=====

```

BertConfig {
  "_attn_implementation_autoset": true,
  "architectures": [
    "BertForMaskedLM"
  ],
  "attention_probs_dropout_prob": 0.1,
  "classifier_dropout": null,
  "gradient_checkpointing": false,
  "hidden_act": "gelu",
  "hidden_dropout_prob": 0.1,
  "hidden_size": 768,
  "initializer_range": 0.02,
  "intermediate_size": 3072,
  "layer_norm_eps": 1e-12,
  "max_position_embeddings": 512,
  "model_type": "bert",
  "num_attention_heads": 12,
  "num_hidden_layers": 12,
  "pad_token_id": 0,
  "position_embedding_type": "absolute",
  "torch_dtype": "float32",
  "transformers_version": "4.50.3",
  "type_vocab_size": 2,
  "use_cache": true,
  "vocab_size": 28996
}

```

=====


```
num_parameters: 108311810
=====
num_trainable_parameters: 108311810
```

```
[32]: # Freeze/Unfreeze Layers & Additional Activation Function Configuration
layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier.",
]

freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)

for name, param in model.named_parameters():
    print(name, "requires_grad=", param.requires_grad)

print("\nLayers that are 'True' are trainable. 'False' are frozen.")

print("=====")
print(named_model, ":")
print("=====")
# print(model)
print("=====")
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("=====")
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
```

```
bert.embeddings.word_embeddings.weight requires_grad= True
bert.embeddings.position_embeddings.weight requires_grad= True
bert.embeddings.token_type_embeddings.weight requires_grad= True
bert.embeddings.LayerNorm.weight requires_grad= True
bert.embeddings.LayerNorm.bias requires_grad= True
bert.encoder.layer.0.attention.self.query.weight requires_grad= True
bert.encoder.layer.0.attention.self.query.bias requires_grad= True
bert.encoder.layer.0.attention.self.key.weight requires_grad= True
bert.encoder.layer.0.attention.self.key.bias requires_grad= True
bert.encoder.layer.0.attention.self.value.weight requires_grad= True
bert.encoder.layer.0.attention.self.value.bias requires_grad= True
bert.encoder.layer.0.attention.output.dense.weight requires_grad= True
bert.encoder.layer.0.attention.output.dense.bias requires_grad= True
```

[illegible]

[illegible]

bert.encoder.layer.6.attention.output.LayerNorm.weight requires_grad= False
bert.encoder.layer.6.attention.output.LayerNorm.bias requires_grad= False
bert.encoder.layer.6.intermediate.dense.weight requires_grad= False
bert.encoder.layer.6.intermediate.dense.bias requires_grad= False
bert.encoder.layer.6.output.dense.weight requires_grad= False
bert.encoder.layer.6.output.dense.bias requires_grad= False
bert.encoder.layer.6.output.LayerNorm.weight requires_grad= False
bert.encoder.layer.6.output.LayerNorm.bias requires_grad= False
bert.encoder.layer.7.attention.self.query.weight requires_grad= False
bert.encoder.layer.7.attention.self.query.bias requires_grad= False
bert.encoder.layer.7.attention.self.key.weight requires_grad= False
bert.encoder.layer.7.attention.self.key.bias requires_grad= False
bert.encoder.layer.7.attention.self.value.weight requires_grad= False
bert.encoder.layer.7.attention.self.value.bias requires_grad= False
bert.encoder.layer.7.attention.output.dense.weight requires_grad= False
bert.encoder.layer.7.attention.output.dense.bias requires_grad= False
bert.encoder.layer.7.attention.output.LayerNorm.weight requires_grad= False
bert.encoder.layer.7.attention.output.LayerNorm.bias requires_grad= False
bert.encoder.layer.7.intermediate.dense.weight requires_grad= False
bert.encoder.layer.7.intermediate.dense.bias requires_grad= False
bert.encoder.layer.7.output.dense.weight requires_grad= False
bert.encoder.layer.7.output.dense.bias requires_grad= False
bert.encoder.layer.7.output.LayerNorm.weight requires_grad= False
bert.encoder.layer.7.output.LayerNorm.bias requires_grad= False
bert.encoder.layer.8.attention.self.query.weight requires_grad= True
bert.encoder.layer.8.attention.self.query.bias requires_grad= True
bert.encoder.layer.8.attention.self.key.weight requires_grad= True
bert.encoder.layer.8.attention.self.key.bias requires_grad= True
bert.encoder.layer.8.attention.self.value.weight requires_grad= True
bert.encoder.layer.8.attention.self.value.bias requires_grad= True
bert.encoder.layer.8.attention.output.dense.weight requires_grad= True
bert.encoder.layer.8.attention.output.dense.bias requires_grad= True
bert.encoder.layer.8.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.8.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.8.intermediate.dense.weight requires_grad= True
bert.encoder.layer.8.intermediate.dense.bias requires_grad= True
bert.encoder.layer.8.output.dense.weight requires_grad= True
bert.encoder.layer.8.output.dense.bias requires_grad= True
bert.encoder.layer.8.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.8.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.9.attention.self.query.weight requires_grad= True
bert.encoder.layer.9.attention.self.query.bias requires_grad= True
bert.encoder.layer.9.attention.self.key.weight requires_grad= True
bert.encoder.layer.9.attention.self.key.bias requires_grad= True
bert.encoder.layer.9.attention.self.value.weight requires_grad= True
bert.encoder.layer.9.attention.self.value.bias requires_grad= True
bert.encoder.layer.9.attention.output.dense.weight requires_grad= True
bert.encoder.layer.9.attention.output.dense.bias requires_grad= True

```

bert.encoder.layer.9.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.9.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.9.intermediate.dense.weight requires_grad= True
bert.encoder.layer.9.intermediate.dense.bias requires_grad= True
bert.encoder.layer.9.output.dense.weight requires_grad= True
bert.encoder.layer.9.output.dense.bias requires_grad= True
bert.encoder.layer.9.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.9.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.10.attention.self.query.weight requires_grad= True
bert.encoder.layer.10.attention.self.query.bias requires_grad= True
bert.encoder.layer.10.attention.self.key.weight requires_grad= True
bert.encoder.layer.10.attention.self.key.bias requires_grad= True
bert.encoder.layer.10.attention.self.value.weight requires_grad= True
bert.encoder.layer.10.attention.self.value.bias requires_grad= True
bert.encoder.layer.10.attention.output.dense.weight requires_grad= True
bert.encoder.layer.10.attention.output.dense.bias requires_grad= True
bert.encoder.layer.10.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.10.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.10.intermediate.dense.weight requires_grad= True
bert.encoder.layer.10.intermediate.dense.bias requires_grad= True
bert.encoder.layer.10.output.dense.weight requires_grad= True
bert.encoder.layer.10.output.dense.bias requires_grad= True
bert.encoder.layer.10.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.10.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.11.attention.self.query.weight requires_grad= True
bert.encoder.layer.11.attention.self.query.bias requires_grad= True
bert.encoder.layer.11.attention.self.key.weight requires_grad= True
bert.encoder.layer.11.attention.self.key.bias requires_grad= True
bert.encoder.layer.11.attention.self.value.weight requires_grad= True
bert.encoder.layer.11.attention.self.value.bias requires_grad= True
bert.encoder.layer.11.attention.output.dense.weight requires_grad= True
bert.encoder.layer.11.attention.output.dense.bias requires_grad= True
bert.encoder.layer.11.attention.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.11.attention.output.LayerNorm.bias requires_grad= True
bert.encoder.layer.11.intermediate.dense.weight requires_grad= True
bert.encoder.layer.11.intermediate.dense.bias requires_grad= True
bert.encoder.layer.11.output.dense.weight requires_grad= True
bert.encoder.layer.11.output.dense.bias requires_grad= True
bert.encoder.layer.11.output.LayerNorm.weight requires_grad= True
bert.encoder.layer.11.output.LayerNorm.bias requires_grad= True
bert.pooler.dense.weight requires_grad= True
bert.pooler.dense.bias requires_grad= True
classifier.weight requires_grad= True
classifier.bias requires_grad= True

```

Layers that are 'True' are trainable. 'False' are frozen.

=====

bert-base-cased :

```

=====
=====
BertConfig {
  "_attn_implementation_autoset": true,
  "architectures": [
    "BertForMaskedLM"
  ],
  "attention_probs_dropout_prob": 0.1,
  "classifier_dropout": null,
  "gradient_checkpointing": false,
  "hidden_act": "gelu",
  "hidden_dropout_prob": 0.1,
  "hidden_size": 768,
  "initializer_range": 0.02,
  "intermediate_size": 3072,
  "layer_norm_eps": 1e-12,
  "max_position_embeddings": 512,
  "model_type": "bert",
  "num_attention_heads": 12,
  "num_hidden_layers": 12,
  "pad_token_id": 0,
  "position_embedding_type": "absolute",
  "torch_dtype": "float32",
  "transformers_version": "4.50.3",
  "type_vocab_size": 2,
  "use_cache": true,
  "vocab_size": 28996
}

```

```

=====
num_parameters: 108311810
=====
num_trainable_parameters: 58696706

```

```

[33]: print("Experiment configuration used with this experiment:")
      print("model used:", named_model)
      print("learning rate used:", learning_rate)
      print("number of epochs:", num_epochs)
      print("maximum sequence length:", length_max)
      print("batch size used:", size_batch)
      print("regularization value:", regularization_weight_decay)
      print("outcome variable:", y_col)
      print("task:", x_task)
      print("input column:", x_col)

```

```

Experiment configuration used with this experiment:
model used: bert-base-cased
learning rate used: 1e-05

```

```

number of epochs: 25
maximum sequence length: 256
batch size used: 16
regularization value: 0.1
outcome variable: binary_complexity
task: multi
input column: sentence_no_contractions

```

```

[34]: def validate_dataframe(df, df_name):
    """
    Performs basic functional tests on a pandas DataFrame
    to ensure it matches expected structure and content.
    """
    print(f"\n[VALIDATION] Checking {df_name}...")

    # 1) Check shape
    print(f" - Shape: {df.shape}")

    # 2) Check columns
    print(f" - Columns: {list(df.columns)}")

    # 3) Check label distribution (assuming 'binary_complexity' is the label)
    if "binary_complexity" in df.columns:
        label_counts = df["binary_complexity"].value_counts(dropna=False)
        print(f" - Label distribution:\n{label_counts}")
    else:
        print(" - WARNING: 'binary_complexity' column not found!")

    # 4) Peek at top few rows
    print(" - Sample rows:\n", df.head(3))

    validate_dataframe(train_multi_df, "train_multi_df")
    validate_dataframe(trial_val_multi_df, "trial_val_multi_df")
    validate_dataframe(test_multi_df, "test_multi_df")

```

```

[VALIDATION] Checking train_multi_df...
 - Shape: (1517, 12)
 - Columns: ['id', 'corpus', 'sentence', 'token', 'complexity',
'sentence_no_contractions', 'contraction_expanded', 'pos_sequence',
'dep_sequence', 'morph_sequence', 'morph_complexity', 'binary_complexity']
 - Label distribution:
binary_complexity
0    759
1    758
Name: count, dtype: int64
 - Sample rows:

```

id	corpus	\
0	759	
1	758	

```

0 3S37Y8CWI80N8KVM53U4E6JKCDC4WE bible
1 3WGCNLZJKF877FYC1Q6COKNWTWD11 bible
2 3UOMW19E6D6WQ5TH2HDD74IVKTP5CB bible

```

```

                                sentence          token \
0 but the seventh day is a Sabbath to Yahweh you... seventh day
1 But let each man test his own work, and then h... own work
2 To him who by understanding made the heavens; ... loving kindness

```

```

complexity          sentence_no_contractions \
0 0.027778 but the seventh day is a Sabbath to Yahweh you...
1 0.050000 But let each man test his own work, and then h...
2 0.050000 To him who by understanding made the heavens; ...

```

```

contraction_expanded          pos_sequence \
0 False ['CCONJ', 'DET', 'ADJ', 'NOUN', 'AUX', 'DET', ...
1 False ['CCONJ', 'VERB', 'DET', 'NOUN', 'VERB', 'PRON...
2 False ['ADP', 'PRON', 'PRON', 'ADP', 'VERB', 'VERB',...

```

```

                                dep_sequence \
0 ['cc', 'det', 'amod', 'nsubj', 'ccomp', 'det',...
1 ['cc', 'ROOT', 'det', 'nsubj', 'ccomp', 'poss'...
2 ['prep', 'pobj', 'nsubj', 'prep', 'pcomp', 'ad...

```

```

                                morph_sequence morph_complexity \
0 [ConjType=Cmp, Definite=Def|PronType=Art, Degr... 1.341772
1 [ConjType=Cmp, VerbForm=Inf, , Number=Sing, Ve... 1.608696
2 [, Case=Acc|Gender=Masc|Number=Sing|Person=3|P... 1.562500

```

```

binary_complexity
0 0
1 0
2 0

```

[VALIDATION] Checking trial_val_multi_df...

- Shape: (99, 12)

- Columns: ['id', 'corpus', 'sentence', 'token', 'complexity',
'sentence_no_contractions', 'contraction_expanded', 'pos_sequence',
'dep_sequence', 'morph_sequence', 'morph_complexity', 'binary_complexity']

- Label distribution:

binary_complexity

```

1 51
0 48

```

Name: count, dtype: int64

- Sample rows:

```

                                id corpus \
0 31HLTCK4BLVQ5B01AUR91TX9V9IVGH bible
1 389A2A3040IXVY7G5B71Q9M43LE0CL bible

```


2 31N9JPQXIPIRX2A3S9NOCCFX06TNHR bible

	sentence	token \
0	The name of one son was Gershom, for Moses sai...	foreign land
1	unleavened bread, unleavened cakes mixed with ...	wheat flour
2	However the high places were not taken away; t...	burnt incense

	complexity	sentence_no_contractions \
0	0.000000	The name of one son was Gershom, for Moses sai...
1	0.157895	unleavened bread, unleavened cakes mixed with ...
2	0.200000	However the high places were not taken away; t...

	contraction_expanded	pos_sequence \
0	False	['DET', 'NOUN', 'ADP', 'NUM', 'NOUN', 'AUX', '...
1	False	['ADJ', 'NOUN', 'PUNCT', 'ADJ', 'NOUN', 'VERB'...
2	False	['ADV', 'DET', 'ADJ', 'NOUN', 'AUX', 'PART', '...

	dep_sequence \
0	['det', 'nsubj', 'prep', 'nummod', 'pobj', 'RO...
1	['amod', 'dep', 'punct', 'amod', 'appos', 'acl...
2	['advmod', 'det', 'amod', 'nsubjpass', 'auxpas...

	morph_sequence	morph_complexity \
0	[Definite=Def PronType=Art, Number=Sing, , Num...	1.520000
1	[Degree=Pos, Number=Sing, PunctType=Comm, Degr...	1.200000
2	[, Definite=Def PronType=Art, Degree=Pos, Numb...	1.190476

	binary_complexity
0	0
1	0
2	0

[VALIDATION] Checking test_multi_df...

- Shape: (184, 12)
- Columns: ['id', 'corpus', 'sentence', 'token', 'complexity', 'sentence_no_contractions', 'contraction_expanded', 'pos_sequence', 'dep_sequence', 'morph_sequence', 'morph_complexity', 'binary_complexity']
- Label distribution:

binary_complexity

1 99
0 85

Name: count, dtype: int64

- Sample rows:

	id	corpus \
0	3UXQ63NLAAMRIP4WG4XPD98A0YOBLX	bible
1	3FJ2RVH25Z62TA3R8E1077EBUYU92W	bible
2	3Y04AH2FPDK1PZHZA78WAE7L70EQ0F	bible

```

                                sentence          token \
0  for he had an only daughter, about twelve year...  only daughter
1  All these were cities fortified with high wall...   high walls
2  In the morning, 'It will be foul weather today...  weather today

complexity                                sentence_no_contractions \
0      0.025  for he had an only daughter, about twelve year...
1      0.100  All these were cities fortified with high wall...
2      0.125  In the morning, 'It will be foul weather today...

contraction_expanded                                pos_sequence \
0      False  ['SCONJ', 'PRON', 'VERB', 'DET', 'ADJ', 'NOUN'...
1      False  ['DET', 'PRON', 'AUX', 'NOUN', 'VERB', 'ADP', ...
2      False  ['ADP', 'DET', 'NOUN', 'PUNCT', 'PUNCT', 'PRON...

                                dep_sequence \
0  ['mark', 'nsubj', 'ROOT', 'det', 'amod', 'dobj...
1  ['predet', 'nsubj', 'ROOT', 'attr', 'acl', 'pr...
2  ['prep', 'det', 'pobj', 'punct', 'punct', 'nsu...

                                morph_sequence  morph_complexity \
0  [, Case=Nom|Gender=Masc|Number=Sing|Person=3|P...      1.722222
1  [, Number=Plur|PronType=Dem, Mood=Ind|Tense=Pa...      1.136364
2  [, Definite=Def|PronType=Art, Number=Sing, Pun...      1.476190

binary_complexity
0      0
1      0
2      0

```

[35]: *# Train & Evaluate*

```

trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,
    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay
)

metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)

```

```
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)
```

```
/usr/local/lib/python3.11/dist-packages/transformers/training_args.py:1611:
FutureWarning: `evaluation_strategy` is deprecated and will be removed in
version 4.46 of Transformers. Use `eval_strategy` instead
  warnings.warn(
<ipython-input-20-c2ee9f934517>:31: FutureWarning: `tokenizer` is deprecated and
will be removed in version 5.0.0 for `Trainer.__init__`. Use `processing_class`
instead.
  trainer = Trainer(
<IPython.core.display.HTML object>
<IPython.core.display.HTML object>
Validation metrics: {'eval_loss': 1.7527879476547241, 'eval_accuracy':
0.6152019002375297, 'eval_precision': 0.5773195876288659, 'eval_recall':
0.5833333333333334, 'eval_f1': 0.5803108808290155, 'eval_runtime': 2.4004,
'eval_samples_per_second': 175.389, 'eval_steps_per_second': 11.248, 'epoch':
25.0}
Test metrics: {'eval_loss': 1.9492871761322021, 'eval_accuracy':
0.5561613958560524, 'eval_precision': 0.5425, 'eval_recall':
0.49206349206349204, 'eval_f1': 0.5160523186682521, 'eval_runtime': 4.1347,
'eval_samples_per_second': 221.781, 'eval_steps_per_second': 14.028, 'epoch':
25.0}
```

```
[36]: # save model checkpoint

timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    ↪f"{x_task}_{named_model}_{y_col}_{timestamp}")

trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")
```

```
Model checkpoint saved to: /content/drive/MyDrive/266-final/models/multi_bert-
base-cased_binary_complexity_20250410_034203
```

```
[37]: experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze
```

```

}

model_info = gather_model_details(trained_model)

all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf
)

log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath
)

print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

<IPython.core.display.HTML object>

EXPERIMENT LOGGED TO:
/content/drive/MyDrive/266-final/results/experiment_runs.txt

0.2.5 3.1.3 from pretrained bert-base-cased Y: single task 1 & X: pos_sequence —

```

[38]: # Define Experiment Parameters
named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert
#####
regularization_weight_decay = 0.1
learning_rate = 1e-5
size_batch = 16
length_max = 256
num_epochs = 25
#####
# x_col = "sentence"
# x_col = "sentence_no_contractions"
x_col = "pos_sequence"
# x_col = "dep_sequence"
# x_col = "morph_sequence"
#####
y_col = "binary_complexity"
# y_col = "complexity"

```

```

#####
x_task = "single"
# x_task = "multi"
if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df
#####
# Tokenize & Prepare Datasets
train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])
#####
custom_config = BertConfig.from_pretrained("bert-base-cased")
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
custom_config.attention_probs_dropout_prob = 0.1
custom_config.hidden_dropout_prob = 0.1
custom_config.gradient_checkpointing = False
#####
model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config)
#####
# model, tokenizer = get_model_and_tokenizer(

```

```

#     remote_model_name=None
#     local_model_path="...CONFIGURE_PATH...",
#     config=custom_config)
print("=====")
print(named_model, ":")
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters at load:", model.
    ↪ num_parameters(only_trainable=True))
print("=====")
print("model lineage:", MODEL_LINEAGE)
print("=====")
#####
layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier.",
]
freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
print("=====")
#####
print("Experiment configuration used with this experiment:")
print("model used:", named_model)
print("learning rate used:", learning_rate)
print("number of epochs:", num_epochs)
print("maximum sequence length:", length_max)
print("batch size used:", size_batch)
print("regularization value:", regularization_weight_decay)
print("outcome variable:", y_col)
print("task:", x_task)
print("input column:", x_col)

```

Map: 0%| | 0/7662 [00:00<?, ? examples/s]

Map: 0%| | 0/421 [00:00<?, ? examples/s]

Map: 0%| | 0/917 [00:00<?, ? examples/s]

Datasets prepared. Sample from train_data_hf:


```

num_parameters: 108311810
num_trainable_parameters at load: 108311810
=====
model lineage: {'type': 'huggingface_hub', 'path': 'bert-base-cased',
'timestamp': '2025-04-10 03:42:41'}
=====
BertConfig {
  "_attn_implementation_autoset": true,
  "architectures": [
    "BertForMaskedLM"
  ],
  "attention_probs_dropout_prob": 0.1,
  "classifier_dropout": null,
  "gradient_checkpointing": false,
  "hidden_act": "gelu",
  "hidden_dropout_prob": 0.1,
  "hidden_size": 768,
  "initializer_range": 0.02,
  "intermediate_size": 3072,
  "layer_norm_eps": 1e-12,
  "max_position_embeddings": 512,
  "model_type": "bert",
  "num_attention_heads": 12,
  "num_hidden_layers": 12,
  "pad_token_id": 0,
  "position_embedding_type": "absolute",
  "torch_dtype": "float32",
  "transformers_version": "4.50.3",
  "type_vocab_size": 2,
  "use_cache": true,
  "vocab_size": 28996
}

=====
num_parameters: 108311810
num_trainable_parameters: 58696706
=====
Experiment configuration used with this experiment:
model used: bert-base-cased
learning rate used: 1e-05
number of epochs: 25
maximum sequence length: 256
batch size used: 16
regularization value: 0.1
outcome variable: binary_complexity
task: single
input column: pos_sequence

```



```
[ ]: # Train & Evaluate
trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,
    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay)
metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)
```

/usr/local/lib/python3.11/dist-packages/transformers/training_args.py:1611:
FutureWarning: `evaluation_strategy` is deprecated and will be removed in
version 4.46 of Transformers. Use `eval_strategy` instead

```
warnings.warn(
<ipython-input-20-c2ee9f934517>:31: FutureWarning: `tokenizer` is deprecated and  

will be removed in version 5.0.0 for `Trainer.__init__`. Use `processing_class`  

instead.
    trainer = Trainer(

<IPython.core.display.HTML object>
```

/usr/local/lib/python3.11/dist-packages/sklearn/metrics/_classification.py:1565:
UndefinedMetricWarning: Precision is ill-defined and being set to 0.0 due to no
predicted samples. Use `zero_division` parameter to control this behavior.

```
_warn_prf(average, modifier, f"{metric.capitalize()} is", len(result))
```

```
[ ]: # save model checkpoint
timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    f"{x_task}_{named_model}_{y_col}_{timestamp}")
trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")
# log experiment results
experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
```

```

        "layers_to_unfreeze": layers_to_unfreeze}
model_info = gather_model_details(trained_model)
all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf)
log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath)
print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

0.2.6 3.1.4 from pretrained bert-base-cased Y: multi task 2 & X: pos_sequence —

```

[ ]: # Define Experiment Parameters
named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert
#####
regularization_weight_decay = 0.1
learning_rate = 1e-5
size_batch = 16
length_max = 256
num_epochs = 25
#####
# x_col = "sentence"
# x_col = "sentence_no_contractions"
x_col = "pos_sequence"
# x_col = "dep_sequence"
# x_col = "morph_sequence"
#####
y_col = "binary_complexity"
# y_col = "complexity"
#####
# x_task = "single"
x_task = "multi"
if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df

```

```

    df_test = test_multi_df
#####
# Tokenize & Prepare Datasets
train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])
#####
custom_config = BertConfig.from_pretrained("bert-base-cased")
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
custom_config.attention_probs_dropout_prob = 0.1
custom_config.hidden_dropout_prob = 0.1
custom_config.gradient_checkpointing = False
#####
model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config)
#####
# model, tokenizer = get_model_and_tokenizer(
#     remote_model_name=None
#     local_model_path="...CONFIGURE_PATH...",
#     config=custom_config)
print("=====")
print(named_model, ":")
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters at load:", model.
    ↪ num_parameters(only_trainable=True))
print("=====")

```

```

print("model lineage:", MODEL_LINEAGE)
print("=====")
#####
layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier.",
]
freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
print("=====")
#####
print("Experiment configuration used with this experiment:")
print("model used:", named_model)
print("learning rate used:", learning_rate)
print("number of epochs:", num_epochs)
print("maximum sequence length:", length_max)
print("batch size used:", size_batch)
print("regularization value:", regularization_weight_decay)
print("outcome variable:", y_col)
print("task:", x_task)
print("input column:", x_col)

```

```

[ ]: # #QA

# def validate_dataframe(df, df_name):
#     """
#     Performs basic functional tests on a pandas DataFrame
#     to ensure it matches expected structure and content.
#     """
#     print(f"\n[VALIDATION] Checking {df_name}...")

#     # 1) Check shape
#     print(f" - Shape: {df.shape}")

#     # 2) Check columns
#     print(f" - Columns: {list(df.columns)}")

```

```

# # 3) Check label distribution (assuming 'binary_complexity' is the label)
# if "binary_complexity" in df.columns:
#     label_counts = df["binary_complexity"].value_counts(dropna=False)
#     print(f" - Label distribution:\n{label_counts}")
# else:
#     print(" - WARNING: 'binary_complexity' column not found!")

# # 4) Peek at top few rows
# print(" - Sample rows:\n", df.head(3))

# # Example usage for multi data:
# validate_dataframe(train_multi_df, "train_multi_df")
# validate_dataframe(trial_val_multi_df, "trial_val_multi_df")
# validate_dataframe(test_multi_df, "test_multi_df")

```

```

[ ]: def check_dataframe_invariants(df, df_name, expected_shape, expected_columns):
    """
    Ensures that df has the exact shape and columns expected.
    Raises AssertionError if not.
    """
    print(f"\n[CHECK] {df_name}")

    actual_shape = df.shape
    actual_columns = set(df.columns)

    # 1) Check shape
    assert actual_shape == expected_shape, (
        f"[ERROR] {df_name} shape mismatch. "
        f"Expected {expected_shape}, got {actual_shape}."
    )

    # 2) Check columns
    assert actual_columns == set(expected_columns), (
        f"[ERROR] {df_name} columns mismatch. "
        f"Expected {set(expected_columns)}, got {actual_columns}."
    )

    print(" - PASS: shape and columns match expectations")

    # Suppose the actual columns are exactly:
    my_expected_cols = [
        "id", "sentence", "sentence_no_contractions", "token",
        "contraction_expanded", "pos_sequence", "morph_sequence",
        "dep_sequence", "morph_complexity", "complexity",
        "binary_complexity", "corpus"
    ]

```

```

check_dataframe_invariants(
    train_multi_df,
    "train_multi_df",
    expected_shape=(1517, 12), # example only
    expected_columns=my_expected_cols
)

```

```

[ ]: # Train & Evaluate
trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,
    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay)
metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)

```

```

[ ]: # save model checkpoint
timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    f"{x_task}_{named_model}_{y_col}_{timestamp}")
trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")
# log experiment results
experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze}
model_info = gather_model_details(trained_model)
all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf)

```

```

log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath)
print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

0.2.7 3.1.5 from pretrained bert-base-cased Y: single task 1 & X: morph_sequence

```

[ ]: # Define Experiment Parameters
named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert
#####
regularization_weight_decay = 0.1
learning_rate = 1e-5
size_batch = 16
length_max = 256
num_epochs = 25
#####
# x_col = "sentence"
# x_col = "sentence_no_contractions"
# x_col = "pos_sequence"
# x_col = "dep_sequence"
x_col = "morph_sequence"
#####
y_col = "binary_complexity"
# y_col = "complexity"
#####
x_task = "single"
# x_task = "multi"
if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df
#####
# Tokenize & Prepare Datasets
train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,

```

```

        label_col=y_col,
        max_length=length_max)
val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])
#####
custom_config = BertConfig.from_pretrained("bert-base-cased")
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
custom_config.attention_probs_dropout_prob = 0.1
custom_config.hidden_dropout_prob = 0.1
custom_config.gradient_checkpointing = False
#####
model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config)
#####
# model, tokenizer = get_model_and_tokenizer(
#     remote_model_name=None
#     local_model_path="...CONFIGURE_PATH...",
#     config=custom_config)
print("=====")
print(named_model, ":")
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters at load:", model.
    ↪num_parameters(only_trainable=True))
print("=====")
print("model lineage:", MODEL_LINEAGE)
print("=====")
#####
layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",

```



```

        "bert.encoder.layer.8.",
        "bert.encoder.layer.9.",
        "bert.encoder.layer.10.",
        "bert.encoder.layer.11.",
        "bert.pooler.",
        "classifier.",
    ]
    freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)
    print(model.config)
    print("=====")
    print("num_parameters:", model.num_parameters())
    print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
    print("=====")
    #####
    print("Experiment configuration used with this experiment:")
    print("model used:", named_model)
    print("learning rate used:", learning_rate)
    print("number of epochs:", num_epochs)
    print("maximum sequence length:", length_max)
    print("batch size used:", size_batch)
    print("regularization value:", regularization_weight_decay)
    print("outcome variable:", y_col)
    print("task:", x_task)
    print("input column:", x_col)

```

```

[ ]: # Train & Evaluate
trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,
    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay)
metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)

```

```

[ ]: # save model checkpoint
timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    ↪ f"{x_task}_{named_model}_{y_col}_{timestamp}")
trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")

```

```

# log experiment results
experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze}
model_info = gather_model_details(trained_model)
all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf)
log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath)
print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

0.2.8 3.1.6 from pretrained bert-base-cased Y: multi task 2 & X: morph_sequence

```

[ ]: # Define Experiment Parameters
named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert
#####
regularization_weight_decay = 0.1
learning_rate = 1e-5
size_batch = 16
length_max = 256
num_epochs = 25
#####
# x_col = "sentence"
# x_col = "sentence_no_contractions"
# x_col = "pos_sequence"
# x_col = "dep_sequence"
x_col = "morph_sequence"
#####
y_col = "binary_complexity"
# y_col = "complexity"

```

```

#####
# x_task = "single"
x_task = "multi"
if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df
#####
# Tokenize & Prepare Datasets
train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])
#####
custom_config = BertConfig.from_pretrained("bert-base-cased")
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
custom_config.attention_probs_dropout_prob = 0.1
custom_config.hidden_dropout_prob = 0.1
custom_config.gradient_checkpointing = False
#####
model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config)
#####
# model, tokenizer = get_model_and_tokenizer(

```

```

#     remote_model_name=None
#     local_model_path="...CONFIGURE_PATH...",
#     config=custom_config)
print("=====")
print(named_model, ":")
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters at load:", model.
    ↪ num_parameters(only_trainable=True))
print("=====")
print("model lineage:", MODEL_LINEAGE)
print("=====")
#####
layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier.",
]
freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
print("=====")
#####
print("Experiment configuration used with this experiment:")
print("model used:", named_model)
print("learning rate used:", learning_rate)
print("number of epochs:", num_epochs)
print("maximum sequence length:", length_max)
print("batch size used:", size_batch)
print("regularization value:", regularization_weight_decay)
print("outcome variable:", y_col)
print("task:", x_task)
print("input column:", x_col)

```

```

[ ]: # Train & Evaluate
trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,

```

```

    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay)
metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)

```

```

[ ]: # save model checkpoint
timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    ↪f"{x_task}_{named_model}_{y_col}_{timestamp}")
trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")
# log experiment results
experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze}
model_info = gather_model_details(trained_model)
all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf)
log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath)
print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

0.2.9 3.1.0.1 from pretrained bert-base-cased Y: single task 1 & X: sentence —

```

[ ]: # Define Experiment Parameters
named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"

```

```

# named_model = "roberta-large"
# named_model = "" # modern bert
#####
regularization_weight_decay = 0.1
learning_rate = 1e-5
size_batch = 16
length_max = 256
num_epochs = 25
#####
x_col = "sentence"
# x_col = "sentence_no_contractions"
# x_col = "pos_sequence"
# x_col = "dep_sequence"
# x_col = "morph_sequence"
#####
y_col = "binary_complexity"
# y_col = "complexity"
#####
x_task = "single"
# x_task = "multi"
if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df
#####
# Tokenize & Prepare Datasets
train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,

```

```

        max_length=length_max)
print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])
#####
custom_config = BertConfig.from_pretrained("bert-base-cased")
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
custom_config.attention_probs_dropout_prob = 0.1
custom_config.hidden_dropout_prob = 0.1
custom_config.gradient_checkpointing = False
#####
model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config)
#####
# model, tokenizer = get_model_and_tokenizer(
#     remote_model_name=None
#     local_model_path="...CONFIGURE_PATH...",
#     config=custom_config)
print("=====")
print(named_model, ":")
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters at load:", model.
    ↪ num_parameters(only_trainable=True))
print("=====")
print("model lineage:", MODEL_LINEAGE)
print("=====")
#####
layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier."
]
freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
print("=====")

```

```
#####
print("Experiment configuration used with this experiment:")
print("model used:", named_model)
print("learning rate used:", learning_rate)
print("number of epochs:", num_epochs)
print("maximum sequence length:", length_max)
print("batch size used:", size_batch)
print("regularization value:", regularization_weight_decay)
print("outcome variable:", y_col)
print("task:", x_task)
print("input column:", x_col)
```

```
[ ]: # Train & Evaluate
trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,
    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay)
metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)
```

```
[ ]: # save model checkpoint
timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")
model_save_path = os.path.join(dir_models,
    f"{x_task}_{named_model}_{y_col}_{timestamp}")
trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")
# log experiment results
experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze}
model_info = gather_model_details(trained_model)
all_run_metrics = gather_all_run_metrics(
```



```

        trainer=trainer_obj,
        train_dataset=train_data_hf,
        val_dataset=val_data_hf,
        test_dataset=test_data_hf)
log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath)
print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

0.2.10 3.1.0.2 from pretrained bert-base-cased Y: multi task 2 & X: sentence —

```

[ ]: # Define Experiment Parameters
named_model = "bert-base-cased"
# named_model = "roberta-base"
# named_model = "bert-large"
# named_model = "roberta-large"
# named_model = "" # modern bert
#####
regularization_weight_decay = 0.1
learning_rate = 1e-5
size_batch = 16
length_max = 256
num_epochs = 25
#####
x_col = "sentence"
# x_col = "sentence_no_contractions"
# x_col = "pos_sequence"
# x_col = "dep_sequence"
# x_col = "morph_sequence"
#####
y_col = "binary_complexity"
# y_col = "complexity"
#####
# x_task = "single"
x_task = "multi"
if x_task == "single":
    df_train = train_single_df
    df_val = trial_val_single_df
    df_test = test_single_df
else:
    df_train = train_multi_df
    df_val = trial_val_multi_df
    df_test = test_multi_df
#####
# Tokenize & Prepare Datasets

```

```

train_data_hf = prepare_dataset(
    df_train,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
val_data_hf = prepare_dataset(
    df_val,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
test_data_hf = prepare_dataset(
    df_test,
    tokenizer,
    text_col=x_col,
    label_col=y_col,
    max_length=length_max)
print("Datasets prepared. Sample from train_data_hf:\n", train_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", val_data_hf[10])
# print("Datasets prepared. Sample from train_data_hf:\n", test_data_hf[10])
#####
custom_config = BertConfig.from_pretrained("bert-base-cased")
custom_config.hidden_act = "gelu" # alts: "relu" "silu"
custom_config.attention_probs_dropout_prob = 0.1
custom_config.hidden_dropout_prob = 0.1
custom_config.gradient_checkpointing = False
#####
model, tokenizer = get_model_and_tokenizer(
    remote_model_name="bert-base-cased",
    local_model_path=None,
    config=custom_config)
#####
# model, tokenizer = get_model_and_tokenizer(
#     remote_model_name=None
#     local_model_path="...CONFIGURE_PATH...",
#     config=custom_config)
print("=====")
print(named_model, ":")
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters at load:", model.
    ↪num_parameters(only_trainable=True))
print("=====")
print("model lineage:", MODEL_LINEAGE)
print("=====")
#####

```

```

layers_to_unfreeze = [
    "bert.embeddings.",
    "bert.encoder.layer.0.",
    # "bert.encoder.layer.1.",
    "bert.encoder.layer.8.",
    "bert.encoder.layer.9.",
    "bert.encoder.layer.10.",
    "bert.encoder.layer.11.",
    "bert.pooler.",
    "classifier."
]
freeze_unfreeze_layers(model, layers_to_unfreeze=layers_to_unfreeze)
print(model.config)
print("=====")
print("num_parameters:", model.num_parameters())
print("num_trainable_parameters:", model.num_parameters(only_trainable=True))
print("=====")
#####
print("Experiment configuration used with this experiment:")
print("model used:", named_model)
print("learning rate used:", learning_rate)
print("number of epochs:", num_epochs)
print("maximum sequence length:", length_max)
print("batch size used:", size_batch)
print("regularization value:", regularization_weight_decay)
print("outcome variable:", y_col)
print("task:", x_task)
print("input column:", x_col)

```

```

[ ]: # Train & Evaluate
trained_model, trainer_obj = train_transformer_model(
    model = model,
    tokenizer = tokenizer,
    train_dataset = train_data_hf,
    val_dataset = val_data_hf,
    output_dir = dir_results,
    num_epochs = num_epochs,
    batch_size = size_batch,
    lr = learning_rate,
    weight_decay = regularization_weight_decay)
metrics = trainer_obj.evaluate()
print("Validation metrics:", metrics)
test_metrics = trainer_obj.evaluate(test_data_hf) if test_data_hf else None
print("Test metrics:", test_metrics)

```

```

[ ]: # save model checkpoint
timestamp = datetime.now().strftime("%Y%m%d_%H%M%S")

```

```

model_save_path = os.path.join(dir_models,
    ↪f"{x_task}_{named_model}_{y_col}_{timestamp}")
trainer_obj.save_model(model_save_path)
print(f"Model checkpoint saved to: {model_save_path}")
# log experiment results
experiment_info = {
    "model_name": named_model,
    "learning_rate": learning_rate,
    "epochs": num_epochs,
    "batch_size": size_batch,
    "weight_decay": regularization_weight_decay,
    "x_task": x_task,
    "x_col": x_col,
    "y_col": y_col,
    "layers_to_unfreeze": layers_to_unfreeze}
model_info = gather_model_details(trained_model)
all_run_metrics = gather_all_run_metrics(
    trainer=trainer_obj,
    train_dataset=train_data_hf,
    val_dataset=val_data_hf,
    test_dataset=test_data_hf)
log_experiment_results_json(
    experiment_meta=experiment_info,
    model_details=model_info,
    run_metrics=all_run_metrics,
    log_file=log_filepath)
print(f"EXPERIMENT LOGGED TO: {log_filepath}")

```

0.2.11 3.1.7 from pretrained roberta-base Y: single task 1 & X: sentence —

[]:

[]:

[]:

0.2.12 3.1.8 from pretrained roberta-base Y: multi task 2 & X: sentence —

[]:

[]:

[]:

0.2.13 3.1.9 from pretrained roberta-base Y: single task 1 & X: sentence_no_contractions —

[]:

[]:

[]:

0.2.14 3.1.10 from pretrained roberta-base Y: multi task 2 & X: sentence_no_contractions —

[]:

[]:

[]: