

Rajalakshmi Engineering College

Name: Jhanani shree
Email: 240701215@rajalakshmi.edu.in
Roll no: 240701215
Phone: 7373333511
Branch: REC
Department: I CSE AH
Batch: 2028
Degree: B.E - CSE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 5_COD_Question 1

Attempt : 1
Total Mark : 10
Marks Obtained : 0

Section 1 : Coding

1. Problem Statement

John is learning about Binary Search Trees (BST) in his computer science class. He wants to create a program that allows users to delete a node with a given value from a BST and print the remaining nodes using an in-order traversal.

Implement a function to help him delete a node with a given value from a BST.

Input Format

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the BST nodes.

The third line consists of an integer V, which is the value to delete from the BST.

Output Format

The output prints the space-separated values in the BST in an in-order traversal, after the deletion of the specified value.

If the specified value is not available in the tree, print the given input values in-order traversal.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5
10 5 15 2 7
15

Output: 2 5 7 10

Answer

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
#include <stdio.h>
#include <stdlib.h>
```

// Define the structure for a tree node

```
struct TreeNode {  
    int val;  
    struct TreeNode* left;  
    struct TreeNode* right;  
};
```

// Function to insert a key into the BST

```
struct TreeNode* insert(struct TreeNode* root, int key) {  
    if (root == NULL) {  
        struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct  
TreeNode));  
        newNode->val = key;  
        newNode->left = NULL;  
        newNode->right = NULL;  
        return newNode;  
    }  
    if (key < root->val) {  
        root->left = insert(root->left, key);  
    } else {  
        root->right = insert(root->right, key);  
    }  
    return root;  
}
```

// Function to find the minimum value node in the BST

```
struct TreeNode* findMin(struct TreeNode* root) {  
    while (root->left != NULL) {  
        root = root->left;  
    }  
    return root;  
}
```

struct TreeNode* deleteNode(struct TreeNode* root, int key) {

```
    if (root == NULL) {  
        return root; // Key not found  
    }  
    if (key < root->val) {  
        root->left = deleteNode(root->left, key);  
    } else if (key > root->val) {  
        root->right = deleteNode(root->right, key);  
    }
```

```

    } else {
        // Node with only one child or no child
        if (root->left == NULL) {
            struct TreeNode* temp = root->right;
            free(root);
            return temp;
        } else if (root->right == NULL) {
            struct TreeNode* temp = root->left;
            free(root);
            return temp;
        }

        struct TreeNode* temp = findMin(root->right);
        root->val = temp->val; // Copy the inorder successor's value
        root->right = deleteNode(root->right, temp->val); // Delete the inorder
        successor
    }
    return root;
}

```

```

void inorderTraversal(struct TreeNode* root) {
    if (root != NULL) {
        inorderTraversal(root->left);
        printf("%d ", root->val);
        inorderTraversal(root->right);
    }
}

```

```

// Main function
int main() {
    int N, V;
    scanf("%d", &N);
    struct TreeNode* root = NULL;

    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        root = insert(root, key);
    }

    scanf("%d", &V);

```

```
// Delete the node and print the in-order traversal
root = deleteNode(root, V);
inorderTraversal(root);
printf("\n"); // Print a newline after the in-order traversal
return 0;
}
```

```
int main()
{
    int N, rootValue, V;
    scanf("%d", &N);
    struct TreeNode* root = NULL;
    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }
    scanf("%d", &V);
    root = deleteNode(root, V);
    inorderTraversal(root);
    return 0;
}
```

Status : Wrong

Marks : 0/10