

DH-IPC-HFW3101C

1.3Megapixel WDR HD Network IR-Bullet Network Camera



Features

- 1/3" 1.3Megapixel progressive scan Aptina CMOS
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1.3M(1280×960)&25/30fps@720P(1280×720)
- WDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 2.8~12mm varifocal lens
- Built-in 2/1 alarm in/out
- Max. IR LEDs length 20m
- Micro SD memory, IP66, PoE

DH-IPC-HFW3101C


Specifications

Model		DH-IPC-HFW3101CP		DH-IPC-HFW3101CN	
Camera					
Image Sensor		1/3" 1.3Megapixel Aptina CMOS			
Effective Pixels		1280(H)x960(V)			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual, 1/3~1/10000s		Auto/Manual, 1/4~1/10000s	
Min. Illumination		0. 1Lux/F1.2 (Color), 0.005Lux/F1.2(B/W);0Lux/F1.2(IR on)			
S/N Ratio		>50dB			
Video Output		1 channel BNC(1.0Vp-p, 75Ω)			
Camera Features					
Max. IR LEDs Length		20m			
Day/Night		Auto(ICR)/Color/B/W			
Backlight Compensation		BLC / HLC / WDR (128dB)			
White Balance		Auto			
Gain Control		Auto/Manual			
Noise Reduction		2D			
Privacy Masking		Up to 4 areas			
Lens					
Focal Length		2.8~12mm			
Max Aperture		F1.4			
Focus Control		Manual			
Angle of View		H: 92°(Wide)~ 27.2°(Tele)			
Lens Type		Manual / Auto Iris (DC)			
Mount Type		Board-in Type			
Video					
Compression		H.264 / MJPEG			
Resolution		1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)		1.3M(1280×960) / 720P(1280×720) / D1(704×480) / CIF(352×240)	
Frame Rate	Main Stream	1.3M/720P(1 ~ 25/30fps)			
	Sub Stream	D1/CIF(1 ~ 25/30fps)			
Bit Rate		H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps			
Audio					
Compression		G.711a / G.711u(64kbps) / PCM(128kbps)			
Interface		1/1 channel In/Out			
Network					
Ethernet		RJ-45 (10/100Base-T)			
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour			
ONVIF		ONVIF Ver. 2.0			

DH-IPC-HFW3101C

Max. User Access	10 users, password authentication(encrypted via HTTPS)
Smart Phone	iPhone, iPad, Android, Windows Phone
Auxiliary Interface	
Memory Slot	Micro SD, Max 32GB
Alarm	2/1 channel In/Out
General	
Power Supply	DC12V(AC24 optional), PoE(802.3af)
Power Consumption	<10W
Working Environment	-30°C~+60°C, 10%~90%
Ingress Protection	IP66, IK10
Dimensions	φ104mm × 306.7mm
Weight	1.25Kg

Dimensions (mm)



Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email:overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.