Transformer Language Models


CSCI 601-771 (NLP: Self-Supervised Models)

https://self-supervised.cs.jhu.edu/fa2026/

After Transformer ...




Topology variations




Encoder-Decoders

Encodes an input sequence and generates an output sequence autoregressively, with the decoder also attending to the encoder's representations.



Encoders

Builds contextual representations of input tokens by allowing each token to attend to all input positions.




Decoders

Generates tokens autoregressively, with each position attending only to itself and earlier positions.

The Evolution of Language Models

Selected milestones • 2017 – 2026

Updated October 2026



Branches group approaches, not checkpoint ancestry. Categories can overlap; proprietary architectures may be undisclosed.

Inspired by Yang et al. (2023).

Other architectural variations

- **Topology:** Decoder-only, Encoder-decoder, Encoder-only.
- **Sequence mixing in each layer:**
  - Example: MHA, MQA, GQA, etc.
  - Patterns: global, sliding-window, or interleaved local/global.
- **Positional encodings:** e.g., RoPE.
- **Feedforward layers:** Dense vs. MoE, Activations: GELU, SwiGLU, etc.
- **Normalization and block layout:** pre-norm vs. post-norm.
- **Dimensions:** Depth vs. width, head count and head dimension.
- **Tokenization:** Vocab size and algorithm (e.g., BPE), tokenizer-free models
- **Output scheme:** Next-token prediction, multi-token prediction, Diffusion LMs

Legend: Already covered them; will cover next; will hopefully cover at some point.

Normalization

Quiz: Pre-norm vs Post-norm


- Which is the original implementation?
- Which one gives gradients a direct identity path?

Post-norm

$$\text{LayerNorm}\big(x + \text{SubLayer}(x)\big)$$

Pre-norm

$$x + \text{SubLayer}\big(\text{LayerNorm}(x)\big)$$



Pre-norm vs Post-norm

- Pre-norm (right) is set up so that LayerNorm does not disrupt the residual stream (in gray)
- Both are valid architectures, but their optimization behavior differs.
- In practice, however, **Pre-norm is preferred over Post-norm**.





Figure 1. (a) Post-LN Transformer layer; (b) Pre-LN Transformer layer.

On Layer Normalization in the Transformer Architecture, 2020


Pre-norm vs Post-norm: Empirical Result

More balanced gradients: Post-norm has large gradients near the output at initialization; pre-norm keeps them more uniform across layers.




On Layer Normalization in the Transformer Architecture, 2020

Other forms of LayerNorm



Who uses what?



QK-norm also normalizes q and k tensors.

LayerNorm vs. RMSNorm

- Original transformer: **LayerNorm**
  - LayerNorm both centers activations and controls their scale.
  - What if we keep scale control **but skip centering**?

Stats computed across **each hidden dimensions**

$$\text{LayerNorm}(x) = \gamma \odot \frac{x - \mu(x)}{\sqrt{\text{Var}(x) + \epsilon}} + \beta.$$

- **RMSNorm:** Does not subtract mean or add a bias term

$$\text{RMSNorm}(x) = \gamma \odot \frac{x}{\sqrt{\frac{1}{d}\sum_i x_i^2 + \epsilon}}.$$

Pulse Check: Normalization (1)

- How many learnable parameters do each normalization have?

- **Q1:** LayerNorm:
- **A1:** 2d (weight γ and bias β)

$$\mathrm{LayerNorm}(x) = \gamma \odot \frac{x - \mu(x)}{\sqrt{\mathrm{Var}(x) + \epsilon}} + \beta.$$

- **Q2:** RMS Norm:
- **A2:** d (weight γ)

$$\mathrm{RMSNorm}(x) = \gamma \odot \frac{x}{\sqrt{\frac{1}{d}\sum_i x_i^2 + \epsilon}}.$$

Pulse Check: Normalization (2)

- How many FLOPS do each normalization have?
- **Q1:** LayerNorm:
- **A1:** 7d
  - Variance: 3d (why?)
  - Numerator subtract: d
  - Element-wise scaling and division by denominator: 2d
  - Sum bias term: d

$$\mathrm{LayerNorm}(x) = \gamma \odot \frac{x - \mu(x)}{\sqrt{\mathrm{Var}(x) + \epsilon}} + \beta.$$

- **Q2:** RMS Norm:
- **A2:** 4d
  - Squaring each element (d)
  - Summing squared elements (d)
  - Element-wise gamma (d)
  - Element-wise division (d)

$$\mathrm{RMSNorm}(x) = \gamma \odot \frac{x}{\sqrt{\frac{1}{d}\sum_i x_i^2 + \epsilon}}.$$

Why RMSNorm?

- **Modern explanation** – it's faster (and just as good).
  - **Fewer operations** (no mean calculation)
  - **Fewer parameters** (no bias term to store)

- But does floating point operations really determine speed? No!!
  - Non-matmul ops only make up 0.2% of FLOPS (in a specific study).
  - But GPUs achieve far lower throughput on non-matmul ops!!
    - (e.g., they may be memory-bound because you need to read/write)

"Tensor Contraction" := matmuls

Table 1. Proportions for operator classes in PyTorch.

Operator class	% flop	% Runtime
△ Tensor contraction	99.80	61.0
□ Stat. normalization	0.17	25.5
○ Element-wise	0.03	13.5

[Slide credit: Tatsu Hashimoto]

Why RMSNorm?

- **RMSNorm** runtime (and surprisingly, performance) gains have been seen in papers.


Model	Params	Ops	Step/s	Early loss	Final loss	SGLUE	XSum	WebQ	WMT EnDe
Vanilla Transformer	$223M$	$11.1T$	3.50	2.182 ± 0.005	1.838	71.66	17.78	23.02	26.62
RMS Norm	$223M$	$11.1T$	3.68	2.167 ± 0.008	**1.821**	**75.45**	**17.94**	**24.07**	**27.14**

approximately 5% higher throughput.

Performance slightly better.

[Slide credit: Tatsu Hashimoto]

Who uses what?



LayerNorms: Recap

- Basically, most recent works use pre-norm.
  - Intuition – keep the good parts of residual connections.
  - Observations – nicer gradient propagation, fewer spike.

- Most people do RMSnorm
  - In practice, works as well as LayerNorm.
  - But, has fewer parameters to move around (and less memory traffic), which saves on wall-clock time.

[Slide credit: Tatsu Hashimoto]

FFN layers

$$\mathrm{FFN}(\mathbf{x}) = f(\mathbf{x}\boldsymbol{W}_1 + b_1)\boldsymbol{W}_2 + \boldsymbol{b}_2$$

Is the Bias Term Necessary?

- FFN: The same nonlinear transformation independently to **each** token.
- Most modern transformers don't have bias terms.
  - Original Transformer:

$$\text{FFN}(\mathbf{x}) = f(\mathbf{x}\boldsymbol{W}_1 + b_1)\boldsymbol{W}_2 + \boldsymbol{b}_2 \qquad \boldsymbol{W}_1 \in \mathbb{R}^{d \times d_{\text{ff}}}, \; \boldsymbol{W}_2 \in \mathbb{R}^{d_{\text{ff}} \times d}$$

  - Most implementations (if they're not gated):

$$\text{FFN}(\mathbf{x}) = f(\mathbf{x}\boldsymbol{W}_1)\boldsymbol{W}_2$$


- Reasons:
  - Removing biases saves $d + d_{\text{ff}}$ params (a small reduction rel to total of $2d \times d_{\text{ff}}$)
  - Less memory (similar to RMSNorm).
  - PaLM paper specifically notes dropping it improves training stability.

Who uses bias term?

	With FFN bias	No FFN bias
2017	Transformer	—
2018	GPT-1, BERT	—
2019	GPT-2	T5
2020	GPT-3	—
2021	GPT-J	—
2022	OPT, BLOOM, GPT-NeoX-20B	PaLM
2023	Phi-2	LLaMA, Llama 2, Falcon, Mistral 7B, Qwen
2024	—	Llama 3, Gemma, Mixtral, OLMo, DeepSeek-V3
2025	gpt-oss	Llama 4, Qwen3, Gemma 3, Kimi K2, GLM-4.5
2026	—	Kimi K2.5, Qwen3.5, GLM-5, MiniMax M2.5, Gemma 4


Which Activation fun should we use?

- There are many choices; but trending toward “gated” functions.




Which Activation fun should we use?

- There are many choices; but trending toward “gated” functions.



Activations: ReLU vs GELU

- **ReLU:**
  - **Notable models:** Original transformer, T5, Chinchilla
- **GELU:**
  - **Notable models:** GPT1/2/3, BERT, RoBERTa.




Bonus


GELU function, in details

$$\mathrm{GELU}(\mathbf{y}) \coloneqq \mathbf{y}\Phi(\mathbf{y})$$

- Here $\Phi(\mathbf{y})$ is the cumulative distribution function (CDF) of a normal distribution:

$$\Phi(\mathrm{y}) = \frac{1}{2}\left(1 + \mathrm{erf}\left(\frac{x}{\sqrt{2}}\right)\right)$$





Gated activations (*GLU)

- Gated activations modify the first part of the FFN layer:

$$\mathrm{FFN}(\mathbf{x}) = f(\mathbf{x}\boldsymbol{W}_1)\boldsymbol{W}_2$$

$$\boldsymbol{W}_1 \in \mathbb{R}^{d \times d_{\mathrm{ff}}},\ \boldsymbol{W}_2 \in \mathbb{R}^{d_{\mathrm{ff}} \times d}$$

- What if the first layer depended on two different views of the input?

$$f(\mathbf{x}\boldsymbol{W}_1) \rightarrow f(\mathbf{x}\boldsymbol{W}_1) \odot (\mathbf{x}\boldsymbol{V})$$

$$\boldsymbol{W}_1, \boldsymbol{V} \in \mathbb{R}^{d \times d_{\mathrm{ff}}},$$

  - The input is projected **twice**.
  - One projection, through the activation, acts as a **gate** (a soft volume knob), and it multiplies the other projection **elementwise**.

- The fully gated FFN is written in this form:


$$\mathrm{FFN}(\mathbf{x}) = (f(\mathbf{x}\boldsymbol{W}_1) \odot (\mathbf{x}\boldsymbol{V}))\boldsymbol{W}_2.$$

$$\boldsymbol{W}_1, \boldsymbol{V} \in \mathbb{R}^{d \times d_{\mathrm{ff}}},\ \boldsymbol{W}_2 \in \mathbb{R}^{d_{\mathrm{ff}} \times d}$$


Language Modeling with Gated Convolutional Networks, 2017
GLU Variants Improve Transformer, 2020

Gated activations (*GLU)

Original Transformer (2017)



Llama1 (2023)



Activations: Gated activations variants

- **GeGLU**

$$\mathrm{FFN}_{GeGLU}(\mathbf{x}; \boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{V}) = (\mathrm{GELU}(\mathbf{x}\boldsymbol{W}_1) \odot (\mathbf{x}\mathbf{V}))\boldsymbol{W}_2.$$

  - **Notable models:** T5 v1.1, Gemma family (1 - 4)

- **SwiGLU** (or sometimes called: **SiLU**)**:** swish function is $x \cdot \mathrm{sigmoid}(x)$:

$$\mathrm{FFN}_{SwiGLU}(\mathbf{x}; \boldsymbol{W}_1, \boldsymbol{W}_2, \boldsymbol{V}) = (\mathrm{Swish}(\mathbf{x}\boldsymbol{W}_1) \odot (\mathbf{x}\mathbf{V}))\boldsymbol{W}_2.$$

  - **Notable models:** Widely used in recent LLMs

Do Gated Linear Units work?

- Yes, fairly consistently so.

	Score Average	CoLA MCC	SST-2 Acc
FFN_{ReLU}	83.80	51.32	94.04
FFN_{GELU}	83.86	53.48	94.04
$\text{FFN}_{\text{Swish}}$	83.60	49.79	93.69
FFN_{GLU}	84.20	49.16	94.27
$\text{FFN}_{\text{GEGLU}}$	84.12	53.65	93.92
$\text{FFN}_{\text{Bilinear}}$	83.79	51.02	**94.38**
$\text{FFN}_{\text{SwiGLU}}$	84.36	51.59	93.92
$\text{FFN}_{\text{ReGLU}}$	**84.67**	**56.16**	**94.38**
[Raffel et al., 2019]	83.28	53.84	92.68
ibid. stddev.	0.235	1.111	0.569

GLU Variants Improve Transformer, 2020

Do gated linear units work?

- Yes, fairly consistently so.

Lower loss

Alas the gains of pre-training do not uniformly generalize to the end tasks. sigh …

Model	Params	Ops	Step/s	Early loss	Final loss	SGLUE	XSum	WebQ
Vanilla Transformer	$223M$	$11.1T$	3.50	2.182 ± 0.005	1.838	71.66	17.78	23.02
GeLU	$223M$	$11.1T$	3.58	2.179 ± 0.003	1.838	**75.79**	**17.86**	**25.13**
Swish	$223M$	$11.1T$	3.62	2.186 ± 0.003	1.847	**73.77**	17.74	**24.34**
ELU	$223M$	$11.1T$	3.56	2.270 ± 0.007	1.932	67.83	16.73	23.02
GLU	$223M$	$11.1T$	3.59	2.174 ± 0.003	**1.814**	**74.20**	**17.42**	24.34
GeGLU	$223M$	$11.1T$	3.55	2.130 ± 0.006	**1.792**	**75.96**	**18.27**	**24.87**
ReGLU	$223M$	$11.1T$	3.57	2.145 ± 0.004	**1.803**	**76.17**	**18.36**	**24.87**
SeLU	$223M$	$11.1T$	3.55	2.315 ± 0.004	1.948	68.76	16.76	22.75
SwiGLU	$223M$	$11.1T$	3.53	2.127 ± 0.003	**1.789**	**76.00**	**18.20**	**24.34**
LiGLU	$223M$	$11.1T$	3.59	2.149 ± 0.005	**1.798**	**75.34**	**17.97**	**24.34**
Sigmoid	$223M$	$11.1T$	3.63	2.291 ± 0.019	1.867	**74.31**	17.51	23.02
Softplus	$223M$	$11.1T$	3.47	2.207 ± 0.011	1.850	**72.45**	17.65	**24.34**

Recap: FFN layers

- Many variations (ReLU, GELU, *GLU) across models.

- **Gated activations (*GLU):** two projections; one projection gates the other elementwise.
  - **Cost:** three matrices instead of two, so we shrink d_ff maintain same FLOPS.
  - **Gains:** Modest gains at equal compute (Shazeer, 2020).
  - Default in nearly all LLMs since 2023; SwiGLU is the most common.

- **Bias term:** People more generally drop bias terms.

Architecture layout

Serial vs Parallel Layer

- The standard “serial” formulation: they compute attention, then the MLP
  - h = x + Attention(LayerNorm_1(x))
  - y = h + MLP(LayerNorm_2(h))

- The **parallel** formulation:
  - y = x + MLP(LayerNorm(x)) + Attention(LayerNorm(x))

- **Tradeoff:** the parallel MLP does not receive the block’s attention output.
- **Efficiency:**
  - Both branches read the **same** LN(x), so one LayerNorm suffices.
  - The attention QKV and MLP up-projection can be fused into one matmul.


Proposed by GPT-J (Wang & Komatsuzaki, 2021)

Parallel Layer: do they work?

- The evidence is sparse.
- PaLM claims that parallel formulation:
  - *“~15% faster training speed at large scales”*
  - *“Ablation showed a small quality degradation at 8B but no quality degradation at 62B scale”*
  - the paper didn’t ablate at 540B; it extrapolated from the 8B and 62B results.

PaLM: Scaling Language Modeling with Pathways, 2022


Serial vs Parallel Layer: who uses what?



Embedding parameter tying

- Embed matrix (vocab × d): turns token IDs into vectors
- Output projection (d × vocab): turns hidden states back into logits over the vocabulary.

- **Problem:** Both are vocab-sized and often among the largest single tensors in the model.
  - Their dimensions match (after a **transpose**).
  - Do we need to keep separate matrices?




Using the Output Embedding to Improve Language Models, 2017

Embedding parameter tying

- The same weight matrix can be used for both the input embeddings and the output (projection) lay

```
class TransformerWithTiedEmbeddings(nn.Module):
    def __init__(self, vocab_size, d_model):
        super().__init__()
        self.embedding = nn.Embedding(vocab_size, d_model)
        self.transformer = nn.Transformer(d_model=d_model)
        self.output_layer = nn.Linear(d_model, vocab_size)

        # Tying embeddings
        self.output_layer.weight = self.embedding.weight
```



Because nn.Linear stores a linear layer's weight as (out_features, in_features).

Where did the transpose go? Hmm …


Using the Output Embedding to Improve Language Models, 2017

Embedding parameter tying: justification

- **Intuition:** Input & output embeddings should live in the same space.
  - Intuitively, a token's meaning shouldn't depend on whether it's being *read* in or *predicted*.

- **Better embeddings for rare words:**
  - The output matrix gets a gradient for *every* vocab token at every softmax step.
  - The input emb only updates for tokens in the batch.
  - Tying lets rare words learn from that dense signal.


- **Memory efficiency:** Cuts one vocab × d matrix.
  - GPT-2 small: ~38M of 124M params (~30%).
  - Though the gains diminish for larger models (why?).



Using the Output Embedding to Improve Language Models, 2017

Embedding parameter tying: demo

- Play with the embedding tying demo here.



https://huggingface.co/spaces/HuggingFaceTB/smol-training-playbook

Who ties embedding parameters?



One caveat about this visualization: tying can vary within a family. There is often more incentive to tie embed/unembed matrices for **smaller** models.

Recap so far

- **Serial vs parallel layers:**
  - Parallel layers have a compute win.
    - (even though their arithmetic work is not necessarily lower.)
  - Empirical evidence is sparse.

- **Parameter tying:**
  - Reduces model parameters and leads to (modest) gains.
  - Unclear how much it matters at scale; many large LLMs (e.g., LLaMA) don’t tie.

Architecture Hyperparams

There are many question regarding architecture hyperparameters:

- How much bigger should the feedforward size be compared to hidden size?
- How many heads? Should # of heads always divide hidden size?
- Should we make our model wide or deep?

- **Note:** Ultimately the goal is to set these params in a way that we reach the lowest loss, given a set of constraints (e.g., total compute budget).

d_{ff}: How Wide Should the FFN Be?

- **Feedforward – model dimension ratio:**

$$\text{FFN}(\mathbf{x}) = f(\mathbf{x}\boldsymbol{W}_1 + b_1)\boldsymbol{W}_2 + \boldsymbol{b}_2$$
$$\boldsymbol{W}_1 \in \mathbb{R}^{d \times d_{\text{ff}}},$$
$$\boldsymbol{W}_2 \in \mathbb{R}^{d_{\text{ff}} \times d}$$

- There are two dimensions that are relevant – the feedforward dim (d_{ff}) and model dim (d). What should their relationship be?

$$d_{\text{ff}} = 4d$$


- This is *almost* always true. There's just a few exceptions.

[Slide credit: Tatsu Hashimoto]

d_{ff}: How Wide Should the FFN Be?

- Each point is a ~50M (non-embedding) param model. We vary the ratio $d_{\text{ff}}/d_{\text{model}}$.

- Empirically, there's a basin between 1-10 where this hyperparam is near-optimal.




[Slide credit: Tatsu Hashimoto]

Scaling Laws for Neural Language Models, 2020

Setting d_{ff} for GLU/Gated variants

- Remember that GLU activations add extra matrix computation.
- One tradition is to set its d_{ff} in a way that it maintains that FFN param counts (hence, FLOPS).
  - Params in a non-gated FFN: $2d_{\text{ff}} \times d = 2 \times 4d \times d = 8d^2$
  - Params in a gated FFN: $3d_{\text{ff}} \times d$
  - $3d_{\text{ff}} \times d = 8d^2 \rightarrow \ d_{\text{ff}} = \frac{8}{3}d = 2.66d$

Setting d_{ff} for GLU/Gated variants



Notice that most models are within the range $\frac{d_{\text{ff}}}{d} \approx 2.66$

Head Dimension vs. Model Dimension

Bonus

- Remember:

$$\text{head}_i = \text{Attention}\left(\mathbf{x}\mathbf{W}_i^q, \mathbf{x}\mathbf{W}_i^k, \mathbf{x}\mathbf{W}_i^v\right)$$
$$\text{MultiHeadedAttention}(\mathbf{x}) = \text{Concat}(\text{head}_1, \ldots, \text{head}_h)\boldsymbol{W}^O$$

In practice, we use a reduced dimension for each head.


$$\mathbf{W}_i^q, \mathbf{W}_i^k, \mathbf{W}_i^v \in \mathbb{R}^{d_{\text{model}} \times d_{\text{head}}}, \qquad \boldsymbol{W}^O \in \mathbb{R}^{(h \times d_{\text{head}}) \times d_{\text{model}}}$$

- The consensus: $h \times d_{\text{head}} = d_{\text{model}}$
- This doesn't have to be true since the matrix ($\boldsymbol{W}^O$) can take care of projection to model-dim.

[Slide credit: Tatsu Hashimoto]

Head Dimension vs. Model Dimension

Bonus



Most models have ratio = $\frac{h \times d_{\text{head}}}{d_{\text{model}}}$ around 1.


Aspect ratios (width vs depth)

Bonus

- Wide range of ‘good’ values (100-200) with respect to loss.

[Kaplan et al 2020]

- System-level considerations are not reflected here.
  - Extremely deep models are harder to parallelize.
    - Depth introduces sequential dependencies;
  - Width enables more within-layer parallelism
    - but can also increase communication.




Scaling Laws for Neural Language Models, 2020

[Slide credit: Tatsu Hashimoto]

Bonus

Aspect ratios (width vs depth)

- Should my model be deep or wide? How deep and how wide?
- Note here width is the hidden dimension, **not** the context window width.
- Most models stick to ratio between 100-200.



Recap of architecture hyperparams

- FFN width (d_{ff}/d)
  - 4× (standard) and 8/3× (GLU) are parameter-matched defaults
  - Kaplan: flat basin at ~1–4× at fixed N (50M scale)
  - Modern GLU models span ~2.5–8× (median 3.5)

- Attention head dim:
  - Standard: $d_{head} \times h = d$
  - Standard convention; Kaplan finds weak sensitivity at fixed N

- Aspect ratio (d/n_{layers})
  - Wide range of ‘good’ values (100-200).
  - Systems constraints (in addition to quality constraints) influence the choice.

Pre-training data

LLM consume how much tokens?

Model	Release	Training tokens	Training data
BERT	2018	~131B	BooksCorpus (800M words) + English Wikipedia (2.5B words)
T5	2019	34B	C4 (cleaned Common Crawl)
GPT-3	2020	300B	Filtered Common Crawl, WebText2, Books1, Books2, Wikipedia
Gopher	2021	300B	MassiveText
Chinchilla	2022	1.4T	MassiveText
PaLM	2022	780B	Web pages, books, Wikipedia, conversations, GitHub code
BLOOM	2022	366B	ROOTS (46 natural + 13 programming languages)
Llama 2	2023	2T	Publicly available online data
Llama 3	2024	15T+	Publicly available online data
DeepSeek-V3	2024	14.8T	Multilingual web, with extra math and code
Qwen2.5	2024	18T	Multilingual web, code, math
OLMo 2 (13B)	2024	5.6T	OLMo-Mix-1124 + Dolmino-Mix-1124 (fully open)
Gemma 3 (27B)	2025	14T	Multilingual web, code, math, images
Qwen3	2025	~36T	119 languages; web, code, STEM, synthetic data
Kimi K2	2025	15.5T	Web, code, math, knowledge, plus rephrased data

Note that token counts depend on the tokenizer of each model.

They used to be in billions of tokens; now they're in trillions.

Where do we begin to collect data?

- Where do I find a very large dataset?
  - Crawling web is non-trivial (unless you're OpenAI with ton of resources).
  - The alternative is to look for websites that do the crawling for you.



- A non-profit that release a new crawl of the internet **every month**.
  - So far, there have been 100+ crawls from 2008.
  - In 2016, a crawl took 10-12 days on 100 machines.
  - **Not** a complete of the internet; they have some overlap but try to diversify.
    - Common Crawl follows links from previously crawled pages.

https://data.commoncrawl.org/crawl-data/CC-MAIN-2024-30/index.html



Bonus


- CC is a common sources of pre-training data.
  - **WARC**: The raw HTTP responses, including full web pages.
  - **WAT**: The metadata summary from WARC files.
  - **WET**: The extracted plaintext from WARC files, stripping out HTML and other non-textual content.
- Also note, its crawler respects robots.txt. (if the website does not allow it, it won't get crawled).

https://data.commoncrawl.org/crawl-data/CC-MAIN-2024-30/index.html

Data Type	File List	#Files	Total Size Compressed (TiB)
Segments	segment.paths.gz	100	
WARC	warc.paths.gz	90000	76.08
WAT	wat.paths.gz	90000	17.68
WET	wet.paths.gz	90000	7.00
Robots.txt files	robotstxt.paths.gz	90000	0.15
Non-200 responses	non200responses.paths.gz	90000	2.59
URL index files	cc-index.paths.gz	302	0.19
Columnar URL index files	cc-index-table.paths.gz	900	0.22

How many dumps of CC do people use?

- Most efforts use many dumps to prepare their pre-training data.



CC: Examples

- These are some random documents that we fetched from CommonCrawl.
  - https://github.com/danyaljj/sample-cc-docs/
- What do you think?


CC is not clean. Is that a concern?

Cleaning data

- There is a lot of “junk” in CC data.
- It’s common to remove a large chunk of it so obtain high-quality data.

Data set	Size
★ C4	745GB
C4, unfiltered	6.1TB

Cleaning data: example from the C4 dataset



Menu


Lemon

Introduction

The lemon, Citrus Limon (l.) Osbeck, is a species of small evergreen tree in the flowering plant family rutaceae.
The tree's ellipsoidal yellow fruit is used for culinary and non-culinary purposes throughout the world, primarily for its juice, which has both culinary and cleaning uses. The juice of the lemon is about 5% to 6% citric acid, with a ph of around 2.2, giving it a sour taste.

Article

The origin of the lemon is unknown, though lemons are thought to have f[illegible]t grown in Assam (a region in nort[illegible]dia), northern Burma o[illegible]




Please enable JavaScript to use our site.

Home
Products
Shipping
Contact
FAQ

Dried Lemons, $3.59/pound

Organic dried lemons from our farm in California.
Lemons are harvested and sun-dried for maximum flavor.
Good in soups and on popcorn.

The lemon, Citrus Limon (l.) Osbeck, is a species of small evergreen tree in the flowering plant family rutaceae.
The tree's ellipsoidal yellow fruit is used for culinary and non-culinary purposes throughout the world, primarily for its juice, which has both culinary and cleaning uses. The juice of the lemon is about 5% to 6% citric acid, with a ph of around 2.2, giving it a sour taste.



Lorem ipsum dolor sit amet, consectetur adipiscing elit.
Curabitur in tempus quam. In mollis et ante at consectetur.
Aliquam erat volutpat.
Donec at lacinia est.
Duis semper, magna tempor interdum suscipit, ante elit molestie urna, eget efficitur risus nunc ac elit.
Fusce quis blandit lectus.
Mauris at mauris a turpis tristique lacinia at nec ante.
Aenean in scelerisque tellus, a efficitur ipsum.
Integer justo enim, ornare vitae sem non, mollis fermentum lectus.
Mauris ultrices nisl at libero porta sodales in ac orci.

```
function Ball(r) {
  this.radius = r;
  this.area = pi * r ** 2;
  this.show = function(){
    drawCircle(r);
  }
}
```

Retain:
- Sentences with terminal punctuation marks
- Pages with at least 5 sentences, sentences with at least 3 words

Remove any:
- "Lorem ipsum" text (dummy text), "terms of use", etc.

Slide adapted from Colin Raffel

Pre-training Data: Experiment

- Takeaway:
  - Clean and compact data is better than large, but noisy data.
  - Pre-training on in-domain data helps.

Data set	Size	GLUE	CNNDM	SQuAD	SGLUE	EnDe	EnFr	EnRo
★ C4	745GB	83.28	**19.24**	80.88	71.36	**26.98**	**39.82**	**27.65**
C4, unfiltered	6.1TB	81.46	19.14	78.78	68.04	26.55	39.34	27.21

Exploring the limits of transfer learning with text-to-text transfer transformers, 2020

Does it matter that my data has ton of repetitions?

Pre-training Data Duplicates


- There is a non-negligible number of duplicates in any pre-training data.
- Maybe we should not spend our training budget re-learning things we have already seen.

Dataset	Example	Near-Duplicate Example
Wiki-40B	\n_START_ARTICLE_\nHum Award for Most Impactful Character \n_START_SECTION_\nWinners and nominees\n_START_PARAGRAPH_\nIn the list below, winners are listed first in the colored row, followed by the other nominees. [...]	\n_START_ARTICLE_\nHum Award for Best Actor in a Negative Role \n_START_SECTION_\nWinners and nominees\n_START_PARAGRAPH_\nIn the list below, winners are listed first in the colored row, followed by the other nominees. [...]
LM1B	I left for California in 1979 and tracked Cleveland 's changes on trips back to visit my sisters .	I left for California in 1979 , and tracked Cleveland 's changes on trips back to visit my sisters .
C4	Affordable and convenient holiday flights take off from your departure country, "Canada". From May 2019 to October 2019, Condor flights to your dream destination will be roughly 6 a week! Book your Halifax (YHZ) - Basel (BSL) flight now, and look forward to your "Switzerland" destination!	Affordable and convenient holiday flights take off from your departure country, "USA". From April 2019 to October 2019, Condor flights to your dream destination will be roughly 7 a week! Book your Maui Kahului (OGG) - Dubrovnik (DBV) flight now, and look forward to your "Croatia" destination!

Deduplicating Training Data Makes Language Models Better, 2020

Deduplicating Data Improves LMs


- Perf of 1.4B param model (lower is better) with progressively more pre-processing.
- Applying a quality filter and de-duplication stages significantly improves quality.



Scaling Language Models: Methods, Analysis & Insights from Training Gopher, 2022

Deduplicating Data: Caution

- Don’t over-deduplicate: some repetition is signal!
- Facts that matter appear organically and often, in many phrasings
  - e.g., “Obama was US president from 2009 to 2017”
- Aggressive near-dup can collapse these, so the model may forget them



Thanks to Marc Marone who informed these!

How do you scale data deduplication?

- Pre-training is huge. Naively deduplicating the data is going to take forever!!

- How do you deduplicate it?
  - **Exact deduplication:** Hashing documents
  - **Approximate deduplication:** requires advanced data structures.
    - SuffixArray
    - MinHash
    - BloomFilters

- There is no consensus on how dedup should be done (different works do it differently: different combination of algorithms and levels of aggressiveness.).

The simplest: hashing documents

Bonus

- Hash all documents, so each document with unique text receives one unique hash.
- **Efficiency:** This will be fast.
- **Granularity:**
  - This will be sensitive to small changes; any change in the document (e.g., one word change) would change its hash.
  - Also, we're deduplicating full documents.
- Different choices of hashing functions (trade off between efficiency vs collision):
  - Collison: h(x) = h(y), if x!=y.
  - Cryptographic hashing (SHA-256, SHA-3, BLAKE2); collision resistant but slow.
  - DJB2, MurmurHash, CityHash: Not collision resistant but fast.

Bonus

What are Suffix Arrays?

- A common approach is using **Suffix arrays** — A suffix array for a string *T* (of length m) is an array of integers [0, m) that correspond to suffixes of *T* $, stored in sorted order.
  - Example: *T* = “abaaba$”
- Space complexity:
  - O(m)

0	abaaba$
1	baaba$
2	aaba$
3	aba$
4	ba$
6	a$
7	$

Sort suffixes lexicographically

6	$
5	a$
2	aaba$
3	aba$
0	abaaba$
4	ba$
1	baaba$

Now you can drop the strings

6
5
2
3
0
4
1

Suffix arrays: a new method for on-line string searches, 1993

What are Suffix Arrays?

Bonus

- A common approach is using **Suffix arrays** — A suffix array for a string *T* (of length m) is an array of integers [0, m) that correspond to suffixes of *T* $, stored in sorted order.
  - Example: *T* = “abaaba$”
- Space complexity:
  - O(m)

0	abaaba$
1	baaba$
2	aaba$
3	aba$
4	ba$
6	a$
7	$

Sort suffixes lexicographically

6	$
5	a$
2	aaba$
3	aba$
0	abaaba$
4	ba$
1	baaba$

Now you can drop the strings

6
5
2
3
0
4
1

- You don’t need the suffixes since, given their index, you can look them up from *T*.

Bonus


Suffix arrays: querying

- Querying: Is *P* a substring of *T*?
- Two crucial observations:
  1. For P to be a substring, it must be a prefix of ≥1 of T's suffixes.
  2. Suffixes sharing a prefix are consecutive in the suffix array.

- Example: Given SA of *T* = "abaaba$"
  find the indices (if any) of substring *P* = "aba".
- In practice, we can use binary search to to check whether P is a prefix of any suffix.
- Complexity: O(n log m)
  - for m = len(T) and n = len(P)
  - See an example here.

6	$
5	a$
2	aaba$
3	aba$
0	abaaba$
4	ba$
1	baaba$

Now you can drop the strings



6
5
2
3
0
4
1

LCS with SuffixArrays

Bonus

- Suffix arrays also allows us to quickly check overlap between pairs of documents.
- Querying: Given SA of T, what is its Longest Common Substring (LCS) with *P?*
- This can also be done with binary search O(n log m) for m = len(T) and n = len(P).
- See an example here.

Find more about these algorithms in Ben Langmead's course: https://www.langmead-lab.org/teaching.html

Deduplication with Suffix Arrays

Bonus

- Concatenating all text in the corpus together and then sorting each suffix.
- By scanning this sorted list, substrings with a common prefix can by identified by scanning the prefixes of neighboring elements in the sorted list.
- This latter step can be done in an embarrassingly parallel fashion.
- **Granularity:**
  - Note SAs can only do exact deduplication!
  - But it can allow you to do deduplication on substrings/sub-documents.
- **Hyperparameter:** the length of overlap
  - Lee at al. deduplicated substrings that are at least 50 tokens long.

See example here: https://github.com/google-research/deduplicate-text-datasets/blob/master/README.md
Uses MinHash: Lee at al. Deduplicating Training Data Makes Language Models Better, 2020

Deduplication with MinHash

Bonus

- **MinHash** is a locality-sensitive hashing technique used to group sets into collections based on their Jaccard similarity.
  - Note, unlike SuffixArrays, MinHash can do “fuzzy” deduplication!
  - Hyperparameters: the n-gram-size, and the number of permutations used.
  - Lee et al used:
    - n-gram-size of 5 tokens and Jaccard sim < 0.8;
    - 9K permutations, split into 450 buckets of 20 hashes each.
  - Li et al. used: 1,395 permutations, split into 93 buckets of size 15.

Uses MinHash: Lee at al. Deduplicating Training Data Makes Language Models Better, 2020
Uses MinHash: Li et al. DataComp-LM: In search of the next generation of training sets for language models, 2024
Also see: https://blog.nelhage.com/post/fuzzy-dedup/

Deduplication with BloomFilters

Bonus

- **Bloom filters** are a data structure that enable space-efficient set membership queries.
  - A Bloom filter maintains a sketch of a set that supports an
    - insert operation,
    - a probabilistic membership_query operation.
      - Note: The latter operation has no false negatives (i.e., return False for an element in the set), but it may occasionally return a false positive (i.e., return True for an element not in the set).
- **Efficiency:** Li et al. say that BF is “vastly more efficient than a MinhHash and SuffixArrays.”
- **Granularity:**
  - Can be used for both exact dedup (like Sondaini et al) and ”fuzzy” dedup!
  - Caveat: MinHash performs doc-level deduplication at a document vs. document level, whereas BFF performs document-level deduplication at a document vs. corpus level.
- Hyperparams: Number of hashers which determines the false positive rate.

BloomFilters: Space/time trade-offs in hash coding with allowable errors, 1970

Uses BloomFilter: Soldaini at al. Dolma: An open corpus of three trillion tokens for language model pretraining research, 2024 https://github.com/allenai/bff

Bonus

Comparison between dedup algorithms

- Single methods: BF better than any other method standalone.
- Combination: The competitive approaches are last row (exact -> MH -> SA) and BF-only. The former leads to more compact data.

Individual technique

Combined techniques

Exact Dedup	MinHash	Suffix Array	Bloom Filter	Tokens	Removal Rate	CORE	Δ from Baseline
✗	✗	✗	✗	76B	00%	40.1	+0.0
✓	✗	✗	✗	66B	13%	41.0	+0.9
✗	✓	✗	✗	62B	18%	40.9	+0.8
✗	✗	✓	✗	51B	33%	41.4	+1.3
✗	✗	✗	✓	**56B**	**26%**	**41.7**	**+1.6**
✓	✓	✗	✗	58B	24%	40.2	+0.1
✓	✗	✓	✗	49B	36%	41.3	+1.3
✗	✓	✓	✗	48B	37%	41.2	+1.2
✓	✓	✓	✗	**45B**	**41%**	**41.7**	**+1.6**

Li et al. DataComp-LM: In search of the next generation of training sets for language models, 2024

Bonus

What people do

- There are a few different angles here:
  1. What dedup algorithm do people use?
  2. They dedup over what unit? (full doc vs. a smaller unit)
  3. The dedups are done over what population? (the whole data vs. a subset)
  4. What do they do after finding duplicates?

Bonus

What people do: Deduplicate over what unit?

- You can look for repeats across different units: documents, paragraphs, etc.
- Most works dedup on document-level.
- Some pipelines are very thorough (e.g., Llama3) and cover many units.

Unit	Catches	Used by
URL	Same page recrawled	Llama 3
Document	Copies, mirrors, templated pages, small edits	FineWeb, Essential-Web, FineWeb2, HPLT v2, DCLM, Llama 3, Nemotron-CC, TxT360, OLMo 3
Paragraph	Shared quotes and disclaimers	DCLM
Line	Menus, cookie banners, footers	Llama 3
Substring	Long repeated passages	Nemotron-CC, OLMo 3

Bonus

What people do: Which algorithm?

- Which algorithm you use depends on what unit of data you apply them to.
- MinHash LSH is near-universal for near-duplicates;
  - DCLM's Bloom filter is the main exception.
- Approximate matching happens almost only at the document level.
  - Finer units use exact matching, which is cheaper and less error-prone on short text.

Unit	Exact match	Approximate match
URL	URL hash · Llama 3	—
Document	Content hash · Essential-Web · Nemotron-CC · OLMo 3	MinHash LSH · FineWeb · Essential-Web · FineWeb2 · Llama 3 · Nemotron-CC · TxT360 · OLMo 3 Bloom filter · DCLM
Paragraph	—	Bloom filter · DCLM
Line	Line hash + count · Llama 3	—
Substring	Suffix array · Nemotron-CC · OLMo 3	—

Bonus

What people do: Which population gets dedup?

- Shards are arbitrary slices made for parallel computing dedup algorithms.
- Dedup on dumpts or shards reduces its aggressiveness.
  - In FineWeb, global dedup cut 36T tokens to 4T and trained worse, because cross-year repeats turned out to be useful.

Population	URL	Document	Paragraph	Line	Substring	...
Each dump	—	FineWeb Essential-Web	—	—	—	
Each language across all dumps	—	FineWeb2	—	—	—	
Each shard or bucket	—	DCLM OLMo 3 (32 shards)	DCLM	Llama 3 (30M docs	OLMo 3 (56 shards)	
Entire corpus	Llama 3	Essential-Web OLMo 3 Llama 3 Nemotron-CC TxT360	—	—	—	

Hashing (exact) MinHash LSH (fuzzy) Bloom filter Suffix array

Bonus

What people do: What do you do with the duplicates?

- Most efforts simply keep one copy.
- Newer pipelines dedup maintain some degree of duplicates somewhere in the pipeline.

Approach	What happens	Used by
Keep one copy	Other copies removed	FineWeb, Essential-Web, HPLT v2, DCLM, Llama 3, Nemotron-CC
Keep cross-dump repeats	Dedup per dump only	FineWeb, Essential-Web
Upsample by count	Repeat by cluster size; huge clusters once	FineWeb2
Upsample by quality	Repeat the best documents	OLMo 3


"Upsample by *": once duplicates are removed, deliberately put back some controlled repetition.

Should I worry about old data in my pre-training?

Prevalence of stale data: RedPejamas

Bonus

- Individual dumps of CC are incomplete picture of the internet.
- Therefore, developers fetch multiple dumps. But older dumps contain more older content!
- Old/stale data in pre-training can skew your model toward them.




Dated Data: Tracing Knowledge Cutoffs in Large Language Models, 2024

Should I worry about skew of the data mixtures in my pre-training?

Data mixtures (and the long tail)

Bonus

- Data in the world is always skewed. For example,
  - English has a lot more language than other domains.
  - Reddit is a lot larger than science papers.



Upsample or Upweight? Balanced Training on Heavily Imbalanced Datasets, 2024
DoReMi: Optimizing Data Mixtures Speeds Up Language Model Pretraining, 2023

Data mixtures (and the long tail)

Bonus

- Data in the world is always skewed. For example,
  - English has a lot more language than other domains.
  - Reddit is a lot larger than science papers.
- A uniform ”weight” of data during pre-training is not good.
  - Overrepresented domains would dominate
  - (e.g., your model would be a muchx100 better at English than Azeri).
- Therefore, you need to balance the data!

Upsample or Upweight? Balanced Training on Heavily Imbalanced Datasets, 2024
DoReMi: Optimizing Data Mixtures Speeds Up Language Model Pretraining, 2023

Bonus

Language filtering


- Many models limit their data to English.
- Danger in English-only filtering:
  - accidentally filtering out dialect of English.
  - Ill-defined for code-switching (e.g., English + Chinese).

- To go beyond English, you need to identify langs. How do people identify languages?
  - A popular choice is fastText which supports 176 langs.
  - GlotLID is a similar classifier but identifies many more (1665) languages

Dataset / model	Year	LID	Scope
Dolma, FineWeb, DCLM	2024	lid.176	English
Llama 3	2024	lid.176	8% non-English
FineWeb2	2025	GlotLID	1,000+ languages
Apertus	2025	GlotLID	1,811 languages

A typical data pipeline


Starts with the massive crawled data by CommonCrawl.
The WET format that contains textual information.
WARC is raw, WAT is metadata, WET is text+some metadata.



https://twitter.com/tarantulae/status/1650170087708454913?t=ncWWY0FI0tYC_dYLs76r5g

A typical data pipeline


Shard WET content into shards of 5GB each (one CC snapshot can have 30TB). Then you normalize paragraphs (lowercasing, numbers as placeholders, etc), compute per-paragraph hashes and then deduplicate them.



https://twitter.com/tarantulae/status/1650170087708454913?t=ncWWY0FI0tYC_dYLs76r5g

A typical data pipeline

Perform language identification and decide whether to keep or discard languages.
The order of when you do this in the pipeline can impact the language discrimination quality.




https://twitter.com/tarantulae/status/1650170087708454913?t=ncWWY0FI0tYC_dYLs76r5g

A typical data pipeline

Do further quality filtering: Train a simple LM (n-gram) on target languages using Wikipedia, then compute per-paragraph perplexity on the rest of the data:

- Very high PPL: Very different than Wiki and likely low-quality → Drop
- Very low PPL: Very similar or near duplicates to Wiki → Drop



CCNet: Extracting High Quality Monolingual Datasets from Web Crawl Data, 2019

Summary: preparing pre-training data

- Data does not fall from the sky. You have to work to get it!
- **Finding large data:** CommonCrawl has a ton of crawled dumps.
- **Cleaning data** can save tons of compute and even give you perf gains.

The actual pre-training

Considerations for running pre-training

- **Model architecture and scaling**
  - Model ladder and scaling laws (parameters, tokens, compute)
  - Architectural hyperparameters (depth, width, attention heads, context length, MoE)
- **Optimization:**
  - What optimizer to use (AdamW, Muon, etc.)
  - Learning rate schedule (warmup, decay)
  - Global batch size and gradient accumulation
  - Numerical precision (BF16, FP8, etc.)
  - Training stability (gradient clipping, loss spikes)
- **System-level considerations:**
  - Parallelism (data, tensor, pipeline, expert, sequence)
  - Efficiency and FLOP utilization (MFU, throughput)
  - Networking and fault tolerance
  - Data pipeline

Legend: Already covered them; will cover next; will hopefully cover at some point.

How should we select the right hyperparams?

Q: What would you do?

- Zuckerberg gave you a $500M budget for training Muse-10.
- You set aside $10M to find the best setup at small scale, then scale up.
- The plan:
  - Tune training hyperparameters on a small model: learning rate, warmup, weight decay, batch size, etc.
  - Scale every architecture dimension (depth, width, heads) by 50×.


- **Q:** What do you like about this recipe? What worries you?

- **Few concerns:**
  - Optimal hyperparameters are not scale-invariant by default.
  - “50× each” is not a 50× model.
  - You also want to think about how the model will be used at inference.

IsoFLOP profiles: Tradeoffs at a smaller scale

- The performance of your model depends on a complex combination of many factors.
- Goal: find the best combinations, for a fixed compute.
- Approach:
  1. Fix a compute budget FLOP
  2. Train a few models and vary their size
  3. Fit a parabola and find the minimum


IsoFLOP plot



Note: at fixed compute, changing model size also changes the number of training tokens.

IsoFLOP profiles: Tradeoffs at a smaller scale


- The performance of your model depends on a complex combination of many factors.
- Goal: find the best combinations, for a fixed compute.
- Approach:
  1. Fix a compute budget FLOP
  2. Train a few models and vary their size
  3. Fit a parabola and find the minimum
  4. Repeat 1-3 for various FLOP budgets



IsoFLOP profiles: Tradeoffs at a smaller scale


- The performance of your model depends on a complex combination of many factors.
- Goal: find the best combinations, for a fixed compute.
- Approach:
  1. Fix a compute budget FLOP
  2. Train a few models and vary their size
  3. Fit a parabola and find the minimum
  4. Repeat 1-3 for various FLOP budgets
- It's good to change various parameter (e.g., training data, size, or other hyperparams) and see how it's quality (loss) changes.

IsoFLOP plot



Predictive models for parameters

- Overall, IsoPlots show how loss depends on three axes: model size (parameters N), dataset size (tokens D), and compute budget C.
- They're a tool for reasoning about *how to spend your training budget efficiently*.
- But it also allows one to see track effective hyperparams (LR, batch size, etc.) changes with N, C, or D.
- **Lesson:**
  - Don't overtune your hyperparameters at small scales and expect to use them at large
  - Instead develop predictive metrics based on parameters:



One nuance regarding the previous analysis

- Selecting hyper-parameters this way ignores inference costs.
- For example, consider these two alternatives:
  - **Alternative A:** model that is expected to generate 20 tokens (avg) at inference.
  - **Alternative B:** model that is expected to generate 20M tokens (avg) at inference.
- If B is the target, we would prefer architectures that are faster for inference.
  - This often means: smaller models that are trained longer and on more data.
- This is sometimes are “over-training”. (relative to training-compute-optimal allocation).


Optimizer

- There are various optimizers out there. Which one should we use?

Optimizer	PyTorch class	Key idea	Optimizer states per param
SGD	torch.optim.SGD	Gradient descent	0
SGD + Momentum	torch.optim.SGD	Accumulates momentum	1
Adam	torch.optim.Adam	Adaptive first and second moments	2
AdamW	torch.optim.AdamW	Adam with decoupled weight decay	2
Adamax	torch.optim.Adamax	Adam using infinity norm	2
Adagrad	torch.optim.Adagrad	Accumulates squared gradients	1
Adadelta	torch.optim.Adadelta	Tracks squared gradients and updates	2
…	…	…	


Adam/AdamW

- Adam optimization is based on adaptive estimation of “momentum”
  - first-order and second-order “moments”.
- We call these “momentum” tensors “optimizer states”.
- They take up additional GPU memory.



https://pytorch.org/docs/stable/generated/torch.optim.AdamW.html
https://pytorch.org/docs/stable/generated/torch.optim.Adam.html
Decoupled Weight Decay Regularization, 2017

Beware of GPU memory usage



https://huggingface.co/spaces/nanotron/ultrascale-playbook?section=activation_recomputation

Bonus

Who uses what optimizer

- Older works used Adam/AdamW. Recent works use a combination of optimizers.

Model	Year	Optimizer
Pythia-12B	2023	Adam
Llama 2	2023	AdamW
OLMo 7B	2024	AdamW
OLMo 2	2024	AdamW
LLM360 K2-65B	2024	AdamW
DeepSeek-V3	2024	AdamW
SmolLM3	2025	AdamW
Apertus	2025	AdEMAMix
GLM-4.5	2025	Muon + AdamW
Kimi K2	2025	MuonClip
DeepSeek-V4-Flash	2026	Muon + AdamW
DeepSeek-V4-Pro	2026	Muon + AdamW

No one uses vanilla SGD!!

It's quite common to use weight decay ("W" in AdamW).

"Muon + AdamW" means Muon for weight matrices and AdamW for embeddings, output head and norms

The design space of optimizers

- Optimizer behavior depends on:
  - The algorithm,
  - Learning rate,
  - Learning rate schedule,
  - Batch size,
  - Weight decay (if the optimizer supports it)

Learning rate


- Learning rate controls the magnitude of parameter updates during optimization
  - Too large: Training may become unstable or diverge.
  - Too small: Training progresses slowly and may underutilize the compute budget.

$$\theta_{t+1} = \theta_t - \eta_t \nabla_\theta \mathcal{L}(\theta_t)$$

Learning rate

- For Adam/AdamW/Muon, the update rule looks slightly different but learning rate plays the same role.

Learning rate schedule




Learning rate schedule




More forgiving if you don't know your training data size in advance

Peak learning rate



Peak learning rate



Pulse check: learning rate

- **Q1:** Why can't we simply use a very small learning rate throughout pretraining?
- **A1:** Small learning rates can make progress too slow, wasting the compute budget.

- **Q2:** Why might the optimal learning rate decrease as model size increases? What could go wrong if we used the same learning rate for a 1B and a 70B parameter model?
- **A2:** Larger models can have different update sensitivities and optimization dynamics. A learning rate that works at one scale may be unstable at another. The empirical trend is toward smaller peak learning rates for larger models.


Weight Decay


- “W” in AdamW: it decouples “weight decay” from gradient-based optimization steps.
  - Weight decay *discourages large param values.*
  - It gradually shrinks weights toward zero.
  - Acts as a form of regularization, helping reduce overfitting.
  - Larger weight decay → stronger regularization.

https://pytorch.org/docs/stable/generated/torch.optim.AdamW.html
https://pytorch.org/docs/stable/generated/torch.optim.Adam.html
Decoupled Weight Decay Regularization, 2017

Effect of weight decay

- Here ”Adam” uses wd = 0.1.
- Left: Removing weight decay worsens validation loss; moderate WD performs best.
- Right: Weight decay limits the growth of the model's parameter norm.





Benchmarking Optimizers for Large Language Model Pretraining, 2025

Regularization: dropout vs. weight decay.

- Regularization mechanisms that reduce overfitting.

--	**Dropout**	**Weight decay**
Mechanism	Randomly zeroes activations	Shrinks parameters
Where applied	Forward pass during training	Parameter update
Hyperparameter	Dropout probability p	Decay coefficient lambda

- Do we need regularization during pretraining?
- Arguments against:
  - There is *a lot* of data (trillions of tokens), more than parameters.
  - Training only does a single pass on a corpus (hard to memorize)

- What do people do?

Dropout vs weight decay: in practice

- Most of the times papers just don't discuss dropout. On open models, this closely matches not doing dropout. This may not be true of closed models.

Model	Year	Dropout*	Weight decay
Original transformer	2017	0.1	0
GPT-2	2019	0.1	0.1
T5	2019	0.1	0
GPT-3	2020	0.1	0.1
OPT	2022	0.1	0.1
LLaMA	2023	0	0.1
Pythia	2023	0	0.1
Llama 2	2023	0	0.1
Qwen 14B	2023	0.1	0.1
OLMo 2	2024	0	0.1
LLM360 K2	2024	0	0.1
DeepSeek-V3	2024	0	0.1
SmolLM3	2025	0	0.1

Many older models used dropout during pretraining

Newer models (except Qwen) rely only on weight decay


Pulse check: weight decay

- **Q1:** Two models achieve the same training loss, but one uses weight decay and the other doesn't. What differences might we expect in their weights or validation performance?
- **A1:** Weight decay generally restrains parameter norm growth. Validation performance may improve, but this is empirical rather than guaranteed.

- **[Bonus] Q2:** If we double the learning rate while keeping the weight decay coefficient fixed in AdamW, what happens to the amount of weight decay per update?
- **A2:** The shrinkage per step increases. In AdamW, the multiplicative decay factor is approximately 1 − learning_rate × weight_decay. Decoupled means separate from the gradient-based update, not independent of learning rate.

Batching Data

- GPUs are faster at Tensor operations and hence, we want to do batch processing
- The lager batch of data, the faster they get processed.
- Alas, the speedup is often sub-linear (e.g., 2x larger batch leads to less than 2x speedup).
- If you can afford larger batch (larger GPU), it's generally worth it.
- What if we cannot afford to fit a large batch in our GPU?



Efficient Memory Management for Large Language Model Serving with PagedAttention, 2023

How should we select batch size?

- Reasons to prefer larger batch sizes because:
  - **Faster wall-clock training**
  - **Better hardware utilization**
  - **Less noisy gradients.** Each update is a more accurate estimate of the true gradient

- Reasons we may **not** want very large batch sizes:
  - **Wasted tokens beyond a certain point.** If gradients estimates are good enough, spending more data and compute (larger batches) will yield little gains.

Gradient accumulation


- Batch size determines how many training tokens contribute to **each optimizer update**.
- Accumulate gradients over multiple micro-batches before updating parameters.
- Allows you simulate a **large** batch size when your GPU can only fit a **small** one.
- *Effective/global batch size := micro-batch size × K accumulation steps*

```
optimizer.zero_grad()
for i, (x, y) in enumerate(loader):
    loss = loss_fn(model(x), y) / K   # scale by accumulation steps
    loss.backward()                   # gradients add up
    if (i + 1) % K == 0:
        optimizer.step()              # update once every K micro-batches
        optimizer.zero_grad()
```


Gradient accumulation across many GPUs

- The same idea also holds if you want to estimate gradients across many GPUs in parallel.

$$B_{\text{global}} = B_{\text{micro}} \times N_{\text{GPU}} \times K$$



Effective batch size, in practice



MoE models are all i
this corner possibly
because smaller batc
sizes are unstable (?

Efforts with larger train
data use larger batch
size.


Batch size over the course of training

- **Early in training,** the gradient signal is strong; a small batch already points the right way.
- **Later in training,** the loss is lower and the remaining signal is subtler. So gradients are noisier relative to it. The batch size grows as loss falls.
- Batch size also interacts with LR (out of scope for us).



DeepSeek's Scaling laws of batch size

- The intuition behind these results is that as training becomes larger and longer, we want *more stable updates* (smaller learning rates and larger batch sizes).



(a) Batch size scaling curve

(b) Learning rate scaling curve

Figure 3 | Scaling curves of batch size and learning rate. The grey circles represent models whose generalization error exceeded the minimum by no more than 0.25%. The dotted line represents the power law fitting the smaller model. The blue stars represent DeepSeek LLM 7B and 67B.

DeepSeek LLM Scaling Open-Source Language Models with Longtermism, 2024

Pulse check: batch size

- **Q1:** Why might we want to increase batch size as training progresses? What changes about the gradient signal over time?
- **A1:** Early gradients tend to have a stronger signal relative to noise. Later, as the loss decreases, larger batches can help estimate smaller remaining gradients more reliably.

Document/sequence packing

- Say you're pre-training a model with context window 4096.
- What would you do if some of the docs are shorter than this?
- In principle, you can pad; but that would be a waste of your compute.
- People generally like to **pack** as much documents as possible, in each training sequence.
  - This improves GPU utilization and reduces wasted computation on padding.




Figure from: https://huggingface.co/spaces/HuggingFaceTB/smol-training-playbook#which-hyperparameters-actually-matter

Document/sequence packing

- Should the documents attend to each other?
  - Some works apply cross-doc masking (e.g. Llama 3, SmolLM3)
  - Some others let them attend to one another (e.g., Pythia, OLMo 1)




Figure from: https://huggingface.co/spaces/HuggingFaceTB/smol-training-playbook

Epoching

- Epoch := the number of the times we train on our data.
- How large should we set our epochs?
- Pre-training is done on massive data (>15T tokens). At certain point you run out of data.
- Prior studies show that, up to 4 epochs you can continue to extract gains from repeatedly training on your data.)
  - After 4 epochs, there is diminishing returns compared with training on new tokens.

Scaling Data-Constrained Language Models, 2023


Epoching, in practice


- People rarely go beyond >4 or >8 epochs (BERT is a big exception)
- And most recent models (even the “open” ones) are unclear about their epoch counts

Epochs (overall)	Models
~1	PaLM, OPT-175B†, BLOOM† (~1.1), Pythia (standard Pile), LLaMA (~1 overall), OLMo 7B (~1.2), OLMo 2†, Qwen3 (implied, see below)
~1.5	Pythia (deduplicated Pile)
~2	SmolLM2, SHARE-4B, Comma v0.1-2T
~4	Galactica (~4.25), StarCoderBase†, StarCoder2-15B†
~8	phi-1, RoBERTa
~40	BERT (2018): about 40 epochs over a 3.3B-word corpus, as stated in the paper
Varies by source (0.1–6×)	LLaMA, Stable LM 2, Comma v0.1-1T, German/English sovereign model (2026)
Not reported	Llama 2, Llama 3/3.1, DeepSeek-V3/V4, Kimi K2, GLM-5, Apertus, OLMo 3, SmolLM3 (pretraining), Qwen1–Qwen2.5, Yi

Training stability

- In practice, your model's loss should continue to go down with more training on more data.
- So, the real bottlenecks are:
  - (1) compute
  - (2) data
- Sometimes training diverges (spikes in the loss), at which point practitioners usually restart training from an earlier checkpoint.





An example of how data can cause training instability



u/No-Equivalent-3169 · 2 mo. ago

MMMM

Monitoring the convergence with end tasks

- Some works have also monitored **end task** performance during pre-training.
- Use **likelihood** of the correct answer rather than accuracy
  - (you don't even need to consider the incorrect answers)
- Very similar to the "cloze mmlu" trend where you use the probability of the full answer instead of A, B, C, D.
  - Not discrete metrics (e.g., Accuracy)

Understanding Emergent Abilities of Language Models from the Loss Perspective

Monitoring the convergence with end tasks

- These two typically correlate, but not always.




Figure 1: **The performance-vs-loss curves of 1.5B, 6B, and 32B models.** Each data point is the loss (x-axis) and performance (y-axis) of the intermediate checkpoint of one of the three models. We mark the results of random guess in black dashed lines.

[Understanding Emergent Abilities of Language Models from the Loss Perspective]

Recap of training LLMs

- **IsoPlots:** for a fixed compute, which combination of parameters give you the best bang for the buck.
- Careful batching makes your training go brrr!
- Memory usage can be tricky since there are various moving parts.
  - More on distributed training later on.
- Dropout is less common but you still ‘regularize’ LMs via large-scale training.