Question 1

What keyword would you use to define an anonymous function?

- ✓ `lambda`
- `def`
- `afun`
- `yield`

Question 2

Select the true statements. (Select two answers)

- ✓ The `lambda` function can accept **any number** of arguments
- ✓ The `lambda` function can evaluate **only one** expression
- The `lambda` function can accept **a maximum of two** arguments
- The `lambda` function can evaluate **multiple** expressions

Question 3

Look at the code below:

```
1  my_list = [1, 2, 3]
2  # Insert line of code here.
3  print(foo)
4
```

Which snippet would you insert in order for the program to output the following result (tuple):

Output

```
(1, 4, 27)
```

- ✓ `foo = tuple(map(lambda x: x**x, my_list))`
- `foo = list(map(lambda x: x**x, my_list))`
- `foo = tuple(map(lambda x: x*x, my_list))`
- `foo = list(map(lambda x: x*x, my_list))`

Question 4

Look at the code below:

```
1  my_tuple = (0, 1, 2, 3, 4, 5, 6)
2  # Insert line of code here.
3  print(foo)
4
```

Which snippet would you insert in order for the program to output the following result (list):

Output

```
[2, 3, 4, 5, 6]
```

- ✓ `foo = list(filter(lambda x: x-0 and x-1, my_tuple))`
- `foo = tuple(filter(lambda x: x-0 and x-1, my_tuple))`
- `foo = tuple(filter(lambda x: x>1, my_tuple))`
- `foo = list(filter(lambda x: x==0 and x==1, my_tuple))`

Question 5

What is the expected result of executing the following code?

```
def I():
    s = 'abcdef'
    for c in s[::2]:
        yield c


for x in I():
    print(x, end='')

```

- ✓ It will print `ace`
- It will print `bdf`
- It will print `abcdef`
- It will print an empty line

Question 6

What is the expected result of executing the following code?

```
def fun(n):
    s = '+'
    for i in range(n):
        s += s
        yield s


for x in fun(2):
    print(x, end='');

```

- ✓ It will print `++++++`
- It will print `+`
- It will print `++`
- It will print `+++`

Question 7

What is the expected result of executing the following code?

```
def o(p):
    def q():
        return '*' * p
    return q


r = o(1)
s = o(2)
print(r() + s())

```

- ✓ It will print `***`
- It will print `**`
- It will print `*`
- It will print `****`

Question 8

Which of the following open modes allow you to perform **read** operations? (Select two answers)

- ✓ `r`
- ✓ `r+`
- `w`
- `a`

Question 9

What is the meaning of the value represented by `errno.EEXIST` ?

- ✓ File exists
- File doesn't exist
- Bad file number
- Permission denied

Question 10

What is the expected result of the following code?

```
1  b = bytearray(3)
2  print(b)
3
```

- ✓ `bytearray(b'\x00\x00\x00')`
- `bytearray(0, 0, 0)`
- `bytearray(b'3')`
- `3`

Question 11

What is the expected result of the following code?

```
1  import os
2
3  os.mkdir('pictures')
4  os.chdir('pictures')
5  os.mkdir('thumbnails')
6  os.chdir('thumbnails')
7  os.mkdir('tmp')
8  os.chdir('../')
9
10 print(os.getcwd())
11
```

- It prints the path to the *pictures* directory
- ✗ It prints the path to the *thumbnails* directory
- It prints the path to the *tmp* directory

Question 12

What is the expected result of the following code?

```
1  import os
2
3  os.mkdir('thumbnails')
4  os.chdir('thumbnails')
5
6  sizes = ['small', 'medium', 'large']
7
8  for size in sizes:
9      os.mkdir(size)
10
11 print(os.listdir())
12
```

- ✓ `['large', 'small', 'medium']`
- `['.', 'large', 'small', 'medium']`
- `['.', '..', 'large', 'small', 'medium']`

Question 13

What is the expected result of the following code?

```
1  from datetime import date
2
3  date_1 = date(1992, 1, 16)
4  date_2 = date(1991, 2, 5)
5
6  print(date_1 - date_2)
7
```

- ✓ `345 days, 0:00:00`
- `345 days`
- `345`
- `345, 0:00:00`

Question 14

What is the expected result of the following code?

```
1  from datetime import datetime
2
3  datetime = datetime(2019, 11, 27, 11, 27, 22)
4  print(datetime.strftime('%y/%B/%d %H:%M:%S'))
5
```

- ✓ `19/November/27 11:27:22`
- `2019/Nov/27 11:27:22`
- `2019/11/27 11:27:22`
- `19/11/27 11:27:22`

Question 15

Which program will produce the following output:

Output

```
Mo Tu We Th Fr Sa Su
```

A:

```
import calendar
print(calendar.weekheader(2))
```

B:

```
import calendar
print(calendar.weekheader())
```

C:

```
import calendar
print(calendar.weekheader(3))
```

D:

```
import calendar
print(calendar.week)
```

✓ A

Question 16

What is the expected result of the following code?

```
import calendar

c = calendar.Calendar()

for weekday in c.iterweekdays():
    print(weekday, end=" ")

```

- ✓ `0 1 2 3 4 5 6`
- `1 2 3 4 5 6 7`
- `Mo Tu We Th Fr Sa Su`
- `Su Mo Tu We Th Fr Sa`