

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

1.1

INSTALLATION

 Copy as Markdown

Installation

Prerequisites

Serverpod is tested on Mac, Windows, and Linux. Before you can install Serverpod, you need to have [Flutter](#) installed. Serverpod 4 requires Flutter 3.44.4 or later, which includes Dart 3.12.2.

INFO

Check your Flutter installation by running the following command in your terminal:

```
$ flutter doctor
```

Install Serverpod

Serverpod is installed using the Dart package manager. To install Serverpod, run the following command in your terminal:

```
$ dart install serverpod_cli
```

This command will install the Serverpod command-line interface (CLI) globally on your machine. You can verify the installation by running:

```
$ serverpod
```

If everything is correctly configured, the help for the `serverpod` command is now displayed.

 **WARNING**



If a previous version of Serverpod is already installed with `dart pub global activate`, deactivate it before installing or upgrading:

```
$ dart pub global deactivate serverpod_cli
```

Install the VS Code extension (recommended)

The Serverpod VS Code extension makes it easy to work with your Serverpod projects. It provides real-time diagnostics and syntax highlighting for model files in your project.



```
user.spy lib/src/protocol/user.spy
1  class: User
2  table: user
3  fields:
4    addressId: int
5    address: Address?, relation(name = user_address, field = addressId)
6  indexes:
7    user_address_unique_idx:
8      fields: addressId
9      unique: true
```

You can [install the extension](#) from the VS Code Marketplace or search for *Serverpod* from inside VS Code.

Install Serverpod Insights (optional)

Serverpod Insights is a companion app bundled with Serverpod. It allows you to access your server's logs and health metrics. Insights is available for Mac and Windows, but we will be adding support for Linux in the

future.

Serverpod

Endpoint Any Method Any Open Slow Error

Session ID	Endpoint	Method	Duration	Queries	Time
22	FutureCallSession	testCall	0.00	0	2022-01-12 18:11:06
21	futureCalls	makeFutureCall	0.00	0	2022-01-12 18:11:05
20	logging	logInfo	0.00	0	2022-01-12 18:11:03
19	logging	logInfo	0.00	0	2022-01-12 18:11:02
18	transactionsDatabase	updateInsertDelete	0.01	4	2022-01-12 18:11:01
17	basicDatabase	createSimpleTestData	0.30	100	2022-01-12 18:11:01
16	basicDatabase	deleteAllSimpleTestData	0.00	1	2022-01-12 18:11:00
15	logging	twoQueries	0.01	2	2022-01-12 18:10:59
14	logging	logDebugAndInfoAndError	0.00	0	2022-01-12 18:10:58

Clear Logs

Log Settings

Session Log Entry

Session ID 17

Endpoint basicDatabase

Method createSimpleTestData

Log Entries

No log entries were captured for this session.

Queries

INSERT INTO simple_data ("num") VALUES (0) RETURNING id

INSERT INTO simple_data ("num") VALUES (1) RETURNING id

INSERT INTO simple_data ("num") VALUES (2) RETURNING id

INSERT INTO simple_data ("num") VALUES (3) RETURNING id

INSERT INTO simple_data ("num") VALUES (4) RETURNING id

INSERT INTO simple_data ("num") VALUES (5) RETURNING id

INSERT INTO simple_data ("num") VALUES (6) RETURNING id

Connected

Log Settings

Global

Method overrides

basicDatabase.createSimpleTestData

Log level: Error

☐ Log all sessions

☒ Log failed sessions

☒ Log slow sessions

Slow session duration (ms) 1000

☐ Log all queries

☒ Log failed queries

☒ Log slow queries

Slow query duration (ms) 1000

Add Override

Cancel

Save