

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..20..1

SETUP

 Copy as Markdown

Set up anonymous sign-in

WARNING

The anonymous identity provider is **experimental**. It doesn't support account linking yet. To move an anonymous user's data to an account from another provider, merge the accounts. See [Merging accounts](#).

To properly configure anonymous authentication, you must allow anonymous access in your Serverpod auth configuration.

CAUTION

You need to install the auth module before you continue, see [Setup](#).

Server-side configuration

In your main `server.dart` file, configure the anonymous identity provider using the `AnonymousIdpConfig` object and add it to your `pod.initializeAuthServices()` configuration:

```
import 'package:serverpod_auth_idp_server/core.dart';
import 'package:serverpod_auth_idp_server/providers/anonymous.dart';

import 'src/generated/serverpod.dart';

void run(List<String> args) async {
  final pod = Serverpod(args);

  pod.initializeAuthServices(
    tokenManagerBuilders: [
      JwtConfigFromPasswords(),
    ],
    identityProviderBuilders: [
      // Configure the anonymous identity provider
    ],
  );
}
```



```

        AnonymousIdpConfig(),
      ],
    );

    await pod.start();
  }

```

Then, extend the abstract endpoint to expose it on the server:

```

import 'package:serverpod_auth_idp_server/providers/anonymous.dart';

class AnonymousIdpEndpoint extends AnonymousIdpBaseEndpoint {}

```

Then, start the server with `serverpod start` to generate the client code, then create and apply the migration that initializes the database for the provider (in the `serverpod start` terminal, press **M**). More detailed instructions can be found in the general [identity providers setup section](#).

Basic configuration options

Although the anonymous identity provider can be used directly with no other configuration, it is recommended to add some form of app attestation to prevent abuse in production environments. See the [Using a token for app attestation section](#) for more details.

For other configuration options such as callbacks (before/after account creation) and rate limiting, see the [customizations page](#).

Client-side configuration

If you have configured the `SignInWidget` as described in the [setup section](#), the anonymous identity provider will be automatically detected and displayed in the sign-in widget as a "Continue without account" option.

You can also use the `AnonymousSignInWidget` to include anonymous sign-in in your own custom UI:

```

import 'package:serverpod_auth_idp_flutter/serverpod_auth_idp_flutter.dart';

AnonymousSignInWidget(
  client: client,
  onAuthenticated: () {
    // Do something when the user is authenticated.
    //
    // NOTE: You should not navigate to the home screen here, otherwise
    // the user will have to sign in again every time they open the app.
  },
  onError: (error) {
    // Handle errors
    ScaffoldMessenger.of(context).showSnackBar(
      SnackBar(content: Text('Error: $error')),
    );
  }
)

```

```
    },  
  )
```

The widget displays a "Continue without account" button that creates an anonymous session when pressed. For details on customizing the button (size, shape), using a custom widget with `SignInWidget`, or building a fully custom UI with `AnonymousAuthController`, see the [customizations](#) page.