

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..53

GLOBAL OPTIONS

 Copy as Markdown

Global options

The global options of `serverpod` can be specified anywhere on the command line, in conjunction with any command.

They control output verbosity, analytics, interactive prompts, and experimental features.

Usage

Manage your serverpod app development

Usage: serverpod <command> [arguments]

Global options:

<code>-h, --help</code>	Print this usage information.
<code>-q, --quiet</code>	Suppress all cli output. Is overridden by <code>-v, --verbose</code> .
<code>-v, --verbose</code>	Prints additional information useful for development.
<code>Overrides --q, --quiet.</code>	
<code>-a, --[no-]analytics</code>	Toggles if analytics data is sent. (defaults to on)
<code>--[no-]interactive</code>	Enable interactive prompts. Automatically disabled in CI environments.
<code>--version</code>	Prints the active version of the Serverpod CLI.
<code>--experimental-features</code>	Enable experimental features. Experimental features might be removed at any time.

Available commands:

<code>cloud</code>	Manage Serverpod Cloud projects through the Serverpod Cloud.
<code>completion</code>	Command line completion commands
<code>create</code>	Creates a new Serverpod project, specify project name (must be lowercase with no special characters).
<code>create-migration</code>	Creates a migration from the last migration to the current state of the database.
<code>create-repair-migration</code>	Repairs the database by comparing the target state to the latest migration in the live database instead of comparing to the latest migration.
<code>database</code>	Manage the embedded PostgreSQL database used by a Serverpod project.



Ask AI

<code>generate</code>	Generate code from yaml files for server and clients.
<code>language-server</code>	Launches a serverpod language server communicating with JSON-RPC-2 intended to be used with a client integrated in an IDE.
<code>mcp-server</code>	Start an MCP bridge to the `serverpod start` runner of one server project.
<code>quickstart</code>	Creates a new Serverpod project with basic options.
<code>run</code>	Run a script defined in the "serverpod/scripts" section of pubspec.yaml.
<code>start</code>	Start the full development stack with hot reload: generates code, runs the server, and launches the companion Flutter apps in an interactive terminal UI.
<code>upgrade</code>	Upgrade the Serverpod CLI to the latest version.
<code>version</code>	Prints the active version of the Serverpod CLI.

Run "serverpod help <command>" for more information about a command.