

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..54.3

CREATE

 Copy as Markdown

serverpod create

`serverpod create` scaffolds a new Serverpod project. By default it generates a full server project with a database, a server package, a client package, and a Flutter app.

In an interactive terminal, `serverpod create` opens a setup screen where you choose the project's features. Pass `--template server` for a server without a Flutter app, or `--template module` to create a shareable module. To set up the prerequisites first, see [Installation](#).

The `--database`, `--redis`, `--auth`, `--webapp`, `--website`, and `--ide` flags apply only when the setup screen does not open, for example with `--no-interactive` or in CI. Without the setup screen, the project also gets Redis configuration and editor setup for Claude, Cursor, and VS Code, unless you pass `--no-redis` or choose editors with `--ide`.

To create a project without a database, deselect **Database (recommended)** under **Database & caching** on the setup screen, or pass `--no-interactive --no-database`. The new project still has the generator's database feature on, so set `database: false` under `features` in `config/generator.yaml`, then run `serverpod generate`.

Usage

Creates a new Serverpod project, specify project name (must be lowercase with no special characters).

Usage: `serverpod create` [arguments]

<code>-h, --help</code>	Print this usage information.
<code>-f, --force</code>	Create the project even if there are issues that prevent it from running out of the box.
<code>--[no-]database</code>	Include a database in the project.
<code>--[no-]redis</code>	Include Redis caching in the project.
<code>--[no-]auth</code>	Include authentication in the project. Requires database.
<code>--[no-]webapp</code>	Configure the server to host a Flutter web app.



Ask AI

`--[no-]website` Configure the server to host a website.
`--ide` Configure agent skills and MCP servers for one or more IDEs. Use "none" to disable all IDE configuration.

<code>[none]</code>	Do not configure agent skills or MCP servers
<code>[antigravity]</code>	Configure agent skills and MCP for Antigravity
<code>[codex]</code>	Configure agent skills and MCP for Codex
<code>[claude] (default)</code>	Configure agent skills and MCP for Claude
<code>[cursor] (default)</code>	Configure agent skills and MCP for Cursor
<code>[opencode]</code>	Configure agent skills and MCP for OpenCode
<code>[vscode] (default)</code>	Configure agent skills and MCP for VS Code

`-n, --name (mandatory)` The name of the project to create.
Can also be specified as the first argument.

Project Template

`-t, --template` Template to use when creating a new project

<code>[fullstack] (default)</code>	Fullstack project including a server and a companion Flutter app
<code>[server]</code>	Server project with standard features including database
<code>[module]</code>	Serverpod Module project

Run "serverpod help" to see global options.