

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..17

GET STARTED

 Copy as Markdown

Get started with authentication

When you create a project with `serverpod create`, email sign-in is already built in. The server is configured, the database is ready, and your app is connected to it. You only need to turn on the sign-in screen and run the app.

This guide walks you through that, then shows how to test signing up and signing in.



Sign In with email



[Forgot password?](#)

Sign in

Don't have an account? [Sign up](#)

or continue with



Continue with Google



Continue with Apple

Prerequisites

- A project created with `serverpod create` on Serverpod 4.0 or later. For older projects, see [Setup](#) first to add the authentication module manually.
- The Flutter SDK installed, so you can run the app.
- Docker installed and running, if your project uses a Docker Postgres. Projects on the embedded Postgres option don't need Docker.

NOTE

If you run on macOS (`flutter run -d macos`), add the Keychain Sharing entitlement before testing sign-in. See [Set up authentication on macOS](#).

Show the sign-in screen

Your app already includes a sign-in screen. It is turned off by default. Turn it on with two small edits to your app's `main.dart`.

First, import the screen:

```
import 'screens/sign_in_screen.dart';
```

Then show it as the home screen. In `MyHomePage.build()`, comment out the existing `body:` line and uncomment the `SignInScreen` block right below it, so it reads:

```
// body: const GreetingsScreen(),  
body: SignInScreen(  
  child: GreetingsScreen(  
    onSignOut: () async {  
      await client.auth.signOutDevice();  
    },  
  ),  
)
```

That is the only change your app needs.

Start your project

From the project root, start everything with one command:

```
serverpod start
```

This sets up the database and starts the server and your app.

The app opens on the sign-in screen. To create an account:

1. Choose to create a new account, enter your email, and continue.
2. Look in the server console for the verification code. While testing, it is logged instead of emailed:

```
Registration code for you@example.com: <12345678>
```

3. Enter the code, then set a password to finish.

Once you are signed in, the app shows your content with a sign-out button.

Next steps

- Send verification emails from your own email service instead of the default. See [Use your own email provider](#).
- Customize the sign-in screen. See [UI components](#).
- Build your own sign-in UI with the email controller. See [Customizing the UI](#).
- Change password rules, code length, and rate limits. See [Email configuration](#).
- Require sign-in on your endpoints. See [The basics](#).
- Add more sign-in options, like Google or Apple. See [Identity providers configuration](#).