

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..20..9

ADMIN OPERATIONS

 Copy as Markdown

Google admin operations

The Google identity provider exposes admin operations through `GoogleIdpAdmin`. Use them from server-side code to look up a Serverpod user by Google user ID and to attach a Google identity to an existing user.

WARNING

Call these methods only from secure server-side code. Do not expose them through client endpoints without authorization checks.

Accessing the GoogleIdpAdmin

The admin operations are available through `AuthServices.instance.googleIdp` after you add the Google identity provider (see [setup](#)).

```
import 'package:serverpod_auth_idp_server/providers/google.dart';
import 'package:serverpod_auth_idp_server/core.dart';

final googleIdp = AuthServices.instance.googleIdp;
final admin = googleIdp.admin;
```

Finding accounts

The `findUserByGoogleUserId` method is static. Pass the Google user ID (`userIdentifier`) when you have it and need the linked Serverpod auth user ID.

```
final userId = await GoogleIdpAdmin.findUserByGoogleUserId(
  session,
  userIdentifier: 'google-user-id',
);
```



The method returns `null` if no Google account row exists for that ID.

Linking Google authentication

Link an existing Serverpod user to a Google account. This is useful when migrating users from another provider or when an admin tool attaches Google sign-in to a user that already exists.

First load the account details from a Google ID token (and an access token when you have one), then link them:

```
final accountDetails = await admin.fetchAccountDetails(  
  session,  
  idToken: googleIdToken,  
  accessToken: googleAccessToken,  
);  
  
final googleAccount = await admin.linkGoogleAuthentication(  
  session,  
  authUserId: existingUserId,  
  accountDetails: accountDetails,  
);
```

The `accessToken` parameter may be `null` when you only have the ID token. The `linkGoogleAuthentication` method returns the created `GoogleAccount`.

Related

- [Setup](#): configure the Google Auth Platform and register the identity provider.
- [Customizations](#): configuration options and sign-in UI customization.
- [Troubleshooting](#): fix common Google sign-in errors.
- [Working with users](#): the server-side user APIs these operations complement.