

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..20..13

ADMIN OPERATIONS

 Copy as Markdown

Apple admin operations

The Apple identity provider exposes admin operations through `AppleIdpAdmin`. Use them from server-side code to check whether Sign in with Apple accounts are still in good standing and to react when Apple has revoked an account.

WARNING

Call these methods only from secure server-side code. Do not expose them through client endpoints without authorization checks.

Accessing the AppleIdpAdmin

The admin operations are available through `AuthServices.instance.appleIdp` after you add the Apple identity provider (see [setup](#)).

```
import 'package:serverpod_auth_idp_server/providers/apple.dart';
import 'package:serverpod_auth_idp_server/core.dart';

final appleIdp = AuthServices.instance.appleIdp;
final admin = appleIdp.admin;
```

Checking account status

The `checkAccountStatus` method walks Apple accounts that have not been checked in the last 24 hours and validates their stored refresh tokens with Apple. Call it from a scheduled task (for example a [recurring task](#)).

When Apple has revoked the authorization, the `onExpiredUserAuthentication` callback receives the user's auth user ID. Revoke every session created through Sign in with Apple for that user.



Ask AI

```
await admin.checkAccountStatus(  
  session,  
  onExpiredUserAuthentication: (authUserId) {  
    // Revoke sessions for this auth user.  
  },  
);
```

The method loads accounts in batches of 100 by default (`databaseBatchSize`).

Related

- [Setup](#): configure Sign in with Apple on the server and in your app.
- [Customizations](#): configuration options and sign-in UI customization.
- [Troubleshooting](#): covers the revoked-notification route, the push counterpart of the polling this page documents.
- [Working with users](#): manage auth users and react to account events.