

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..20..17

TROUBLESHOOTING

 Copy as Markdown

Troubleshoot Facebook sign-in

This page helps you identify common Sign in with Facebook failures, explains why they occur, and shows how to resolve them. For underlying issues with the native SDK, see the [flutter_facebook_auth](#) package.

Setup checklist

Go through this before investigating a specific error. Most problems come from a missed step.

Facebook App Dashboard

- ☐ Created an app with the **Authenticate and request data from users with Facebook Login** use case at [Facebook for Developers](#).
- ☐ Requested the permissions you need under **Use cases > Customize > Permissions and features** (`email` and `public_profile` are enough for basic sign-in).
- ☐ For web and macOS: set **Login with the JavaScript SDK** to **Yes** and added every serving origin to **Allowed Domains for the JavaScript SDK**.
- ☐ Copied the **App ID** and **App secret** (**App settings > Basic**) and the **Client token** (**App settings > Advanced**).
- ☐ Switched the app to **Live** mode (or added your account as a tester) so non-role users can sign in.

Server

- ☐ Added `facebookAppId` and `facebookAppSecret` to `config/passwords.yaml` under the matching environment (`development:` for local, `production:` for prod), or set the matching `SERVERPOD_PASSWORD_facebookAppId` and `SERVERPOD_PASSWORD_facebookAppSecret` environment variables.
- ☐ Added `FacebookIdpConfigFromPasswords()` to `identityProviderBuilders` in `server.dart`.



- ☐ Created a `FacebookIdpEndpoint` file in `lib/src/auth/`.
- ☐ Started the server with `serverpod start`, then created and applied the migration (pressed **M**).

Client

- ☐ Installed the `serverpod_auth_idp_flutter_facebook` package.
- ☐ Called `client.auth.initializeFacebookSignIn()` after `client.auth.initialize()` inside `initializeClient()` in your Flutter app's `lib/client.dart`.
- ☐ On **web** and **macOS**, supplied the App ID (directly or via the `FACEBOOK_APP_ID` dart-define).
- ☐ On **Android**, added `strings.xml` with the app ID, protocol scheme, and client token, plus the `<meta-data>` and `<queries>` entries in `AndroidManifest.xml`, and registered the debug or release key hash on the Facebook app.
- ☐ On **iOS**, added the `CFBundleURLTypes`, `FacebookAppID`, `FacebookClientToken`, and `LSApplicationQueriesSchemes` entries to `Info.plist`.

Web sign-in fails with "JSSDK Option is Not Toggled"

Problem: On web (or macOS), clicking the Facebook button fails immediately with a message like "JSSDK Option is Not Toggled. Please toggle the Login with Javascript SDK Option to Yes in developers.facebook.com".

Cause: Web and macOS sign-in use the Facebook JavaScript SDK, which the app must explicitly opt into. It is off by default on a new app.

Resolution: In the [Facebook App Dashboard](#), go to **Use cases > Customize > Settings**, set **Login with the JavaScript SDK** to **Yes**, and save. See [Settings](#).

Web sign-in is blocked by CORS or the domain is not allowed

Problem: The Facebook popup does not load, or the browser console shows a CORS error or "can't load URL: the domain of this URL isn't included in the app's domains".

Cause: The origin serving your Flutter web app is not listed in **Allowed Domains for the JavaScript SDK**.

Resolution: Add every serving origin to **Use cases > Customize > Settings > Allowed Domains for the JavaScript SDK**, including `https://www.facebook.com`, your development origin (e.g., `http://localhost:8082`), and your production domain. The Facebook JavaScript SDK only works over `https` in production; `localhost` over `http` loads but logs a console warning. See [Web](#).

iOS sign-in fails after denying tracking permission

Problem: On iOS, Facebook sign-in fails or the server cannot read the user's profile, especially after the user declines the App Tracking Transparency (ATT) prompt.

Cause: When ATT permission is not granted, Facebook may issue a **limited access token**. Limited tokens cannot be validated by the server or used to fetch profile data, so authentication fails.

Resolution: Request ATT authorization before starting the Facebook sign-in flow, for example with the `app_tracking_transparency` package:

```
import 'package:app_tracking_transparency/app_tracking_transparency.dart';

final status = await AppTrackingTransparency.requestTrackingAuthorization();
```

See [iOS](#) for the full iOS configuration.

Android opens Facebook but the sign-in never completes

Problem: On Android, tapping the Facebook button opens the login flow, but after authorizing, the app returns an error or the session is never established.

Cause: The key hash registered on the Facebook app does not match the keystore that signed the build, or the `strings.xml` / `AndroidManifest.xml` entries are missing or wrong.

Resolution:

1. Confirm `android/app/src/main/res/values/strings.xml` contains `facebook_app_id`, `fb_login_protocol_scheme` (your app ID prefixed with `fb`), and `facebook_client_token`.
2. Confirm the `com.facebook.sdk.ApplicationId` and `com.facebook.sdk.ClientToken` `<meta-data>` entries and the `com.facebook.katana.provider.PlatformProvider` `<queries>` entry are in `AndroidManifest.xml`.
3. Register the key hash for the keystore you are building with. Generate the debug hash with:

```
keytool -exportcert -alias androiddebugkey -keystore ~/.android/debug.keystore |
openssl sha1 -binary | openssl base64
```

Add the output under the Android platform in the Facebook app. For release builds, generate and add the release keystore's hash too. See [Android](#).

Sign-in works for you but not for other users

Problem: Sign-in works for your own Facebook account but other users get an error saying the app is not available or is still in development.

Cause: The Facebook app is in **Development mode**, which only allows people with a role on the app (admins, developers, testers) to sign in.

Resolution: Switch the app to **Live** mode at the top of the [Facebook App Dashboard](#), or add the specific users as testers under **App roles**. Going Live requires a Privacy Policy URL and, for permissions beyond `email` and `public_profile`, App Review. See [Publishing to production](#).

Sign-in succeeds but the user has no email

Problem: The user signs in successfully, but the server-side `FacebookAccountDetails.email` value is `null`.

Cause: Users can decline to share their email during the Facebook login flow, or the `email` permission was not requested. A custom validator that requires an email will then block the sign-in.

Resolution:

- Confirm the `email` permission is requested (it is included by default; see [Accessing Facebook APIs](#)).
- If you do not strictly need an email, keep the default validator, which only checks `userIdentifier`. Avoid rejecting accounts without an email unless you must. See [Custom account validation](#).
- Surface a helpful message to the user instead of failing silently.

Server crashes on startup with a missing password

Problem: The server crashes on startup with a `PasswordNotFoundException` for `facebookAppId` or `facebookAppSecret`.

Cause: The keys are missing from `config/passwords.yaml`, are spelled differently, or are not present under the active environment section.

Resolution: Confirm both keys exist under the section matching your run mode (`development:` when running locally, `production:` when deployed):

```
development:
  facebookAppId: 'your-facebook-app-id'
  facebookAppSecret: 'your-facebook-app-secret'
```

Quoting the values is a safeguard. YAML parses unquoted values that look like numbers as numbers instead of strings. Facebook App IDs are numeric, so an unquoted `facebookAppId` crashes startup with an "Invalid

password entries" error instead of this one. On Serverpod Cloud, set them with `serverpod cloud password set` instead. See [Publishing to production](#).

Server crashes on first Facebook sign-in with "no such table"

Problem: The server builds and starts, but crashes when a user tries to sign in with Facebook. The error cites a missing table such as `serverpod_auth_idp_facebook_account`.

Cause: The database migration that creates the provider's tables was never created or applied.

Resolution: In the running `serverpod start` terminal, press **M** to create and apply the migration. See [Start the server](#).

Sign-in works in dev but fails after deploy

Problem: Facebook sign-in works locally but fails in production.

Cause: The production domain is not registered on the Facebook app, the app is still in Development mode, or the production Flutter build was not given the App ID.

Resolution:

1. Add your production domain to **Allowed Domains for the JavaScript SDK** (web and macOS) and register the release key hash (Android).
2. Switch the app to **Live** mode.
3. Confirm the production server has `facebookAppId` and `facebookAppSecret` set, and that the production web build passes `--dart-define=FACEBOOK_APP_ID=...`. See [Publishing to production](#).

Related

- [Setup](#): set up the Facebook identity provider on the server and in your app.
- [Customizations](#): configuration options and sign-in UI customization.
- [UI components](#): the sign-in widgets and how to compose them.