

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..54.2

COMPLETION

 Copy as Markdown

serverpod completion

`serverpod completion` sets up shell tab-completion for the `serverpod` command. Use the `install` subcommand to add completion to your shell, or `generate` to print a completion specification you can wire up yourself.

Both subcommands target a completion tool with `--tool`, either `completely` or `carapace`. For a walkthrough, see [Shell completion](#).

Usage

Command line completion commands

Usage: `serverpod completion <subcommand> [arguments]`

`-h, --help` Print this usage information.

Available subcommands:

`generate` Generate a command line completion specification

`install` Install a command line completion script

Run "`serverpod help`" to see global options.

Sub commands

generate

Generate a command line completion specification

Usage: `serverpod completion generate [arguments]`

`-h, --help` Print this usage information.

`-t, --tool (mandatory)` The completion tool to target

`[completely]` Use the ``completely`` tool (<https://github.com/bashly-framework/completely>)



```
[carapace]      Use the `carapace` tool (https://carapace.sh/)

-e, --exec-name  Override the name of the executable
-f, --file       Write the specification to a file instead of stdout
```

Run "serverpod help" to see global options.

install

Install a command line completion script

Usage: serverpod completion install [arguments]

```
-h, --help      Print this usage information.
-t, --tool (mandatory)  The completion tool to target

[completely]   Use the `completely` tool (https://github.com/bashly-
framework/completely)
[carapace]     Use the `carapace` tool (https://carapace.sh/)
```

```
-e, --exec-name  Override the name of the executable
-d, --write-dir  Override the directory to write the script to
```

Run "serverpod help" to see global options.