

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..54.6

DATABASE

 Copy as Markdown

serverpod database

The `serverpod database` command manages the embedded PostgreSQL database of a Serverpod project. Use `serverpod database start` to boot the database on its own, without starting the server, and keep it running until you stop it with Ctrl+C. This is useful for connecting external database tools while the server is stopped.

The database configuration comes from the run mode selected with `--mode`, which must have `database.dataPath` set. For that option and its default, see the [Configuration reference](#).

Usage

Manage the embedded PostgreSQL database used by a Serverpod project.

Usage: `serverpod database <subcommand> [arguments]`

`-h, --help` Print this usage information.

Available subcommands:

`start` Start the configured embedded PostgreSQL database over TCP.

Run "`serverpod help`" to see global options.

Sub commands

start

Start the configured embedded PostgreSQL database over TCP.

Usage: `serverpod database start [arguments]`

`-h, --help` Print this usage information.

`-s, --server-dir=<path>` Server project directory. Defaults to auto-detection.

`-m, --mode` Serverpod run mode whose database config should be used (defaults to "development")



Ask AI

`-p, --port=<integer>` TCP port override. Defaults to the configured database port.

Run "serverpod help" to see global options.