

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..54.10

QUICKSTART

 Copy as Markdown

serverpod quickstart

`serverpod quickstart` creates a new Serverpod project with a small set of options, suited to a quick experiment or a simple app. It is a streamlined version of `serverpod create`.

Choose a template with `--template`:

- `fullstack` (default): a server and a Flutter app.
- `server`: a server only.
- `module`: a shareable module.

For a guided first project, see [Quickstart](#).

Usage

Creates a new Serverpod project with basic options.
Suitable for a simple project or quick experiment.
Specify project name (must be lowercase with no special characters).

Usage: `serverpod quickstart [arguments]`

<code>-h, --help</code>	Print this usage information.
<code>-f, --force</code>	Create the project even if there are issues that prevent it from running out of the box.
<code>-t, --template</code>	Template to use when creating a new project
<code>[fullstack]</code> (default)	Fullstack project including a server and a companion Flutter app
<code>[server]</code>	Server project with standard features including database
<code>[module]</code>	Serverpod Module project
<code>-n, --name (mandatory)</code>	The name of the project to create. Can also be specified as the first argument.



Ask AI

Run "serverpod help" to see global options.