

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3..54.12

START

 Copy as Markdown

serverpod start

The `serverpod start` command runs your project in development mode. It generates the latest code, starts the server with hot reload, and launches your companion Flutter apps, all in a single interactive terminal.

```
serverpod start
```

Run it from anywhere inside your project folder.

Usage

Start the full development stack with hot reload: generates code, runs the server, and launches the companion Flutter apps in an interactive terminal UI.

Usage: `serverpod start [-- <server-args>]`

`-h, --help` Print this usage information.

`-w, --[no-]watch` Watch files and use the Frontend Server for fast incremental compilation. With `--no-watch`, the server is started via ``dart run``.
(defaults to on)

`-d, --directory` The server directory (defaults to auto-detect from current directory).
(defaults to "")

`--[no-]docker` Start Docker Compose services if a Docker Compose file exists. Defaults to on if the project has a Docker Compose file and the database is configured to PostgreSQL on localhost without a `dataPath`. Otherwise, defaults to off. Pass `--docker` or `--no-docker` to override the default behavior.

`--[no-]tui` Show interactive terminal UI.
(defaults to on)

`--[no-]flutter` Auto-launch the companion Flutter apps as configured on the server `pubspec.yaml` with ``auto_launch: true``. Use `--no-flutter` to disable auto-launch. Apps can still be started on demand from the TUI.
(defaults to on)

Run `"serverpod help"` to see global options.



Ask AI

