

This is unreleased documentation for Serverpod **Next** version.

For up-to-date documentation, see the [latest version](#) (4.0.0).

3.5

COMMAND LINE COMPLETION

 Copy as Markdown

Command line completion

As a `serverpod` user, you can enable command line completion in most shells. The Serverpod CLI supports completion through [Carapace](#), which provides tab-completion for commands, options, and their values in bash, zsh, fish, PowerShell, and more.

Installing completion

Prerequisites

Install [Carapace](#) for your platform:

macOS:

```
brew install carapace
```

Ubuntu/Debian:

```
sudo apt install carapace-bin
```

Windows:

```
winget install carapace
```

For other platforms, see the [Carapace installation guide](#).

Enable Carapace completion for Serverpod

Bash



Install the completion spec:

```
serverpod completion install --tool carapace
```

Then add the following to your `~/.bashrc` to enable Carapace:

```
source <(carapace _carapace)
```

Restart your shell or run `source ~/.bashrc` to apply.

Zsh

Install the completion spec:

```
serverpod completion install --tool carapace
```

Then add the following to your `~/.zshrc` to enable Carapace:

```
zstyle ':completion:*' format '${\e[2;37mCompleting %d\e[m}'  
source <(carapace _carapace)
```

Restart your shell or run `source ~/.zshrc` to apply.

Other shells

Carapace supports fish, PowerShell, elvish, and more. After installing the completion spec with `serverpod completion install --tool carapace`, see the [Carapace setup documentation](#) for instructions specific to your shell.

Alternative: Completely

The Serverpod CLI also supports [Completely](#), a lightweight alternative to Carapace that supports bash and zsh. Unlike Carapace, Completely does not require a separate tool running in your shell. It generates a standalone bash completion script.

To generate a Completely spec and create a completion script:

```
serverpod completion generate --tool completely -f serverpod.yaml  
completely generate serverpod.yaml serverpod.bash
```

Then source the generated script in your shell config (e.g., `source /path/to/serverpod.bash` in `~/.bashrc` or `~/.zshrc`).

 NOTE

Carapace is the recommended tool as it supports a wider range of shells and comes with a pre-built completion spec that can be installed directly with `serverpod completion install`. Completely requires generating and processing the script manually.