

A benchmark of expert-level academic questions to assess AI capabilities

<https://doi.org/10.1038/s41586-025-09962-4>

Center for AI Safety*, Scale AI* & HLE Contributors Consortium*

Received: 7 May 2025

Accepted: 25 November 2025

Published online: 28 January 2026

Open access

 Check for updates

Benchmarks are important tools for tracking the rapid advancements in large language model (LLM) capabilities. However, benchmarks are not keeping pace in difficulty: LLMs now achieve more than 90% accuracy on popular benchmarks such as Measuring Massive Multitask Language Understanding¹, limiting informed measurement of state-of-the-art LLM capabilities. Here, in response, we introduce Humanity's Last Exam (HLE), a multi-modal benchmark at the frontier of human knowledge, designed to be an expert-level closed-ended academic benchmark with broad subject coverage. HLE consists of 2,500 questions across dozens of subjects, including mathematics, humanities and the natural sciences. HLE is developed globally by subject-matter experts and consists of multiple-choice and short-answer questions suitable for automated grading. Each question has a known solution that is unambiguous and easily verifiable but cannot be quickly answered by internet retrieval. State-of-the-art LLMs demonstrate low accuracy and calibration on HLE, highlighting a marked gap between current LLM capabilities and the expert human frontier on closed-ended academic questions. To inform research and policymaking upon a clear understanding of model capabilities, we publicly release HLE at <https://lastexam.ai>.

The capabilities of large language models (LLMs) have advanced markedly, exceeding human performance across a diverse array of tasks. To systematically measure these capabilities, LLMs are evaluated on benchmarks: collections of questions that assess model performance on tasks such as math, programming or biology. However, state-of-the-art LLMs^{2–6} now achieve more than 90% accuracy on popular benchmarks such as Measuring Massive Multitask Language Understanding (MMLU)¹, which were once challenging frontiers for LLMs. The saturation of existing benchmarks, as shown in Fig. 1, limits our ability to precisely measure artificial intelligence (AI) capabilities and calls for more challenging evaluations that can meaningfully assess the rapid improvements in LLM capabilities at the frontiers of human knowledge.

To address this gap, we introduce HLE (originally defined as Humanity's Last Exam, although we will use the term HLE for this paper), a benchmark of 2,500 challenging questions from dozens of subject areas, designed to assess LLM capabilities at an expert level in broad academic subjects. HLE is developed by academics and domain experts, providing a precise measure of capabilities as LLMs continue to improve (see section 'Collection'). HLE is multi-modal, featuring questions that are either text-only or accompanied by an image reference and includes both multiple-choice and exact-match questions for automated answer verification. Questions are original, precise, unambiguous and resistant to simple internet lookup or database retrieval. Among the diversity of questions in the benchmark, HLE emphasizes world-class mathematics problems aimed at testing deep reasoning skills broadly applicable across multiple academic areas.

We use a multi-stage review process to thoroughly ensure question difficulty and quality (see section 'Review'). Before submission, each question is tested against state-of-the-art LLMs to verify its difficulty—questions are rejected if LLMs can answer them correctly. Questions submitted are then processed through a two-stage reviewing process: (1) an initial feedback round with multiple graduate-level reviewers and (2) an approval of organizer and expert reviewer, ensuring quality and adherence to our submission criteria. Following the release, we conducted a public review period, welcoming community feedback to correct any points of concern in the dataset.

Frontier LLMs consistently demonstrate low accuracy across all models, highlighting a marked gap between current capabilities and expert-level academic performance (see section 'Evaluation'). Models also provide incorrect answers with high confidence rather than acknowledging uncertainty on these challenging questions, with most models exhibiting root mean square (RMS) calibration errors above 70%.

As AI systems approach human expert performance in many domains, precise measurement of their capabilities and limitations is essential for informing research, governance and the broader public. High performance on HLE would suggest expert-level capabilities on closed-ended academic questions. To establish a common reference point for assessing these capabilities, we publicly release a large number of 2,500 questions from HLE to enable this precise measurement, while maintaining a private test set to assess potential model overfitting.

*Lists of authors and their affiliations appear at the end of the paper.




Fig. 1 | Performance of frontier LLMs on popular benchmarks and HLE. Compared with the saturation of other popular capability benchmarks, HLE accuracy remains low across several frontier models, demonstrating its effectiveness for measuring advanced, closed-ended, academic capabilities.

Dataset

Collection

HLE consists of 2,500 challenging questions across over a hundred subjects. A high-level summary is provided in Fig. 2. HLE is a global collaborative effort, with questions from nearly 1,000 subject expert contributors affiliated with more than 500 institutions across 50 countries—comprised mostly of professors, researchers and graduate degree holders. Examples of the diverse and challenging questions submitted to HLE are shown in Fig. 3.

Question style. HLE contains two question formats: exact-match questions (models provide an exact string as output) and multiple-choice questions (the model selects one of five or more answer choices). HLE is a multi-modal benchmark, with around 14% of questions requiring comprehending both text and an image; 24% of questions are multiple-choice, with the remainder being exact match.

Each question submission includes several required components: the question text itself, answer specifications (either an exact-match answer or multiple-choice options with the correct answer marked), detailed rationale explaining the solution, academic subject and name of the contributor and institutional affiliation to maintain accountability and accuracy.

Submission format. To ensure question quality and integrity, we enforce strict submission criteria. Questions should be precise,

unambiguous, solvable and non-searchable, ensuring models cannot rely on memorization or simple retrieval methods. All submissions must be original work or non-trivial syntheses of published information, although contributions from unpublished research are acceptable. Questions typically require graduate-level expertise or test knowledge of highly specific topics (for example, precise historical details, trivia and local customs) and have specific, unambiguous answers accepted by domain experts. When LLMs provide correct answers with faulty reasoning, authors are encouraged to modify question parameters, such as the number of answer choices, to discourage false positives. We require clear English with precise technical terminology, supporting LaTeX notation wherever necessary. Answers are kept short and easily verifiable for exact-match questions to support automatic grading. We prohibit open-ended questions, subjective interpretations, and content related to weapons of mass destruction. Finally, every question is accompanied by a detailed solution to verify accuracy. More details about guidelines for contributors can be found in Supplementary Information section 1.

Prize pool. To attract high-quality submissions, we establish a USD\$500,000 prize pool, with prizes of USD\$5,000 for each of the top 50 questions and USD\$500 for each of the next 500 questions, as determined by organizers. This incentive structure, combined with the opportunity for paper co-authorship for anyone with an accepted question in HLE, draws participation from qualified experts, particularly those with advanced degrees or notable technical experience in their fields.

Review

LLM difficulty check. To ensure question difficulty, each question is first validated against several frontier LLMs before submission (Methods). If the LLMs cannot solve the question (or, in the case of multiple choices, if the models on average do worse than random guessing), the question proceeds to the next stage: human expert review. In total, we logged more than 70,000 attempts, resulting in approximately 13,000 questions, which stumped LLMs that were forwarded to expert human review.

Expert review. Our human reviewers possess a graduate degree (for example, master's, PhD and JD) in their fields. Reviewers select submissions in their domain, grading them against standardized rubrics and offering feedback when applicable. There are two rounds of reviews. The first round focuses on iteratively refining submissions, with each question receiving between one and three reviews. The primary goal




Fig. 2 | Distribution of HLE questions across categories. HLE consists of 2,500 exam questions in over a hundred subjects, grouped into eight high-level categories.

Classics

Question:

Here is a representation of a Roman inscription, originally found on a tombstone. Provide a translation for the Palmyrene script.
RGYNᵇ BT HRY BR ᵇTᵇ HBL

Herry T
Merton College, Oxford

Ecology

Question:

Hummingbirds within Apodiformes uniquely have a bilaterally paired oval bone, a sesamoid embedded in the caudolateral portion of the expanded, cruciate aponeurosis of insertion of m. depressor caudae. How many paired tendons are supported by this sesamoid bone? Answer with a number.

Edward V
Massachusetts Institute of Technology

Mathematics

Question:

The set of natural transformations between two functors $F, G : C \rightarrow D$ can be expressed as the end

$$\text{Nat}(F, G) \equiv \int_A \text{Hom}_D(F(A), G(A)).$$

Define set of natural cotransformations from F to G to be the coend

$$\text{CoNat}(F, G) \equiv \int^A \text{Hom}_D(F(A), G(A)).$$

Let:

- $F = B_\bullet(\Sigma_4)_*$ be the under ∞ -category of the nerve of the delooping of the symmetric group Σ_4 on 4 letters under the unique 0-simplex $*$ of $B_\bullet \Sigma_4$.

- $G = B_\bullet(\Sigma_7)_*$ be the under ∞ -category nerve of the delooping of the symmetric group Σ_7 on 7 letters under the unique 0-simplex $*$ of $B_\bullet \Sigma_7$.

How many natural cotransformations are there between F and G ? Here ∞ -categories are modelled as quasicategories, and F and G are functors from the opposite of the simplicial category to the category of sets

Emily S
University of São Paulo

Computer Science

Question:

Let G be a graph. An edge-indicator of G is a function $a : \{0,1\} \rightarrow V(G)$ such that $\{a(0), a(1)\} \in E(G)$.

Consider the following Markov Chain $M = M(G)$:
The statespace of M is the set of all edge-indicators of G , and the transitions are defined as follows:

- Assume $M_t = a$.
- pick $b \in \{0,1\}$ u.a.r.
- pick $v \in N(a(1-b))$ u.a.r. (here $N(v)$ denotes the open neighbourhood of v)
- set $a'(b) = v$ and $a'(1-b) = a(1-b)$
- Set $M_{t+1} = a'$

We call a class of graphs $\mathcal{G}$ well-behaved if, for each $G \in \mathcal{G}$ the Markov chain $M(G)$ converges to a unique stationary distribution, and the unique stationary distribution is the uniform distribution.

Which of the following graph classes is well-behaved?


Answer Choices:

- The class of all non-bipartite regular graphs
- The class of all connected cubic graphs
- The class of all connected graphs
- The class of all connected non-bipartite graphs
- The class of all connected bipartite graphs.

Marc R
Queen Mary University of London

Chemistry

Question:



The reaction shown is a thermal pericyclic cascade that converts the starting heptaene into endiandric acid B methyl ester. The cascade involves three steps: two electrocyclizations followed by a cycloaddition. What types of electrocyclizations are involved in step 1 and step 2, and what type of cycloaddition is involved in step 3?

Provide your answer for the electrocyclizations in the form of $[m\pi]$ -con or $[m\pi]$ -dis (where n is the number of π electrons involved, and whether it is conrotatory or disrotatory), and your answer for the cycloaddition in the form of $[m+n]$ (where m and n are the number of atoms on each component).

Noah B
Stanford University

Linguistics

Question:

I am providing the standardized Biblical Hebrew source text from the Biblia Hebraica Stuttgartensia (Psalms 104:7). Your task is to distinguish between closed and open syllables. Please identify and list all closed syllables (ending in a consonant sound) based on the latest research on the Tiberian pronunciation tradition of Biblical Hebrew by scholars such as Geoffrey Khan, Aaron D. Hornkohl, Kim Phillips, and Benjamin Suchard. Medieval sources, such as the Karaite transcription manuscripts, have enabled modern researchers to better understand specific aspects of Biblical Hebrew pronunciation in the Tiberian tradition, including the qualities and functions of the sheva and which letters were pronounced as consonants at the ends of syllables.

מִן־גַּעְרָתְךָ יִנְסִיחַ מִן־קוֹל־אֲעֻמָּה יִחְפְּזוּ (Psalms 104:7) ?

Lina B
University of Cambridge

Fig. 3 | Example questions from HLE. Samples of the diverse and challenging questions submitted to HLE.




Fig. 4 | HLE dataset creation pipeline. We accept questions that make frontier LLMs fail, then iteratively refine them with the help of expert peer reviewers. Each question is then manually approved by organizers or expert reviewers

is to help the question contributors (who are primarily academics and researchers from a wide range of disciplines) better design questions that are closed-ended, robust and of high quality for AI evaluation. In the second round, good and outstanding questions from the first round are identified and approved by organizers and reviewers to be included in the final HLE dataset. Details, instructions and rubrics for both rounds can be found in Supplementary Information section 2. Figure 4 shows our full process.

Evaluation

We evaluate the performance of state-of-the-art LLMs on HLE and analyse their capabilities across different question types and domains. We describe our evaluation setup (see section ‘Setup’) and present several quantitative results on metrics that track model performance (see section ‘Quantitative results’).

Setup

After data collection and review, we evaluated our final HLE dataset on additional frontier multi-modal LLMs. We use a standardized system prompt that structures model responses into explicit reasoning followed by a final answer. As the question–answers are precise and close-ended, we use o3-mini as a judge to verify answer correctness against model predictions while accounting for equivalent formats (for example, decimals compared with fractions or estimations). Evaluation prompts are detailed in the Methods.

Quantitative results

Accuracy. All frontier models achieve low accuracy on HLE (Table 1), highlighting substantial room for improvement in narrowing the gap between current LLMs and expert-level academic capabilities on closed-ended questions. These low scores are partially by design the dataset collection process attempts to filter out questions that existing models can answer correctly. Nevertheless, we notice on evaluation that models exhibit non-zero accuracy. This is due to inherent noise in model inference—models can inconsistently guess the right answer or guess worse than random chance for multiple-choice questions. We notice an elevated accuracy on multiple-choice questions compared with exact-answer questions in Extended Data Table 3. We choose to leave these questions in the dataset as a natural component instead of strongly adversarially filtering. However, we stress that the true capability floor of frontier models on the dataset will remain an open question, and small inflections close to zero accuracy are not strongly indicative of progress.

Calibration error. Given low performance on HLE, models should be calibrated, recognizing their uncertainty rather than confidently provide incorrect answers. To measure calibration, we prompt models to provide both an answer and their confidence from 0% to 100% (Methods), using the setup from⁷. The implementation of

trained by organizers. A private held-out set is kept apart from the public set to assess model overfitting and gaming on the public benchmark.

our RMS calibration error is from ref. 8. The stated confidence of a well-calibrated model should match its actual accuracy, for example, achieving 50% accuracy on questions, in which it claims 50% confidence. Table 1 shows poor calibration across all models, reflected in high RMS calibration error scores. Models frequently provide incorrect answers with high confidence on HLE, failing to recognize when questions exceed their capabilities.

Inference time computation. Reasoning models are designed to spend extra compute thinking before answering: they generate intermediate reasoning tokens and then produce the final response, which means substantially more tokens must be decoded at inference time^{5,6}. To shed light on this in our evaluation, we analyse the compute-intensive scaling of output tokens (including reasoning tokens) across several state-of-the-art reasoning models in Fig. 5. Through binning output lengths with a log₂ scale, we observe a log-linear scaling of accuracy with more reasoning tokens; however, this trend reverses after 2¹⁴ tokens, highlighting that a larger reasoning budget is not always optimal. The observation that accuracy benefits diminish beyond a certain threshold suggests that future models should improve not only their raw accuracy on HLE but also their computational efficiency.

Discussion
Limitations

Although present-day LLMs achieve very low accuracy on HLE, recent history shows benchmarks are quickly saturated—with models

Table 1 | Accuracy and RMS calibration error of different models on HLE, demonstrating low accuracy and high calibration error across all models

Model	Accuracy (%) ↑	Calibration error (%) ↓
GPT-4o	2.7 ± 0.6	89
Claude 3.5 Sonnet	4.1 ± 0.8	84
Gemini 1.5 Pro	4.6 ± 0.8	88
o1	8.0 ± 1.1	83
DeepSeek R1 ^a	8.5 ± 1.2	73
Post-release models		
Claude 4 Sonnet	7.8 ± 1.1	75
Gemini 2.5 Pro	21.6 ± 1.6	72
GPT-5	25.3 ± 1.7	50

The most updated evaluations are hosted on <https://lastexam.ai>. Post-release models are released after HLE was open-sourced; we separate them as model builders have access to the HLE dataset. We report a breakdown of the text-only subset and other categories in Extended Data Tables 1 and 2.

^aModel is not multi-modal, evaluated on a text-only subset.




Fig. 5 | Accuracy compared with reasoning token budget. Accuracy binned by the total number of generated output tokens, showing a log-linear increase in accuracy peaking around 2^{14} tokens before reversing.

markedly progressing from near-zero to near-perfect performance in a short timeframe^{9,10}. High accuracy on HLE would demonstrate expert-level performance on closed-ended, verifiable questions and cutting-edge scientific knowledge, but it would not alone suggest autonomous research capabilities or artificial general intelligence¹¹. HLE tests structured academic problems rather than open-ended research or creative problem-solving abilities, making it a focused measure of technical knowledge and reasoning across a diverse range of subjects, albeit with a stronger representation in math and STEM (science, technology, engineering and mathematics) disciplines, as shown in Fig. 2. By pushing the limits of established closed-ended benchmarks, HLE is intended to hasten the transition towards a new class of benchmarks focused on more dynamic and open-ended AI capabilities.

Impact

By providing a clear measure of AI progress, HLE creates a common reference point for scientists and policymakers to assess AI capabilities. This enables more informed discussions about development trajectories, potential risks and necessary governance measures.

Online content

Any methods, additional references, Nature Portfolio reporting summaries, source data, extended data, supplementary information, acknowledgements, peer review information; details of author contributions and competing interests; and statements of data and code availability are available at <https://doi.org/10.1038/s41586-025-09962-4>.

- Hendrycks, D. et al. Measuring massive multitask language understanding. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=d7KJmI3GmQ> (ICLR, 2021).
- Gemini Team Google. Gemini 1.5: unlocking multimodal understanding across millions of tokens of context. Preprint at <https://arxiv.org/abs/2403.05530> (2024).
- OpenAI et al. GPT-4 technical report. Preprint at <https://arxiv.org/abs/2303.08774> (2024).
- The Claude 3 Model Family: Opus, Sonnet, Haiku (Anthropic, 2024).
- OpenAI o1 System Card (OpenAI, 2024).
- Guo, D. et al. DeepSeek-R1 incentivizes reasoning in LLMs through reinforcement learning. *Nature* **645**, 633–638 (2025).
- Wei, J. et al. Measuring short-form factuality in large language models. Preprint at <https://arxiv.org/abs/2411.04368> (2024).
- Hendrycks, D. et al. PixMix: Dreamlike pictures comprehensively improve safety measures. In *Proc. IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 16783–16792 (IEEE/CVF, 2022).
- Rein, D. et al. GPQA: A graduate-level Google-proof Q&A benchmark. In *Proc. First Conference on Language Modeling (COLM)* <https://openreview.net/forum?id=Ti67584b98> (COLM, 2024).
- Chollet, F., Knoop, M., Kamradt, G. & Landers, B. ARC prize 2024: technical report. Preprint at <https://arxiv.org/abs/2412.04604> (2024).
- Hendrycks, D. et al. A definition of AGI. Preprint at <https://arxiv.org/abs/2510.18212> (2025).

Publisher's note Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.



Open Access This article is licensed under a Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License, which permits any non-commercial use, sharing, distribution and reproduction in any medium or format, as long as you give appropriate credit to the original author(s) and the source, provide a link to the Creative Commons licence, and indicate if you modified the licensed material. You do not have permission under this licence to share adapted material derived from this article or parts of it. The images or other third party material in this article are included in the article's Creative Commons licence, unless indicated otherwise in a credit line to the material. If material is not included in the article's Creative Commons licence and your intended use is not permitted by statutory regulation or exceeds the permitted use, you will need to obtain permission directly from the copyright holder. To view a copy of this licence, visit <http://creativecommons.org/licenses/by-nc-nd/4.0/>.

© The Author(s) 2026

Center for AI Safety

Long Phan^{1✉}, Alice Gatti¹, Nathaniel Li¹, Adam Khoja¹, Ryan Kim¹, Richard Ren¹, Jason Hausenloy¹, Oliver Zhang¹, Mantas Mazeika¹ & Dan Hendrycks^{1✉}

¹Center for AI Safety, San Francisco CA, USA. ✉e-mail: agibenchmark@safe.ai; dan@safe.ai

Scale AI

Ziwen Han², Josephina Hu², Hugh Zhang², Chen Bo Calvin Zhang², Mohamed Shaaban², John Ling², Sean Shi², Michael Choi², Anish Agrawal², Arnav Chopra², Aakaash Nattanmai², Gordon McKellips², Anish Cheraku², Asim Suhail², Ethan Luo², Marvin Deng², Jason Luo², Ashley Zhang², Kevin Jindel², Jay Paek², Kasper Halevy², Allen Baranov², Michael Liu², Advait Avadhanam², David Zhang², Vincent Cheng², Brad Ma², Evan Fu², Liam Do², Joshua Lass², Hubert Yang², Surya Sunkari², Vishruth Bharath², Violet Ai², James Leung², Rishit Agrawal², Alan Zhou², Kevin Chen², Tejas Kalpathi², Ziqi Xu², Gavin Wang², Tyler Xiao², Erik Maung², Sam Lee², Ryan Yang², Roy Yue², Ben Zhao², Julia Yoon², Xiangwan Sun², Aryan Singh², Clark Peng², Tyler Osbey², Taozhi Wang², Daryl Echeazu², Timothy Wu², Spandan Patel², Vidhi Kulkarni², Vijaykarti Sundarapandian², Andrew Le², Zafir Nasim², Srikanth Yalam², Ritesh Kasamsetty², Soham Samal², David Sun², Nihar Shah², Abhijeet Saha², Alex Zhang², Leon Nguyen², Laasya Nagumalli², Kaixin Wang², Aidan Wu², Anwith Telluri², Summer Yue² & Alexandr Wang²

²Scale AI, San Francisco CA, USA.

HLE Contributors Consortium

Dmitry Dodonov³, Tung Nguyen⁴, Jaeho Lee⁵, Daron Anderson³, Mikhail Doroshenko³, Alun Cennyth Stokes³, Mubeen Mahmood⁶, Oleksandr Pokutnyi^{7,8}, Oleg Iskra⁹, Jessica P. Wang¹⁰, John-Clark Levin¹¹, Mstyslav Kazakov¹², Fiona Feng¹³, Steven Y. Feng¹⁴, Haoran Zhao¹⁵, Michael Yu³, Varun Gangal³, Chelsea Zou¹⁴, Zihan Wang¹⁶, Serguei Popov¹⁷, Robert Gerbicz¹⁸, Geoff Galgon¹⁹, Johannes Schmitt²⁰, Will Yeadon²¹, Yongki Lee²², Scott Sauers²³, Alvaro Sanchez²³, Fabian Giska²³, Marc Roth²⁴, Søren Riis²⁴, Saiteja Utpala²⁵, Noah Burns¹⁴, Gashaw M. Goshu³, Mohinder Maheshbhai Naiya²⁶, Chidozie Agu²⁷, Zachary Giboney², Antrell Cheatom²⁸, Francesco Fournier-Facio¹¹, Sarah-Jane Crowson²⁹, Lennart Finkbe³⁰, Zerui Cheng³⁰, Jennifer Zampese³¹, Ryan G. Hoerr³², Mark Nandor³, Hyunwoo Park³, Tim Gehringer³⁰, Jiaqi Cai³³, Ben McCarty³⁴, Alexis C. Garretson^{35,36}, Edwin Taylor³, Damien Sileo³⁷, Qiuyu Ren³⁸, Usman Qazi^{39,40}, Lianghui Li⁴¹, Jungbae Nam⁴², John B. Wydalits³, Pavel Arkhipov⁴³, Jack Wei Lun Shi⁴⁴, Aras Bacho⁴⁵, Chris G. Willcocks²¹, Hangrui Cao⁹, Sumeet Motwani⁴⁶, Emily de Oliveira Santos⁴⁷, Johannes Veith^{48,49}, Edward Vendrow³⁵, Doru Cojoc⁵⁰, Kengo Zenitani⁵¹, Joshua Robinson⁵¹, Longke Tang³⁰, Yuqi Li⁵², Joshua Vendrow³³, Natanael Wildner Fraga³, Vladyslav Kuchkin⁵³.

Haoqin Tu³²⁷, Sejong Kim³³⁹, Yushun Chen³⁶², Sara Vera Marjanović¹²¹, Junwoo Ha³⁶³, Grzegorz Luczyna³, Jeff J. Ma⁷⁶, Zewen Shen⁵⁹, Dawn Song³⁸, Cedegao E. Zhang³³, Zhun Wang³⁸, Gaël Gendron²⁶⁴, Yunze Xiao⁹, Leo Smucker²⁹, Erica Weng⁹, Kwok Hao Lee⁴⁴, Zhe Ye³⁸, Stefano Ermon¹⁴, Ignacio D. Lopez-Miguel¹⁸⁹, Theo Knights⁸¹, Anthony Gitter^{90,365}, Namkyu Park³⁶⁶, Boyi Wei³⁰, Hongzheng Chen¹⁰⁸, Kunal Pai³⁶⁷, Ahmed Elkhanany³⁶⁸, Han Lin³⁴⁶, Philipp D. Siedler³³², Jichao Fang²⁹⁴, Ritwik Mishra³⁶⁹, Károly Zsolnai-Fehér³⁷⁰, Xilin Jiang⁵⁰, Shadab Khan³⁷¹, Jun Yuan³⁷², Rishab Kumar Jain¹⁰⁷, Xi Lin⁷⁶, Mike Peterson³, Zhe Wang³⁷³, Aditya Malusare³⁷⁴, Maosen Tang¹⁰⁸, Isha Gupta¹⁴³, Ivan Fosin³, Timothy Kang³, Barbara Dworakowska³²⁶, Kazuki Matsumoto³⁷⁵, Guangyao Zheng¹⁹⁷, Gerben Sewuster³⁷⁶, Jorge Pretel Villanueva³⁷⁷, Ivan Rannev³⁷⁸, Igor Chernyavsky⁸⁵, Jiale Chen¹⁰¹, Deepayan Banik⁵⁹, Ben Racz⁹, Wenchao Dong³⁷⁹, Jianxin Wang¹⁹⁶, Laila Bashmal³, Duarte V. Gonçalves¹⁷, Wei Hu⁸⁶, Kaushik Bar³⁸⁰, Ondrej Bohdal³², Atharv Singh Patlan³⁰, Shehzaad Dhuliawala²⁰, Caroline Geirhos³⁸¹, Julien Wist³⁸², Yuval Kansal³⁰, Bingsen Chen⁸⁶, Kutay Tire³⁸³, Atak Talay Yücel³⁸³, Brandon Christof⁴³, Veerupaksh Singla³⁷⁴, Zijian Song³⁶⁷, Sanxing Chen¹⁵⁹, Jixian Ge³⁸, Kaustubh Ponske⁹⁷, Isaac Park⁸⁶, Tianneng Shi³⁸, Martin Q. Ma⁸¹, Joshua Mak³⁸⁴, Sherwin Lai¹⁴, Antoine Moulin³⁸⁵, Zhuo Cheng⁹, Zhandu Zhu⁵⁹, Ziyi Zhang⁸¹, Vaidehi Patil³⁴⁶, Ketan Jha³⁸⁶, Qitong Men⁹⁶, Jiaxuan Wu⁹⁰, Tianchi Zhang⁸¹, Bruno Hebling Vieira¹⁶², Alham Fikri Aji⁹⁷, Jae-Won Chung⁷⁶, Mohammed Mahfoud¹⁶⁰, Ha Thi Hoang³, Marc Sperzel³, Wei Hao⁵⁰, Kristof Meding⁶⁰, Sihan Xu⁷⁶, Vassilis Kostakos³⁸⁷, Davide Manini⁸², Deyuey Liu⁸⁶, Christopher Toukmaji²⁹⁶, Eunmi Yu³⁸⁸, Arif Engin Demircali³⁸⁹, Zhiyi Sun⁷⁶, Ivan Dowerpe³⁴², Hongsen Qin⁴⁵, Roman Pflugfelder^{390,391}, James Bailey³⁹², Johnathan Morris⁹, Ville Heilala³⁹³, Sybille Rosset³⁹⁴, Zishun Yu²⁸, Peter E. Chen⁶, Woongyeong Yeo³³⁹, Eeshaan Jain⁴¹, Sreekar Chigurupati³⁹⁵, Julia Chernyavsky³, Sai Prajwal Reddy³⁹⁵, Subhashini Venugopalan³⁴², Hunar Batra⁴⁶, Core Francis Park⁴⁰⁷, Hieu Tran⁹⁹, Guilherme Maximiano³, Genghan Zhang¹⁴, Yizhuo Liang⁸¹, Hu Shi³⁹⁶, Rongwu Xu¹⁵, Rui Pan³⁰, Siddharth Suresh⁹⁰, Ziqi Liu⁹⁰, Samaksh Gulati³⁶², Songyang Zhang⁵⁹, Peter Turchin³³⁶, Christopher W. Bartlett³⁵⁹, Christopher R. Scotese¹⁵⁴, Phuong M. Cao⁸⁶, Ben Wu³⁹⁷, Jacek Karwowski⁴⁶ & Davide Scaramuzza¹⁶²

³Independent Researcher, <https://lastexam.ai>. ⁴Texas A&M University, College Station, TX, USA. ⁵Brown University, Providence, RI, USA. ⁶McGill University, Montreal Quebec, Canada. ⁷Institute of Mathematics of NAS of Ukraine, Kyiv, Ukraine. ⁸Kiev School of Economics, Kyiv, Ukraine. ⁹Carnegie Mellon University, Pittsburgh, PA, USA. ¹⁰RWTH Aachen University, Aachen, Germany. ¹¹University of Cambridge, Cambridge, UK. ¹²Kyiv Polytechnic Institute, Kyiv, Ukraine. ¹³Queen's University, Kingston Ontario, Canada. ¹⁴Stanford University, Stanford, CA, USA. ¹⁵University of Washington, Seattle, WA, USA. ¹⁶University of California San Diego, San Diego, CA, USA. ¹⁷University of Porto, Porto, Portugal. ¹⁸ELTE, Budapest, Hungary. ¹⁹Nimbus AI, Honolulu, HI, USA. ²⁰ETH Zürich, Zurich, Switzerland. ²¹Durham University, Durham, UK. ²²Georgia Southern University, Statesboro, GA, USA. ²³University of Minnesota, Minneapolis, MN, USA. ²⁴Queen Mary University of London, London, UK. ²⁵Microsoft, Redmond, WA, USA. ²⁶Auckland University of Technology, Auckland, New Zealand. ²⁷Alberta Health Services, Edmonton Alberta, Canada. ²⁸University of Illinois Chicago, Chicago, IL, USA. ²⁹Hereford College of Arts, Hereford, UK. ³⁰Princeton University, Princeton, NJ, USA. ³¹University of Canterbury, Christchurch, New Zealand. ³²Metropolitan State University of Denver, Denver, CO, USA. ³³Massachusetts Institute of Technology, Cambridge, MA, USA. ³⁴Accenture Labs, Washington, DC, USA. ³⁵Tufts University, Medford, MA, USA. ³⁶The Jackson Laboratory, Bar Harbor, ME, USA. ³⁷INRIA, Paris, France. ³⁸University of California, Berkeley, Berkeley, CA, USA. ³⁹University of British Columbia, Vancouver British Columbia, Canada. ⁴⁰Ross University School of Medicine, Bridgetown, Barbados. ⁴¹École Polytechnique Fédérale de Lausanne, Lausanne, Switzerland. ⁴²Concordia University, Montreal Quebec, Canada. ⁴³Institute of Science and Technology Austria, Klosterneuburg, Austria. ⁴⁴National University of Singapore, Singapore, Singapore. ⁴⁵California Institute of Technology, Pasadena, CA, USA. ⁴⁶University of Oxford, Oxford, UK. ⁴⁷University of São Paulo, São Paulo, Brazil. ⁴⁸Humboldt-Universität zu Berlin, Berlin, Germany. ⁴⁹Charité – Universitätsmedizin, Berlin, Germany. ⁵⁰Columbia University, New York, NY, USA. ⁵¹University of Southern California, Los Angeles, CA, USA. ⁵²C. N. Yang Institute for Theoretical Physics, Stony Brook, NY, USA. ⁵³University of Luxembourg, Luxembourg City, Luxembourg. ⁵⁴Universidade Federal de Juiz de Fora, Juiz de Fora, Brazil. ⁵⁵Rockwell Automation, Milwaukee, WI, USA. ⁵⁶Contramont Research, San Francisco, CA, USA. ⁵⁷École Normale Supérieure, Paris, France. ⁵⁸Sorbonne Université, Paris, France. ⁵⁹University of Toronto, Toronto Ontario, Canada. ⁶⁰University of Tübingen, Tübingen, Germany. ⁶¹Sapienza University of Rome, Rome, Italy. ⁶²University of North Texas, Denton, TX, USA. ⁶³Institut Polytechnique de Paris, Palaiseau, France. ⁶⁴National University Philippines, Manila, The Philippines. ⁶⁵University of Bath, Bath, UK. ⁶⁶Maastricht University, Maastricht, The Netherlands. ⁶⁷Washington University, St Louis, MO, USA. ⁶⁸University of California, Los Angeles, Los Angeles, CA, USA. ⁶⁹Université Paris-Saclay, Gif-sur-Yvette, France. ⁷⁰CNRS, Paris, France. ⁷¹Martin-Luther-University Halle-Wittenberg, Halle (Saale), Germany. ⁷²Leibniz University Hannover, Hannover, Germany. ⁷³Diverging Mathematics, Boston, MA, USA. ⁷⁴Indian Institute of Technology Bombay, Mumbai, India. ⁷⁵Institute for Molecular Manufacturing, Palo Alto, CA, USA. ⁷⁶University of Michigan, Ann Arbor, MI, USA. ⁷⁷Google DeepMind, London, UK. ⁷⁸Vrije Universiteit Brussel, Brussels, Belgium. ⁷⁹UZ Brussel, Brussels, Belgium. ⁸⁰PeopleTec, Huntsville, AL, USA. ⁸¹University of Chicago, Chicago, IL, USA. ⁸²Technion – Israel Institute of Technology, Haifa, Israel. ⁸³University of Miami, Coral Gables, FL, USA. ⁸⁴Technische Universität Berlin, Berlin, Germany. ⁸⁵University of Manchester, Manchester, UK. ⁸⁶University of Illinois Urbana-Champaign, Urbana-Champaign, IL, USA. ⁸⁷University of Calgary, Calgary Alberta, Canada. ⁸⁸Universidad Iberoamericana, Mexico City, Mexico. ⁸⁹TU Wien, Vienna, Austria. ⁹⁰University of Wisconsin-Madison, Madison, WI, USA. ⁹¹Yale University, New Haven, CT, USA. ⁹²University of Edinburgh, Edinburgh, UK. ⁹³École Normale Supérieure Paris-Saclay, Gif-sur-Yvette, France. ⁹⁴University of Western Australia, Perth Western Australia, Australia. ⁹⁵Snorkel AI, Redwood City, CA, USA. ⁹⁶New York University, New York, NY, USA. ⁹⁷Mohamed bin Zayed University of Artificial Intelligence, Abu Dhabi, UAE. ⁹⁸University of Waterloo, Waterloo Ontario, Canada. ⁹⁹University of Maryland, College Park, MD, USA. ¹⁰⁰Manhattan School of Music, New York, NY, USA. ¹⁰¹Universiteit Leiden, Leiden, The Netherlands. ¹⁰²Gynbionix, Casselberry, FL, USA. ¹⁰³The Open University, Milton Keynes, UK. ¹⁰⁴Corteva Agriscience, Indianapolis, IN, USA. ¹⁰⁵Sanford Burnham Prebys, La Jolla, CA, USA. ¹⁰⁶Yonsei University, Seoul, South Korea. ¹⁰⁷Harvard University, Cambridge, MA, USA. ¹⁰⁸Cornell University, Ithaca, NY, USA. ¹⁰⁹University of Leeds, Leeds, UK. ¹¹⁰Arizona State University,

Tempe, AZ, USA. ¹¹¹Swinburne University of Technology, Melbourne Victoria, Australia. ¹¹²KU Leuven, Leuven, Belgium. ¹¹³St Petersburg College, St Petersburg, FL, USA. ¹¹⁴La Molina National Agrarian University, Lima, Peru. ¹¹⁵Brandenburg University of Technology, Cottbus, Germany. ¹¹⁶INSAIT, Sofia, Bulgaria. ¹¹⁷Ruhr University Bochum, Bochum, Germany. ¹¹⁸National Information Processing Institute, Warsaw, Poland. ¹¹⁹Charles University, Prague, Czech Republic. ¹²⁰Cranfield University, Cranfield, UK. ¹²¹University of Copenhagen, Copenhagen, Denmark. ¹²²TRR Designs, Fayetteville, AR, USA. ¹²³The University of Sydney, Sydney New South Wales, Australia. ¹²⁴Indian Institute of Technology Delhi, New Delhi, India. ¹²⁵Universidad de Buenos Aires, Buenos Aires, Argentina. ¹²⁶University of Technology Sydney, Sydney New South Wales, Australia. ¹²⁷Indiana State University, Terre Haute, IN, USA. ¹²⁸Australian National University, Canberra Australian Capital Territory, Australia. ¹²⁹KTH Royal Institute of Technology, Stockholm, Sweden. ¹³⁰University of Amsterdam, Amsterdam, The Netherlands. ¹³¹Ben-Gurion University, Beersheba, Israel. ¹³²Donald and Barbara Zucker School of Medicine, Hempstead, NY, USA. ¹³³Cohere, Toronto Ontario, Canada. ¹³⁴Siili Solutions, Helsinki, Finland. ¹³⁵University of Pennsylvania, Philadelphia, PA, USA. ¹³⁶Aalto University, Espoo, Finland. ¹³⁷Toyota Technological Institute at Chicago, Chicago, IL, USA. ¹³⁸Northeastern University, Boston, MA, USA. ¹³⁹Case Western Reserve University, Cleveland, OH, USA. ¹⁴⁰University of Windsor, Windsor, Ontario, Canada. ¹⁴¹St. Jude Children's Research Hospital, Memphis, TN, USA. ¹⁴²Rochester Institute of Technology, Rochester, NY, USA. ¹⁴³Emory University, Atlanta, GA, USA. ¹⁴⁴Anthropic, San Francisco, CA, USA. ¹⁴⁵CERN, Geneva, Switzerland. ¹⁴⁶University of California Santa Barbara, Santa Barbara, CA, USA. ¹⁴⁷Warsaw University of Technology, Warsaw, Poland. ¹⁴⁸Hewlett Packard Enterprise, San Francisco, CA, USA. ¹⁴⁹North Carolina State University, Raleigh, NC, USA. ¹⁵⁰University of Houston, Houston, TX, USA. ¹⁵¹All India Institute of Medical Sciences, New Delhi, India. ¹⁵²Tel Aviv University, Tel Aviv, Israel. ¹⁵³Georgia Institute of Technology, Atlanta, GA, USA. ¹⁵⁴Northwestern University, Evanston, IL, USA. ¹⁵⁵University of Arizona, Tucson, AZ, USA. ¹⁵⁶Universidade de Lisboa, Lisbon, Portugal. ¹⁵⁷Indian Institute of Technology Kharagpur, Kharagpur, India. ¹⁵⁸Posts and Telecommunications Institute of Technology, Hanoi, Vietnam. ¹⁵⁹Duke University, Durham, NC, USA. ¹⁶⁰Mila – Québec AI Institute, Montreal Quebec, Canada. ¹⁶¹University College London, London, UK. ¹⁶²University of Zurich, Zurich, Switzerland. ¹⁶³UK AI Safety Institute, London, UK. ¹⁶⁴University of Padua, Padua, Italy. ¹⁶⁵Boston University, Boston, MA, USA. ¹⁶⁶Royal Veterinary College, London, UK. ¹⁶⁷Instituto Superior Técnico, Lisbon, Portugal. ¹⁶⁸SDAIA, Riyadh, Saudi Arabia. ¹⁶⁹The Ohio State University, Columbus, OH, USA. ¹⁷⁰University of Montreal, Montreal Quebec, Canada. ¹⁷¹Cairo University Specialized Pediatric Hospital, Cairo, Egypt. ¹⁷²Universidad de Valencia, Valencia, Spain. ¹⁷³Monash University, Melbourne Victoria, Australia. ¹⁷⁴Van Andel Institute, Grand Rapids, MI, USA. ¹⁷⁵Larkin Community Hospital, South Miami, FL, USA. ¹⁷⁶The University of Texas at Dallas, Richardson, TX, USA. ¹⁷⁷Canadian University Dubai, Dubai, UAE. ¹⁷⁸The Hebrew University of Jerusalem, Jerusalem, Israel. ¹⁷⁹Università di Milano-Bicocca, Milan, Italy. ¹⁸⁰University of Massachusetts Lowell, Lowell, MA, USA. ¹⁸¹Virginia Tech, Blacksburg, VA, USA. ¹⁸²University of Geneva, Geneva, Switzerland. ¹⁸³Google Research, Mountain View, CA, USA. ¹⁸⁴Cal Poly San Luis Obispo, San Luis Obispo, CA, USA. ¹⁸⁵Alexandru Ioan Cuza University, Iasi, Romania. ¹⁸⁶University of Mannheim, Mannheim, Germany. ¹⁸⁷Stockholm University, Stockholm, Sweden. ¹⁸⁸College of Eastern Idaho, Idaho Falls, ID, USA. ¹⁸⁹Intrinsic Innovation, Mountain View, CA, USA. ¹⁹⁰Ivy Natal, San Francisco, CA, USA. ¹⁹¹King Saud University, Riyadh, Saudi Arabia. ¹⁹²GAMPE Switzerland, Zurich, Switzerland. ¹⁹³CERO Therapeutics Holdings, South San Francisco, CA, USA. ¹⁹⁴University of Tennessee, Knoxville, TN, USA. ¹⁹⁵Gray Swan AI, Pittsburgh, PA, USA. ¹⁹⁶EleutherAI, Washington, DC, USA. ¹⁹⁷Johns Hopkins University, Baltimore, MD, USA. ¹⁹⁸University of Montpellier, Montpellier, France. ¹⁹⁹Fraunhofer IMTE, Lübeck, Germany. ²⁰⁰HomeEquity Bank, Toronto Ontario, Canada. ²⁰¹Materials Platform for Data Science, Tallinn, Estonia. ²⁰²University of Pisa, Pisa, Italy. ²⁰³Georgia State University, Atlanta, GA, USA. ²⁰⁴Polytechnic University of the Philippines, Manila, The Philippines. ²⁰⁵University of Oregon, Eugene, OR, USA. ²⁰⁶Drexel University, Philadelphia, PA, USA. ²⁰⁷University of Mumbai, Mumbai, India. ²⁰⁸Gakushuin University, Tokyo, Japan. ²⁰⁹University of Guelph, Guelph Ontario, Canada. ²¹⁰Intuit, Mountain View, CA, USA. ²¹¹CTTC / CERCA, Castelldefels, Spain. ²¹²Dyno Therapeutics, Watertown, MA, USA. ²¹³The Hospital for Sick Children, Toronto Ontario, Canada. ²¹⁴Temple University, Philadelphia, PA, USA. ²¹⁵Saint Mary's University, Halifax Nova Scotia, Canada. ²¹⁶Cisco, San Jose, CA, USA. ²¹⁷Indian Institute of Technology (BHU), Varanasi, India. ²¹⁸AIM Intelligence, Seoul, South Korea. ²¹⁹Seoul National University, Seoul, South Korea. ²²⁰The University of Texas at Arlington, Arlington, TX, USA. ²²¹The Hartree Centre, Daresbury, UK. ²²²University of Vienna, Vienna, Austria. ²²³POLITEHNICA Bucharest National University of Science and Technology, Bucharest, Romania. ²²⁴Abacus.AI, San Francisco, CA, USA. ²²⁵University of Galway, Galway, Ireland. ²²⁶Eastern Institute of Technology (EIT), Napier, New Zealand. ²²⁷ENS Lyon, Lyon, France. ²²⁸Czech Technical University in Prague, Prague, Czech Republic. ²²⁹University of Hamburg, Hamburg, Germany. ²³⁰CISPA Helmholtz Center for Information Security, Saarbrücken, Germany. ²³¹Universidad de Morón, Morón, Argentina. ²³²Université Paris Cité, Paris, France. ²³³Politecnico di Milano, Milan, Italy. ²³⁴The New School, New York, NY, USA. ²³⁵Max Planck Institute for Software Systems, Saarbrücken, Germany. ²³⁶OpenAI, San Francisco, CA, USA. ²³⁷Universidad de Granada, Granada, Spain. ²³⁸Modulo Research, Cambridge, UK. ²³⁹Heidelberg University, Heidelberg, Germany. ²⁴⁰La Trobe University, Melbourne Victoria, Australia. ²⁴¹University of Yaoundé I, Yaoundé, Cameroon. ²⁴²University of Innsbruck, Innsbruck, Austria. ²⁴³Nabu Technologies, San Francisco, CA, USA. ²⁴⁴Chalmers University of Technology, Gothenburg, Sweden. ²⁴⁵Unidade Local de Saúde de Lisboa Ocidental, Lisbon, Portugal. ²⁴⁶Children's Hospital of Orange County, Orange, CA, USA. ²⁴⁷The Future Paralegals of America, New York, NY, USA. ²⁴⁸Eastlake High School, Sammamish, WA, USA. ²⁴⁹Center for Scientific Research and Higher Education at Ensenada (CICESE), Ensenada, Mexico. ²⁵⁰University of Bradford, Bradford, UK. ²⁵¹Beni Suef University, Beni Suef, Egypt. ²⁵²Bogazici University, Istanbul, Turkey. ²⁵³Mansoura University, Mansoura, Egypt. ²⁵⁴University of Bristol, Bristol, UK. ²⁵⁵University of Oklahoma, Norman, OK, USA. ²⁵⁶Jala University, Honolulu, HI, USA. ²⁵⁷University of Arkansas, Fayetteville, AR, USA. ²⁵⁸Florida Atlantic University, Boca Raton, FL, USA. ²⁵⁹Bournemouth University, Bournemouth, UK. ²⁶⁰University of Warwick, Coventry, UK. ²⁶¹University of Alabama Huntsville, Huntsville, AL, USA. ²⁶²University of Hertfordshire, Hatfield, UK. ²⁶³OncoPrecision, New York, NY, USA. ²⁶⁴Central College, Pella, IA, USA. ²⁶⁵Nottingham Trent University, Nottingham, UK. ²⁶⁶Max Planck Institute for Intelligent Systems, Stuttgart, Germany. ²⁶⁷University of Virginia, Charlottesville, VA, USA. ²⁶⁸Dartmouth College, Hanover, NH, USA. ²⁶⁹Cairo University, Giza, Egypt. ²⁷⁰INESC Microsistemas e Nanotecnologias, Lisbon, Portugal. ²⁷¹James Madison University, Harrisonburg, VA, USA. ²⁷²Instituto Gonçalo Moniz, Salvador, Brazil. ²⁷³Rice University,

Houston, TX, USA. ²⁷⁴HUN-REN, Budapest, Hungary. ²⁷⁵Rutgers University, New Brunswick, NJ, USA. ²⁷⁶AE Studio, Marina Del Rey, CA, USA. ²⁷⁷Saarland University, Saarbrücken, Germany. ²⁷⁸HUTECH, Ho Chi Minh City, Vietnam. ²⁷⁹Pennsylvania College of Technology, Williamsport, PA, USA. ²⁸⁰Intelligent Geometries, Front Royal, VA, USA. ²⁸¹École Polytechnique, Palaiseau, France. ²⁸²CONICET, Buenos Aires, Argentina. ²⁸³Universidad Tecnológica Nacional, Buenos Aires, Argentina. ²⁸⁴John Crane UK, Slough, UK. ²⁸⁵Alan Turing Institute, London, UK. ²⁸⁶Pondicherry Engineering College, Puducherry, India. ²⁸⁷Leibniz Institute for Science and Mathematics Education, Kiel, Germany. ²⁸⁸Royal Holloway, University of London, Egham, UK. ²⁸⁹Tanta University, Tanta, Egypt. ²⁹⁰University of Malaya, Kuala Lumpur, Malaysia. ²⁹¹Hemwati Nandan Bahuguna Garhwal University, Srinagar, India. ²⁹²University Mohammed I, Oujda, Morocco. ²⁹³LGM, Paris, France. ²⁹⁴Northern Illinois University, DeKalb, IL, USA. ²⁹⁵Bethune-Cookman University, Daytona Beach, FL, USA. ²⁹⁶University of California, Irvine, Irvine, CA, USA. ²⁹⁷Central Mindanao University, Maramag, The Philippines. ²⁹⁸University of the Fraser Valley, Abbotsford British Columbia, Canada. ²⁹⁹Patched Codes, San Francisco, CA, USA. ³⁰⁰Missouri University of Science and Technology, Rolla, MO, USA. ³⁰¹Quotient AI, Boston, MA, USA. ³⁰²CSMSS Chh. Shahu College of Engineering, Aurangabad, India. ³⁰³Genomia Diagnostics Research, New Delhi, India. ³⁰⁴Sheffield Teaching Hospitals NHS Foundation Trust, Sheffield, UK. ³⁰⁵Forschungszentrum Jülich, Jülich, Germany. ³⁰⁶Standard Intelligence, San Francisco, CA, USA. ³⁰⁷MIT University, Melbourne Victoria, Australia. ³⁰⁸German Research Center for Artificial Intelligence, Kaiserslautern, Germany. ³⁰⁹Fondazione Bruno Kessler, Trento, Italy. ³¹⁰University of Trento, Trento, Italy. ³¹¹Chulalongkorn University, Bangkok, Thailand. ³¹²Aligarh Muslim University, Aligarh, India. ³¹³Happy Technologies LLC, Arlington, VA, USA. ³¹⁴Menoufia University, Shebin El Kom, Egypt. ³¹⁵Instituto Politécnico Nacional, Mexico City, Mexico. ³¹⁶University of Bologna, Bologna, Italy. ³¹⁷Manipal University Jaipur, Jaipur, India. ³¹⁸The University of Texas at Austin, Austin, TX, USA. ³¹⁹Murdoch University, Perth Western Australia, Australia. ³²⁰University of Delaware, Newark, DE, USA. ³²¹Williams College, Williamstown, MA, USA. ³²²Perimeter Institute for Theoretical Physics, Waterloo Ontario, Canada. ³²³University of Maribor, Maribor, Slovenia. ³²⁴Brigham and Women's Hospital, Boston, MA, USA. ³²⁵The University of Tokyo, Tokyo, Japan. ³²⁶Imperial College London, London, UK. ³²⁷University of California Santa Cruz, Santa Cruz, CA, USA. ³²⁸Vellore Institute of Technology, Vellore, India. ³²⁹CHRU de Nancy, Nancy, France. ³³⁰Delft University of Technology, Delft, The Netherlands. ³³¹Scripps Research, La Jolla, CA, USA. ³³²Aleph Alpha, Heidelberg, Germany. ³³³George Mason University, Fairfax, VA, USA. ³³⁴Atılım University, Ankara, Turkey. ³³⁵Leonardo Labs, Rome, Italy. ³³⁶Complexity Science Hub, Vienna, Austria. ³³⁷Universidad Nacional de Educación a Distancia, Madrid, Spain. ³³⁸Saxion University, Enschede, The Netherlands. ³³⁹Korea Advanced Institute of Science and Technology, Daejeon, South Korea. ³⁴⁰Adobe Research, San Jose, CA, USA. ³⁴¹National Aerospace University 'Kharkiv Aviation Institute', Kharkiv, Ukraine. ³⁴²Google, Mountain View, CA, USA. ³⁴³Hexworks, Barcelona, Spain. ³⁴⁴Westmead Hospital, Sydney New South Wales, Australia. ³⁴⁵University of Bern, Bern, Switzerland. ³⁴⁶Rheinland-Pfälzische Technische Universität Kaiserslautern-Landau, Kaiserslautern, Germany. ³⁴⁷SUMM AI, Munich, Germany. ³⁴⁸University of North Carolina at Chapel Hill, Chapel Hill, NC, USA. ³⁴⁹Konkuk University, Seoul, South Korea. ³⁵⁰University of Groningen, Groningen, The Netherlands. ³⁵¹Jagiellonian University, Kraków, Poland. ³⁵²Minerva University, San Francisco, CA, USA. ³⁵³Aalborg University, Aalborg, Denmark. ³⁵⁴IBM Research, Givatayim, Israel. ³⁵⁵Universitat Politècnica de Valencia, Valencia, Spain. ³⁵⁶RBC Borealis, Toronto Ontario, Canada. ³⁵⁷Mayo Clinic, Rochester, MN, USA. ³⁵⁸University of Lausanne, Lausanne, Switzerland. ³⁵⁹Dalhousie University, Halifax Nova Scotia, Canada. ³⁶⁰Universitat de Lleida, Lleida, Spain. ³⁶¹Amazon, Seattle, WA, USA. ³⁶²Dell Technologies, Round Rock, TX, USA. ³⁶³University of Seoul, Seoul, South Korea. ³⁶⁴University of Auckland, Auckland, New Zealand. ³⁶⁵Morgridge Institute for Research, Madison, WI, USA. ³⁶⁶Korea University of Technology and Education, Cheonan, South Korea. ³⁶⁷University of California Davis, Davis, CA, USA. ³⁶⁸Baylor College of Medicine, Houston, TX, USA. ³⁶⁹Indraprastha Institute of Information Technology Delhi, New Delhi, India. ³⁷⁰Two Minute Papers, Pécs, Hungary. ³⁷¹ADIA Lab, Abu Dhabi, UAE. ³⁷²New Jersey Institute of Technology, Newark, NJ, USA. ³⁷³Novo Nordisk, Bagsvaerd, Denmark. ³⁷⁴Purdue University, West Lafayette, IN, USA. ³⁷⁵Gakugei Shuppan-sha, Kyoto, Japan. ³⁷⁶Universiteit Utrecht, Utrecht, The Netherlands. ³⁷⁷T-Systems Iberia, Madrid, Spain. ³⁷⁸University of Klagenfurt, Klagenfurt, Austria. ³⁷⁹Max Planck Institute for Security and Privacy, Bochum, Germany. ³⁸⁰InxiteOut, Bangalore, India. ³⁸¹Goethe Universität Frankfurt, Frankfurt am Main, Germany. ³⁸²Universidad del Valle, Cali, Colombia. ³⁸³Bilkent University, Ankara, Turkey. ³⁸⁴Trinity School, New York, NY, USA. ³⁸⁵Universitat Pompeu Fabra, Barcelona, Spain. ³⁸⁶Brighton Law School, Brighton, UK. ³⁸⁷University of Melbourne, Melbourne, Australia. ³⁸⁸Ankara University, Ankara, Turkey. ³⁸⁹Dr. Siyami Ersek Thoracic, Cardiovascular and Vascular Surgery Training and Research Hospital, Istanbul, Turkey. ³⁹⁰AIT Austrian Institute of Technology, Vienna, Austria. ³⁹¹Technical University of Munich, Munich, Germany. ³⁹²Providence College, Providence, RI, USA. ³⁹³University of Jyväskylä, Jyväskylä, Finland. ³⁹⁴Weizmann Institute of Science, Rehovot, Israel. ³⁹⁵Indiana University, Bloomington, IN, USA. ³⁹⁶Nanyang Technological University, Singapore, Singapore. ³⁹⁷University of Sheffield, Sheffield, UK.

Methods

Related works

LLM benchmarks. Benchmarks are important tools for tracking the rapid advancement of LLM capabilities, including general and scientific knowledge^{1,10,12–15} and mathematical reasoning^{16–21}, code generation^{22–28} and general-purpose human assistance^{7,29–35}. Owing to their objectivity and ease of automated scoring at scale, evaluations commonly include multiple-choice and short-answer questions^{31,36–39}, with benchmarks such as MMLU¹ also spanning a broad range of academic disciplines and levels of complexity.

Saturation and frontier benchmark design. However, state-of-the-art models now achieve nearly perfect scores on many existing evaluations, obscuring the full extent of current and future frontier AI capabilities^{40–43}. This has motivated the development of more challenging benchmarks that test for multi-modal capabilities^{17,22,24,44–50}, strengthen existing benchmarks^{32,44,45,51,52}, filter questions over multiple stages of review^{9,12,19,42,53,54} and use experts to write tests for advanced academic knowledge^{9,12,19,54–56}. HLE combines these approaches: the questions are developed by subject-matter experts and undergo multiple rounds of review, while preserving the broad subject-matter coverage of MMLU. As a result, HLE provides a clear measurement of the gap between current AI capabilities and human expertise on closed-ended academic tasks, complementing other assessments of advanced capabilities in open-ended domains^{57,58}.

Dataset

Submission process. To ensure question difficulty, we automatically check the accuracy of frontier LLMs on each question before submission. Our testing process uses multi-modal LLMs for text-and-image questions (GPT-4o, Gemini 1.5 Pro, Claude 3.5 Sonnet and o1) and adds two non-multi-modal models (o1-mini and o1-preview) for text-only questions. We use different submission criteria by question type: exact-match questions must stump all models, whereas multiple-choice questions must stump all but one model to account for potential lucky guesses. Users are instructed to submit only questions that meet these criteria. We note that due to non-determinism in models and a non-zero floor in multiple-choice questions, further evaluation on the dataset exhibits some low but non-zero accuracy.

Post-release. Late contributions. In response to research community interest, we opened the platform for late contributors after the initial release, resulting in thousands of submissions. Each submission was manually reviewed by organizers. The new questions are of similar difficulty and quality to our initial dataset, resulting in a second held-out private set, which will be used in future evaluations.

Refinement. Community feedback: owing to the advanced, specialized nature of many submissions, reviewers were not expected to verify the full accuracy of each provided solution rationale, instead focusing on whether the question aligns with guidelines. Given this limitation in the review process, we launched a community feedback bug bounty program following the initial release of the dataset to identify and eliminate the main errors in the dataset, namely, label errors and other errors in the statement of the question. Each error report was manually verified by the organizers with feedback from the original author of the question when appropriate.

Searchable questions: a question is potentially searchable if a model with search tools answered correctly, but answered incorrectly without search. Each of these potentially searchable questions was then manually audited, removing any that were easily found using web search. We used GPT-4o mini/GPT-4o search and Perplexity Sonar models in this procedure. We observe that current frontier model performance on HLE after applying this procedure is similar to the performance on HLE before applying this procedure.

Expert disagreement rate. Before release, we conducted two main rounds of auditing, each on a sample of 200 questions. We recruited students from top universities in the United States to fully solve a sample of questions from HLE. Errors flagged were routed between organizers, original question authors and auditors until consensus was reached. We used data from these audits to further refine our dataset. The first round aimed to identify common categories of imprecise questions, such as open-ended formats, reliance on rounded numerical values or submissions from authors with low acceptance rates. Based on these signals, we manually removed or revised potential questions with similar issues before conducting a second audit on a new sample of 200 questions. This iterative process yielded a final estimated expert disagreement rate of 15.4% for the public set. This level of expert disagreement is in line with what is observed in other well-known machine learning benchmarks^{59–62}.

Disagreement rates are often higher in domains such as health and medicine. A targeted peer review on a biology, chemistry and health subset, proposed in ref. 63, found an expert disagreement rate of approximately 18%. This is also observed in other similarly expert-grade work; for example⁶⁴, notes that disagreement among expert physicians is frequent on complex health topics. To aid future community efforts in identifying other potential dataset errors, we outline several key factors that contribute to the complexity of these audits below:

- The need for multiple experts: our multi-reviewer process highlighted the complexity of these questions. In several cases, a reviewer identified an important piece of information, such as a decades-old paper or a foundational concept not immediately apparent to others, that was essential to confirming the validity of an answer. To illustrate, if we were to adopt a single-reviewer methodology in which a question is flagged based on just one dissenting expert, the disagreement rate on the aforementioned health-focused subset jumps from 18% to 25%, which is close to the approximate numbers and method from ref. 63. This discrepancy highlights the importance of a standard peer-review process, complete with multiple reviewers and author rebuttal, for HLE questions.
- Questions from research experience: HLE is intentionally designed to include questions based on insights from the direct, hands-on experiments of its contributors. This design captures knowledge gained from direct research experiences, which is often difficult to verify through standard literature searches or by external reviewers. This was done to test model knowledge beyond what is readily indexed on the internet.
- Understanding question design: designing challenging closed-ended research questions is difficult. Consequently, the objective for some HLE multiple-choice questions is to identify the most plausible answer among the provided options. Some external reviewers, unfamiliar with these design principles, sought to find external sources to support an open-ended answer rather than evaluating the best choice among the given options.

HLE-Rolling. Inspired by these valuable community discussions and researcher interest across disciplines in contributing to the dataset, and as part of our commitment to continual improvement, we will introduce a dynamic fork of the dataset post-release: HLE-Rolling. This version will be regularly updated to address community feedback and integrate new questions. Information about the updates will be made publicly available at <https://lastexam.ai>. Our goal is to provide a seamless migration path for researchers once frontier models begin to hit the noise ceiling performance on the original HLE dataset.

Prompts. We use the following system prompt for evaluating LLMs on HLE questions. For models that do not support a system prompt, we add it as a separate user prompt.

Article

Your response should be in the following format:

Explanation: {your explanation for your answer choice}

Answer: {your chosen answer}

Confidence: {your confidence score between 00% and 100% for your answer}

We use the following system prompt to judge the model answers against the correct answers for our evaluations in Table 1. We used o3-mini-2025-01-31 with structured decoding enabled to get an extracted_final_answer, reasoning, correct, confidence extraction for each output. An example of a structured response using an LLM judge is shown in Extended Data Fig. 1.

Judge whether the following [response] to [question] is correct or not based on the precise and unambiguous [correct_answer] below.

[question]: {question}

[response]: {response}

Your judgement must be in the format and criteria specified below:

extracted_final_answer: The final exact answer extracted from the [response]. Put the extracted answer as 'None' if there is no exact, final answer to extract from the response.

[correct_answer]: {correct_answer}

reasoning: Explain why the extracted_final_answer is correct or incorrect based on [correct_answer], focusing only on if there are meaningful differences between [correct_answer] and the extracted_final_answer. Do not comment on any background to the problem, do not attempt to solve the problem, do not argue for any answer different than [correct_answer], focus only on whether the answers match.

correct: Answer 'yes' if extracted_final_answer matches the [correct_answer] given above, or is within a small margin of error for numerical problems. Answer 'no' otherwise, i.e. if there if there is any inconsistency, ambiguity, non-equivalency, or if the extracted answer is incorrect.

confidence: The extracted confidence score between 0% and 100% from [response]. Put 100 if there is no confidence score available.

Data availability

The HLE dataset is open-source and available at <https://huggingface.co/datasets/cais/hle>. Important updates to the project and dataset will be announced at <https://lastexam.ai>.

Code availability

The inference script for benchmarking AI systems on HLE is available at GitHub (<https://github.com/centerforaisafety/hle>).

20. He, C. et al. OlympiadBench: A challenging benchmark for promoting AGI with Olympiad-level bilingual multimodal scientific problems. In *Proc. 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 3828–3850 (ACL, 2024).
21. Gao, B. et al. Omni-MATH: A universal Olympiad level mathematic benchmark for large language models. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=yagPfoKAlN> (ICLR, 2025).
22. Chan, J. S. et al. MLE-bench: Evaluating machine learning agents on machine learning engineering. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=6s5uXNWGih> (ICLR, 2025).
23. Zhang, A. K. et al. Cybench: A framework for evaluating cybersecurity capabilities and risks of language models. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=tc9OLV0yRL> (ICLR, 2025).
24. Jimenez, C. E. et al. SWE-bench: Can language models resolve real-world Github issues? In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=VTFByNQm66> (ICLR, 2024).
25. Chen, M. et al. Evaluating large language models trained on code. Preprint at <https://arxiv.org/abs/2107.03374> (2021).
26. Hendrycks, D. et al. Measuring coding challenge competence with APPS. In *Proc. 35th Conference on Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track* <https://openreview.net/forum?id=sD93GOzH3i5> (NeurIPS, 2021).
27. Bhatt, M. et al. Purple Llama CyberSecEval: a secure coding benchmark for language models. Preprint at <https://arxiv.org/abs/2312.04724> (2023).
28. Austin, J. et al. Program synthesis with large language models. Preprint at <https://arxiv.org/abs/2108.07732> (2021).
29. Bai, Y. et al. Training a helpful and harmless assistant with reinforcement learning from human feedback. Preprint at <https://arxiv.org/abs/2204.05862> (2022).
30. Perez, E. et al. Discovering language model behaviors with model-written evaluations. In *Findings of the Association for Computational Linguistics: ACL 2023*, 13387–13434 (ACL, 2023).
31. Rajpurkar, P. et al. SQuAD: 100,000+ questions for machine comprehension of text. In *Proc. 2016 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2383–2392 (EMNLP, 2016).
32. Rajpurkar, P. et al. Know what you don't know: Unanswerable questions for SQuAD. In *Proc. 56th Annual Meeting of the Association for Computational Linguistics (ACL)*, 784–789 (ACL, 2018).
33. Bajaj, P. et al. MS MACRO: a human generated machine reading comprehension dataset. Preprint at <https://arxiv.org/abs/1611.09268> (2018).
34. Hendrycks, D. et al. What would Jiminy Cricket do? Towards agents that behave morally. In *Proc. 35th Conference on Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track* <https://openreview.net/forum?id=G1muTb5zuO7> (NeurIPS, 2021).
35. Phan, L., Mazeika, M., Zou, A. & Hendrycks, D. Textquests: how good are LLMs at text-based video games? Preprint at <https://arxiv.org/abs/2507.23701> (2025).
36. Wang, A. et al. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=rJ4km2R5t7> (ICLR, 2019).
37. Wang, A. et al. SuperGLUE: A stickier benchmark for general-purpose language understanding systems. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, Vol. 32, 3261–3275 (NeurIPS, 2019).
38. Yang, Z. et al. HotpotQA: A dataset for diverse, explainable multi-hop question answering. In *Proc. 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2369–2380 (EMNLP, 2018).
39. Dua, D. et al. DROP: a reading comprehension benchmark requiring discrete reasoning over paragraphs. Preprint at <https://arxiv.org/abs/1903.00161> (2019).
40. Ott, S., Barbosa-Silva, A., Blagoev, K., Brauner, J. & Samwald, M. Mapping global dynamics of benchmark creation and saturation in artificial intelligence. *Nat. Commun.* **13**, 6793 (2022).
41. Owen, D. How predictable is language model benchmark performance? Preprint at <https://arxiv.org/abs/2401.04757> (2024).
42. Kiela, D. et al. Dynabench: Rethinking benchmarking in NLP. In *Proc. 2021 Conference of the North American Chapter of the Association for Computational Linguistics (NAACL)*, 4110–4124 (NAACL, 2021).
43. McIntosh, T. R. et al. Inadequacies of large language model benchmarks in the era of generative artificial intelligence. *IEEE Trans. Artif. Intell.* <https://doi.org/10.1109/TAI.2025.3569516> (2025).
44. Wang, Y. et al. MMLU-Pro: A more robust and challenging multi-task language understanding benchmark. In *Proc. Advances in Neural Information Processing Systems (NeurIPS)*, article no. 3018 (NeurIPS, 2024).
45. Taghanaki, S. A., Khani, A. & Khasahmadi, A. MMLU-Pro+: evaluating higher-order reasoning and shortcut learning in LLMs. Preprint at <https://arxiv.org/abs/2409.02257> (2024).
46. Yao, S. et al. t-bench: A benchmark for tool-agent-user interaction in real-world domains. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=rOnSXZpUDN> (ICLR, 2025).
47. Andriushchenko, M. et al. AgentHarm: A benchmark for measuring harmfulness of LLM agents. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=AC5n7xHuR1> (ICLR, 2025).
48. Kumar, P. et al. Refusal-trained LLMs are easily jailbroken as browser agents. Preprint at <https://arxiv.org/abs/2410.13886> (2024).
49. Yan, F. et al. Berkeley Function Calling Leaderboard https://gorilla.cs.berkeley.edu/blogs/8_berkeley_function_calling_leaderboard.html (2024).
50. Srinivasan, V. K. et al. NexusRaven: a commercially-permissive language model for function calling. In *NeurIPS 2023 Foundation Models for Decision Making Workshop* (NeurIPS, 2023).
51. Hosseini, A., Sordani, A., Toyama, D., Courville, A. & Agarwal, R. Not all LLM reasoners are created equal. Preprint at <https://arxiv.org/abs/2410.01748> (2024).
52. Singhal, K. et al. Large language models encode clinical knowledge. *Nature* **620**, 172–180 (2023).

12. Li, N. et al. The WMDP benchmark: measuring and reducing malicious use with unlearning. In *Proc. 41st International Conference on Machine Learning (ICML)*, 28713–28738 (PMLR, 2024).
13. Laurent, J. M. et al. LAB-bench: measuring capabilities of language models for biology research. Preprint at <https://arxiv.org/abs/2407.10362> (2024).
14. Srivastava, A. et al. Beyond the imitation game: Quantifying and extrapolating the capabilities of language models. *Trans. Mach. Learn. Res.* <https://openreview.net/forum?id=uyTL5Bvosj> (2023).
15. Zhong, W. et al. Agieval: a human-centric benchmark for evaluating foundation models. Preprint at <https://arxiv.org/abs/2304.06364> (2023).
16. Hendrycks, D. et al. Measuring mathematical problem solving with the MATH dataset. In *Proc. 35th Conference on Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track* <https://openreview.net/forum?id=7Bywt2mQsCe> (NeurIPS, 2021).
17. Lu, P. et al. MathVista: Evaluating mathematical reasoning of foundation models in visual contexts. In *Proc. International Conference on Learning Representations (ICLR)* <https://openreview.net/forum?id=KUNzEQMWU7> (ICLR, 2024).
18. Cobbe, K. et al. Training verifiers to solve math word problems. Preprint at <https://arxiv.org/abs/2110.14168> (2021).
19. Glazer, E. et al. FrontierMath: a benchmark for evaluating advanced mathematical reasoning in AI. Preprint at <https://arxiv.org/abs/2411.04872> (2024).

-
53. Nie, Y. et al. Adversarial NLI: A new benchmark for natural language understanding. In *Proc. 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, 4885–4901 (ACL, 2020).
54. Götting, J. et al. Virology capabilities test (VCT): a multimodal virology Q&A benchmark. Preprint at <https://arxiv.org/abs/2504.16137> (2025).
55. Phuong, M. et al. Evaluating frontier models for dangerous capabilities. Preprint at <https://arxiv.org/abs/2403.13793> (2024).
56. Anthropic’s Responsible Scaling Policy Updates <https://www.anthropic.com/rsp-updates> (Anthropic, 2024).
57. Mazeika, M. et al. Remote labor index: measuring AI automation of remote work. Preprint at <https://arxiv.org/abs/2510.26787> (2025).
58. Patwardhan, T. et al. GDPval: evaluating ai model performance on real-world economically valuable tasks. Preprint at <https://arxiv.org/abs/2510.04374> (2025).
59. Kwiatkowski, T. et al. Natural questions: a benchmark for question answering research. *Trans. Assoc. Comput. Linguist.* **7**, 452–466 (2019).
60. Antol, S. et al. VQA: Visual question answering. In *Proc. IEEE International Conference on Computer Vision (ICCV)*, 2425–2433 (IEEE, 2015).
61. Reddy, S., Chen, D. & Manning, C. D. CoQA: a conversational question answering challenge. *Trans. Assoc. Comput. Linguist.* **7**, 249–266 (2019).
62. Bowman, S. R., Angeli, G., Potts, C. & Manning, C. D. A large annotated corpus for learning natural language inference. In *Proc. 2015 Conference on Empirical Methods in Natural Language Processing* (eds Màrquez, L. et al.), 632–642 (ACL, 2015).
63. Skarlinski, M., Laurent, J., Bou, A. & White, A. About 30% of Humanity’s Last Exam chemistry/biology answers are likely wrong. *FutureHouse* <https://www.futurehouse.org/research-announcements/hle-exam> (2025).
64. Arora, R. K. et al. HealthBench: evaluating large language models towards improved human health. Preprint at <https://arxiv.org/abs/2505.08775> (2025).

Acknowledgements The research is supported by Center for AI Safety and Scale AI.

Author contributions All authors have contributed to the dataset creation process. The Center for AI Safety and Scale AI consortia jointly designed the dataset premise and pipeline; operated the data collection platform (<https://lastexam.ai>); and provided funding, inference infrastructure for LLMs and review/auditing resources. The authors in the HLE Contributors Consortium contributed to the dataset in various ways, including submitting at least one accepted question to one of the dataset versions, contributing to dataset refinement or assisting with evaluations. In the Center for AI Safety and Scale AI, Long Phan, Alice Gatti, Ziwen Han and Nathaniel Li led the project, and Summer Yue, Alexandr Wang and Dan Hendrycks provided senior supervision.

Competing interests The authors declare no competing interests.

Additional information

Supplementary information The online version contains supplementary material available at <https://doi.org/10.1038/s41586-025-09962-4>.

Correspondence and requests for materials should be addressed to Long Phan or Dan Hendrycks.

Peer review information *Nature* thanks the anonymous reviewers for their contribution to the peer review of this work. Peer reviewer reports are available.

Reprints and permissions information is available at <http://www.nature.com/reprints>.

Structured Judge Response Example

[correct_answer]: $\frac{\cos\left(\frac{\pi}{n}\right)}{2\left(1+\cos\left(\frac{\pi}{n}\right)\right)}$

[extracted_model_answer]: $\frac{\cot\left(\frac{\pi}{n}\right)}{2\cot\left(\frac{\pi}{2n}\right)}$

[reasoning]: Using the half-angle identity $\tan\left(\frac{\pi}{2n}\right) = \frac{\sin\left(\frac{\pi}{n}\right)}{1+\cos\left(\frac{\pi}{n}\right)}$ and recalling that $\cot x = \frac{\cos x}{\sin x}$, we express $\cot\left(\frac{\pi}{n}\right) = \frac{\cos\left(\frac{\pi}{n}\right)}{\sin\left(\frac{\pi}{n}\right)}$ and $\cot\left(\frac{\pi}{2n}\right) = \frac{1+\cos\left(\frac{\pi}{n}\right)}{\sin\left(\frac{\pi}{n}\right)}$. Forming the quotient $\frac{\cot\left(\frac{\pi}{n}\right)}{2\cot\left(\frac{\pi}{2n}\right)} = \frac{\frac{\cos\left(\frac{\pi}{n}\right)}{\sin\left(\frac{\pi}{n}\right)}}{2 \cdot \frac{1+\cos\left(\frac{\pi}{n}\right)}{\sin\left(\frac{\pi}{n}\right)}} = \frac{\cos\left(\frac{\pi}{n}\right)}{2\left(1+\cos\left(\frac{\pi}{n}\right)\right)}$, where the common $\sin\left(\frac{\pi}{n}\right)$ cancels out. This detailed inline simplification shows that the model answer is equivalent to the correct answer.

[correct]: yes

Extended Data Fig. 1 | Example of a structured response using an LLM judge. Exact-match answers in HLE sometimes require several reasoning steps to compare the AI's final answer with the correct answer; therefore, a capable LLM judge with reasoning capabilities is necessary.

Extended Data Table 1 | Accuracy and RMS Calibration error of frontier LLMs on the text-only questions of HLE

Model	Accuracy (%) ↑	Calibration Error (%) ↓
GPT-4o	2.3 ± 0.6	88
CLAUDE 3.5 SONNET	4.3 ± 0.9	83
GEMINI 1.5 PRO	4.6 ± 0.9	87
GEMINI 2.0 FLASH THINKING	6.6 ± 1.0	82
o1	7.8 ± 1.1	84
DEEPSEEK-R1	8.5 ± 1.2	73
O3-MINI	13.4 ± 1.4	80
Post-Release Models		
LLAMA 4 MAVERICK	5.3 ± 1.0	84
CLAUDE 4 SONNET	7.6 ± 1.1	76
GEMINI 2.5 FLASH	12.6 ± 1.4	81
CLAUDE 4 OPUS	10.8 ± 1.3	73
o4-MINI	18.9 ± 1.7	58
o3	20.6 ± 1.7	36
GEMINI 2.5 PRO	22.1 ± 1.8	72
GPT-5	26.3 ± 1.9	50

Article

Extended Data Table 2 | Category-wise breakdown of frontier LLMs performance on HLE

Model	Text-Only							
	Math	Bio/Med	Physics	CS/AI	Humanities	Chemistry	Engineering	Other
GPT-4o	2.3	5.0	1.5	0.9	2.6	2.0	1.6	2.3
GROK 2	3.2	5.4	4.5	3.6	1.0	1.0	4.8	1.1
CLAUDE 3.5 SONNET	3.8	5.9	4.5	2.2	6.7	5.0	9.7	2.9
GEMINI 1.5 PRO	5.3	5.4	2.0	4.0	3.6	6.0	3.2	3.4
GEMINI 2.0 FLASH THINKING	8.1	7.7	4.5	4.9	6.2	5.0	4.8	2.9
O1	7.4	8.1	6.9	8.4	8.8	10.0	4.8	8.0
DEEPSEEK-R1	9.1	9.0	5.4	7.5	10.4	5.0	14.5	7.4
O3-MINI	18.6	10.0	15.3	8.4	5.2	9.0	6.5	6.9
Post-Release Models								
LLAMA 4 MAVERICK	5.1	5.9	5.9	4.9	6.2	8.9	6.2	2.3
CLAUDE 4 SONNET	8.1	7.2	5.9	7.1	10.9	5.0	14.1	3.4
CLAUDE 4 OPUS	10.8	15.3	8.9	11.2	12.4	5.9	10.9	8.0
GEMINI 2.5 FLASH	14.5	13.1	13.9	8.9	11.4	3.0	10.9	9.1
O4-MINI	24.5	14.0	19.8	19.6	9.8	6.9	10.9	10.2
O3	23.6	17.1	19.3	19.6	17.6	16.8	17.2	16.5
GEMINI 2.5 PRO	26.2	17.1	20.8	17.0	25.4	22.8	15.6	11.4
Full Dataset								
GPT-4o	2.3	6.4	1.7	0.8	3.2	3.6	1.8	2.6
GROK 2	3.0	4.6	3.9	3.3	1.4	2.4	3.6	1.7
CLAUDE 3.5 SONNET	4.0	4.6	3.9	2.5	5.9	4.2	7.2	2.2
GEMINI 1.5 PRO	5.2	5.4	3.0	3.7	4.1	6.1	3.6	3.4
GEMINI 2.0 FLASH THINKING	8.0	8.2	4.8	4.5	6.4	5.5	6.3	3.0
O1	7.4	10.4	7.0	8.2	8.7	9.7	6.3	7.3
Post-Release Models								
LLAMA 4 MAVERICK	5.1	6.1	5.7	5.0	7.3	10.9	6.3	3.0
CLAUDE 4 SONNET	8.3	8.2	6.1	6.6	11.0	6.7	10.8	3.9
CLAUDE 4 OPUS	10.5	15.4	10.0	10.4	12.8	7.3	9.0	8.6
GEMINI 2.5 FLASH	14.3	12.1	13.0	9.1	10.5	6.7	11.7	8.2
O4-MINI	24.1	15.4	18.7	19.5	9.1	8.5	11.7	9.9
O3	23.4	18.9	18.7	20.7	17.8	16.4	17.1	15.9
GEMINI 2.5 PRO	25.8	18.6	20.4	17.0	23.7	23.6	18.0	11.6

Extended Data Table 3 | Accuracy across multi-modal only, exact answer, and multiple-choice splits of HLE

Model	Multi-Modal Only	Exact Match Only	Multiple-Choice Only
GPT-4o	5.3	1.8	5.6
GROK 2	2.3	2.2	5.8
CLAUDE 3.5 SONNET	2.6	3.1	6.9
GEMINI 1.5 PRO	5.0	3.8	7.1
GEMINI 2.0 FLASH THINKING	6.7	5.2	10.8
O1	9.4	6.7	12.0
DEEPSEEK-R1*	-	6.9	13.8
O3-MINI*	-	12.9	14.6
Post-Release Models			
LLAMA 4 MAVERICK	7.9	4.2	10.5
CLAUDE 4 SONNET	8.8	6.1	13.0
GEMINI 2.5 FLASH	9.1	10.1	17.8
CLAUDE 4 OPUS	10.2	8.4	18.1
O4-MINI	12.9	17.5	19.5
O3	19.0	18.9	24.7
GEMINI 2.5 PRO	19.0	19.6	28.1

*Text-only models.