

SLM / Edge Device arXiv Daily Summary

생성일: 2026-08-28 12:41 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: A Layer Importance Metric for Quantization Accounting for the Speed-Quality Trade-off in Autoregressive Models

저자: Artem Safronov

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2608.26926

제출일: 2026-08-27T10:23:01+00:00

수정일: 2026-08-27T10:23:01+00:00

최근성: 최근 0일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.26926.pdf>

[초록 원문]

Small language models (sLLMs) are nowadays hosted on devices with limited memory and computational budget. In an autoregressive setup, inference is memory-bandwidth bound: uniform quantization is often detrimental to such models, since their architecture has limited redundancies and only a few layers are not very sensitive to lower precision. We propose a composite metric that combines two orthogonal criteria: information retention (measured in terms of a normalized SQNR-based coefficient) and throughput gains (modeled using a roofline-based latency analysis). By profiling Gemma 3 1B, we find that Feed-Forward Network blocks and the embedding matrix are the most promising targets for acceleration. For each candidate, we estimate a normalized quality score based on simulated quantization and a normalized speed score based on roofline modeling with no actual execution needed. We combine the two scores in a composite priority coefficient, allowing us to tune the trade-off between speed and quality as needed. Our metric is general and can be used to prioritize individual blocks, their projection sublayers, or transformer layers as a whole. We evaluate our approach on several model architectures, showing that our estimates have at around 4% prediction error for the accelerated speedup. We find that our method

generally allocates more resources to the most expressive layers compared to evolutionary search, specialized accelerators, or Shapley-value-based approaches that require expensive approximate inference. Our analytical approach makes sLLM quantization a predictable engineering task.

[PDF 앞부분/서론 일부]

A Layer Importance Metric for Quantization Accounting for the Speed-Quality Trade-off in Autoregressive Models
A.K. Safronov safro@sfedu.ru Abstract Small large language models (sLLMs) are now deployed on devices with limited memory and compute budget. Within the autoregressive setting, inference is memory-bandwidth bound: typical homogeneous quantization is typically detrimental to such models due to their compactness, as their architectures do not retain much redundancy, and in particular a handful of components display extremely poor tolerance to lower precision. This paper introduces a composite metric that combines two orthogonal assessment criteria for such components: the information retention after quantization, captured by a normalized coefficient, and the gains in throughput that can be expected from accelerating individual layers, analytically estimated using a roofline-based latency model. Using an architectural profiling benchmark on Gemma 3 1B, we identify the Feed-Forward Network (FFN) blocks and the embedding matrix as the most promising candidates for accelerated inference, and we estimate for each candidate a normalized quality score, computed via simulated quantization, and a normalized speed score, computed without any model execution. The metric uses a single prioritization coefficient to combine the two scores into a composite value, which can be tuned to prioritize speed vs quality according to a specific application's needs. The metric is general and can be applied to blocks of layers (such as FFNs in the transformer), their internal projections (such as the feed forward network within a transformer block), or single transformer layers, with no modifications to the computation. We evaluated our method on multiple model architectures, measuring around 4% error in predicted speedups on average, and demonstrated that it enables significantly better resource allocation decisions than existing approaches, which usually rely on extensive evolutionary search strategies, domain-specific inference accelerators, or require access to expensive Shapley-value approximations. In short, our analytical approach makes sLLM quantization both faster, easier, and more intuitive, turning a trial-and-error process into a mathematical exercise. Keywords: quantization, small language models, sLLM, roofline model, SQNR, inference acceleration, model compression

1 Introduction

The current practice in large language model (LLM) design appears to be contradictory, in that while model architectures become increasingly complex, their physical realization is subject to rather strict limitations imposed by memory bus widths, battery capacity, or the available silicon area. AI assistants are now omnipresent in smartphones and other local machines where they perform a variety of non-critical tasks such as content creation and web browsing [23]. Yet even in this setting, when an LLM is used for generic-purpose assistance, the emphasis is placed on the model's ability to operate in a memory-constrained environment rather than perform hundreds of billions of operations per second; put otherwise, a compactly represented LLM is significantly more valuable

1 arXiv:2608.26926v1 [cs.LG] 27 Aug 2026 than a large one at the same level of functional complexity. Now, the critical question is: how to achieve a high degree of model reduction while preserving the response quality, as witnessed by the recent advances in knowledge distillation and parameter sharing. It is not accidental that currently available small LLMs (Llama 3 1B/3B, Gemma 3 1B, Qwen 3 1.7B, etc.) are the result of aggressive model distillation: a large-scale LLM possesses ample resources to withstand the pruning of its parameter count, which

has little effect on its accuracy, while an sLLM (small LLM) does not have these advantages. If post-training quantization (PTQ) is applied to an sLLM, it may not produce acceptable results: the internal structure of the model remains intact, but its behavioral patterns are altered, so that the response quality decreases substantially. Another issue is that modern accelerators are often memory-bandwidth-constrained [3]: the majority of the time spent in autoregressive decoding is occupied by offloading weights from video memory, not performing arithmetic operations, which also appears to be the case when naively implementing the attention mechanism [16]. Thus, the utilization of a GPU in this scenario is significantly lower than could be the case, and the user must wait for the next token to be generated. A uniform reduction in the precision of weights and activations, applicable to each layer of the model, is not the only possibility; indeed, different network layers may respond differently to such a reduction. Some layers are relatively inert and can safely undergo aggressive quantization without noticeable effects on the quality of generation, while others store crucial information that should be left untouched. Several methods have been developed to date that allow one to quantify different elements of the model with varying degrees of precision. However, each of them is limited by certain design decisions: CARVQ [4] and IMPQ [6] utilize multi-level vector quantization or require extensive computation to estimate each component's contribution to the total model performance using Shapley-value estimation [21], while HAPM [5] requires specialized inference software to demonstrate its effectiveness. Thus, none of these approaches provides a practical solution for easily identifying the set of layers within an sLLM that could benefit from higher precision. The paper suggests that in order to achieve the best possible trade-off between performance and quality, one must move away from uniform quantization and instead attempt to find groups of operations within the model that contribute the most to its quality. In other words, it is more useful to spend computational resources (measured in FLOPS) on operations that pre ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '최근 소형 언어 모델(sLLM)은 제한된 메모리 및 연산 자원을 가진 장치에 탑재되어 활용되고 있습니다. 자기회귀(autoregressive) 설정에서 추론은 메모리 대역폭에 의해 제약을 받으며, 균일 양자화(uniform quantization)는 이러한 모델에 성능 저하를 야기하는 경우가 많습니다. 이는'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 359, 'candidatesTokenCount': 82, 'totalTokenCount': 2403, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 359}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseld': 'PgORaqXcO5Gy1MkPlsS2oAw'}

[논문 후보 2]

제목: Learning New Facts with QLoRA: An Acquisition-Retention Frontier
저자: Estelle Zheng, Sébastien Warichet, Emmanuel Helbert, Christophe Cerisara
카테고리: Deployment/Quantization/Efficiency
arXiv ID: 2608.25677
제출일: 2026-08-26T11:54:58+00:00
수정일: 2026-08-27T14:10:56+00:00
최근성: 최근 0일 이내

[초록 원문]

Parameter-efficient fine-tuning is often assumed to preserve pretrained capabilities because it updates only a small number of parameters. We show that this assumption depends strongly on adapter capacity. We study factual acquisition in a controlled OpenStreetMap-derived benchmark where Qwen3-4B must acquire anonymized geographic associations while retaining unrelated capabilities. Comparing full fine-tuning (FFT) with quantized low-rank adaptation (QLoRA) at ranks 8, 16, 32, and 64, we find that rank induces a clear acquisition--retention frontier. Low-rank QLoRA preserves out-of-domain (OOD) performance but acquires fewer facts, whereas higher ranks improve same-fact paraphrase generalization at an increasing cost in performance on unrelated benchmarks. FFT behaves as a conservative baseline: it retains general capabilities well, but does not reach the highest factual-acquisition regime. Distributional, weight-space, and spectral diagnostics mirror this behavioral trade-off, with higher-rank QLoRA moving farther from the pretrained model. A separate math adaptation experiment shows a weaker frontier, suggesting that the effect is most pronounced when adaptation must install new factual associations rather than reinforce skills already supported by pretraining. Code and data are available at https://github.com/zhngstl/new_facts_forgetting.

[PDF 앞부분/서론 일부]

Learning New Facts with QLoRA: An Acquisition-Retention Frontier Estelle Zheng^{1,2}, Sébastien Warichet², Emmanuel Helbert², Christophe Cerisara¹ ¹LORIA, CNRS, France ²Alcatel-Lucent Enterprise, France {estelle.zheng, cerisara}@loria.fr {sebastien.warichet, emmanuel.helbert}@al-enterprise.com

Abstract Parameter-efficient fine-tuning is often assumed to preserve pretrained capabilities because it updates only a small number of parameters. We show that this assumption depends strongly on adapter capacity. We study factual acquisition in a controlled OpenStreetMap-derived benchmark where Qwen3-4B must acquire anonymized geographic associations while retaining unrelated capabilities. Comparing full fine-tuning (FFT) with quantized low-rank adaptation (QLoRA) at ranks 8, 16, 32, and 64, we find that rank induces a clear acquisition-retention frontier. Low-rank QLoRA preserves out-of-domain (OOD) performance but acquires fewer facts, whereas higher ranks improve same-fact paraphrase generalization at an increasing cost in performance on unrelated benchmarks. FFT behaves as a conservative baseline: it retains general capabilities well, but does not reach the highest factual acquisition regime. Distributional, weightspace, and spectral diagnostics mirror this behavioral trade-off, with higher-rank QLoRA moving farther from the pretrained model. A separate math adaptation experiment shows a weaker frontier, suggesting that the effect is most pronounced when adaptation must install new factual associations rather than reinforce skills already supported by pretraining.

1 Introduction Pretrained language models (PLMs) are often finetuned for new domains, task-specific skills, or factual knowledge. Full fine-tuning (FFT) updates all model parameters and can be effective, but it is costly and may degrade performance outside the adaptation distribution. Parameter-efficient finetuning (PEFT) methods such as low-rank adaptation (LoRA) and its quantized variant QLoRA reduce this cost by freezing pretrained weights ¹Code and data are available at https://github.com/zhngstl/new_facts_forgetting. and learning low-rank updates (Hu et al., 2022; Dettmers et al., 2023). This restriction is often assumed to improve retention of previous capabilities, but it may also limit what the model can

acquire. Recent work shows that the relationship between LoRA and FFT is not simply one of efficiency. Biderman et al. (2024) find that LoRA can preserve more out-of-domain (OOD) behavior partly because it learns less from the target distribution. Shuttleworth et al. (2025) show that LoRA and FFT can reach similar accuracy from different regions of weight space. Other comparisons study broad adaptation settings such as coding (Männistö et al., 2025), mathematics (Biderman et al., 2024), question answering (Sun et al., 2023), or instruction tuning (Xin et al., 2024). These settings mix several gains: format adaptation, skill reinforcement, domain shift, or new information. We focus next on factual knowledge acquisition. In this context, retention is ambiguous unless acquisition is measured at the same time: a low-capacity adapter may appear safer simply because it has not strongly incorporated the target facts. Our setting relates to factual knowledge editing, which modifies specific associations while preserving unrelated behavior (Meng et al., 2022; Mitchell et al., 2022; Meng et al., 2023; Yang et al., 2025b), and continual learning, which studies the stability- plasticity trade-off under sequential updates (Jang et al., 2022; Shi et al., 2025). However, model editing benchmarks often focus on localized modifications of previously known facts, sometimes replacing existing associations, while continual learning approaches commonly evaluate sequences of tasks or updates, including PEFT-based methods that regularize, initialize, or merge adapter subspaces (Lu et al., 2025; Qiao and Mahdavi, 2026). Our goal is different: we study a single controlled batch-adaptation stage in which models acquire novel factual associations using standard FFT and QLoRA. We measure how adaptation capacity affects facts acquisition, paraphrase generalization, and retention of general LLM capabilities. We introduce a factual acquisition benchmark derived from OpenStreetMap (OSM) in which models are trained to acquire anonymized geographic associations. The anonymized entities reduce direct reliance on pretrained world knowledge, while the OSM structure preserves realistic relational dependencies. We compare FFT with QLoRA ranks $r \in \{8, 16, 32, 64\}$ and evaluate supervised fact memorization, same-fact paraphrase generalization, and OOD retention. We further connect behavioral performance to model-drift diagnostics, including KL divergence from the base model, RMS-normalized dense update norms, and SVD-based spectral changes. A standard-LoRA rank sweep on Qwen3-1.7B separately tests whether the rank trend persists without quantization. Our results show that LoRA rank induces a clear acquisition-retention frontier. Low-rank LoRA preserves OOD performance but acquires fewer facts, whereas higher-rank LoRA improves factual acquisition at the cost of larger OOD degradation. FFT behaves as a baseline: it retains general capabilities relatively well, but does not reach the highest factual-acquisition regime observed with high-rank LoRA. The same trend appears in model-drift diagnostics, where higher-acquisition LoRA runs move farther away from the pretrained model. This paper makes three contributions: (i) we introduce a controlled OpenStreetMap-derived benchmark for factual acquisition, using anonymized entities to reduce direct reliance on pretrained world knowledge; (ii) we show that QLoRA rank controls an acquisition-retention frontier for new factual associations; and (iii) we connect this behavioral trade-off to model-drift diagnostics, showing that stronger factual acquisition is associated with larger distributional and weigh ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '파라미터 효율적 미세 조정(parameter-efficient fine-tuning)은 적은 수의 파라미터만을 업데이트하므로 사전 학습된 능력을 보존한다고 흔히 가정된다. 본 연구는 이러한 가정이 어댑터 용량에 강하게 의존함을 보여준다. 우리는 Qwen3-4B 모델이 익명화된 지리 정보

연관성을}}, 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}}, 'usageMetadata': {'promptTokenCount': 339, 'candidatesTokenCount': 82, 'totalTokenCount': 2383, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 339}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'SAORasWQEu2hjrEPqZuv4AM'}

[논문 후보 3]

제목: Geo-LoRA: Geometry-Aware Subspace Evolution for Low-Rank Adaptation in Continual Learning

저자: Yibo Feng

카테고리: Format-LoRA/Structured Output

arXiv ID: 2608.26960

제출일: 2026-08-27T11:00:50+00:00

수정일: 2026-08-27T11:00:50+00:00

최근성: 최근 0일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.26960.pdf>

[초록 원문]

Rehearsal-free class-incremental learning (CIL) with LoRA adapters remains challenging because the low-rank subspaces updated across tasks evolve without geometric control, causing unstable shared representations and repetitive collapse of task-specific updates into previously occupied directions. We introduce Geo-LoRA, a geometry-aware framework that explicitly regulates how low-rank subspaces, both shared and task-specific, evolve during continual learning. For the shared branch, Subspace Projection Preservation (SPP) constrains consecutive updates to follow smooth trajectories on the Grassmann manifold, and Adaptive Core-Slack Alignment (ACSA) decomposes transitions into principal and residual components, aligning the former while modulating the latter to balance stability and plasticity. For the task-specific branch, Median-Calibrated Block Overlap (MCBO) imposes a statistical constraint via normalized projection overlap, penalizing excessive reuse to mitigate subspace crowding. These constraints jointly regulate the evolution of all LoRA subspaces across layers and tasks without introducing additional adapter types beyond standard LoRA. Geo-LoRA provides a principled geometric formulation for continual low-rank adaptation and consistently achieves state-of-the-art performance across multiple benchmark datasets and different task lengths.

[PDF 앞부분/서론 일부]

Geo-LoRA: Geometry-Aware Subspace Evolution for Low-Rank Adaptation in Continual Learning Yibo Feng
University of Electronic Science and Technology of China Chengdu, China 2022090917012@std.uestc.edu.cn
Abstract Rehearsal-free class-incremental learning (CIL) with LoRA adapters remains challenging because the low-rank subspaces updated across tasks evolve without geometric control, causing unstable shared representations and repetitive collapse of task-specific updates into previously occupied directions. We introduce Geo-LoRA, a geometry-aware framework that explicitly regulates how low-rank subspaces-shared and task-specific-evolve during continual learning. For the shared branch, Subspace Projection Preservation (SPP) constrains consecutive updates to follow smooth trajectories on the Grassmann manifold, and Adaptive Core-Slack Alignment (ACSA) decomposes transitions into principal and residual components, aligning the former while

modulating the latter to balance stability and plasticity. For the task-specific branch, Median-Calibrated Block Overlap (MCBO) imposes a statistical constraint via normalized projection overlap, penalizing excessive reuse to mitigate subspace crowding. These constraints jointly regulate the evolution of all LoRA subspaces across layers and tasks without introducing additional adapter types beyond standard LoRA. Geo-LoRA provides a principled geometric formulation for continual low-rank adaptation and consistently achieves state-of-the-art performance across multiple benchmark datasets and different task lengths. CCS Concepts • Computing methodologies -> Machine learning; Computer vision; Transfer learning. Keywords Continual Learning; Class-Incremental Learning; Low-Rank Adaptation; Parameter-Efficient Fine-Tuning ACM Reference Format: Yibo Feng. 2026. Geo-LoRA: Geometry-Aware Subspace Evolution for LowRank Adaptation in Continual Learning. In Efficient Systems and AI for the Planet (GreenMM '26), November 10-14, 2026, Rio de Janeiro, Brazil. ACM, New York, NY, USA, 9 pages. <https://doi.org/10.1145/3840750.3841444>

1 Introduction Class-incremental learning (CIL)[11, 18, 19, 42] requires models to learn new classes over time without forgetting previously acquired knowledge. With the rise of pre-trained vision transformers (ViTs), recent work increasingly adopts parameter-efficient fine-tuning (PEFT)[3, 10, 41] to enable exemplar-free CIL, where the backbone remains frozen and lightweight modules handle continual adaptation. Among PEFT techniques, Low-Rank Adaptation (LoRA)[14] is particularly attractive due to its efficiency and its interpretation as learning task-dependent low-dimensional feature subspaces.

65 Geo-LoRA (Ours) CL-LoRA L2P SEMA BiLoRA InfLoRA DualPrompt SD-LoRA ACMap

	0.1	0.2	0.3	0.4	0.5	0.6	0.7	1.2
Trainable Parameters (Million)	0	68	71	74	77	80		
Average Accuracy (%)								

Figure 1: Comparison of different PTM-based CIL methods on ImageNet-R dataset (20 tasks). The X-axis stands for the number of trainable parameters, and the Y-axis represents the average accuracy. For a fair comparison, all methods are based on pre-trained ViT-B/16-IN1K. However, although existing LoRA-based CIL methods[37, 39, 43] have highlighted interference among low-rank updates, they still provide limited explicit control over the geometric evolution of these low-rank subspaces. Most approaches attach independent task-specific LoRA modules for each task, while recent dual-branch designs[12] introduce shared adapters across tasks. In both cases, low-rank directions learned at different stages are optimized mostly in isolation: shared subspaces may drift across tasks, and deep task-specific updates may repeatedly occupy previously used directions. These effects lead to misaligned shared representations and subspace crowding in layers, undermining the stability[24]-plasticity[6, 33] trade-off. These observations motivate a different perspective. Instead of viewing continual LoRA tuning as merely adding or freezing adapters, we formulate it as regulating the evolution of low-rank subspaces across tasks. This geometric viewpoint forms the basis of Geo-LoRA. Rather than modifying the LoRA architecture itself, GeoLoRA introduces projection-based geometric objectives that guide low-rank updates to evolve within a stable yet flexible envelope. To enable such geometric control, we adopt the Dual-LoRA architecture from CL-LoRA[12] as a structural backbone. This design separates continual adaptation into two regimes: shallow layers maintain a shared low-rank subspace that accumulates transferable structure, while deeper layers host task-specific LoRA updates for semantic specialization. This decomposition allows different geometric constraints to regulate shared and task-specific subspaces. arXiv:2608.26960v1 [cs.CV] 27 Aug 2026

GreenMM '26, November 10-14, 2026, Rio de Janeiro, Brazil Yibo Feng

Importantly, our goal is not to propose a new LoRA architecture, but to introduce geometry-aware objectives that stabilize and structure the learning dynamics within this framework. Within this hierarchy we design three complementary objectives. Subspace

Projection Preservation (SPP) constrains consecutive shared updates using Grassmann-consistent projection distance to reduce cross-task drift. Adaptive Core-Slack Alignment (ACSA) aligns principal shared directions while adaptively moderating residual directions to balance stability and plasticity. MedianCalibrated Block Overlap (MCBO) regulates deep-layer updates through normalized projection overlap, penalizing only statistically excessive reuse of historical directions. Together these components form a multi-level geometric regularization framework that controls subspace evolution without introducing additional adapter types and with modest training overhead. As illustrated in Figure 1, Geo-LoRA achieves state-of-the-art (SOTA) performance while maintaining a small number of trainable parameters. Our key contributions are summarized as follows: (1) W ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '리허설 없는 클래스 증분 학습(CIL)에서 LoRA 어댑터를 활용하는 것은 여전히 어려운 과제입니다. 이는 태스크에 걸쳐 업데이트되는 저랭크 부분 공간이 기하학적 제어 없이 진화하여 불안정한 공유 표현을 야기하고, 태스크별 업데이트가 이전에 점유된 방향으로 반복적으로 붕괴되기 때문입니다'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 307, 'candidatesTokenCount': 82, 'totalTokenCount': 2351, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 307}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'UAORap33N5HjugfW94Vo'}