

SLM / Edge Device arXiv Daily Summary

생성일: 2026-08-17 04:47 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: NAS-Driven Hardware Accelerator Exploration for Edge AI and Quantization Effects on the Pareto Space

저자: Eleftherios Mylonas, Angelos Kouprizas, Michael Birbas, Alexios Birbas

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2608.13293

제출일: 2026-08-13T14:26:08+00:00

수정일: 2026-08-13T14:26:08+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.13293.pdf>

[초록 원문]

Edge AI deployment demands neural architectures that are simultaneously accurate, computationally efficient, and hardware-deployable - a challenge addressed by hardware-aware Neural Architecture Search (NAS). While recent works incorporate quantization directly into the NAS loop, these approaches expand search complexity and tightly couple architecture and quantization design. The simpler post-search quantization strategy has received little analytical attention: the effects of Post-Training Quantization (PTQ) on the NAS-discovered Pareto structure remain uncharacterised, and no framework combines quantized architecture mapping onto reconfigurable accelerators with automated hardware exploration. This paper addresses both gaps. First, a three-stage pipeline is proposed: a hardware-agnostic Pareto rank surrogate frontend on NAS-Bench-201, a quantization bridge with Pareto-aware filtering and feedback control, and an evolutionary Domain Space Exploration (DSE) backend on CGRA4ML for optimal hardware mapping. Second, an empirical study characterises how INT4 PTQ perturbs the NAS-Bench-201 Pareto space through formal stability metrics on ground-truth data for all 15,625 architectures, and demonstrates that an FP32 zero-shot surrogate outperforms a dedicated INT4-trained surrogate in Pareto space coverage across two standard search strategies.

© 2026 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses, in any current or future media, including reprinting/republishing this material for advertising or promotional purposes, creating new collective works, for resale or redistribution to servers or lists, or reuse of any copyrighted component of this work in other works.

NAS-Driven Hardware Accelerator Exploration for Edge AI and Quantization Effects on the Pareto Space Eleftherios Mylonas Dept. of ECE University of Patras Patras, Greece 0000-0002-7676-685X Angelos Kouprizas Dept. of ECE University of Patras Patras, Greece 0009-0000-6577-7142 Michael Birbas Dept. of ECE University of Patras Patras, Greece 0000-0002-6124-221X Alexios Birbas Dept. of ECE University of Patras Patras, Greece 0000-0002-9468-7215

Abstract-Edge AI deployment demands neural architectures that are simultaneously accurate, computationally efficient, and hardware-deployable - a challenge addressed by hardware-aware Neural Architecture Search (NAS). While recent works incorporate quantization directly into the NAS loop, these approaches expand search complexity and tightly couple architecture and quantization design. The simpler post-search quantization strategy has received little analytical attention: the effects of Post-Training Quantization (PTQ) on the NAS-discovered Pareto structure remain uncharacterised, and no framework combines quantized architecture mapping onto reconfigurable accelerators with automated hardware exploration. This paper addresses both gaps. First, a three-stage pipeline is proposed: a hardware-agnostic Pareto rank surrogate frontend on NAS-Bench-201, a quantization bridge with Pareto-aware filtering and feedback control, and an evolutionary Domain Space Exploration (DSE) backend on CGRA4ML for optimal hardware mapping. Second, an empirical study characterises how INT4 PTQ perturbs the NAS-Bench-201 Pareto space through formal stability metrics on ground-truth data for all 15,625 architectures, and demonstrates that an FP32 zero-shot surrogate outperforms a dedicated INT4-trained surrogate in Pareto space coverage across two standard search strategies.

Index Terms-CGRAs, Domain Space Exploration, Hardware-aware Neural Architecture Search, Neural Architecture Search, Surrogate Models I.

INTRODUCTION Artificial Intelligence (AI) deployment has fundamentally changed as a result of deep learning's explosive growth. The emphasis shifted from centralized cloud AI to the more resource-constrained edge AI for more data privacy, inference latency decrement, and autonomous operation in settings where cloud access is not possible. This transition came with lots of computing, memory and power demands towards This work has received funding from European Projects: COP-PILOT Grant agreement ID: 101189819, 6G-XCEL Grant agreement ID: 101139194. Funded by the European Union. Views and opinions expressed are however those of the author(s) only and do not necessarily reflect those of the European Union or the Smart Networks and Services Joint Undertaking or the European Commission. Neither the European Union nor the granting authority can be held responsible for them.

edge devices, highlighting the need for new types of Alcapable systems, but also new efficient methods of AI task deployment across heterogeneous platforms. The challenge of efficiently designing models that are simultaneously accurate and deployable on diverse hardware - without manual trial-and-error across a combinatorial space of architectural choices - made automated model design an essential research priority, giving rise to the domain of Neural Architecture Search (NAS) [1]. NAS automates the AI model design, testing, search and selection process in various ways, either by testing different neural network layer combinations from the start or based on benchmarks from pre-trained combinations. However, it is still an open challenge, especially when it comes to edge AI deployment. Benchmark coverage

remains limited: most NAS benchmarks target a small set of tasks and focus on full-precision (FP32) model accuracies, completely neglecting other hardware performance metrics. Exceptions like HW-NAS-Bench [2] capture performance data from a fixed set of hardware targets which operate almost exclusively with FP32 precision, and do not examine the effects of quantization - which is the standard practice during any AI model deployment on hardware platforms - on NASdiscovered architectures. Search efficiency is also non-trivial: naive exhaustive search over large spaces is intractable, and without a principled estimation strategy, NAS may converge to suboptimal architectures. Performance estimation is also dependent on how an architecture is encoded for the NAS process, since a proper encoding reveals the most useful model structural and operational data. Lastly, no existing work has examined the effect of quantization on multi-objective performance estimators or offers a hardware Design Space Exploration (DSE) framework targeting flexible reconfigurable accelerator architectures for edge deployment. This paper addresses these challenges via a three-stage hardware-aware NAS workflow that identifies optimal candidate architectures and maps them onto a configurable Coarse Grain Reconfigurable Array (CGRA)-based accelerator. The arXiv:2608.13293v1 [cs.AI] 13 Aug 2026 main contributions of this work are: • a three-stage hardware-aware NAS procedure comprising a hardware-agnostic frontend trained on NAS-Bench-201 [3] and CIFAR-10 [4] that identifies the best candidate architectures in full precision, the quantization bridge that applies the quantization scheme and filters out the failing architectures, and a hardware-aware backend that searches for the optimal CGRA architecture per surviving architecture via evolutionary optimisation; • an empirical study of the effect of INT4 Post Training Quantization (PTQ) via the open-source Brevitas on NAS-Bench- ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '엣지 AI 배포는 정확하고, 계산 효율적이며, 하드웨어에 배포 가능한 신경망 아키텍처를 요구하며, 이는 하드웨어 인식 신경망 아키텍처 탐색(NAS)으로 해결되는 과제이다. 최근 연구들은 양자화를 NAS 루프에 직접 통합하지만, 이러한 접근 방식은 탐색 복잡성을 증가시키고 아}], 'role': 'model'}, {'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 321, 'candidatesTokenCount': 81, 'totalTokenCount': 2365, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 321}], 'thoughtsTokenCount': 1963, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'vBOCasmMH9ac-8YPlv76mA4'}

[논문 후보 2]

제목: A Cost-Efficient Routing Pipeline for Multilingual Short-Text Classification Using Small Language Models

저자: Wajdi Ben Saad, Safa Madiouni

카테고리: SLM/Edge/On-device

arXiv ID: 2608.10939

제출일: 2026-08-11T14:06:53+00:00

수정일: 2026-08-11T14:06:53+00:00

최근성: 최근 5일 이내

arXiv PDF: <https://arxiv.org/pdf/2608.10939.pdf>

[초록 원문]

Multilingual short-text classification supports operational systems such as content moderation, customer support routing, and intent recognition, yet aggregate evaluation often hides large differences between high-resource and low-resource languages. Uniform inference policies are simple to deploy, but they assume that all languages are equally well served. In this work, we evaluate a fixed-list routing strategy that keeps stronger languages on a direct multilingual path and selectively sends weaker languages through translation into English before zero-shot classification. The pipeline is fully self-hosted, uses pretrained compact sentence encoders, and requires no task-specific fine-tuning. We test the approach on two benchmarks chosen to differ in scale and label granularity: a 15-language subset of SIB-200 for seven-way topic classification and a 15-locale subset of MASSIVE for intent classification over an official 60-intent inventory. On SIB-200, the best overall configuration is R1, which translates only the low-resource tier: high-tier and mid-tier Macro-F1 remain unchanged, while low-tier Macro-F1 rises from 0.4632 to 0.6828. On the MASSIVE subset, the same low-tier intervention raises low-tier Macro-F1 from 0.2143 to 0.4417, but the best overall result is obtained by full translation, R3, at Macro-F1 0.4647. Across these two benchmarks, selective translation is a reliable intervention for weaker languages, whereas the optimal routing boundary depends on the task. We therefore report routing through tier-level quality gains and tier-level latency rather than a single global efficiency score.

[PDF 앞부분/서론 일부]

A Cost-Efficient Routing Pipeline for Multilingual Short-Text Classification Using Small Language Models Wajdi BEN SAAD Carthago Labs Paris, France Safa MADIOUNI Université Paris Dauphine-PSL Paris, France

Abstract-Multilingual short-text classification supports operational systems such as content moderation, customer support routing, and intent recognition, yet aggregate evaluation often hides large differences between high-resource and low-resource languages. Uniform inference policies are simple to deploy, but they assume that all languages are equally well served. In this work, we evaluate a fixed-list routing strategy that keeps stronger languages on a direct multilingual path and selectively sends weaker languages through translation into English before zero-shot classification. The pipeline is fully self-hosted, uses pretrained compact sentence encoders, and requires no task-specific fine-tuning. We test the approach on two benchmarks chosen to differ in scale and label granularity: a 15-language subset of SIB-200 for seven-way topic classification and a 15-locale subset of MASSIVE for intent classification over an official 60-intent inventory. On SIB-200, the best overall configuration is R1, which translates only the low-resource tier: high-tier and mid-tier Macro-F1 remain unchanged, while low-tier Macro-F1 rises from 0.4632 to 0.6828. On the MASSIVE subset, the same low-tier intervention raises low-tier Macro-F1 from 0.2143 to 0.4417, but the best overall result is obtained by full translation, R3, at Macro-F1 0.4647. Across these two benchmarks, selective translation is a reliable intervention for weaker languages, whereas the optimal routing boundary depends on the task. We therefore report routing through tier-level quality gains and tier-level latency rather than a single global efficiency score.

Index Terms-multilingual text classification, routing, translation, sentence embeddings, low-resource languages, intent classification

I. INTRODUCTION Multilingual short-text classification is required in content moderation, search assistance, customer support, and multilingual monitoring systems. A common deployment choice is to apply one inference path to every language, either with a single multilingual encoder or by translating every input into a pivot language. That uniform treatment is convenient, but benchmarks such as XTREME [1], SIB-200 [2], and MASSIVE [3] show broad variation across languages, scripts,

and task settings even under the same model family. This paper was accepted for publication at the 16th International Conference on Advanced Computer Information Technologies (ACIT 2026), <https://acit.tech/>. © 2026 IEEE. Personal use of this material is permitted. Permission from IEEE must be obtained for all other uses. Translation-based transfer remains a competitive alternative to direct multilingual inference [4], [5], but it adds latency, depends on translation-model coverage, and may introduce artifacts [6]. Our work targets a local, cost-aware deployment regime in which compact self-hosted models remain attractive relative to larger generative systems with higher serving overhead [7], [8]. The practical question is therefore not only which method is strongest overall, but whether translation should be reserved for the languages that benefit from it most. In this work, we examine that question with a fixedlist routing policy. We compare multilingual-only inference, translation-only inference, and a static router that sends selected language tiers through a translate-then-classify path. Unlike standard translate-and-test pipelines, our goal is not to replace direct multilingual inference everywhere, but to identify where translation should begin and where it should stop. Both paths use the same prototype-matching rule over English labels, and no task-specific fine-tuning is introduced. We conduct the analysis on a 15-language subset of SIB-200 for topic classification and a 15-locale subset of MASSIVE for intent classification. Although MASSIVE is commonly used for supervised multilingual natural language understanding (NLU), here we use only the public test split for zero-shot inference, with no training or weak supervision. The main finding is localized rather than universal. On SIB-200, translating only the low-resource tier raises lowtier Macro-F1 from 0.4632 to 0.6828 while the high-tier and mid-tier remain unchanged, and R1 is the strongest overall configuration. On the MASSIVE subset, the same low-tier intervention raises low-tier Macro-F1 from 0.2143 to 0.4417, again without changing the stronger tiers under R1, but the strongest overall result is obtained by full translation, R3. Under this setup, the central design question is not whether routing should be made more complex, but where the translation boundary should be placed for the task at hand. In this paper, we make three contributions: 1) We present a fully self-hosted empirical study of fixedlist routing for multilingual short-text classification without task-specific fine-tuning, evaluated on topic classification and intent classification. arXiv:2608.10939v1 [cs.CL] 11 Aug 2026 2) We report the results in a deployment-oriented form based on delta Macro-F1 relative to a multilingual-only baseline and latency measured separately by resource tier. 3) We show that the routing boundary is dataset-dependent: SIB-200 is best served by translating only the lowtier, whereas the MASSIVE subset reaches its strongest overall result under full translation even though the lowtier R1 gain still persists. The remainder of this paper is organised as follows: Section II reviews prior work on multilingual evaluation, crosslingual transfer, and routing-related deployment questions. Section III presents our routing pipeline, inference paths, and reporting strategy. Section IV describes the datasets, language tiers, models, execution environment, and evaluation conditions. Section V reports the main experimental results o ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '다국어 단문 텍스트 분류는 콘텐츠 조정, 고객 지원 라우팅, 의도 인식과 같은 운영 시스템을 지원하지만, 종합적인 평가는 고자원 언어와 저자원 언어 간의 큰 성능 차이를 종종 가린다. 균일한 추론 정책은 배포가 간단하지만, 모든 언어가 동등하게 잘 처리된다고'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 427,

'candidatesTokenCount': 79, 'totalTokenCount': 2471, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 427}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseld': 'xBOCaqXGL6rXz7IPpY-SgQM'}

[논문 후보 3]

제목: Motif 3: Technical Report
저자: Junghwan Lim, Joon Son Chung, Sungmin Lee, Wai Ting Cheung, Gihun Cho, Minsu Ha, Sangho Kang, Beomgyu Kim, Dongseok Kim, Jangwoong Kim, Taehyun Kim, Taewhan Kim, Jeessoo Lee, Jeongdoo Lee, Junhyeok Lee, Dongpin Oh, Hyeyeon Cho, Dahye Choi, Jaeheui Her, Hanbin Jung, Changjin Kang, Minjae Kim, Youngrok Kim, Hyukjin Kweon, Hongjoo Lee, Yeongjae Park, Bokki Ryu
카테고리: Deployment/Quantization/Efficiency
arXiv ID: 2608.09119
제출일: 2026-08-10T04:53:05+00:00
수정일: 2026-08-10T04:53:05+00:00
최근성: 최근 6일 이내
arXiv PDF: <https://arxiv.org/pdf/2608.09119.pdf>

[초록 원문]

We introduce Motif 3, a decoder-only Mixture-of-Experts language model with 314 billion total parameters and 13.2 billion activated per token. Each sparse MoE layer contains 384 routed experts, with eight selected per token. This fine-grained sparsity provides substantial expert capacity while limiting computation. Motif 3 is built around Grouped Differential Latent Attention (GDLA), which integrates grouped differential attention with the compressed key-value representation of Multi-head Latent Attention. The architecture further incorporates modified manifold-constrained hyper-connections, Expert Specific PolyNorm activations, and multi-token prediction to improve optimization stability, expert specialization, and inference efficiency. We pretrain Motif 3 on approximately 12.5 trillion tokens spanning web documents, STEM, code, mathematics, multilingual content, and domain-specialized corpora. Expert-balancing and numerical-stabilization techniques support stable training at scale, while selective MXFP8 computation and communication, memory-efficient fused kernels, and window-aware context parallelism enable training with context lengths up to 256K tokens. Our post-training pipeline combines general supervised fine-tuning, six specialist teachers trained with reinforcement learning, a software-engineering teacher trained with supervised fine-tuning, and Multi-teacher On-Policy Distillation. The resulting unified model consolidates complementary capabilities in reasoning, coding, tool use, professional work, long-context understanding, calibrated abstention, and instruction following. Across a broad evaluation suite, Motif 3 demonstrates competitive performance against leading open weight models, including strong results on long-horizon agentic tasks, mathematical reasoning, scientific knowledge, and hallucination-sensitive evaluation.

[PDF 앞부분/서론 일부]

2026-08-11 Motif 3: Technical Report Motif Technologies Abstract We introduce Motif 3, a decoder-only Mixture-of-Experts language model with 314 billion total parameters and 13.2 billion parameters activated for each token. Each sparse MoE layer contains 384 routed experts, while only eight are selected foreach token. This

fine-grained sparsity provides substantial expert capacity while limiting the expert computation required for each token. Motif 3 is built around Grouped Differential Latent Attention (GDLA), which integrates grouped differential attention with the compressed key-value representation of Multi-head Latent Attention. The architecture further incorporates modified manifold-constrained hyper-connections, Expert-Specific PolyNorm activations, and multi-token prediction to improve optimization stability, expert specialization, and inference efficiency. We pretrain Motif 3 on approximately 12.5 trillion tokens spanning web documents, STEM, code, mathematics, multilingual content, and domain-specialized corpora. A collection of expert-balancing and numerical-stabilization techniques supports stable training at scale, while selective MXFP8 computation and communication, memory-efficient fused kernels, and window-aware context parallelism enable training with context lengths up to 256K tokens. Our post-training pipeline combines general supervised fine-tuning, six specialist teachers trained with reinforcement learning, a software-engineering teacher trained with supervised fine-tuning, and Multiteacher On-Policy Distillation. The resulting unified model consolidates complementary capabilities in reasoning, coding, tool use, professional work, long-context understanding, calibrated abstention, and instruction following. Across a broad evaluation suite, Motif 3 demonstrates competitive performance against leading open-weight models, including strong results on long-horizon agentic tasks, mathematical reasoning, scientific knowledge, and hallucination-sensitive evaluation.

1 Introduction Large language models (LLMs) have rapidly evolved from general-purpose language systems into increasingly capable problem solvers, demonstrating substantial progress in reasoning, coding, tool use, and long-horizon agentic tasks [17, 19, 30, 69]. In parallel, recent open-weight models have continued to narrow the capability gap with leading proprietary systems, while Mixture-of-Experts (MoE) architectures have enabled the scaling of model capacity without proportionally increasing the computational cost incurred for each token. These advances highlight that further progress in foundation models depends not only on scaling data and computation, but also on developing more expressive and efficient architectures that can translate large-scale training into strong and broadly generalizable intelligence. In this work, we introduce Motif 3, a Mixture-of-Experts language model with 314 billion total parameters and 13.2 billion parameters activated for each token. A defining feature of Motif 3 is its fine-grained sparse expert design: each MoE layer contains 384 routed experts, of which only eight are selected for each token. This design provides a large pool of expert capacity while limiting the expert computation incurred by each token. At the core of Motif 3 is Grouped Differential Latent Attention (GDLA), a novel attention architecture that combines our grouped formulation of differential attention [63], building on Differential Transformer [70], with Multi-head Latent Attention (MLA) [14]. GDLA is designed to retain the expressive attention dynamics enabled by differential attention while substantially reducing the key-value cache requirements through latent representations. Motif 3 further incorporates manifold-constrained hyperconnections (mHC) [68] and the gated-attention mechanism adopted in Qwen3-Next [55, 57], forming an architecture designed for efficient inference and stable optimization at scale. We pretrain Motif 3 on approximately 12.5 trillion tokens drawn from a diverse mixture of high-quality web documents, STEM content, source code, mathematical data, synthetic question-answer pairs, and domain-specialized corpora, with additional emphasis on Korean and multilingual data, reasoning-intensive examples, and legal and financial domains. To train this large expert pool reliably, we employ a layered expert-balancing strategy that combines sigmoid-based routing, auxiliary-loss-free expert biases, sequence-wise load-balancing objectives, decaying router noise, and layer-adaptive

auxiliary-loss coefficients. Together, these mechanisms encourage broad expert exploration during the early stages of training while preventing persistent expert overload, starvation, and specialization collapse as training progresses. We additionally anneal the mHC post-mapping multiplier from its original value of two to one to limit the accumulation of residual-stream activation outliers. 1 arXiv:2608.09119v1 [cs.AI] 10 Aug 2026 Starting from the pretrained model, we employ a staged post-training pipeline comprising general Supervised Fine-Tuning (SFT), specialized teacher training, and Multi-teacher On-Policy Distillation (MOPD) [48, 67]. We first use a preliminary SFT model to identify capability-specific failure modes and generate targeted supervision, particularly for failure-prone decisions in agentic trajectories. We then restart from the pretrained checkpoint and train the general SFT model on the consolidated corpus, combining these targeted examples with complete interaction trajectories and broader instruction, reasoning, coding, and knowledge data. From this general SFT checkpoint, we train six specialist teachers with domain-specific GRPO across 13 verifier domains and construct a seventh, software-engineering teacher through SFT. MOPD then consolidates the complementary capabilities of all seven teachers into the general student, producing a single model with broad coverage and targeted expertise. The rema ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '우리는 총 3,140억 개의 매개변수를 가지며 토큰당 132억 개의 매개변수가 활성화되는 디코더 전용 전문가 혼합(Mixture-of-Experts, MoE) 언어 모델인 Motif 3를 소개한다. 각 회소 MoE 레이어는 384개의 라우팅된 전문가를'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 411, 'candidatesTokenCount': 82, 'totalTokenCount': 2455, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 411}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'zBOCapeVNs2fz7IPnr7nsAE'}