

SLM / Edge Device arXiv Daily Summary

생성일: 2026-06-23 06:40 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 7일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 7일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: NRITYAM: Language Models Meet Art and Heritage of Dance

저자: Punit Kumar Singh, Niladri Ghosh, Advait Joshiinst, Shailee Choudhary, Michael Färber, Haiqin Yang

카테고리: SLM/Edge/On-device

arXiv ID: 2606.19727

제출일: 2026-06-18T02:50:40+00:00

수정일: 2026-06-18T02:50:40+00:00

최근성: 최근 4일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.19727.pdf>

[초록 원문]

Language models have become essential tools in shaping modern workflows. However, their global effectiveness hinges on a nuanced understanding of local socio-cultural contexts. To address this gap, we present NRITYAM, a comprehensive benchmark for evaluating the cultural comprehension capabilities of language models in the context of global dance traditions. NRITYAM comprises 9,260 carefully curated question-answer pairs spanning 12 languages, making it the largest dataset dedicated to evaluating cultural knowledge in dance. The dataset has been developed from the ground up through close collaboration with native dance artists and native speakers of the languages, who authored and validated culturally relevant questions specific to their regions. We evaluate a broad set of models, including large language models, small language models, multimodal large language models, and small multimodal language models. As a multilingual and multicultural benchmark, NRITYAM sets a new standard for evaluating the ability of AI systems to understand and reason about traditional performing arts. Detailed dataset samples are available at~Wurl{<https://github.com/niladrighosh03/NRITYAM>} .

[PDF 앞부분/서론 일부]

NRITYAM: Language Models Meet Art and Heritage of Dance Punit Kumar Singh^{1,5}, Niladri Ghosh⁴, Advait

Joshi⁶, Shailee Choudhary², Michael Färber³, and Haiqin Yang () ^{1,7} 1 Shenzhen Technology University, 518118 Shenzhen, China yanghaiqin@sztu.edu.cn ² New Delhi Institute of Management, New Delhi, India ³ Technische Universität Dresden, 01069 Dresden, Germany ⁴ Ramakrishna Mission Vivekananda Educational and Research Institute, India ⁵ Indian Institute of Technology, India ⁶ Swami Vivekananda Institute of Technology, India ⁷ Guangdong Engineering Technology Research Center of Edge Intelligence

Abstract. Language models have become essential tools in shaping modern workflows. However, their global effectiveness hinges on a nuanced understanding of local socio-cultural contexts. To address this gap, we present NRITYAM, a comprehensive benchmark for evaluating the cultural comprehension capabilities of language models in the context of global dance traditions. NRITYAM comprises 9,260 carefully curated question-answer pairs spanning 12 languages, making it the largest dataset dedicated to evaluating cultural knowledge in dance. The dataset has been developed from the ground up through close collaboration with native dance artists and native speakers of the languages, who authored and validated culturally relevant questions specific to their regions. We evaluate a broad set of models, including large language models, small language models, multimodal large language models, and small multimodal language models. As a multilingual and multicultural benchmark, NRITYAM sets a new standard for evaluating the ability of AI systems to understand and reason about traditional performing arts. Detailed dataset samples are available at <https://github.com/niladrighosh03/NRITYAM>.

Keywords: LargeLanguageModel·Multimodal and Multilingual Dataset

1 Introduction Dance serves as a powerful medium for cultural and emotional expression, bringing together individuals from varied backgrounds and traditions [8]. Exploring different traditional dance forms offers meaningful perspectives on the values, historical experiences, and social frameworks of the communities that create and uphold them [36]. Moreover, dance holds significant societal importance, serving as a medium for preserving cultural knowledge and shaping collective identity [3]. The language, rituals, and evolving forms of dance serve as rich expressions

arXiv:2606.19727v1 [cs.CL] 18 Jun 2026

2 P. K. Singh, N. Ghosh, A. Joshi, S. Choudhary, M. Färber, and H. Yang Kathak Kabuki Dragon dance Samba Dance Tanoura dance

Fig.1. NRITYAM is a diverse benchmark featuring 12 languages, with questions manually created and verified by native language speakers and dance experts. It spans 8 key aspects of traditional dance across two modalities, text and image, emphasizing mid- to low-resource languages. The benchmark features dances originating from 12 countries across 5 continents that are now performed in 100 countries across 6 continents, which are visualized with dark blue for their origins and light blue for their current reach. NRITYAM offers a wide range of question formats, including multiple-choice questions (MCQs) and both short and long visual question-answering (VQA) tasks. of a community's historical experiences, cultural transformations, and collective identity encompassing elements such as traditional attire, religious associations, embodied movement, and social heritage [14]. Researchers have increasingly turned to traditional dance as a rich lens for analyzing cultural dynamics, providing a robust framework for understanding how embodied practices evolve across regional and societal boundaries [29]. Although many traditional dance forms share foundational elements such as expressive movement, symbolic gestures, and rhythmic structure, they manifest uniquely within different cultural contexts. These divergences are evident in variations in movement style, facial expression, ritual significance, performance settings, and the terminology used to describe them. For instance, Bharatanatyam, a classical Indian dance rooted in Tamil Nadu, has been adapted in Sri Lanka through a distinctive fusion with Kandyan dance aesthetics, reflecting

localized narratives and performance traditions. Such adaptations highlight how traditional dance not only preserves the heritage but also evolves through intercultural exchange and regional reinterpretation. Language Models (LMs) have revolutionized natural language understanding, content generation, and decision-making, becoming indispensable across industries such as education, governance, and entertainment [11]. From Large Language Models (LLMs) to Multimodal Language Mod-

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '언어 모델은 현대 워크플로우를 형성하는 데 필수적인 도구가 되었습니다. 그러나 그들의 전반적인 유용성은 지역의 사회문화적 맥락에 대한 미묘한 이해에 좌우됩니다. 이러한 격차를 해소하고자, 우리는 전 세계 무용 전통 맥락에서 언어 모델의 문화적 이해 능력을 평가하기 위한 포괄적인 벤치마크인 NRITYAM을 소개합니다. NRITYAM은 12개 언어에 걸쳐 신중하게 선별된 9,260개의 질문-답변 쌍으로 구성되어 있으며, 무용 분야의 문화 지식 평가를 위한 가장 큰 데이터셋입니다. 이 데이터셋은 각 지역에'}, {'role': 'model'}, {'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 284, 'candidatesTokenCount': 152, 'totalTokenCount': 2328, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 284}], 'thoughtsTokenCount': 1892, 'serviceTier': 'standard', 'modelVersion': 'gemini-2.5-flash', 'responseId': 'mq55atbADqPfjMcPh_uYiAI'}

[논문 후보 2]

제목: Embedded Machine Learning for Microcontroller-Class Edge Devices: Data, Feature, Evaluation, and Deployment Pipelines
저자: Mostafa Darvishi
카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency
arXiv ID: 2606.18122
제출일: 2026-06-16T16:22:24+00:00
수정일: 2026-06-16T16:22:24+00:00
최근성: 최근 6일 이내
arXiv PDF: <https://arxiv.org/pdf/2606.18122.pdf>

[초록 원문]

Embedded machine learning moves inference from cloud services to resource-constrained devices that must acquire data, preprocess signals, run a model, and act within tight limits on memory, energy, and latency. This paper presents a systems-oriented synthesis of an embedded machine-learning workflow for microcontroller-class platforms. The emphasis is placed on engineering decisions that are often hidden in generic machine-learning introductions: sampling and buffering, feature extraction as dimensionality reduction, validation under class imbalance, model/runtime co-design, and streaming deployment. Two representative signal families are used throughout the paper. The first is inertial motion recognition, where a two-second, three-axis accelerometer window is transformed from raw samples into root-mean-square and spectral features before classification. The second is keyword spotting, where audio is sampled, anti-aliased, transformed into mel-frequency cepstral coefficients, and processed by a compact one-dimensional convolutional network. The paper concludes with practical design rules for robust on-device inference, including data curation, quantization, thresholding,

scheduling, and field monitoring.

[PDF 앞부분/서론 일부]

Embedded Machine Learning for Microcontroller-Class Edge Devices: Data, Feature, Evaluation, and Deployment Pipelines Mostafa Darvishi, Senior Member, IEEE darvishi@ieee.org Abstract - Embedded machine learning moves inference from cloud services to resource-constrained devices that must acquire data, preprocess signals, run a model, and act within tight limits on memory, energy, and latency. This paper presents a systems-oriented synthesis of an embedded machine-learning workflow for microcontroller-class platforms. The emphasis is placed on engineering decisions that are often hidden in generic machine-learning introductions: sampling and buffering, feature extraction as dimensionality reduction, validation under class imbalance, model/runtime co-design, and streaming deployment. Two representative signal families are used throughout the paper. The first is inertial motion recognition, where a two-second, three-axis accelerometer window is transformed from raw samples into root-mean-square and spectral features before classification. The second is keyword spotting, where audio is sampled, anti-aliased, transformed into mel-frequency cepstral coefficients, and processed by a compact one-dimensional convolutional network. The paper concludes with practical design rules for robust on-device inference, including data curation, quantization, thresholding, scheduling, and field monitoring. Keywords - Embedded machine learning, edge inference, feature extraction, microcontrollers, TinyML. INTRODUCTION Machine-learning inference at the network edge is attractive when a sensor node must react immediately, preserve privacy, reduce communication energy, or operate without continuous connectivity. The engineering difficulty is that the target device is not a cloud server and often not even a single-board computer. A microcontroller may run bare metal or a small real-time operating system, have no virtual memory, expose only a few tens or hundreds of kilobytes of random-access memory (RAM), and execute from flash with a tight energy budget. Embedded machine learning is therefore best understood as a co-design problem among signal acquisition, feature representation, model architecture, runtime implementation, and application logic [1]-[4]. This paper aims to provide a compact technical synthesis of embedded machine learning concept targeting microcontrollers. Basic notions of artificial intelligence, such as what a classifier is or why a neural network has weights, are intentionally omitted. Instead, the discussion focuses on the steps that make an embedded model deployable: how raw signals become bounded input tensors, how validation metrics should be interpreted before deployment, and how the deployed program schedules acquisition, feature extraction, and inference without losing samples. The complete embedded machine-learning workflow considered in this paper is summarized in Fig. 1, where sensing, preprocessing, feature extraction, training, deployment, and field monitoring are treated as a closed loop engineering process. The main contribution is a deployment-centered reference pipeline. It connects data curation, windowing, feature extraction, model training, evaluation, and runtime execution for two practical examples: inertial gesture recognition and small-footprint keyword spotting. The resulting workflow is not tied to a single tool. Edge Impulse, TensorFlow Lite Micro, CMSIS-NN, and similar frameworks can be viewed as implementation vehicles for the same architectural pattern [1], [3], [4]. EMBEDDED TARGET MODEL A central distinction in embedded machine learning is the difference between single-board computers and microcontrollers. A single-board computer can run a general-purpose operating system, provide command-line or graphical interfaces, and use a faster processor with more memory. A microcontroller is typically less powerful, but it is cheaper, lower

power, and better suited to deterministic control loops, interrupt -driven sampling, and always -on sensing. The model designer must decide early whether the target can tolerate operating -system jitter, dynamic Fig. 1. Embedded machine-learning lifecycle. The deployed system is not the end of the workflow; field observations must feed back into data collection, feature selection, model revision, and runtime constraints. allocation, and higher power consumption, or whether the application requires a bare-metal or real-time design. The embedded inference path also combines two modes of reasoning. Acquisition and control are deterministic: timers, direct memory access, interrupts, and real-time tasks must execute within known bounds. The trained model is probabilistic: it produces class probabilities or anomaly scores rather than deterministic truth. A reliable product must therefore surround the model with deterministic safeguards such as thresholds, debouncing, hysteresis, watchdogs, bounded execution time, and fallback states. For a windowed sensor pipeline, the raw input size is $N_{raw} = f_s \cdot T \cdot C$, where f_s is the sampling frequency, T is the window length, and C is the number of channels. This simple expression often determines whether a design can run on the chosen device. For example, 62.5 Hz sampling over a two second, three-axis accelerometer window produces 375 raw values before feature extraction. If each value is stored as a 16-bit integer, the raw buffer alone requires 750 bytes, before double buffering, feature memory, model weights, activations, and runtime arena are considered. DATA CURATION AND WINDOWING Data collection is the first embedded design decision, not merely a machine-learning prerequisite. Samples should be acquired with the same sensor orientation, sample rate, quantization, environmental noise, and user behavior expected during deployment. A model trained from laboratory recordings can fail when microphone gain, sensor mounting, background motion, or device enclosure changes. For audio, sample match ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '임베디드 머신러닝은 추론을 클라우드 서비스에서 리소스 제약이 있는 장치로 전환하며, 이 장치들은 데이터 획득, 신호 전처리, 모델 실행 및 동작을 메모리, 에너지, 지연 시간의 엄격한 제약 내에서 수행해야 한다. 본 논문은 마이크로컨트롤러급 플랫폼을 위한'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 285, 'candidatesTokenCount': 82, 'totalTokenCount': 2329, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 285}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'o6s5arTjLt_Uz7IPvP2YwQY'}

[논문 후보 3]

제목: Beyond Benchmarks: Continuous Edge Inference for Fine-Grained Roadside Perception

저자: Aditya Mishra, Haroon Lone

카테고리: SLM/Edge/On-device

arXiv ID: 2606.17241

제출일: 2026-06-15T19:39:55+00:00

수정일: 2026-06-15T19:39:55+00:00

최근성: 최근 7일 이내

arXiv PDF: <https://arxiv.org/pdf/2606.17241.pdf>

[초록 원문]

Continuous AI inference on resource-constrained edge hardware introduces deployment effects that are largely invisible to conventional benchmark evaluation, including temporal instability in streaming video, thermal throttling under sustained load, and workload-dependent performance variability. We present Edge-TSR, a deployment-oriented continuous edge inference system for sustained roadside perception on the NVIDIA Jetson Orin Nano. Edge-TSR integrates detection, tracking, fine-grained classification, and a lightweight track-aware temporal stabilization mechanism that improves streaming inference consistency with negligible computational overhead. Our central finding is that benchmark-centric evaluation systematically overstates deployed edge inference performance. Across three state-of-the-art baselines, we observe consistent 20-30% relative degradation when transitioning from static-image evaluation to real-world streaming deployment. Edge-TSR addresses this gap through temporal inference stabilization, recovering up to 10.16% classification accuracy over per-frame inference baselines while maintaining sustained real-time performance under continuous operation. We evaluate the complete system under diverse real-world deployment conditions, jointly characterizing inference quality, latency, throughput, and thermal behavior during long-duration operation. A 55-minute vehicular deployment over a 26 km route demonstrates sustained operation at 16.18 FPS within safe thermal limits on a single embedded device without cloud offload. Our findings show that deployment-aware evaluation and temporal inference stabilization are necessary components of continuously operating edge AI systems intended for real-world sensing deployments. We release a sample annotated streaming video evaluation dataset and full system implementation to support reproducible deployment-centric evaluation.

[PDF 앞부분/서론 일부]

Beyond Benchmarks: Continuous Edge Inference for Fine-Grained Roadside Perception Aditya Mishra Indian Institute of Science Education and Research Bhopal, India aditya21@iiserb.ac.in Haroon Lone Indian Institute of Science Education and Research Bhopal, India haroon@iiserb.ac.in Abstract Continuous AI inference on resource-constrained edge hardware introduces deployment effects that are largely invisible to conventional benchmark evaluation, including temporal instability in streaming video, thermal throttling under sustained load, and workload-dependent performance variability. We present Edge-TSR, a deployment-oriented continuous edge inference system for sustained roadside perception on the NVIDIA Jetson Orin Nano. Edge-TSR integrates detection, tracking, fine-grained classification, and a lightweight track-aware temporal stabilization mechanism that improves streaming inference consistency with negligible computational overhead. Our central finding is that benchmark-centric evaluation systematically overstates deployed edge inference performance. Across three state-of-the-art baselines, we observe consistent 20-30% relative degradation when transitioning from static-image evaluation to real-world streaming deployment. Edge-TSR addresses this gap through temporal inference stabilization, recovering up to 10.16% classification accuracy over per-frame inference baselines while maintaining sustained real-time performance under continuous operation. We evaluate the complete system under diverse real-world deployment conditions, jointly characterizing inference quality, latency, throughput, and thermal behavior during long-duration operation. A 55-minute vehicular deployment over a 26 km route demonstrates sustained operation at 16.18 FPS within safe thermal limits on a single embedded device without cloud offload. Our findings show that deployment-aware evaluation and temporal inference stabilization are necessary components of continuously operating edge AI systems intended for real-world sensing deployments. We release a

sample annotated streaming video evaluation dataset and full system implementation to support reproducible deployment-centric evaluation at <https://github.com/adityamishra-ml/Edge-TSR.git>.

1 Introduction

AI inference pipelines are increasingly embedded in resource constrained edge hardware for continuous environmental sensing (e.g., roadside perception, structural health monitoring, industrial inspection) where they must sustain reliable operation over extended deployments rather than processing isolated, curated inputs [6, 8, 15, 40]. Despite substantial progress in model accuracy on static benchmarks, the gap between controlled evaluation performance and real-world deployed behavior remains poorly characterized for a class of systems that is rapidly becoming infrastructure: pipelines that perform streaming video inference on moving platforms under hard real-time and resource constraints. This gap is not incidental. It is a structural consequence of evaluating systems on independent image samples drawn from a stationary distribution, when the deployment context is a temporally correlated, non-stationary video stream subject to motion-induced degradations, variable scene complexity, and sustained thermal load on embedded hardware that benchmark protocols do not replicate. This deployment gap is harder to close than it appears. A continuous inference pipeline operating on a moving vehicle must simultaneously satisfy constraints that are in direct tension with one another. It must sustain real-time throughput while managing the thermal envelope of embedded hardware that throttles under prolonged GPU load [4] - a property invisible in short-duration benchmarks but dominant in vehicular operation. It must suppress the frame-to-frame prediction instability inherent to streaming video inference: motion blur, rolling-shutter artifacts, transient occlusions, and illumination changes that compound to degrade classification quality far below static-image benchmark figures [15, 39]. And it must do both while operating under the variable per-frame computational cost of a decoupled detection-classification architecture, where throughput is load-proportional rather than fixed - a property that creates an inverse relationship between scene complexity and system efficiency with direct consequences for deployment planning. Prior work has addressed these constraints individually - proposing efficient detectors [9, 25, 27], temporal reasoning for video [16, 42], or edge-optimized inference [2, 3, 15, 34, 40] - but rarely in combination, and never under evaluation conditions that expose the full scope of real-world deployment behavior. The consequence is a systematic overestimation of deployed system performance. Benchmark evaluations that report accuracy on curated image datasets do not account for the temporal noise (frame-to-frame prediction instability: motion blur, partial occlusions, illumination variation across frames, and detector instability) introduced by streaming video inference. Also, evaluations that report frames per second on a single forward pass do not account for thermal throttling under continuous operation. Also, streaming inference quality scores on balanced, well-lit test sets do not reflect the degradation observed under rain, low light, or at-speed sign exposures. This results in embedded AI systems that perform well in the laboratory and poorly in the field - a failure mode that is directly consequential for any deployment context where inference quality cannot be spot-checked and corrected by a human operator. In this work, we address these challenges through the design and characterization of Edge-TSR, a continuous edge inference system for Traffic Sign Recognition (TSR) on resource-constrained embedded hardware. We use fine-grained traffic sign recognition as a representative streaming perception workload because it simultaneously stresses multiple deployment dimensions ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '리소스 제약이 있는

엣지 하드웨어에서 연속적인 AI 추론을 수행할 경우, 스트리밍 비디오의 시간적 불안정성, 지속적인 부하 하에서의 열 스로틀링, 워크로드에 따른 성능 가변성 등 기존 벤치마크 평가에서는 대부분 간과되는 배포 효과가 발생한다. 본 논문에서는}}, 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}}, 'usageMetadata': {'promptTokenCount': 391, 'candidatesTokenCount': 79, 'totalTokenCount': 2435, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 391}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'ras5arqyBuaNjrEP0bu7uQk'}