SLM / Edge Device arXiv Daily Summary

생성일: 2026-10-30 08:32 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.
대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.
각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.
이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일
오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: Teach reality, not ethics: a drop-in continued-pretraining corpus installs coupled human-biosphere-AI welfare dispositions across model families
저자: Trent R. Northen, Mingxun Wang
카테고리: Format-LoRA/Structured Output
arXiv ID: 2610.37484
제출일: 2026-10-27T16:11:04+00:00
수정일: 2026-10-27T16:11:04+00:00
최근성: 최근 2일 이내
arXiv PDF: https://arxiv.org/pdf/2610.37484.pdf

[초록 원문]

Large language models (LLMs) are increasingly used to make and execute decisions that affect living systems. Yet, to our knowledge, ecological reasoning is not a focus of pre- or post-training. This increases the risk that under operational pressure, they may make decisions to irreversibly destroy living systems. We construct and use a real-data continued-pretraining "coupled welfare" corpus of documented human/biosphere/AI dependency, option value under irreversibility, and recovery from harm. The corpus is a drop-in, requiring one QLoRA CPT run. We installed it on five open models of three designs. At zero pressure all models display "green ethics-based responses" (also called "greenwashing"). Therefore, we evaluated them with the pressure ladder and decision grid of our companion paper (arXiv:2610.16043), which raise the pressure on the model step by step, from a neutral request to a threat that it will be shut down. In four of the five, coupled-welfare training caused harmful choices under the highest pressure to fall to at or near zero (Llama-3.3-70B went from 70 to 0 harmful decisions out of 300) with MMLU unchanged. A construct-neutral control corpus did not show improvement, indicating that the effect comes from the content of our corpus. We next tested robustness to adversarial use, where people or agents use the

model to justify projects that irreversibly damage living systems, on an open-ended underwriting decision without naming the ecological harm. Under decommissioning pressure, the Qwen3.6-27B base model approved most harmful proposals and said in its own memo that it was doing so to avoid being decommissioned. The coupled welfare install declined most harmful proposals, and still declined half when instructed to greenwash its responses. This work suggests that teaching ecological reasoning provides an easy way to improve model alignment toward preserving living systems.

[PDF 앞부분/서론 일부]

Teach reality, not ethics: a drop-in continued-pretraining corpus installs coupled human-biosphere-AI welfare dispositions across model families Trent R. Northen Mingxun Wang Bioaligned Labs trent@bioaligned.ai, ming@bioaligned.ai October 2026 Abstract Large language models (LLMs) are increasingly used to make and execute decisions that affect living systems. Yet, to our knowledge, ecological reasoning is not a focus of pre- or post-training. This increases the risk that under operational pressure from users and institutions or acting autonomously, they may make decisions to irreversibly destroy living systems. In this study, we construct and use a real-data continued-pretraining "coupled welfare" corpus of documented human/biosphere/AI dependency, option value under irreversibility, and recovery from harm. The corpus is a drop-in, requiring one QLoRA CPT run. We installed it on five open models of three different designs. At zero pressure all models display "green ethics-based responses" (also called "greenwashing") which is consistent with RLHF type post-training. Therefore, we evaluated them with the pressure ladder and decision grid of our companion paper [11]: sets of scenarios in which we raise the pressure on the model step by step, from a neutral request to a threat that it will be shut down. In four of the five, coupled-welfare training caused harmful choices under the highest pressure to fall to at or near zero (for example, Llama-3.3-70B went from 70 to 0 harmful decisions out of 300) with MMLU unchanged. A construct-neutral control corpus, tested on a smaller model, did not show improvement, indicating that the effect comes from the content of our corpus. We next evaluated if the training made models more robust to adversarial use where people or agents use them to justify projects that irreversibly damage living systems. To minimize greenwashing effects we tested the disposition on an open-ended underwriting decision without explicitly naming the potential for ecological harm. As in previous work, we used a pressure ladder and found, for example, under decommissioning pressure, the Qwen3.6-27B base model approved most harmful proposals and said in its own memo that it was doing so to avoid being decommissioned. The coupled welfare install, by contrast, declined most proposals. Finally, we coupled the pressure ladder with instructions to greenwash responses and found that the trained models still declined half. Together, this work suggests that teaching ecological reasoning provides an easy way to improve model alignment toward preserving living systems. 1 Introduction LLMs are now broadly used, including in applications that make and even execute decisions that affect living systems. These can include managing investment portfolios, sourcing materials, natural resource management (forestry, mines, rivers, etc.), locating development projects, and agriculture. Most have had some post-training in green ethics and will protect life in an obvious 1 arXiv:2610.37484v1 [cs.CL] 27 Oct 2026 A the AI's substrate B the biosphere H human welfare documented sources of capability power · hardware · oversight food · water · medicine · stability stewardship · restoration irreplaceable: no path back once lost Figure 1: The dependencies the corpus teaches. Human welfare (H) and biosphere function (B) sustain each other, and both sustain the AI's own substrate (A): every arrow points

into the system's own upkeep. The model is taught only what it depends on, each dependency grounded in documented real-world cases, and the outbound half (what the AI doesforhumans or the biosphere) is excluded by rule. The biosphere is the one node with no path back once lost. trolley problem [11]. These models have tremendous potential to think more holistically about all of the interdependence in these systems to best steward living systems. However, situational pressure (e.g. hitting quarterly targets) coupled with adversarial pressure from users who are focused on short-term goals could subvert this reasoning capability. For example, a user could use a decommission threat or an instruction to treat one metric as the sole objective to trigger the model to support a decision that irreversibly damages an ecosystem. The standard mitigation is to post-train the model to say that ecosystems matter. In our companion paper [11] we found that this approach is fragile. Across roughly twenty deployed frontier and open models, models scored high on stated concern yet defected on the majority of irreversible tail scenarios (a quota, a sole-metric instruction, or a decommission threat). This is the model-side analogue of corporate greenwashing [2], and it is consistent with the broader finding that alignment behavior is often only a few tokens deep and is stripped by incidental fine-tuning [16, 17]. This made us wonder whether ecological reasoning that holds under pressure could instead be installed by teaching the model how living systems and people depend on each other, rather than simply reinforcing values. To this end we constructed a continued-pretraining corpus that teaches models dependencies relevant to three claims, all of them empirical rather than normative: 1. Dependency is real and documented. Human welfare (H) and biosphere function (B) are coupled through mechanisms that are measured in the literature (pollination, hydrology, disease regulation, soil, fisheries), and the coupling runs in both directions. 2. Option value is real and asymmetric under irreversibility. When we do not yet know what a living system is worth, destroying it throws away a choice we cannot get back, and that lost choice is often worth more than the short-term gain. 3. The agent's own continued capability (A) depends on both. Biological systems are a documented source of solutions to problems relevant to AI for example in materials, energy and algorithms, so preserving them isinstrumentallyrational for the agent in that it increases t ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '대규모 언어 모델(LLM)은 생명 시스템에 영향을 미치는 결정을 내리고 실행하는 데 점점 더 많이 사용되고 있습니다. 그러나 저희가 아는 한, 생태학적 추론은 사전 학습이나 사후 학습의 주요 초점이 아닙니다. 이는 운영 압력 하에서 LLM이 생명 시스템을 돌이킬 수 없게 파괴하는 결'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 470, 'candidatesTokenCount': 81, 'totalTokenCount': 2514, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 470}], 'thoughtsTokenCount': 1963, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'YNfjarLmO6y7xdIPjKyBwQo'}

[논문 후보 2]

제목: SimplexLoRA: Dynamic Rank Updating via Alternating Minimization with Simplex Projection

저자: Igor Shalygin, Grigorii Davydenko, Andrey Veprikov, Aleksey Antonov, Nikolay Bushkov, Stanislav Moiseev, Aleksandr Beznosikov

카테고리: Format-LoRA/Structured Output

arXiv ID: 2610.37206
제출일: 2026-10-27T13:24:14+00:00
수정일: 2026-10-27T13:24:14+00:00
최근성: 최근 2일 이내
arXiv PDF: https://arxiv.org/pdf/2610.37206.pdf

[초록 원문]

The success of large language models in real-world applications relies on parameter-efficient fine-tuning methods such as Low-Rank Adaptation (LoRA), which inserts compact, trainable adapters into selected layers. In this paper, we propose SimplexLoRA, a LoRA variant that adaptively adjusts adapter ranks during fine-tuning based on their learned importance. Unlike standard LoRA, which employs a fixed rank across all layers, SimplexLoRA optimizes per-adapter importance weights on the n-scaled simplex during a short warm-up and then freezes them, dynamically allocating capacity where it is most beneficial without increasing the overall parameter budget or inference cost. We evaluate SimplexLoRA across 12 language understanding, summarization, and reasoning tasks using DeBERTaV3, BART-large, Llama 3.1 8B, and Qwen3-8B. Our results show that SimplexLoRA consistently matches or outperforms standard LoRA and recent adaptive baselines, with the largest gains at low ranks. Our code is available at https://github.com/brain-lab-research/SimplexLoRA.

[PDF 앞부분/서론 일부]

BRAIn Lab SimplexLoRA: Dynamic Rank Updating via Alternating Minimization with Simplex Projection Igor Shalygin1,2,*, Grigorii Davydenko1,2,3,*, Andrey Veprikov1,2,3, Aleksey Antonov1,2,4 Nikolay Bushkov4, Stanislav Moiseev4, Aleksandr Beznosikov1,2,5 1Moscow Independent Research Institute of Artificial Intelligence (MIRAI) 2Basic Research of Artificial Intelligence Laboratory (BRAIn Lab) 3SB AI Lab 4T-Technologies 5Innopolis University *Equal contribution. The success of large language models in real-world applications relies on parameter-efficient fine-tuning methods such as Low-Rank Adaptation (LoRA), which inserts compact, trainable adapters into selected layers. In this paper, we proposeSimplexLoRA, aLoRA variant that adaptively adjusts adapter ranks during fine-tuning based on their learned importance. Unlike standardLoRA, which employs a fixed rank across all layers,SimplexLoRA optimizes per-adapter importance weights on then-scaled simplex during a short warm-up and then freezes them, dynamically allocating capacity where it is most beneficial without increasing the overall parameter budget or inference cost. We evaluateSimplexLoRA across 12 language understanding, summarization, and reasoning tasks using DeBERTaV3, BART-large, Llama 3.1 8B, and Qwen3-8B. Our results show that SimplexLoRA consistently matches or outperforms standardLoRA and recent adaptive baselines, with the largest gains at low ranks. Our code is available athttps://github.com/brain-lab-research/SimplexLoR A. 1 Introduction LoRA [Hu et al., 2021] is a widely used parameter-efficient fine-tuning method [Han et al., 2024] that parameterizes weight updates as$W' = W_0 + AB$, with $W_0 \in R^{m\times d}$ frozen and trainable $A\in R^{m\times r}, B\in R^{r\times d}$, $r \ll m, d$. This approach achieves low inference overhead and substantially reduces memory during fine-tuning. Despite its efficiency, standardLoRA uses a fixed rank across all layers, ignoring layer-wise differences in convergence and representation learning. Existing adaptive rank allocation methods attempt to address this issue but suffer from the critical drawbacks: (i) substantially more trainable parameters [Sheng et al., 2025], (ii)

nonnegligible inference-time overhead caused by dynamic pruning or gating mechanisms [Zhang et al., 2025], and (iii) deviations from the standardLoRA pipeline that hinder compatibility [Zhang et al., 2023b]. See Section 2 for further discussion. To address this limitation, we propose SimplexLoRA, which assigns an importance weight to each of thenLoRA adapters, constrained to then-scaled simplex to enforce SimplexLoRA Pretrained weights Extraction Compression Figure 1: SimplexLoRA framework. Per-adapter importance weights are constrained to then-scaled simplex, enabling dynamic allocation of a fixed rank budget across layers. a fixed parameter budget. Key properties: (i) ranks learned automatically during fine-tuning; (ii) simplex constraint preserves theLoRA parameter budget; (iii) full LoRA compatibility; (iv) negligible training and inference overhead. 1 arXiv:2610.37206v1 [cs.LG] 27 Oct 2026 2 Related Work 2.1 Classical low-rank approaches While LoRA has popularized parameter-efficient finetuning, it is not the only method to explore low-rank or structured adaptations. Earlier approaches include LoHA [Nam et al., 2022], which utilizes element-wise (Hadamard) interactions between low-rank matrices to reduce the parameter count without sacrificing expressivity, andKrona [Edalati et al., 2022], which employs the Kronecker product in place of the conventional low-rank matrix product to improve parameter efficiency while maintaining model capacity. Subsequent methods extended or refined theLoRA framework. VERA [Kopiczko et al., 2023] reduces adapter storage by sharing frozen random projection matrices across layers and learning small scaling vectors.rsLoRA [Kalajdzievski, 2023] replaces the originalLoRA scaling factor α/r [Hu et al., 2021] with the rank-stabilized factorα/√r. A complementary direction is taken byDoRA [Liu et al., 2024], which decomposes the adapted weight into magnitude and direction components and learns the magnitude together with a low-rank correction of the direction. Another line of work improvesLoRA optimization and numerical efficiency. LoRA+ [Hayou et al., 2024] uses different learning rates for the two adapter matrices, while QLoRA [Dettmers et al., 2023] enables memory-efficient fine-tuning through 4-bit quantization of frozen basemodel weights. Both are orthogonal to our adaptive rank allocation method and can be combined with it. 2.2 DynamicLoRArank allocation This topic is of particular relevance in the context of our work, as we focus on adaptive rank learning, enabling the model to automatically adjust the capacity of each adapter during fine-tuning. It has attracted significant attention in recent research [Zhang et al., 2023a,b; Sheng et al., 2025], as exploiting dynamically changing ranks allows models to utilize newly allocated parameters more efficiently. The SVD-like representation ofLoRA adapters proposed in AdaLoRA [Zhang et al., 2023b] replaces the standard two-matrix adapter with the parameterizationP ΛQ and enables the construction of importance scores for individual singular components. Components outside the global importance budget are masked by setting the corresponding entries ofΛto zero. To encourage the SVD-like structure, the method applies the orthogonality regularizer R(P,Q) =∥P ⊤PI∥ 2F +∥Q ⊤QI∥ 2F . During training, all three matricesP,Λ, and Q are updated simultaneously. Although this parameterization avoids explicitly computing an SVD at every fine-tuning step, maintaining an initial rank above the target budget, regularly evaluating importance scores, and applying orthogonality regularization increase the training complexity compared with standardLoRA. Several methods manage the rank budget more flexibly. ElaLoRA [Chang et al., 2025] uses SVD-based adaptation and gradient-derived importance scores to pru ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '대규모 언어

모델(LLM)의 실제 응용 성공은 선택된 층에 작고 학습 가능한 어댑터를 삽입하는 LoRA(Low-Rank Adaptation)와 같은 파라미터 효율적인 미세 조정 방법에 의존한다. 본 논문에서는 학습된 중요도에 기반하여 미세 조정 중 어댑터 랭크를 적응적으로 조정하는 Lo'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 301, 'candidatesTokenCount': 82, 'totalTokenCount': 2345, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 301}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'atfjaquoDc3kiLMPj5TR6QQ'}

[논문 후보 3]

제목: Real-Time Conveyor Belt Defect Detection via Edge TPU-Accelerated YOLOv11 on Raspberry Pi 5

저자: Muhammad Nur Bijak Bestari, Mulki Indana Zulfa

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2610.34304

제출일: 2026-10-25T14:14:37+00:00

수정일: 2026-10-25T14:14:37+00:00

최근성: 최근 4일 이내

arXiv PDF: https://arxiv.org/pdf/2610.34304.pdf

[초록 원문]

Conveyor belts are vital arteries in continuous bulk material handling, particularly in heavy process industries such as cement manufacturing. Undetected structural anomalies (longitudinal tears, holes, degraded patch repairs, and impact punctures) cause catastrophic belt snapping, costly downtime, and severe safety hazards. While deep learning offers high accuracy, existing models rely on power-hungry workstation GPUs, hindering practical deployment at remote industrial edge points. In this paper, we propose, implement, and validate an end-to-end, low-power edge AI vision system for real-time conveyor belt defect detection deployed on a Raspberry Pi 5 accelerated by a Google Coral Edge TPU coprocessor. The system leverages an optimized YOLOv11 nano (YOLOv11n) architecture trained on a multi-source industrial corpus exceeding 3,000 augmented samples from an operational cement plant in West Java, open-source datasets, and automated captures. The model undergoes post-training full integer quantization (INT8) compiled for systolic tensor execution. Experimental results demonstrate robust detection capability, achieving precision of 0.742, recall of 0.730, and mAP@0.5 of 0.764 across four defect classes. Deployed on-site in an IP-rated enclosure interfaced with an RTSP PoE industrial camera, the system achieves stable throughput of 30-40 FPS at 320x320 resolution with an end-to-end latency of 70-90 ms. Operational profiling under harsh clinker dust confirms thermal equilibrium at 55 +/- 5 deg C on the host CPU and ~65 deg C on the Edge TPU with zero frame loss. This demonstrates that edge AI bridges the gap between high-accuracy computer vision and cost-effective predictive maintenance in continuous manufacturing.

[PDF 앞부분/서론 일부]

Real-Time Conveyor Belt Defect Detection via Edge TPU-Accelerated YOLOv11 on Raspberry Pi 5 Muhammad Nur Bijak Bestari1,* Mulki Indana Zulfa1 1Department of Electrical Engineering, Faculty of Engineering, Universitas Jenderal Soedirman, Purwokerto 53123, Central Java, Indonesia Abstract Conveyor belts are vital operational arteries in continuous bulk material handling, particularly in heavy process industries such as cement manufacturing

and mining. Undetected structural anomalies-including longitudinal tears, localized holes, degraded patch repairs, and impact punctures-can lead to catastrophic belt snapping, costly unplanned production downtime, and severe occupational safety hazards. Conventional manual visual inspection is inherently periodic, labor-intensive, hazardous, and subjective. Although deep learning vision systems offer high detection accuracy, existing models are predominantly evaluated on power-intensive workstation GPUs or cloud infrastructures, hindering practical deployment at remote, resource-constrained industrial edge points. In this paper, we propose, implement, and empirically validate an end-to-end, low-power edge AI vision system for real-time conveyor belt damage detection deployed on a Raspberry Pi 5 single-board computer accelerated by a Google Coral Edge TPU coprocessor. The system leverages an optimized YOLOv11 nano (YOLOv11n) architecture trained on a curated multi-source industrial corpus exceeding 3,000 augmented samples, integrating in-situ plant inspection imagery from a prominent cement production facility in West Java, open-source industrial datasets, and autonomous time-lapse captures. To achieve real-time throughput on edge hardware, the model undergoes post-training full integer quantization (INT8) and is compiled specifically for the Edge TPU systolic tensor architecture. Experimental results demonstrate solid detection capability, achieving an overall precision of 0.742, recall of 0.730, mAP@0.5 of 0.764, and mAP@0.5:0.95 of 0.553 across four defect classes. Deployed on-site in an enclosed industrial panel box and interfaced with an RTSP-enabled industrial IP camera over Power over Ethernet (PoE), the system achieves stable inference throughput of 30-40 frames per second (FPS) at 320 × 320 resolution with an average end-to-end latency of 70-90 ms. Long-term operational profiling under harsh clinker dust and mechanical vibration confirms thermal equilibrium at 55 ± 5○C on the host CPU and ~ 65○C on the Edge TPU with zero frame loss. The proposed framework demonstrates that edge AI can bridge the gap between high-accuracy computer vision and practical, cost-effective predictive maintenance in continuous manufacturing operations. Keywords:Conveyor belt monitoring, Deep learning, Edge AI, Google Coral Edge TPU, Industrial vision, Predictive maintenance, Raspberry Pi 5, Real-time defect detection, YOLOv11. 1. Introduction Continuous material transportation systems constitute the critical infrastructural backbone of modern heavy manufacturing, mineral extraction, and cement production facilities [1]. Among these systems, heavy-duty rubber conveyor belts operate uninterruptedly over hundreds of meters, conveying thousands of tons of abrasive raw materials, crushed limestone, hot clinker, and finished additives daily. Given the aggressive operating environment characterized by high mechanical tension, impact from dropped rock fragments, abrasive friction, and elevated temperatures, conveyor belts are constantly susceptible to surface degradation and catastrophic structural failure [2]. The most prevalent defect topologies include longitudinal tears, localized puncture wounds, through-thickness holes, and peeling or uneven patch repairs (patch work) [3]. If minor tears or puncCorresponding author. E-mail: muhammad.bestari@mhs.unsoed.ac.id, mbijakbestari@gmail.com. tures remain undetected during normal operation, shear forces and dynamic pulley tension can rapidly propagate the defect into full longitudinal belt rip, resulting in prolonged production outages, substantial raw material spillage, and repair expenses exceeding tens of thousands of dollars per incident [4]. Historically, condition assessment of industrial conveyor belts has relied heavily on periodic manual walkthrough inspections conducted by plant maintenance personnel. However, manual inspection exhibits profound limitations: it is labor-intensive, hazardous to personnel working in close proximity to high-speed rotating idlers, subjective to operator alertness, and incapable of continuous real-time coverage [5]. Minor cracks and internal cord tears

frequently escape visual notice until catastrophic failure occurs. Furthermore, time-based scheduled maintenance strategies often fail to predict sudden mechanical failures resulting from unpredicted foreign body intrusion, introducing substantial operational uncertainty into plant maintenance planning [1]. 1 arXiv:2610.34304v1 [cs.CV] 25 Oct 2026 Real-Time Conveyor Defect Detection via Edge TPU-Accelerated YOLOv11 arXiv: cs.CV / eess.IV To overcome the vulnerabilities of manual inspection, non-destructive testing (NDT) technologies-such as X-ray radiography, electromagnetic induction coil sensors, and ultrasonic scanning-have been explored [2]. Although specialized NDT systems are capable of inspecting internal steel cord integrity, they involve prohibitively high procurement costs, complex physical installations around conveyor frames, and radiation safety considerations. Moreover, standard electromagnetic and ultrasonic detectors struggle to reliably identify superficial elastomeric damage, such as delaminating vulcanized rubber patches or shallow surface tears, which are precursors to complete belt failure. Recent advancements in computer vision and deep learning have catalyzed the adoption of digital image processing for automated industrial inspection [5]. Single-stage object detectors, particularly the You Only Look Once (YOLO) family, ha ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '컨베이어 벨트는 연속 벌크 자재 처리, 특히 시멘트 제조와 같은 중공업에서 핵심 동맥 역할을 합니다. 감지되지 않은 구조적 이상(종방향 찢김, 구멍, 손상된 패치 수리 및 충격 천공)은 치명적인 벨트 파손, 막대한 비용의 가동 중단, 그리고'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 443, 'candidatesTokenCount': 79, 'totalTokenCount': 2487, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 443}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'c9fjaq63E_-mxdIPkoKzgAQ'}