

SLM / Edge Device arXiv Daily Summary

생성일: 2026-09-28 07:31 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: A Rapid Pipeline for Training and Deploying ML Models on WeBe Band

저자: Ehsan Kourkchi, Asmita Asmita, Houman Homayoun, Mahdi Eslamimehr

카테고리: SLM/Edge/On-device, Deployment/Quantization/Efficiency

arXiv ID: 2609.29084

제출일: 2026-09-24T06:10:59+00:00

수정일: 2026-09-24T06:10:59+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2609.29084.pdf>

[초록 원문]

Developing optimized machine-learning algorithms for edge devices with limited computational and memory resources is challenging, time-consuming, and highly dependent on device-specific constraints. In this work, we streamline an edge ML workflow to enable rapid development, optimization, and deployment of machine-learning (ML) models directly on the WeBe Band, a wrist-worn wearable device designed for multimodal physiological data monitoring. The proposed system automatically generates hardware-efficient ML models that can be easily integrated into the WeBe core firmware, supporting AutoML, hardware-aware quantization, and performance profiling to build models that meet desired latency targets while remaining compatible with device memory and power limitations. The proposed framework tightly integrates the open-source Piccolo AI ecosystem with an automated pipeline that generates deployable firmware artifacts, performs hardware-aware model compilation, and supports over-the-air (OTA) deployment. The system supports multiple lightweight model classes, including classical machine-learning algorithms and neural networks, and provides built-in on-device profiling tools to evaluate inference latency and memory footprint under realistic execution conditions. Experimental results demonstrate clear trade-offs between model complexity and deployability on a microcontroller, showing that

classical models offer strong real-time performance while lightweight neural networks require careful resource management. Rather than proposing new learning architectures, the current work mainly focuses on system-level automation, deployability, and enabling researchers and developers to rapidly iterate on models and evaluate them directly on target hardware. Although demonstrated on the WeBe Band platform, the workflow is designed to be extensible to other ML-powered edge devices.

[PDF 앞부분/서론 일부]

A Rapid Pipeline for Training and Deploying ML Models on WeBe Band 1st Ehsan Kourkchi Dep. of Electrical and Computer Engineering UC Davis, CA, USA. ORCID: 0000-0002-5514-3354 2nd Asmita Asmita Dep. of Electrical and Computer Engineering UC Davis, CA, USA. aasmita@ucdavis.edu 3rd Houman Homayoun Dep. of Electrical and Computer Engineering UC Davis, CA, USA. hhomayoun@ucdavis.edu 4th Mahdi Eslamimehr dept. name of organization (of Aff.) Quandary Peak Research Los Angeles, CA, USA. mahdi@quandarypeak.com

Abstract-Developing optimized machine-learning algorithms for edge devices with limited computational and memory resources is challenging, time-consuming, and highly dependent on device-specific constraints. In this work, we streamline an edge ML workflow to enable rapid development, optimization, and deployment of machine-learning (ML) models directly on the WeBe Band, a wrist-worn wearable device designed for multimodal physiological data monitoring. The proposed system automatically generates hardware-efficient ML models that can be easily integrated into the WeBe core firmware, supporting AutoML, hardware-aware quantization, and performance profiling to build models that meet desired latency targets while remaining compatible with device memory and power limitations. The proposed framework tightly integrates the open source Piccolo Alecosystem with an automated pipeline that generates deployable firmware artifacts, performs hardware-aware model compilation, and supports over-the-air (OTA) deployment. The system supports multiple lightweight model classes, including classical machine-learning algorithms and neural networks, and provides built-in on-device profiling tools to evaluate inference latency and memory footprint under realistic execution conditions. Experimental results demonstrate clear trade-offs between model complexity and deployability on a microcontroller, showing that classical models offer strong real-time performance while lightweight neural networks require careful resource management. Rather than proposing new learning architectures, the current work mainly focuses on system-level automation, deployability, and enabling researchers and developers to rapidly iterate on models and evaluate them directly on target hardware. Although demonstrated on the WeBe Band platform, the workflow is designed to be extensible to other ML-powered edge devices.

Index Terms-TinyML, wearable devices, edge AI, embedded systems, on-device inference, model deployment

I. Introduction Tiny Machine Learning (TinyML) has become a powerful way to run machine learning (ML) models directly on small, low-power edge devices such as microcontrollers, wearable devices, and IoT systems [1]-[3]. It enables real-time inference on ultra-low-power hardware, reduces system latency, and minimizes reliance on cloud computing. TinyML is now * a.k.a Edwin E. Kay (ekay@ucdavis.edu) widely used in many applications, including wearable health monitoring [4], industrial machinery maintenance and anomaly detection [5], and environmental or smart-home automation [6]. Despite its growing use in consumer and industrial products, the adoption of tiny ML models in academic and applied research remains relatively limited. One major reason is the fragmented workflow between model development and deployment on embedded hardware. Researchers are often expected to have expertise not only in machine

learning, but also in embedded systems, including firmware development, compiler toolchains, and hardware-level optimization. This steep technical barrier can slow progress, particularly for domain experts in areas such as healthcare or physiological signal analysis, whose primary focus is on data interpretation rather than low-level system integration. In wearable health research, this gap between model development and embedded deployment is particularly pronounced. Many interdisciplinary teams possess strong expertise in data science or clinical analysis but lack the embedded systems knowledge required to transform machine-learning models into real-time applications on wearable hardware. As a result, promising ML models for edge devices frequently remain confined to offline evaluation environments rather than being tested under realistic sensing and execution conditions. Bridging this gap requires workflows that not only optimize model performance but also streamline integration, compilation, and deployment directly on target devices. In this work, we present a research framework to abstract away the complexities of deploying optimized ML models on embedded devices. Our proposed system provides an end-to-end pipeline for WeBe Band that enables researchers to experiment with diverse ML models and feature sets without manually interacting with the device firmware. The workflow allows users to simply upload collected data and the corresponding ML model artifacts; and our backend framework automatically generates the appropriate header files, configures compiler settings, and produces a deployable binary or ZIP package. This package can then be flashed or delivered via arXiv:2609.29084v1 [cs.AI] 24 Sep 2026 Fig. 1. Overview of the proposed end-to-end pipeline. KP stands for the model knowledge pack, a ZIP file that holds the model artifacts including the compiled flashable library. over-the-air (OTA) to WeBe Band. By automating the integration process, the proposed pipeline allows researchers to mainly focus on model development, performance evaluation, and domain-specific analysis rather than low-level firmware handling. We anticipate that this system will lower the entry barrier for TinyML experimentation and accelerate research in edge-based healthcare analytics. The framework supports multiple lightweight model classes, including classical machine-learning algorithms and neural networks, and provides built-in profiling tools that measure inference latency and memory footprint directly on-device. This hardware-aware evaluation allows ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '제한된 연산 및 메모리 자원을 갖는 엣지 디바이스를 위한 최적화된 머신러닝 알고리즘 개발은 어렵고, 시간이 많이 소요되며, 디바이스별 제약 조건에 크게 의존적입니다. 본 연구에서는 다중 모드 생체 신호 모니터링을 위해 설계된 손목 착용형'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 383, 'candidatesTokenCount': 80, 'totalTokenCount': 2427, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 383}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'DJm5areuLf2Az7IPrPjGwAc'}

[논문 후보 2]

제목: On Growth and Form, and Function: Reusable Regulatory Handles Control Phenotypic Variation

저자: Benedikt Hartl, Milton L. Montero, Marcello Barylli, Sebastian Risi, Michael Levin

카테고리: Format-LoRA/Structured Output

arXiv ID: 2609.29755

제출일: 2026-09-24T13:05:57+00:00

수정일: 2026-09-24T13:05:57+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2609.29755.pdf>

[초록 원문]

How phenotypic transformations are implemented by changes in underlying regulatory dynamics remains a central question in developmental biology. Inspired by D'Arcy Thompson's 1917 "On Growth and Form", we ask whether coherent large-scale transformations of morphology can be encoded as low-dimensional modulations of a self-organizing developmental system. We use neural cellular automata (NCAs) as bio-inspired models of distributed development, in which a shared local regulatory network grows target morphologies from a single cell. We apply low-rank adaptation (LoRA) to pretrained NCAs, representing each adapted developmental program as a low-rank modulation of a fixed regulatory scaffold. Horizontal and vertical scaling of a fully grown 2D emoji phenotype can each be implemented by rank-one adaptations. Their linear combinations parametrically control phenotype size, generalize beyond the training distribution, and compose with target-specific adapters. Strikingly, adaptations learned for one phenotype transfer zero-shot across structurally and semantically diverse phenotypes sharing the same reference scaffold, while largely preserving internal features. This suggests reusable system-level hyper-directions of scale rather than morphology-specific transformations. From approximately 25,000 independently trained phenotype-specific NCA adapters with a shared scaffold, we further identify latent low-dimensional directions that functionally control phenotypic variation including scaling, style, and symmetrical fission. Together, our results provide a computational realization of D'Arcy Thompson's remarkable grid transformations in a 2D NCA---a minimal cybernetic tissue in which variations of fully grown emoji phenotypes can be encoded, combined, and controlled through low-dimensional directions in regulatory weight space.

[PDF 앞부분/서론 일부]

On Growth and Form, and Function: Reusable Regulatory Handles Control Phenotypic Variation Benedikt Hartl¹,
, Milton L. Montero², , Marcello Barylli², , Sebastian Risi^{2,3}, , and Michael Levin^{1,4,, 1}Allen Discovery Center at
Tufts University, Medford, MA, USA 2IT University of Copenhagen, Denmark 3Sakana AI, Japan 4Wyss Institute for
Biologically Inspired Engineering at Harvard University, Boston, MA, USA Corresponding Authors:
hartl.bene.research@gmail.com and michael.levin@tufts.edu Keywords: Evo-Devo, Morphogenesis, Phenotypic
Variation, Cybernetic Tissue, Neural Cellular Automata, Low-Rank Adaptation, Regulatory Networks, Morphospace,
D'Arcy Thompson Running Title: LoRA-NCA: low-rank regulatory control of phenotypic variation Abstract How
phenotypic transformations are implemented by changes in the underlying regulatory dynamics remains a central
question in developmental biology. Inspired by D'Arcy Thompson's 1917 "On Growth and Form", we investigate
whether coherent, large-scale geometric transformations of morphology can be encoded as low-dimensional
modulations of a self-organizing developmental system. We use neural cellular automata (NCAs) as bio-inspired
models of distributed development, in which a shared local regulatory network drives cellular development
from a single seed toward a target morphology. To model how systematic modulations of cellular regulatory
networks unfold into targeted changes in developmental outcomes, we apply low-rank adaptation (LoRA) to the

regulatory parameters of pretrained NCAs. LoRA represents each adapted developmental program as a low-rank weight modulation of a fixed regulatory scaffold shared across adaptations. We show that horizontal and vertical scaling transformations of a fully grown 2D emoji phenotype can each be implemented by rank-one adaptations of the NCA's regulatory weights. Linear combinations of these adaptations parametrically control the size of the resulting phenotype, generalize to scaling factors outside the training distribution, and compose with target-specific adapters. Strikingly, adaptations learned for a single phenotype transfer zero-shot across structurally and semantically diverse phenotypes trained relative to the same reference frame, while largely preserving their internal features. These results suggest that the learned adaptations represent reusable, system-level hyper-directions of scale rather than transformations tied to a particular morphology. From a static dataset of approximately 25,000 independently trained phenotype-specific NCA adapters with shared scaffold, we empirically discover latent low-dimensional hyper-directions that functionally address phenotypic variation such as scaling, style, or symmetrical fission of developmental outcomes. Together, our results provide a computational realization of D'Arcy Thompson's remarkable grid transformations in a 2D NCA—a minimal cybernetic tissue in which variations in shape and other traits of fully grown emoji phenotypes can be encoded, combined, and controlled through interventions along low-dimensional directions in regulatory weight space. Highlights:

- LoRA is effective to fine-tune complex dynamical systems such as NCAs.
- LoRA can map phenotypic variation to regulatory modulation in cybernetic systems.
- The corresponding regulatory weight space has semantic geometry with functional hyper-directions.
- We train and empirically find universal hyper-directions in regulatory space, that generalize across different phenotypes with shared regulatory logic.
- LoRA decomposition provides a principled way to identify such low-rank regulatory handles for topdown control of cybernetic tissue, which has strong implications for evolvability and biological plasticity in general.
- D'Arcy Thompson's grid transformations (1917) can be controlled through such latent regulatory handles anticipated by Howard Pattee (1973).

1 arXiv:2609.29755v1 [cs.NE] 24 Sep 2026

1 Introduction In his 1917 book *On Growth and Form*, D'Arcy Thompson argued for systematically applying mathematical and physical principles to the biological world. He described the effects of scale on the shape of animals and plants, pointing out correlations between biological forms and mechanical phenomena. Most famously, in the chapter "The Comparison of Related Forms", Thompson showed that morphological variations among related species can be understood through simple mathematical transformations. By drawing a Cartesian grid around the anatomy of one species and deforming it, Thompson often obtained the characteristic shapes of other, related species such as certain kinds of fish, see Figure 1 A. The procedure goes as follows: (1) Choose the morphology of a particular species. (2) Draw a Cartesian grid around the morphology. (3) Apply deformations to the grid via coordinate transformations. (4) Carry along the corresponding transformation to the anatomical landmarks by the same map. (Possibly 5) end up with the morphology of a different species. D'Arcy Thompson pioneered the idea that biological organization is strongly governed by mathematical and mechanical principles. These insights inspired great thinkers across biology, mathematics and the physical sciences, including Waddington, Turing and Kauffman, and became important precursors of modern evolutionary developmental biology (evo-devo).² Yet Thompson's transformations still lacked a causal developmental explanation, as emphasized by Arthur:³ they neither identify which microscopic processes produce these anatomical differences nor where-and when-they must change during growth. And despite major scientific

advances in our understanding of growth and form in biological organization, Thompson left behind a century-old inverse problem: 4 if two anatomies are related by a simple grid transformation, what is the corresponding modulation of the developmental dynamics that physically generate them? Put simply, what does the grid, and its global d ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '표현형 변환이 기저의 조절 역학 변화에 의해 어떻게 구현되는지는 발생 생물학의 핵심 질문으로 남아있습니다. D.W. Arcy Thompson의 1917년 저서 "성장과 형태에 관하여(On Growth and Form)"에 영감을 받아, 우리는 일관된 대규모 형태 변환이 자기 조직화하는 발생'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 399, 'candidatesTokenCount': 80, 'totalTokenCount': 2443, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 399}], 'thoughtsTokenCount': 1964, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'FZm5av_pKu7rz7IP0dLvmQw'}

[논문 후보 3]

제목: Edge AI on Constrained Devices for Binary Sleep-Wake Classification in Dynamic Environments
저자: Stefan Reitmann, Lena Oden
카테고리: SLM/Edge/On-device
arXiv ID: 2609.29163
제출일: 2026-09-24T07:36:20+00:00
수정일: 2026-09-24T07:36:20+00:00
최근성: 최근 3일 이내
arXiv PDF: <https://arxiv.org/pdf/2609.29163.pdf>

[초록 원문]

This paper presents an Edge AI-based system for detecting sleep and wake states in non-stationary mobile environments using resource-constrained embedded hardware. Conventional approaches relying on accelerometer-based activity metrics are highly susceptible to motion and vibration artifacts and are limited by strict compute and energy budgets of wearable and IoT devices. To address these challenges, a multimodal pipeline is designed and implemented on an ESP32-S3 microcontroller. The system combines inertial sensing for head movement analysis and visual pose classification. A dual-core architecture with FreeRTOS enables parallel execution of real-time data acquisition and on-device inference. Sleep detection follows a two-stage strategy: low-movement detection over a temporal window, followed by visual validation of poses. Experimental results show accuracies of 96.5% for motion-based detection and 89% for pose classification, yielding robust binary sleep-wake classification. Field tests confirmed feasibility in representative mobile scenarios. The results demonstrate that privacy-preserving, local sleep detection is achievable on edge hardware through careful co-design, while highlighting limitations in sensing intrusiveness, dataset scale, and system integration.

[PDF 앞부분/서론 일부]

Edge AI on Constrained Devices for Binary Sleep-Wake Classification in Dynamic Environments Stefan Reitmann,

Lena Oden[†] Faculty of Computer Science, Chemnitz University of Technology, Chemnitz, Germany Email: stefan.reitmann@informatik.tu-chemnitz.de [†]Faculty of Computer Science, University of Hagen, Hagen, Germany

Email: lena.oden@fernuni-hagen.de **Abstract**-This paper presents an Edge AI-based system for detecting sleep and wake states in non-stationary mobile environments using resource-constrained embedded hardware. Conventional approaches relying on accelerometer-based activity metrics are highly susceptible to motion and vibration artifacts and are limited by strict compute and energy budgets of wearable and IoT devices. To address these challenges, a multimodal pipeline is designed and implemented on an ESP32-S3 microcontroller. The system combines inertial sensing for head movement analysis and visual pose classification. A dual-core architecture with FreeRTOS enables parallel execution of real-time data acquisition and on-device inference. Sleep detection follows a twostage strategy: low-movement detection over a temporal window, followed by visual validation of poses. Experimental results show accuracies of 96.5% for motionbased detection and 89% for pose classification, yielding robust binary sleep-wake classification. Field tests confirmed feasibility in representative mobile scenarios. The results demonstrate that privacy-preserving, local sleep detection is achievable on edge hardware through careful co-design, while highlighting limitations in sensing intrusiveness, dataset scale, and system integration.

Index Terms-edge ai, machine learning, embedded systems, microcontroller, sleep detection

I. INTRODUCTION

Sleep-wake state detection has become increasingly important across a wide range of applications, including health monitoring, recreational use, and safety-critical systems. Recent advances in wearable and Internet of things (IoT) devices enable continuous acquisition of physiological and motionrelated sensor data, providing the foundation for automated sleep analysis. These systems offer the potential for unobtrusive, long-term monitoring outside controlled laboratory environments. However, in many real-world scenarios, such systems operate under non-ideal measurement conditions. In particular, mobile or dynamic environments - such as vehicles or bicycle trailers - introduce additional motion and vibration that affect sensor readings. These external motion artifacts can overlap with the relevant physiological signals, significantly complicating the reliable discrimination between sleep and wake states. Another key challenge arises from the limited computational and energy resources of wearable and IoT devices. Since such systems typically rely on low-power embedded hardware, algorithms for state classification must be both robust to noisy sensor data and efficient in their execution. Computationally complex models are often impractical, while sufficient classification accuracy must still be maintained. Against this background, there is a clear need for methods that enable reliable sleep-wake detection under motion-intensive conditions while remaining suitable for deployment on resource-constrained edge devices. This paper addresses this challenge by developing and prototypically implementing an Edge AI-based system for automatic sleep-wake classification on embedded hardware in mobile environments. The approach focuses on processing sensor data - primarily motion and visual signals - directly on-device, enabling privacy-preserving and energy-efficient operation without reliance on cloud-based computation. The following research questions guide this work: 1) How can motion artifacts originating from mobile platforms be mitigated to enable robust sleep detection on edge devices? 2) Which features and models provide the best trade-off between accuracy and computational efficiency under resource constraints? 3) To what extent, and in which application scenarios, does sensor fusion improve robustness compared to motiononly approaches? The system is evaluated experimentally with respect to classification accuracy, computational cost, energy consumption, and robustness to motion artifacts. The results provide insight

into the feasibility of reliable sleep-wake detection under realistic operating conditions and identify promising methodological approaches for resource-constrained Edge AI systems. The source code, trained models, and anonymized inertial datasets are publicly available under an open-source license at https://github.com/Reitmania/esp32_sleepdetection. The repository includes all necessary implementation details for reproduction and extension of the presented results. Camera data are excluded due to privacy considerations.

A. Background and Related Work 1) Embedded Systems and Edge AI: Embedded systems are a fundamental component of modern cyber-physical applications, performing specialized computational tasks under strict constraints in processing power, memory, and energy consumption [1]. Unlike general-purpose systems, they are arXiv:2609.29163v1 [cs.LG] 24 Sep 2026 optimized for dedicated functionalities and often operate under real-time requirements. These characteristics make them well suited for Edge AI, where data processing is performed locally at the data source rather than in centralized cloud infrastructures. Microcontroller units (MCUs) are widely used in such systems due to their low power consumption and tight hardware-software integration. To manage concurrent tasks such as sensor acquisition and inference, real-time operating systems (RTOS), e.g., FreeRTOS, are commonly employed. Efficient scheduling and resource management are essential to ensure deterministic behavior and system reliability [2]. 2) Sensor Systems and Multimodal Sensing: Sensor systems provide the interface between the physical and digital domains by capturing environmental and phys ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '본 논문은 자원 제약적인 임베디드 하드웨어를 사용하여 비정지 모바일 환경에서 수면 및 각성 상태를 감지하는 엣지 AI 기반 시스템을 제시한다. 가속도계 기반 활동 지표에 의존하는 기존 접근 방식은 움직임 및 진동 아티팩트에 매우 취약하며, 웨어러블'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 298, 'candidatesTokenCount': 79, 'totalTokenCount': 2342, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 298}], 'thoughtsTokenCount': 1965, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'Hpm5atqQN7bo-8YPhcagMA'}