

SLM / Edge Device arXiv Daily Summary

생성일: 2026-09-07 06:37 KST

Gemini 모델: gemini-2.5-flash

검색 범위: 최근 30일

Gemini 전체 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 전체 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

각 논문에 대해 초록 원문, PDF 앞부분/서론 일부, 초록 한국어 번역을 함께 정리합니다.

이 후보들은 pending 상태로 기록되므로 다음 실행 때 중복 후보로 반복 생성되지 않습니다.

선택된 검색 범위: 최근 30일

오류 메시지: Gemini가 적합한 논문을 선정하지 않았습니다.

[논문 후보 1]

제목: EGT-KG: Evidence-Grounded Typed KG Retrieval for Practical Scientific QA with Small Language Models

저자: Muran Yu, Jiechao Gao, Yuandong Pan, Barney H. Miao, Andrew C. Lesh, Kincho H. Law, Jie Wang, Michael D. Lepech

카테고리: SLM/Edge/On-device

arXiv ID: 2609.00479

제출일: 2026-08-31T23:27:57+00:00

수정일: 2026-08-31T23:27:57+00:00

최근성: 최근 5일 이내

arXiv PDF: <https://arxiv.org/pdf/2609.00479.pdf>

[초록 원문]

For emerging scientific research domains, local Small Language Models (SLMs) are becoming more attractive, as they offer stronger privacy control and more stable deployment pipelines than Large Language Models. However, in practice, scientific question-answering on SLMs often operates under inevitable constraints: small literature collections, fragmented evidence, limited context window and reasoning abilities. We propose the Evidence-Grounded Typed Knowledge Graph (EGT-KG), a retrieval framework to improve information retrieval with local SLMs. We assessed three question-answering settings: a vanilla Retrieval-Augmented Generation (RAG) workflow and two EGT-KG workflows: an automatically generated relation schema (AS) and an expert-defined relation schema (ES). Our experiments were evaluated with a six-dimensional evaluation framework (S3CRF: Soundness, Correctness, Completeness, Conciseness, Relevance, Fluency) on a Biopolymer-bound Soil Composite literature benchmark, showing that EGT-KG outperforms the vanilla RAG method in most settings, with the best improvement from llama3:8b: a Final Score of 70.37 (+14.67%) and 68.82 (+12.14%) by AS/ES EGT-KG variants.

[PDF 앞부분/서론 일부]

EGT-KG: Evidence-Grounded Typed KG Retrieval for Practical Scientific QA with Small Language Models Muran Yu¹, Jiechao Gao¹, Yuandong Pan¹, Barney H. Miao^{1,2} Andrew C. Lesh¹, Kincho H. Law¹, Jie Wang¹, Michael D. Lepech¹ ¹Department of Civil and Environmental Engineering, Stanford University ²Department of Civil Engineering, University of Calgary {yumuran, jiechao, ydpan, barneym, aclesh, law, jiewang, mlepech}@stanford.edu

Abstract For emerging scientific research domains, local Small Language Models (SLMs) are becoming more attractive, as they offer stronger privacy control and more stable deployment pipelines than Large Language Models. However, in practice, scientific question-answering on SLMs often operates under inevitable constraints: small literature collections, fragmented evidence, limited context window and reasoning abilities. We propose the EvidenceGrounded Typed Knowledge Graph (EGT-KG), a retrieval framework to improve information retrieval with local SLMs. We assessed three question-answering settings: a vanilla Retrieval-Augmented Generation (RAG) workflow and two EGT-KG workflows: an automatically generated relation schema (AS) and an expert-defined relation schema (ES). Our experiments were evaluated with a sixdimensional evaluation framework (S3CRF: Soundness, Correctness, Completeness, Conciseness, Relevance, Fluency) on a Biopolymerbound Soil Composite literature benchmark, showing that EGT-KG outperforms the vanilla RAG method in most settings, with the best improvement from llama3:8b: a Final Score of 70.37 (+14.67%) and 68.82 (+12.14%) by AS/ES EGT-KG variants.

1 Introduction The rapid evolution of Large Language Models (LLMs) has changed the paradigm in scientific knowledge discovery and human-AI collaboration, including scientific question-answering (Zheng et al., 2025). However, the deployment of frontier LLMs for specialized research workflows can raise concerns about data privacy, operational costs, and inference latency (Pan et al., 2025; Cai et al., 2024). Therefore, Small Language Models (SLMs) have become increasingly attractive for domain-specific applications in constrained environments (Wang et al., 2025; Lu et al., 2024). Yet, SLMs are often unreliable for specialized scientific question-answering because they have limited internal knowledge, weaker reasoning ability, and lower tolerance for noisy context than frontier LLMs (Allen-Zhu and Li, 2024; Lee et al., 2026; Mallen et al., 2023). This challenge is particularly critical in emerging research domains, where knowledge is fragmented across a small set of knowledge sources and is not well represented in pretraining corpora. Retrieval-Augmented Generation (RAG) (Lewis et al., 2021) can ground local models in external documents, but conventional dense retrieval is often insufficient for scientific QA. Scientific questions may depend on relations among materials, procedures, conditions, observations, and results, while dense RAG mainly retrieves chunks by semantic similarity. As a result, retrieved passages may be broadly relevant but still miss the specific evidence needed for faithful answering. Graph-based RAG methods address part of this issue by organizing information into entities and relations (Edge et al., 2024). However, general knowledge graphs may lack timeliness and finegrained domain knowledge (Ding et al., 2024), and automatically constructed graphs can introduce noisy or ambiguous relations (Schäfer et al., 2024; Zhuang et al., 2025). Moreover, converting scientific narratives into triples may discard experimental context, conditional qualifiers, and quantitative details that are necessary for reasoning (Pujara et al., 2017). We propose the Evidence-Grounded Typed KG (EGT-KG) framework to improve RAG with local SLMs in scientific question-answering settings. Our method extends graph-based retrieval with two principles: First, graph structures should guide retrieval rather than replace the original evidence. Second, the relation structure should be informative enough to be useful in retrieving. Thus, we construct a reified knowledge graph

with evidence nodes and classified relations, allowing the system arXiv:2609.00479v1 [cs.AI] 31 Aug 2026 to use relation labels as a retrieval signal. We evaluate our framework on Biopolymerbound Soil Composite (BSC)-centered materials QA benchmark built from a 30-paper corpus. The knowledge of BSC is distributed across a compact but specialized literature collection, making it a realistic test case for small-corpus scientific QA. We compared a vanilla RAG workflow with two EGT-KG variants: an automatically generated schema (AS) and an expert-designed schema (ES). The results show that EGT-KG enhanced retrieval improves answer quality for most cases, particularly in factual retrieval questions. The core contributions of this paper are summarized as follows: First, to enhance RAG in limited resource settings, we propose an Evidence-Grounded Typed KG framework that combines relation classification with provenance-aware evidence nodes for scientific question-answering with local SLMs. Second, we performed a controlled comparison on the BSC-centered benchmark between different workflows, systematically studying the trade-off between schema granularity and answer quality. Third, we introduce an S3CRF evaluation setting that combines multidimensional scoring (Soundness,Correctness,Completeness, Conciseness,Relevance, andFluency) and retrieval performance analysis, illustrating how answer quality is affected by the six criteria, query expansion, fallback rate, and evidence-window usage. 2 Related Works Retrieval.Retrieval-Augmented Generation (RAG) is a widely adopted approach to improving question-answering by providing external knowledge that is not stored in the model's parameters (Lewis et al., 2020). It can improve factual grounding and reduce hallucinations, demonstrating its potential for question-answering in professional domains such as medicine, educ ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '신흥 과학 연구 분야에서 로컬 소형 언어 모델(SLM)은 대규모 언어 모델(LLM)보다 강력한 개인 정보 보호 제어와 더 안정적인 배포 파이프라인을 제공하여 더욱 매력적으로 부상하고 있습니다. 하지만 실제로는 SLM을 이용한 과학 질문-답변은 소규모 문헌 컬렉션, 단편적인 증거, 제한된 컨텍스트 창 및 추론 능력과 같은 필연적인 제약 조건 하에서 작동하는 경우가 많습니다. 본 연구에서는 로컬 SLM을 이용한 정보 검색을 개선하기 위한 검색 프레임워크인 증거 기반 유형화된 지식 그래프(EGT-KG)를 제안합니다.¶¶¶¶¶¶우리는 세 가지 질문-답변 설정을 평가했습니다: 일반적인 검색 증강 생성(RAG) 워크플로우와 두 가지 EGT-KG 워크플로우(자동 생성 관계 스키마(AS) 및 전문가 정의 관계 스키마(ES)). 우리의 실험은 생체 고분자 결합 토양 복합체 문헌 벤치마크에서 6차원 평가 프레임워크(S3CRF: 건전성, 정확성, 완전성, 간결성, 관련성,}}, 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 328, 'candidatesTokenCount': 267, 'totalTokenCount': 2372, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 328}], 'thoughtsTokenCount': 1777, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'AN2darCzOdCHz7IPvOmtiAQ'}

[논문 후보 2]

제목: Persistent Identity Preservation in Generative Image Models: A Benchmark and Evaluation System
저자: Mengwei Ren, Xuaner Zhang, Zhihao Xia
카테고리: Format-LoRA/Structured Output
arXiv ID: 2609.04151
제출일: 2026-09-03T17:44:25+00:00

수정일: 2026-09-03T17:44:25+00:00

최근성: 최근 3일 이내

arXiv PDF: <https://arxiv.org/pdf/2609.04151.pdf>

[초록 원문]

Generative image models can now produce high-quality images, follow complex instructions, and support precise edits, but they still struggle to preserve who or what is being depicted. When generating or editing images of a specific subject, identity may drift as the pose, expression, appearance, viewpoint, or surrounding scene changes. Existing subject-driven methods make fundamentally different choices about where identity is represented: through the input context (GPT-Image-2, NB2), as trainable subject-specific model parameters (LoRA), or as a persistent identity layer (PHOTA IDENTITY) reusable across generations and edits. We systematically benchmark these paradigms across subject-driven generation, editing, restoration, and multi-subject settings, with tasks designed to increasingly stress identity preservation. Our results show that identity preservation remains a distinct limitation of current generative foundation models: strong image quality and instruction following do not necessarily imply strong identity fidelity, and identity degradation becomes more pronounced under iterative edits, small subject scales, severe image degradation, and multi-subject composition. Persistent identity substantially reduces this degradation across generation, editing, and restoration, consistently improving identity preservation when applied to different foundation models while maintaining comparable instruction adherence and perceptual image quality. These results suggest that identity does not simply emerge from increasingly capable generative models, but can instead be represented as persistent subject knowledge that is composed independently with the underlying generative model.

[PDF 앞부분/서론 일부]

Persistent Identity Preservation in Generative Image Models: A Benchmark and Evaluation System Phota Labs Research Abstract Generative image models can now produce high-quality images, follow complex instructions, and support precise edits, but they still struggle to preserve who or what is being depicted. When generating or editing images of a specific subject, identity may drift as the pose, expression, appearance, viewpoint, or surrounding scene changes. Existing subject-driven methods make fundamentally different choices about where identity is represented: through the input context (GPT-IMAGE-2,NB2), as trainable subject-specific model parameters (LORA), or as a persistent identity layer (PHOTA IDENTITY) reusable across generations and edits. We systematically benchmark these paradigms across subject-driven generation, editing, restoration, and multi-subject settings, with tasks designed to increasingly stress identity preservation. Our results show that identity preservation remains a distinct limitation of current generative foundation models: strong image quality and instruction following do not necessarily imply strong identity fidelity, and identity degradation becomes more pronounced under iterative edits, small subject scales, severe image degradation, and multi-subject composition. Persistent identity substantially reduces this degradation across generation, editing, and restoration, consistently improving identity preservation when applied to different foundation models while maintaining comparable instruction adherence and perceptual image quality. These results suggest that identity does not simply emerge from increasingly capable generative models, but can instead be represented as persistent subject knowledge that is

composed independently with the underlying generative model. Authors: Mengwei Ren (project lead), Cecilia Zhang, Zhihao Xia Website:<https://www.photalabs.com/> API doc:<https://docs.photalabs.com/>

1 Introduction

Generative image models are evolving toward general-purpose visual engines. A single foundation model can now synthesize photorealistic scenes, perform complex image edits, reason across multiple input images, and transform images across visual domains. However, these models remain surprisingly unreliable in one of the most fundamental requirements for working with real-world visual content: preserving who is depicted. In subject-driven generation and editing, the objective is not merely to produce a plausible subject, but to preserve the exact identity of a particular person, animal, or character while correctly modifying other aspects of the image. Identity should remain consistent even under substantial changes to pose, expression, clothing, viewpoint, illumination, scene, or style, even when these transformations reveal aspects of the subject not shown in the input images. In other words, the system should be able to substantially transform the image without transforming the subject into someone else. This requirement becomes increasingly important as generative models move beyond isolated generation and editing tasks toward persistent creative workflows. The same subject may be placed in new environments, edited repeatedly across multiple turns, restored from degraded images, depicted at different scales, or composed with other known subjects. Across these interactions, identity becomes a persistent invariant: the visual content may change substantially, but the identity of the subject should not.

1.1 Three paradigms for subject identity

Existing approaches to subject-driven generation and editing differ fundamentally in where and when subject identity is represented. We organize them into three broad paradigms: model-specific identity, in-context identity, and persistent identity.

Model-specific identity

Traditional personalization methods explicitly incorporate subject identity into a particular generative model by treating the subject as a new concept to be learned and encoded into the model parameters. Textual Inversion learns a subject-specific token embedding [Gal et al., 2023], while DreamBooth fine-tunes the generative model using a unique identifier associated with the subject [Ruiz et al., 2023]. Low-rank adaptation (LoRA) [Hu et al., 2022] provides a more parameter-efficient alternative and has become a common recipe for per-subject optimization in open-weight models. Another line of methods [Wei et al., 2025] augments the base model with specialized identity-conditioning components, such as learned encoders, adapters, or explicit identity representations [Ye et al., 2023, Li et al., 2024, Wang et al., 2024, Papantoniou et al., 2024]. Although these methods differ in how identity is encoded, their personalization mechanisms are designed for and coupled to a particular generative model or architecture. Consequently, they are primarily applicable to open-weight models such as Stable Diffusion [Rombach et al., 2022], FLUX2 [Labs, 2025], IDEOGRAM4 [AI, 2026], QWEN-IMAGE [Wu et al., 2025], FIRERED-IMAGE-EDIT [Team et al., 2026]. Moving to a new foundation model generally requires adapting or retraining the personalization mechanism. Within this broad paradigm, our benchmark instantiates model-specific identity using per-subject LoRA adaptation on various foundation models.

In-context identity

As multimodal foundation models have become more capable, subject identity can increasingly be handled directly within the model's native input context. State-of-the-art image foundation models such as GPT-IMAGE-2 [OpenAI, 2026], NB2 [Raisinghani, 2026], REVE-2.1 [Reve, 2026] and SEEDREAM-5-PRO [ByteDance Seed Team, 2026] can take one or more reference images together with an instruction and generate or edit the depicted subject without subject-specific training or an external personalization module. Because these models are closed-weight, however,

their parameters are not available for user-side subject-specific adaptation, m ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '생성형 이미지 모델은 이제 고품질 이미지를 생성하고, 복잡한 지시를 따르며, 정밀한 편집을 지원할 수 있지만, 여전히 묘사되는 대상(who or what)의 정체성을 보존하는 데 어려움을 겪습니다. 특정 대상의 이미지를 생성하거나 편집할 때, 포즈, 표정, 외모, 시'}], 'role': 'model'}, 'finishReason': 'MAX_TOKENS', 'index': 0}], 'usageMetadata': {'promptTokenCount': 342, 'candidatesTokenCount': 82, 'totalTokenCount': 2386, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 342}], 'thoughtsTokenCount': 1962, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'Cd2dapGOA4q4sOIP97vt0Ac'}

[논문 후보 3]

제목: CauseCollab: Causal Unified and Modality-Agnostic Network for Heterogeneous Collaborative Perception
저자: Weize Li, Yang Li, Quan Yuan, Xiaoyuan Fu, Guiyang Luo, Jinglin Li
카테고리: Format-LoRA/Structured Output
arXiv ID: 2609.03818
제출일: 2026-09-03T13:19:50+00:00
수정일: 2026-09-03T13:19:50+00:00
최근성: 최근 3일 이내
arXiv PDF: <https://arxiv.org/pdf/2609.03818.pdf>

[초록 원문]

Collaborative perception enhances environment understanding through multi-agent information sharing, but its performance in real-world scenarios is constrained by heterogeneous sensor modalities and model architectures. Recent protocol-based two-stage methods alleviate this problem by mapping heterogeneous features into a shared protocol space; however, independently trained modality-specific converters often generate modality-specific pseudo-protocol distributions, leading to semantic inconsistency and error accumulation, which is particularly pronounced in scenarios with large modality discrepancies. To address this issue, we propose CauseCollab, a causal unified and modality-agnostic network. CauseCollab formulates representation learning in the protocol space from a causal perspective, explicitly disentangling semantic factors from modality-specific statistical confounders via causal metric learning. Meanwhile, CauseCollab adopts context-guided Unified Converter for heterogeneous modalities to ensure cross-modal semantic consistency. In addition, integrating new modalities only requires training adapters with minimal parameters. Extensive experiments on the OPV2V and DAIR-V2X datasets demonstrate that CauseCollab achieves state-of-the-art performance, with more significant gains in scenarios involving large modality gaps.

[PDF 앞부분/서론 일부]

CauseCollab: Causal Unified and Modality-Agnostic Network for Heterogeneous Collaborative Perception Weize Li * 1 Yang Li* 1 Quan Yuan1 Xiaoyuan Fu 1 Guiyang Luo 1 Jinglin Li 1 Abstract Collaborative perception enhances environment understanding through multi-agent information sharing, but its performance in real-world scenarios is

constrained by heterogeneous sensor modalities and model architectures. Recent protocol-based two-stage methods alleviate this problem by mapping heterogeneous features into a shared protocol space; however, independently trained modality-specific converters often generate modality-specific pseudo-protocol distributions, leading to semantic inconsistency and error accumulation, which is particularly pronounced in scenarios with large modality discrepancies. To address this issue, we propose CauseCollab, a causal unified and modality-agnostic network. CauseCollab formulates representation learning in the protocol space from a causal perspective, explicitly disentangling semantic factors from modality-specific statistical confounders via causal metric learning. Meanwhile, CauseCollab adopts context-guided Unified Converter for heterogeneous modalities to ensure cross-modal semantic consistency. In addition, integrating new modalities only requires training adapters with minimal parameters. Extensive experiments on the OPV2V and DAIR-V2X datasets demonstrate that CauseCollab achieves state-of-the-art performance, with more significant gains in scenarios involving large modality gaps.

1. Introduction

Collaborative perception shares intermediate features among multiple agents through communication, enabling *Equal contribution

¹State Key Laboratory of Networking and Switching Technology, Beijing University of Posts and Telecommunications, Beijing, China. Correspondence to: Quan Yuan <yuanquan@bupt.edu.cn>. Proceedings of the 43rd International Conference on Machine Learning, Seoul, South Korea. PMLR 306, 2026. Copyright 2026 by the author(s).

them to complement each other's perceptual blind spots, and is widely regarded as a key technique for improving the robustness of autonomous driving systems (Arnold et al., 2022; Han et al., 2023; Liu et al., 2023). In recent years, extensive research has focused on enhancing the performance of homogeneous collaboration (Liu et al., 2020; Hu et al., 2022; Xu et al., 2022b). However, in real-world deployments, collaborative agents often originate from different manufacturers and platforms, exhibiting substantial differences in sensor types, voxel sizes, and network architectures. It makes intermediate features difficult to fuse and limits the practical effectiveness of collaborative perception. To address heterogeneity in collaborative perception, prior work has explored feature transformation modules that map heterogeneous modality features from neighboring agents into the local space of the ego agent (Zhao et al., 2023; Yin et al., 2024). Existing approaches can be broadly categorized into two classes. The first class (Xu et al., 2023; Lu et al., 2024) learns a dedicated mapping for each pair of heterogeneous modalities to achieve one-stage alignment, but suffers from poor scalability as the training cost grows rapidly with the number of modalities. The second (Luo et al., 2024; Gao et al., 2025) class introduces a unified protocol modality as an intermediate representation space, and trains a converter and a reconstructor for each modality to map heterogeneous features into this protocol space, achieving improved scalability while maintaining strong performance. Although two-stage heterogeneous adaptation methods based on a protocol space exhibit favorable scalability, their performance is often constrained by error accumulation across stages. When the converters are trained independently for each modality, each modality tends to learn a locally self-consistent mapping between its local representation and the protocol representation. This behavior leads to inconsistent pseudo-protocol distributions in the protocol space. As a result, even after all features are projected into a unified protocol space, significant discrepancies in semantic responses and statistical distributions may persist across modalities, which weakens the effectiveness of local semantic reconstruction. This issue becomes particularly pronounced when the

1 arXiv:2609.03818v1 [cs.AI] 3 Sep 2026 CauseCollab: Causal Unified and Modality-Agnostic Network for HCP modality gap is large, where pseudo-protocol distributions often introduces

noisy responses and spurious activations in background regions. The root cause is that existing methods typically model the protocol space merely as a distributional alignment intermediary, failing to explicitly characterize which semantic factors should be shared across modalities and which modality-specific statistical confounders should be disentangled. To address this problem, we propose a unified two-stage framework from a causal perspective. Unlike previous methods that treat the protocol space as a reversible intermediate and emphasize distribution matching, our framework focuses on semantic extraction and modal factor disentanglement in Stage-1, followed by modality-specific local semantic reconstruction in Stage-2. Specifically, in Stage-1, we adopt a unified converter composed of a semantic context extractor (SCE) and a context-guided dynamic refiner (CGDR) for multi-modality mixed training. By taking global semantics as an anchor to constrain local feature refinement, we reduce background-induced misalignment. Meanwhile, we construct a structural causal model (SCM) (Schölkopf, 2022), depicted in Figure 2, to characterize the relationships among heterogeneous modalities in terms of semantic components. Through a counterfactual intervention strategy based on causal metric learning, we explicitly drive the protocol representations of each modality to approximate the weakly observed protocol modality. This suppresses pseud ... [앞부분 텍스트 일부 생략]

[초록 번역]

초록 번역 실패: Gemini 응답 파싱 실패 또는 응답 불완전: {'candidates': [{'content': {'parts': [{'text': '협력적 인지(Collaborative perception)는 다중 에이전트 정보 공유를 통해 환경 이해를 향상시키지만, 실제 시나리오에서의 성능은 이질적인 센서 모달리티(sensor modalities)와 모델 아키텍처(model architectures)에 의해 제약받습니다. 최근 프로토콜 기반의 2단계(two-stage) 방법들은 이질적인 특징(features)을 공유 프로토콜 공간(protocol space)으로 매핑(mapping)함으로써 이 문제를 완화합니다. 그러나 독립적으로 훈련된 모달리티별 변환기(modality-specific converters)는 종종 모달리티별 의사 프로토콜 분포(modality-specific pseudo-protocol distributions)를 생성하여 의미론적 불일치(semantic inconsistency)와 오류 누적(error accumulation)을 초래하며, 이는 특히 모달리티 불일치(modality discrepancies)가 큰 시나리오에서 두드러집니다. 이 문제를 해결하기 위해, 우리는 인과적 통합 및 모달리티 불가지론적(modality-agnostic) 네트워크인 CauseCollab을 제안합니다. CauseCollab은 인과적 관점(causal perspective)에서 프로토콜 공간 내 표현 학습(representation learning)을 공식화하여, 인과적 거리 학습(causal metric learning)을 통해 의미론적 요인(semantic factors)을 모달리티별 통계적 교란 변수(modality-specific statistical confounders)로부터 명시적으로 분리합니다. 동시에 CauseCollab은 이질적인 모달리티를 위한 컨텍스트 기반 통합 변환기(context-guided Unified Converter)를 채택하여 교차 모달 의미론적 일관성(cross-modal semantic consistency)을 향상시킵니다. 이 작업은 Gemini 2.5 Flash를 사용하여 수행되었으며, 결과는 다음과 같습니다: {'role': 'model', 'finishReason': 'MAX_TOKENS', 'index': 0}, {'usageMetadata': {'promptTokenCount': 292, 'candidatesTokenCount': 371, 'totalTokenCount': 2336, 'promptTokensDetails': [{'modality': 'TEXT', 'tokenCount': 292}], 'thoughtsTokenCount': 1673, 'serviceTier': 'standard'}, 'modelVersion': 'gemini-2.5-flash', 'responseId': 'Ed2dat_zBd-kqtsPsePBgQY'}