

SLM / Edge Device arXiv Daily Summary

생성일: 2026-05-05 20:18 KST

Gemini 모델: gemini-2.5-flash

Gemini 요약 실패

오늘은 Gemini API 오류 또는 서버 혼잡으로 인해 한국어 요약을 생성하지 못했습니다.

대신 arXiv API로 수집하고 중복 제거한 후보 논문 목록을 저장합니다.

이 후보들은 processed_ids.json에 기록하지 않으므로 다음 실행 때 다시 요약 대상이 될 수 있습니다.

오류 메시지: 모든 Gemini 모델 호출 실패:

[논문 후보 1]

제목: Standing on the Shoulders of Giants: Stabilized Knowledge Distillation for Cross--Language Code Clone Detection

저자: Mohamad Khajezade, Fatemeh H. Fard, Mohamed Sami Shehata

arXiv ID: 2605.02860

제출일: 2026-05-04T17:37:16+00:00

수정일: 2026-05-04T17:37:16+00:00

arXiv PDF: <https://arxiv.org/pdf/2605.02860.pdf>

초록:

Cross-language code clone detection (X-CCD) is challenging because semantically equivalent programs written in different languages often share little surface similarity. Although large language models (LLMs) have shown promise for semantic clone detection, their use as black-box systems raises concerns about cost, reproducibility, privacy, and unreliable output formatting. In particular, compact open-source models often struggle to follow reasoning-oriented prompts and to produce outputs that can be consistently mapped to binary clone labels. To address these limitations, we propose a knowledge distillation framework that transfers reasoning capabilities from DeepSeek-R1 into compact open-source student models for X-CCD. Using cross-language code pairs derived from Project CodeNet, we construct reasoning-oriented synthetic training data and fine-tune Phi3 and Qwen-Coder with LoRA adapters. We further introduce response stabilization methods, including forced conclusion prompting, a binary classification head, and a contrastive classification head, and evaluate model behavior using both predictive metrics and response rate. Experiments on Python--Java, Rust--Java, Rust--Python, and Rust--Ruby show that knowledge distillation consistently improves the reliability of compact models and often improves predictive performance, especially under distribution shift. In addition, classification-head variants substantially reduce inference time compared to generation-based inference. Overall, our results show that reasoning-oriented distillation combined with response stabilization makes compact open-source models more practical and reliable for X-CCD detection.

[논문 후보 2]

제목: Compress Then Adapt? No, Do It Together via Task-aware Union of Subspaces

저자: Jingze Ge, Yun Liu, Xue Geng, Wanqi Dong, Wang Zhe Mark, Min Wu, Xulei Yang

arXiv ID: 2605.02829

제출일: 2026-05-04T17:05:45+00:00

수정일: 2026-05-04T17:05:45+00:00

arXiv PDF: <https://arxiv.org/pdf/2605.02829.pdf>

초록:

Adapting large pretrained models to diverse tasks is now routine, yet the two dominant strategies of parameter-efficient fine-tuning (PEFT) and low-rank compression are typically composed in sequence. This decoupled practice first compresses and then fine-tunes adapters, potentially misaligning the compressed subspace with downstream objectives and squandering a global parameter budget. To overcome this limitation, we introduce JACTUS (Joint Adaptation and Compression with a Task-aware Union of Subspaces), a single framework that unifies compression and adaptation. From a small calibration set, JACTUS estimates input and pre-activation gradient covariances, forms their orthogonal union with the pretrained weight subspace, performs a projected low-rank approximation inside this union, allocates rank globally by marginal gain per parameter, and trains only a compact core matrix. This explicitly mitigates the potential misalignment between the compressed subspace and downstream objectives by coupling the directions preserved for compression with those required for adaptation, yielding a deployable low-rank model that avoids retaining full frozen weights while enabling fast and robust tuning. On vision, JACTUS attains an average 89.2% accuracy on ViT-Base across eight datasets at 80% retained parameters, surpassing strong 100% PEFT baselines (e.g., DoRA 87.9%). On language, JACTUS achieves an 80.9% average on Llama2-7B commonsense QA at the same 80% retained-parameter budget, outperforming 100% PEFT (e.g., DoRA 79.7%) and exceeding prior compress-then-finetune pipelines under the same retained-parameter budget. We will release code.

[논문 후보 3]

제목: Global-Local Feature Decoding with Adapter-Guided SAMv2 for Salient Object Detection

저자: Morteza Moradi, Mohammad Moradi, Simone Palazzo, Ali Borji, Concetto Spampinato

arXiv ID: 2605.02616

제출일: 2026-05-04T14:04:38+00:00

수정일: 2026-05-04T14:04:38+00:00

arXiv PDF: <https://arxiv.org/pdf/2605.02616.pdf>

초록:

Salient Object Detection (SOD) remains an essential yet underexplored task in the era of large-scale vision models. Although foundation models like SAM exhibit strong generalization, their potential for SOD is not fully realized, and training or fully fine-tuning them is computationally expensive and prone to overfitting under limited data. To overcome these challenges, we introduce GLASSNet, a Global-Local feature decoding framework that uses SAMv2 as a frozen encoder paired with a lightweight, spatially aware convolutional adapter-reducing learnable encoder parameters by over 97%. To enhance saliency quality, GLASSNet employs a dual-decoder architecture: one

decoder captures global, long-range semantics with an expanded receptive field, while the other captures fine local details such as edges and textures. Fusing these complementary cues yields saliency maps that combine global coherence with local precision, producing accurate final masks. Extensive experiments on standard SOD and camouflaged object detection benchmarks show that GLASSNet surpasses state-of-the-art methods, demonstrating the power of frozen foundation models combined with targeted adaptation and global-local decoding.